

NEW STEEL CONSTRUCTION

NVSC

www.new-steel-construction.com



**Low vibration healthcare structure
Fibre reinforced floors
Demystifying the Eurocodes**



you design it...
we bend it!

Multi axis tube bending up to
1524mm diameter tube x 60mm thick

Single Plane Bending

3 Dimensional Bending

Elliptical Bending

for further details see our website



BARNSHAWS
STEEL BENDING

Barnshaws, Anchor Lane, Coseley,
West Midlands, WV13 9NE, UK

Tel: 01902 880848

Email: greg.north@barnshaws.com

barnshaws.com



Cover Image

ST RICHARD'S HOSPITAL, CHICHESTER

Structural Engineer: Gyouy Self
Steelwork Contractor: F H Dale

EDITOR

Nick Barrett Tel: 01323 422483
nick@new-steel-construction.com

DEPUTY EDITOR

David Fowler Tel: 01892 538191
david@new-steel-construction.com

CONTRIBUTING EDITOR

Ty Byrd Tel: 01892 524455
ty@barrett-byrd.com

PRODUCTION EDITOR

Andrew Pilcher Tel: 01892 524481
andrew@new-steel-construction.com
ISDN: 01892 557302

ADVERTISING SALES MANAGER

Sally Devine Tel: 01424 833871
sally@new-steel-construction.com

PUBLISHED BY

The British Constructional Steelwork Association Ltd
4 Whitehall Court, Westminster, London SW1A 2ES
Telephone 020 7839 8566 Fax 020 7976 1634
Website www.steelconstruction.org
Email postroom@steelconstruction.org

The Steel Construction Institute
Silwood Park, Ascot, Berkshire SL5 7QN
Telephone 01344 623 345 Fax 01344 622 944
Website www.steel-sci.org
Email reception@steel-sci.org

Corus
Corus Construction and Industrial, PO Box 1, Brigg Road,
Scunthorpe, North Lincolnshire DN16 1BP
Telephone 01724 404040 Fax 01724 404224
Website www.corusconstruction.com
Email tsm@corusgroup.com

CONTRACT PUBLISHER & ADVERTISING SALES

Barrett, Byrd Associates
Linden House, Linden Close,
Tunbridge Wells, Kent TN4 8HH
Tel: 01892 524455
www.barrett-byrd.com

EDITORIAL ADVISORY BOARD

Dr D Tordoff (Chairman); Mr N Barrett; Mr D Fowler;
Mrs Sally Devine; Mr D G Brown, SCI; Mr J P Cartz, BDP;
Mr M Crosby, FaberMaunsell; Mr R Gordon, Mace Ltd;
Mr W Gover, Consultant; Mr R Harrison, Glentworth Fabrications
Ltd; Mr A Hughes, Tubelines; Mr A Palmer, Buro Happold;
Mr R Steeper, Corus; Mr O Tyler, Wilkinson Eyre,
The role of the Editorial Advisory Board is to advise on the overall style
and content of the magazine.

New Steel Construction welcomes contributions on any suitable topics relating to
steel construction. Publication is at the discretion of the Editor. Views expressed in
this publication are not necessarily those of the BCSA, SCI, Corus or the Contract
Publisher. Although care has been taken to ensure that all information contained
herein is accurate with relation to either matters of fact or accepted practice at the
time of publication, the BCSA, SCI, Corus and the Editor assume no responsibility for
any errors or misinterpretations of such information or any loss or damage arising
from or related to its use. No part of this publication may be reproduced in any form
without the permission of the publishers.

CHANGES TO THE MAILING LIST

If you wish to notify us of a change:

Non Members of either the SCI or the BCSA please telephone
Barrett, Byrd Associates on 01892 538191

Members BCSA Telephone BCSA on 020 7839 8566

Members SCI Telephone SCI on 01344 623 345


SUBSCRIPTIONS

To take out a subscription please telephone 01344 623 645
Annual subscription £92.00 UK, £117.00 elsewhere.

All rights reserved ©2005. ISSN 0968-0098



www.new-steel-construction.com



5 Editor's comment

6 News: More economic steel buildings promised.

10 Letters and Diary

11 Comment: BCSA President Tom Goldberg looks ahead to more stable steelwork prices in 2005.

12 Analysis: Nick Barrett reports from a seminar which heard about a major success in the developing field of structural fire engineering.

FEATURES

14 David Fowler hears how composite steel decking is becoming even more cost effective on a pioneering multi storey education project.

18 The first healthcare project to benefit from the new hospital floors design guide is nearing completion in Chichester. Jon Masters reports that vibration concerns are a thing of the past.

20 The market for large scale distribution centres is strong, but fast track delivery is essential. NSC reports on how steel delivers for clients with no time to spare.

22 Steel is fast displacing concrete as the preferred material for contractors on highways, the key sector of the bridges market. Price, ease of installation, and technical developments in fabrication and coating technology are among the factors driving this success.

24 The new Eurocodes will introduce fundamental changes in the way buildings are designed. David Fowler reports on the success of the first stage of a pan European drive to make life easier for designers.

26 SCI Deputy Director David Brown says that for most designers there will be no step-change involved when the new Eurocodes are introduced. But be sure to let engineering common sense be your guide.

30 Advisory Desk. The latest advice from the Steel Construction Institute includes interim guidance on the use of BS 5950-1:2000.

32 40 Years Ago. Our regular look back through the pages of Building With Steel.

34 SCI members

36 BCSA members

38 Reviews and Publications



The British
Constructional
Steelwork
Association Ltd



The Steel
Construction
Institute

SPAN

FURTHER

MULTIDECK New Multideck V2 now spans further than ever.

Call now for the new and completely updated
Handbook and CD Software on **0870 761 7004**
or visit our website **kingspanmetlcon.com**



Kingspan Metl-Con Ltd. Sherburn, Malton, North Yorkshire, YO17 8PQ. England.
Tel: 01944 712000 Fax: 01944 710555 e-mail: sales@kingspanmetlcon.co.uk



Exciting times ahead



Nick Barrett - Editor

Welcome to the expanded New Steel Construction, which will now come out monthly to open a more frequent window into the steel construction industry. Our focus will be on the industry's successes and on how challenges are overcome in design, fabrication and steelwork erection.

Regular readers will notice a few changes in this issue, and there will be more over the coming months as we develop our ideas in line with reader feedback on what the steel sector's flagship magazine should be like. We look forward to hearing your comments.

A key idea behind the changes is to provide more timely accounts of what is happening in the industry. This will mean more reports from projects which are at the construction stage. We will still look back to ask if things might have been done better and to learn lessons, but essentially New Steel Construction is about what is happening now.

It is encouraging that Corus has further signalled its support for the sector by joining the British Constructional Steelwork Association and the Steel Construction Institute as a full and equal partner in the magazine. Among other things, this will bring a wider readership to be catered for in our spread of articles and news stories. But whoever the reader is, New Steel Construction aims to be the first place to look to find out what is happening in the steel sector of the construction industry. Exciting times lie ahead for the steel sector and if New Steel Construction reflects that it can hardly fail to be an interesting and essential read.

Keeping the market supplied

The year 2004 was a turbulent one in the steel market, when price rises captured the imagination of newspaper headline writers across the world. Some were more imaginative than others, of course, and a lot of effort has been expended by the industry's lobbyists in correcting some of the more unjustifiable headlines. That might be the case again in 2005, but there are some encouraging signs of more stability in steel prices. The Chinese market, for example, looks like cooling down as a result of government anti inflationary policies which should take pressure off scrap, coke and freight prices.

All major steel consuming markets worldwide saw demand growth in 2004, not just China. Global demand looks like rising again in 2005 and iron ore, coke and scrap shortages will no doubt grab headlines again. It's part of the price we pay for steel being so popular worldwide as a structural framing material, but it's worth remembering that all primary construction materials are feeling upward pressure on prices.

One thing which stood out during the turbulence of 2004, and which is likely to be repeated in 2005, was the ability of steel producers to maintain supplies to their customers during what were extremely challenging times. Prices today are still well below the levels of almost 20 years ago in real terms, and often in absolute terms as well. This reflects the fact that massive improvements in efficiency across the steel sector have been passed on to customers, ensuring that steel is the cost effective construction material of choice for most applications.

Corus has said that it remains dedicated to doing all it can to maintain the competitiveness of its customers, and is confident of being able to keep them supplied during 2005. So when you see the scare headlines arising again, ignore them. Check with New Steel Construction if you want the facts.



Trade Centre tower rises in steel

The last building to collapse as a result of the September 11 attacks is the first to rise from the ashes of New York's World Trade Centre. The main steel frame of the 52 storey, 158,000m² WTC7, which contains around 4000t of steel supplied by Corus, has topped out after a fast track construction programme.

The new primarily glass and steel structure, designed by David Childs of Skidmore Owings & Merrill, is the first of a projected nine buildings that will be erected on the site. The building which it replaces collapsed after the attack on the Twin Towers. New safety features include added load path redundancy for structural steel framing, durable fire proofing materials, reinforced concrete infill walls around the concrete core, and exit stairs 20% wider than US codes specify.

The main steelwork contractor was required to purchase half the steel from the US and sourced the rest from its long-standing supply partner Corus. Completion of the project is scheduled for 2006.

Eurocode safety factor victory promises more economic steel buildings

Steel structures designed to the new Eurocode EN 1993 will be lighter and more efficient thanks to a successful battle by the Steel Construction Institute over factors of safety.

SCI has persuaded ministers that the UK should adopt the recommended factors of safety for materials, overruling the 'no-change' brigade who wanted to adjust them to neutralise the effect of the new code. The potential improvement in design efficiency over the old code, BS5950, is expected to be around 6% to 8%, which compares favourably with profit margins in the steel fabrication industry.

The industry has complained that the cost of implementing the codes, including training and dissemination of the changes, could run into millions of pounds.

SCI Director Dr Graham Owens said: "There will be worthwhile economies for designs governed by gravity loads. This will be an important driver for implementation of the Eurocodes, especially for design and build projects."

The economy arises from the fact that the factors of safety for dead and live loads in Eurocode 3 are lower, at 1.35 and 1.5 respectively, than the values in the old code of 1.4 and 1.6. The recommended factor of safety for materials, γ_m , remains at 1.0.

However, γ_m is a 'nationally determined parameter' for which individual countries are not obliged to adopt the recommended value. Civil

servants and the British Standards Institution had planned to adopt a γ_m of 1.05 to 1.1 to make the new code neutral compared with BS5950.

"That would have meant that after all the efforts the industry had put in to developing the new codes, there would have been no benefit," said Dr Owens. "It's been a sustained fight to get back to unity [ie to a value of 1]." It was not until he raised the matter with Construction Minister Nigel Griffiths at a meeting of Co-construct that he began to make progress.

BCSA has been awarded the contract from the Office of the Deputy Prime Minister (ODPM) to draft the National Annex to EC3. An agreed document on 'Development of the National Annexes' to the Eurocodes, the documents that will specify the nationally determined parameters, says that recommended values should be adopted where differences between the old and the new are less than 10%. Recommended values should also apply where differences are greater but research data or the evidence of successful overseas practice justifies the change. National parameters should only depart from recommendations where neither condition is met. "We think that's a reasonable outcome," said Dr Owens.

The efficiency gains will apply to structures where wind loading does not govern the design, such as low rise office buildings. The situation for portal frames is more complex and has not yet been fully investigated.

New team takes over production

Production and advertising sales of New Steel Construction have been handed over to Barrett Byrd Associates, contract publishers with a long track record of working for the construction industry. BBA has appointed a highly experienced team to take the magazine forward and manage the new demands of monthly publication.

The editorial team is headed by Editor Nick Barrett, who has worked for a wide range of specialist magazines including New Civil Engineer. Deputy Editor is David Fowler, also a former NCE staff writer, and former NCE Editor in

Chief Ty Byrd is a Contributing Editor. Advertising Sales Manager Sally Devine has worked in senior roles on construction magazines for over 15 years, mostly with publisher EMAP.

Production Editor Andrew Pilcher has worked in graphic design since the 1980s, and wrote a daily cartoon strip, Millie, for the Daily Mirror.

Nick Barrett said: "We are delighted to have been given this opportunity to take an already well respected publication on to the next stage of its development. Steel is one of the most exciting sectors of the construction industry and the magazine will help spread that message."



L-R David Fowler, Nick Barrett, Andrew Pilcher, Ty Byrd and Sally Devine

Weathering steel gets out of the block

The UK's biggest sculpture — Manchester's B of the Bang — has been handed over to the client after a successful installation by principal steelwork contractor William Hare, and is due to be officially unveiled this month.

The 56m high sculpture was designed by Thomas Heatherwick in weathering steel and symbolises the burst of speed and energy of a sprinter launching out of the starting blocks. The name was inspired by athlete Linford Christie's comment that he started his Olympic gold medal winning race on the B of the bang of the starter's pistol.

It has been erected next to the City of Manchester Stadium, the main venue for the Commonwealth Games which the sculpture commemorates, and now the home of Manchester City Football Club.

The design, selected through a competition held by the New East Manchester Regeneration Board, consists of 180 steel 'spikes' radiating out from a central point.

The sculpture consists of 3240 weathering steel plates welded to form 180 faceted tapering cones. "The steel was specified by the designer and provided by Corus as plate steel,"

says William Hare Project Manager Dave Fish. "Each cone, or spike, goes into an 80t central core which is also

welded pressed plate. The sculpture's five legs are faceted as well, but clad with 3mm of weathering steel."

Project structural engineer was Packman Lucas. Corus plate sales manager Paul Parkins says the popularity of weathering steel continues to grow among artists. "Designers are finding that weathering steel provides a pleasing finish and we are seeing an increase in demand for this steel for use in artistic and cultural projects."

Room at the top

A 1960s south London block of flats is being extended by the unusual method of building six additional storeys in steel on top of the existing reinforced concrete frame.

The 24 storey Aragon Tower council block in Deptford has been acquired by Berkeley Homes, which is refurbishing 80 flats and adding new penthouses.

The £520,000 contract to erect 250t of steel was won by Bourne Group Holdings subsidiary Bourne Steel. Contracts Manager Nick Flexen-Cook says that to use steel was the quickest and simplest way in which the extra storeys could be grafted on. "Apart from more stringent health and safety considerations, it's essentially like building a conventional steel structure which could be founded at ground level, but 75m off the ground."

He added: "We're doing as much pre-assembly at ground level as possible to minimise assembly at height." By assembling around 15 components into a box 8m long by 6m square, the equivalent of four hours of crane time can be compressed into one lift.

Steelwork was finished two weeks early in mid-December. The project will feature in a BBC documentary series fronted by Anneka Rice, following regeneration in Deptford over two years.



Steel stays strong in market

Steel continues to be overwhelmingly the structural framing material of choice for multi storey non-residential buildings, according to the latest survey from independent market research consultants Construction Markets.

The survey, commissioned by Corus, is the latest in a series going back to 1980 and is thought to be the biggest of its type in the UK, involving over 600 interviews with construction specifiers. The results show that steel frames have a dominant 69% share of the multi storey buildings market. The survey also shows that the market grew

slightly in 2004, with overall floor area constructed in all multi storey buildings increasing to 12,342,000m², from 12,202,000m² in 2003.

Steel now has a 71% share of the multi storey offices market. In the 'other multi storey buildings' sector, which includes retail, education, leisure and health, steel has a 68% share.

The decline of in situ concrete as a choice for building frames continues, with a market share of only 16.8%, the lowest since the survey began, compared to almost 20% in 2003 and 28.3% only seven years ago. Load bearing masonry

had a 9.5% share, while precast concrete accounted for 2.8% and timber 1.7%.

Alan Todd, Corus Construction and Industrial Technical Sales and Marketing General Manager, said: "These figures clearly show that the key multi storey construction markets value steel above any other framing material. The relative competitive situation against other materials like in situ concrete is essentially unchanged by the price increases of the last year, and we can foresee only continued recognition from the construction industry that steel is the natural choice of framing material where factors like speed, cost, and sustainability are important."

The Times*10 December 2004*

Details are emerging about the Burj Dubai, which will be the world's tallest building when it is completed in 2008. It will rise 160 storeys or almost 800m from a 20-acre base which will also incorporate the world's largest shopping mall. The building is being developed by Emaar. Architect is Skidmore, Owings & Merrill and a multinational team of Korea's Samsung, Belgium's Besix and local outfit Arabtec is tipped to win the construction contract.

Construction News*9 December 2004*

Contractors and rebar fabricators have been warned not to drop tender prices in response to falling scrap metal prices. Scrap constitutes as much as 95% of rebar, but bar mills have warned that the market is too volatile to predict what the long-term price of rebar will be, and to cut prices now could leave fabricators exposed to later rises.

Contract Journal*8 December 2004*

Contractor Buckingham Group has replaced Alfred McAlpine on the £42M contract to design and build the 30,000 seat stadium for football club Milton Keynes Dons. Work will start on the project at Denbigh near Bletchley later this month.

Construction News*1 December 2004*

Despite a flat commercial property market the steel sector has unveiled its most impressive figures for 15 years. In 2003 steel accounted for more than 50% of the total deck area of road bridges built. Speed of construction has also helped in the uptake of steel in hospital PFI projects.

Construction News*1 December 2004*

"There is potential for steel framing to replace blockwork," says Metsec director Erle Andrews. "Anywhere blockwork is used, load-bearing steel framing can carry out at least an equivalent, if not superior, function."

Calderdale schools construction nears completion



Steelwork installation is virtually complete on five new schools under construction near Halifax in West Yorkshire in the first phase of the Calderdale PFI Schools project. Elland Steel Structures has supplied 2,300t of steelwork and around 20,000m² of metal decking for the four high schools and one primary school.

Elland designed steelwork connections, erected the steelwork and installed precast stairs and metal deck floors as part of a £2.75M contract for Babcock & Brown Properties. Main contractor Balfour Beatty's programme of works totals £45M.

Martin Tovey, Associate Director

of the project's structural engineer Whitbybird said: "Construction of the schools in steel rather than concrete presented a clear economic advantage at the time of procurement. Steel frames also give greater flexibility to allow future alterations to the buildings that would not be possible with load bearing masonry structures."

Elland Commercial Director Jeremy Shorrocks said that early involvement of his company by the project design team had allowed the introduction of efficiencies in developing the steel frame structures.

Construction began on two of the schools in July 2003 and a start

on the remainder followed later that year. Steelwork installation for each of the schools took around four weeks. The primary school was completed in August 2004 and all of the schools are due to have begun accepting pupils by April 2005.



Collapse rules progress to a higher level

Design to resist disproportionate collapse became more complex last month as a new Building Regulation came into effect.

Regulation A3 and Approved Document A, which came into force on 1 December, remove the blanket exemption for buildings of four storeys or less.

And buildings of more than 15 storeys or 5000m² must undergo a risk assessment taking into account both 'normal' and 'abnormal' hazards.

Rules on disproportionate collapse were introduced to prevent incidents like the 1968 Ronan Point disaster, in which the removal of one wall by a gas explosion led the corner of the building to fail progressively over the whole 23 storeys.

Under the new regulations buildings are divided into four classes by Table 11, which sets out the extent of horizontal and vertical ties needed according to size and occupancy.

For Class 3, the most onerous category, 'a systematic risk assessment of the building should be undertaken taking into account all the normal hazards that may reasonably be foreseen, together with any abnormal hazards'

Charles King, SCI Senior Manager for Standards, said designers should not be misled into thinking that buildings needed to be designed to meet every eventuality, however unlikely — such as being hit by a meteorite. The approved document only gives guidance, he said. "The reg itself is very simple, and that's what you're obliged to fulfil."

The regulation says only that 'the building shall be constructed so that in the event of an accident it will not suffer collapse to an extent disproportionate to the cause'.

A judgement would have to be made on what is disproportionate in the case of rare or highly unlikely events. Mr King said: "It's not very clear, and the designer will have to rely on a sense of reasonableness."

The approved document also stresses that the structural form and concept should be taken into account, something often overlooked. "If you have a concert hall supported on three columns and a train takes one out then you could have a calamity, whereas if it stood on 30 columns you might be able to take out 10 without a disaster occurring," Mr King said. "You could spend weeks doing statistical analysis of improbable events, but it's better to use a form that's inherently insensitive to having elements knocked out."



Steel cuts hospital waiting time

Caunton Engineering is well advanced on steel erection for a 16,000m² extension to Stoke Mandeville hospital, near Aylesbury, Bucks. Three new buildings will provide a new public entrance to the site with links to new and existing facilities, including additional wards with beds for 220 patients and a day surgery operating theatre. In the longer term it will allow a number of older buildings to be demolished.

Part of the main building's curved facade cantilevers over an existing single-storey building. Structurally

the cantilever is supported by a one-storey deep lattice girder, with its diagonal bracing concealed in a specially-widened partition.

Structural engineer White Young Green designed the structure to the SCI's 1989 design guide on the vibration of floors. "As operating theatres are not in critical locations the main worry is that footfalls at night would keep patients awake," said Associate Director Jim Seager. Thickened floor slabs, using Holorib decking, which is not so deeply profiled as similar systems, were

adopted to increase the mass of the floor and inhibit vibration. The 1989 guide is known to be conservative, and since WYG produced its design the SCI has published updated guidance on minimising vibration in hospitals (see feature page 18).

Work started on site in early June and the extension, which uses over 800t of steel, is due to be completed towards the end of this year. Main contractor for the £39.5M PFI scheme is Alfred McAlpine Capital Projects and Haden Young. Architect is HLM Design International.

Erection of over 10,000t of steelwork for the new Swale crossing, linking the Isle of Sheppey to mainland Kent, began in December. Working in partnership with Carillion for Sheppey Route Ltd, steelwork specialist Fairfield-Mabey began by lifting temporary frames to the tops of the permanent bridge piers. The frames will support slipper pads to allow the main girders to be launched into place in early spring.

The Sage Gateshead, a £70m music centre comprising a series of concert halls and educational facilities linked by a spectacular glazed concourse, was opened last month. The new home of the Northern Sinfonia, the Sage was designed by Norman Foster.

The Metal Cladding and Roofing Manufacturers Association has published a comprehensively revised version of its Metal Wall Systems Design Guide. The guide can be obtained from mcrma@compuserve.com or downloaded from www.mcrma.co.uk

Joe Locke, a Director of William Hare, retired in December after an illustrious career in contracting that involved many high profile projects around the world. He was President of the BCSCA 1988-1990 and European President of ECCS 1998-99. (See profile in next month's NSC.)

NSC Deputy Editor David Fowler has won the Automobile Association Trophy in the Guild of Motoring Writers' 2004 awards, for work in the fields of road safety and the environment.

The steel structures department of Spanish contract research and development specialist LBEIN has joined the STEEL project, which is developing web-based guidance to designers using the Eurocodes. (See feature p24)

Corus Construction and Industrial won three categories at the 2004 Construction Marketing Awards organised by Emap Construct. The 'Steel works' series of ads won the Best Use of Advertising award; Campaign of the Year went to the company's integrated marketing on steel-framed hospital design; and Louise Turner was named Young Marketer of the Year for work with the Corus Fire Engineering Consultancy. The Business was also runner up for 'Construction Brand of the Year' and short-listed in the 'Best Technical Literature' category.



New professional challenges for SCI Chairman

Steel Construction Institute Chairman Peter Head is swapping a leading role at FaberMaunsell for one at Arup. The sustainable development and business management specialist is now heading a new business within Arup Consulting intended to put the company at the forefront of urban development.

His remit at Arup is to bring together the company's many skills to create an enhanced, more sustainable offer to clients in urban design and development.



Amec

Return to Waterloo

A £41M project to give a new lease of life to Waterloo station's steel roof was one of five winners in the Institution of Civil Engineers' prestigious Historic Bridge and Infrastructure Awards.

Dating from between 1902 and 1922, the roof covers 19 platforms and is the largest train shed in Europe at 28,000m².

By 1999 maintenance costs had become prohibitive. After a feasibility study of repair and replacement options Network Rail decided to retain the main structure and replace the life-expired roof covering.

Steelwork contractor McNealy

Brown dismantled a total of 380 high level trusses which were grit-blasted and galvanised off-site, then replaced in their original location. The primary steelwork was grit-blasted and repainted in situ. A new laminated glazing system completed the transformation.

The judging panel said: "Excellent conservation. The vast roof is essentially the same as when it was built, but daylight without drips can now be enjoyed by the thousands who use Waterloo every day."

Network Rail was client and project manager and Amec was main contractor.

NSC welcomes letters from readers on steel construction related issues. Please keep your letters brief — the editor reserves the right to condense. Address your letters to: The Editor, NSC, BBA Linden House, Linden Close, Tunbridge Wells, Kent TN4 8HH. Fax: 01892 524456. e: info@new-steel-construction.com

Ringling in the new

May I on behalf of the Marketing and Membership Services Committee of the BCSA wish the new editorial team of New Steel Construction every success with their new charge. New Steel Construction has proved an increasingly important publication for the structural steelwork industry, giving the opportunity it does for the steel contractor to read a sharply focused account of latest developments affecting his trade, while offering the opportunity to highlight his company's own achievements.

The success of NSC has undoubtedly been due to the professional skills and talents of the outgoing Editor, John Rawson. The publication itself was still in its infancy when in the early 1990s John took over from Professor David Nethercot who had most successfully launched it. Through John's considerable journalistic and editorial talents, NSC has developed such that it has become the force it is today. The new team has a strong act to follow, and we in the industry wish you every success with cherishing the old and introducing the new to New Steel Construction. I know the structural steelwork industry would like to thank John for his contribution, and to wish him a happy retirement.

Geoffrey H Taylor, Cauntton Engineering, Chairman, BCSA Marketing and Membership Services Committee

Accoustic innovation

I read with interest the article on No6 Vauxhall Bridge Road. It raised the question in my mind of how this, and other innovative forms of steel construction, could be shown to meet the

regulatory requirements of Part 'E'? Is there any further information available?

**Martin Double
CADOSS
by email**

The Editor replies: To meet the requirements of Part 'E' for new build residential properties two distinct methods are available. The first method uses approved Robust Details (RD) (such as E-FS-1 for composite metal decks), which has been extensively field-tested, and so avoids the need for pre completion testing. It should be noted that every dwelling built using an RD needs to be registered with Robust Detail Ltd and a plot registration fee paid.

The second method is to use pre-completion testing (PCT) where an RD is not specified, and this involves on-site testing of the actual building to prove the acoustic performance. For buildings using innovative construction details such as Vauxhall Bridge Road, PCT would have to be used to prove the acoustic performance.

It should be noted that all forms of construction (including concrete) are subject to the above form of regulation, with no exceptions. The use of an RD only exempts a dwelling from PCT; other forms of residential construction will require PCT to be undertaken.

More information on the above subject can be found in SCI Publication P336 'Acoustic Detailing for Multi-Storey Residential Buildings' or by visiting the following website: www.robustdetails.com

Vibration response

As a grateful beneficiary of support from the SCI with regard to analysis of the vibration response of hospital floors, we write with a structural engineer's endorsement of the SCI's Vibrations Consultancy (NSC November/December

2004). The SCI has clearly put many hours and expertise into the furthering of knowledge in this area and we congratulate it on the effort and its results.

Our experience of analysis support from the SCI relates to design of a new Treatment Centre at Chichester's St Richard's Hospital (see feature p18). Early on the project looked perfect for a steel frame with composite floors and this type of design proved to be the best solution in terms of meeting the tight construction programme. However, standard guidance, from the NHS Building Specification, necessitated heavy beams and considerable cost to meet allowable vibration response factors.

The re-analysis work carried out by the SCI involved some sophisticated finite element software. This enabled the design to be slimmed down and made feasible in terms of cost. As Paul Devine's article in NSC explains, numerical modelling of whole floors with more realistic consideration of relative positioning of loading allows a lot of the conservatism to be taken out of the design.

Most impressive from our point of view though, was the simplicity with which the SCI explained the analysis results. Clearly there can be complex vibrations occurring in multi-element structures, caused by dynamic superimposed loadings, but with the SCI's help, relatively simple checks can now be carried out to help engineers push designs forward while meeting vibration response limits.

**Christopher Self
Partner
Gyours Self Partnership**

Diary

27 January

Preparing for and Implementing Structural Eurocodes

RIBA, London W1.

Organised by Emap Conferences. Understanding the impact on your business and developing a cost-effective strategy for transition. Endorsed by the SCI.

Contact constructconferences@emap.com

27 January - 3 March

Steel in Construction CPD courses.

Glasgow, London and Manchester. Course gives an overview of steel in construction. Six consecutive Thursday evenings with two one-hour lectures

per evening, representing 12 hours or two days of CPD. Sponsored by Corus and the SCI.

Contact: Annabel Herrington, a.herrington@steel_sci.com

**20-21 September
International Architecture Symposium**

Palace de la Méditerranée, Nice (organised by ECCS)

15 November

Steel Construction Conference, The Brewery, Chiswell Street, London EC1 (organised by BCSA)

Healthy, confident and in demand

BCSA President Tom Goldberg reviews the current steel construction market



We have experienced a most unusual 2004 in the steel construction industry. I hope it will help our clients and our steelwork contractors if I review what has happened this year, and what is likely to happen in the future.

Right now, our UK steelwork contractors are experiencing high levels of demand — despite the significant cost increases in our basic material supplies over the last year.

Steel continues to be the UK's (and the world's) most popular construction medium. It is the modern, efficient, sustainable building material. It is constantly achieving new designs, new products and higher standards. It is safe, reliable and eco-friendly. Steel framed buildings only contain 33% more steel than an equivalent reinforced concrete building. While a typical steel framed building's foundations and superstructure use around 65kg of all steel products per m² of gross floor area, a typical reinforced concrete frame and flat slab solution will use around 40kg/m² of rebar for the same elements. Concrete buildings are therefore also affected by material price increases in steel, in addition to the rising costs of cement, aggregates and shuttering.

In the UK structural steelwork remains the favoured framing material for about 95% of all single-storey buildings and 68% of all multi-storey construction. Steel is also now fast becoming the world's first choice — it represents best value for money, it is a modern and efficient material, it is "green", reliable, quality assured, fast and accurate to build with. In the UK steel continues to win new markets in schools, hospitals, residential buildings and car parks.

No surprise, then, that the developing countries of the 21st century are boosting world demand for steel. China, India, Russia and Brazil — and other fast-growing countries — all want the same modern environment as us... "state-of-the-architect" shopping malls, offices, port and airport facilities, distribution hubs, hi-tech parks, schools, hospitals, apartment blocks.

In 2004 worldwide demand for steel increased by 8%. Despite this surge, shortages in the UK have been avoided and there has been no supply problem. Steelwork contractors have worked hard to keep clients informed of increases and early involvement on projects by the steelwork specialists has paid even greater dividends than normal.

The price of raw steel materials has risen 60% in this past 12 months. The effect of this has been an increase of 20–30% in fabricated steelwork prices (dependent upon the type of structure). In turn, the effect upon total building cost will vary between 3% and 20%, with the greatest effect upon predominantly steel buildings like warehouses. However, increases in global raw material prices have also impacted on virtually all other building materials, including concrete and wood.

Where will steelwork prices go from here? Can't say for certain, but the BCSA's evaluation is that for 2005 we will operate in a much more stable environment. Prices for fabricated steelwork used in the construction industry are expected to increase in the range of some 5% for the whole of the forthcoming year. This is good news for our clients and the construction sector at large, as they will be able to more accurately forecast building costs. In real terms, steelwork prices are now still at the same level as 15 years ago.

Steelwork contractors' order books are healthy into 2005 and we do not anticipate any problems with supplies of steel or availability of fabrication capacity. BCSA members have enjoyed very robust conditions in 2004 and BCSA is optimistic that 2005 will continue to see the benefits of building in steel gain further in preference.

City goes long on frame analysis



A large City of London commercial development has been a proving ground for new fire engineering techniques using finite element frame analysis. Nick Barrett reports from a Framed in Steel seminar which heard how it was done.

A groundbreaking application of the developing science of structural fire engineering has delivered a major new high quality office development on a prime site at the heart of the City of London, on the corner of Eastcheap and Mincing Lane.

Plantation Place South is the second of two adjoining buildings which together constitute one of the City's largest developments. Other innovative aspects of the 160,000 sq ft building's design include the use of load-bearing stone rather than simply stone cladding for the envelope. But attention focuses on the use of finite element analysis based software to produce a rigorous analysis of what will happen to a structure in the event of a real world fire — making some conservative assumptions such as that the sprinkler system is not working — and to calculate where extra fire protection could usefully be applied, and where none is in fact needed.

Architects from Arup Associates told the seminar they chose steel frame as a safe and reliable method for the main framework, using a concrete slipform core. Comparisons were made with concrete alternatives but the small number of bays and consequent lack of repetition took concrete multi-bay construction out of consideration. Concrete would also have created foundation loads 20% higher than for steel. The congested nature of the site meant there would be little room for storing formwork for concreting; steel offered off site fabrication and just in time delivery. Overall, for the same floor depth steel offered a 6% saving in frame costs, 10% on foundations and about 5% in programme benefits.

The ambition was not just to save money on fire protection, stresses Dr Barbara Lane of Arup Fire: "We wanted to demonstrate that a building as complex as this one could be safely

and robustly designed using the latest structural fire engineering techniques." Nonetheless, a significant saving was achieved on fire protection.

Dr Lane explained that the traditional fire engineering approach is based substantially on looking up a table and making sure a design complies with it. This regime assumes that all fires are the same, and that a fire in an office is comparable to one at an airport. "Building regulations are derived from old buildings," Dr Lane said.

"They ignore facts such as that whereas an unrestrained beam will deflect at 450°C, a restrained beam will not deflect until 800°C is reached." A frame also has a different response to fire than the traditional furnace tests suggest. Dr Lane and her colleagues drew on the known behaviour of steel in fires from the Broadgate fire and Cardington tests.

She explained: "We calculated what happens in a real fire, using real temperatures. We then calculated the heat transfer through all the structural materials and then we were able to calculate the mechanical response of the whole frame. We then know where fire protection is needed, and also where it is not needed."

At Plantation Place South all secondary beams have been left unprotected. Core connection protection was also modified to accommodate thermal effects. Dr Lane said: "Because of the increased emphasis on structural design we were able to demonstrate that the stability and compartmentation requirement would be met with the reduced level of fire proofing." Armed with this in-depth understanding of structural behaviour in fires, Arup was able to satisfy all other interested parties that the solution was robust — including the client, the building control authority which was the Corporation of London, and the building insurers.

FACT FILE

Client:

The British Land Company plc

Architect and

Structural Engineer:

Arup Associates

Fire Engineering:

Arup Fire

Steelwork Contractor:

William Hare Limited

*For further information see **Framed in Steel: Plantation Place South** available from Corus Literature Line 01724 404400*




The power to integrate

the complete steelwork solution
the complete steelwork solution
the complete steelwork solution

AceCad Software has been providing the structural steelwork industry with the most productive software solution since 1986. All of our products are designed to integrate to form the complete steelwork solution, providing users with the software to fulfil all their requirements from detailing, connection design and analysis through to nesting and fabrication management.

AceCad is dedicated to providing our customers with continued development of our products. With our complete focus on the steel industry we pride ourselves on the level of committed service we supply. In the first half of 2005 alone we already have planned the release of StruCad V11, StruM.I.S 5.2 and StruConnect, AceCad's new connection design program.



AceCad
SOFTWARE

www.acecad.co.uk

sales@acecad.co.uk

Tel: +44 (0) 1332 545800

Fax: +44 (0) 1332 545801



Added fibre for faster floors

Polymer fibres are replacing reinforcement in composite floors on a pioneering project in Derby, following a research programme supervised by the SCI.
David Fowler reports

Composite steel decking is already one of the quickest and most cost-effective ways of constructing floors in multi-storey buildings.

A new development promises to make it even more efficient. A research programme involving the Steel Construction Institute (SCI), Richard Lees Steel Decking and Grace Construction Products has demonstrated that polymer structural fibre reinforcement can replace virtually all the traditional steel reinforcement, both bar and steel fabric, in composite floors.

This is a breakthrough with implications for quality assurance and for health and safety as well as for cost and timing, because the fibres can be incorporated into the concrete mix.

The first major building to use the technique is currently under construction in Derby. The £12M Joseph Wright Centre is a sixth form college which will form part of Derby College when it opens in September 2005, providing nearly 7000m² of classrooms, labs, and IT facilities grouped around a central atrium.

In composite flooring, the profiled steel decking fulfils the function of permanent formwork for the floor slab during construction, and of providing tensile reinforcement when the concrete has cured. Shear connectors are welded through the steel decking to the top flange of the supporting

beams prior to placing the concrete to develop the composite action between the beams and slab.

Additional reinforcement is needed in the form of welded wire fabric over the whole floor area to control shrinkage cracking and to spread the forces generated by the shear connectors through the slab. Additional bars over supporting beams resist bending stresses in the top of the slab. The reinforcement is also needed in a fire, when the strength of the exposed decking is reduced.

Synthetic microfibres have successfully been used for many years to control shrinkage cracks in ground floor slabs, but not as structural reinforcement in this way. Grace Construction Products had developed Strux 90/40 synthetic structural fibre reinforcement with structural applications in floors and sprayed concrete in mind.

European Product Manager Graham Balmer says: "We wanted to look at steel decking as an application for Strux. We knew we needed partners to assist with the development. The SCI was our first port of call, and from those initial contacts we identified Richard Lees Steel Decking as market leader and approached them."

Richard Lees Steel Decking was interested, having briefly looked into the use of synthetic fibres itself several years ago.

Strux 90/40 was developed by Grace Construction Products' parent company in the US for applications ranging from structural slabs to sprayed concrete.

Strux is a flat fibre manufactured from a co-extrusion of two polymers. The length of the fibres, 40mm, was chosen as the optimum compromise between reinforcement, the ability of the fibres to disperse through the mix, and ability to achieve the required finish.





Before and after: Fibre reinforcement eliminates nearly all steel mesh, along with attendant health, safety and logistical problems

There are a number of potentially significant advantages from being able to omit the reinforcing fabric from a concrete floor slab. "It's difficult getting the steel fabric into the building and it disrupts the critical path," says Richard Lees Steel Decking's Technical Director Adrian Shepherd.

In the traditional approach the sheets of fabric have to be craned up to the required floor. This disrupts construction of the steel frame itself and means that either a section of floor has to be left out all the way up the building to allow lifting to take place, or else the fabric must be offered in through the side of the building. If it is not to be fixed in place immediately, the fabric then has to be stacked until needed.

Specialist labour is needed to fix the reinforcement. Checking to make sure all the reinforcement has been fitted correctly is a significant task in itself.

When fixed, it forms a tripping hazard and it provides a far from ideal surface on which to stand while placing the concrete floor slab. This operation is usually carried out by pumping, and the pump nozzle is likely to snag on the fabric.

Mike Atkinson, Project Manager for Bowmer & Kirkland, the main contractor on the Derby project, adds that other tricky operations include trimming the reinforcement around columns. Another problem arises when the steel fabric moves under the traffic of the concrete placing operatives, causing one end to rise up into the finished surface, with implications for the

concrete finish and for corrosion.

By contrast, synthetic structural fibres can be added to the concrete at the supplier's plant and pumped into place in one operation, completely avoiding all these potential problems.

Before any of these advantages could be realised, however, the data to persuade clients and structural engineers of the merits of fibre reinforcement had to be gathered. Grace and Richard Lees Steel Decking commissioned the SCI to oversee a test programme.

Tests included full-scale fire tests to demonstrate that the target fire resistance periods could be met. Small-scale specimens were tested to measure the relationship between cube strength, dosage of fibres and longitudinal shear resistance. Push tests to demonstrate the performance of stud connectors in composite slabs were carried out in which two vertically mounted sections of composite slab were symmetrically loaded in shear through a beam fixed between them.

Mr Balmer says the test programme was extremely rigorous. "The SCI wanted to see a lot of information from first principles, for example how the mechanical properties of the fibre and concrete varied with temperature. So it was a bigger exercise than we initially anticipated."

SCI reported on the tests the partners carried out and produced from the results a set of safe load tables to assist designers using Richard Lees Steel Decking's profiles. The outcome was that the use of fibre allowed all the steel fabric to be

FACT FILE

Joseph Wright Sixth Form Centre, Derby

TEAM

Client

Cedar House Investments

Architect

Maber Associates

Structural engineer

BWB

Main contractor

Bowmer & Kirkland

Steelwork contractor

Severfield-Reeve

Structures

Steel floor contractor

Richard Lees Steel Decking

Civil contractor

C J Haughey

Project value

£12M



Programme included full scale fire tests and push tests to check composite action was being developed



Complicated reinforcement details around columns are avoided

The SCI was commissioned by Richard Lees Steel

Decking and Grace Construction Products to supervise a year-long R&D programme. It provided technical backup, produced a report and devised design guidance in the form of safe load tables on the use of their products in fibre reinforced composite floors.

The SCI Building Engineering Manager Dr Stephen Hicks says: "One of the main questions was: with no bars crossing the shear connectors, could you rely on the forces being transferred into the slab?"

There were also questions over fire resistance. "It wasn't obvious how well the slab would perform at the fire limit state. Because the fibres have a relatively low melting point, you'd expect some loss of strength." Richard Lees Steel Decking had fire-tested a slab in 1988 using standard polypropylene microfibres, the type used for crack control in ground floor slabs. Though the test slab successfully met all the criteria needed to achieve a fire rating, there was concern regarding the extent of cracking over the intermediate support beam and the company did not take the research any further.

Two full-scale fire tests using Holorib and Ribdeck E60 were carried out at Warrington Fire Research Centre. These modelled 3m spans in the most onerous condition, an end bay. The spans were subjected to an imposed load of 6.7kN/m² and

both satisfied the test criteria for load bearing capacity, integrity and insulation. Grace Construction Products supplied additional information on the behaviour of the fibres at elevated temperatures, derived from tests undertaken at their headquarters at Boston, Massachusetts.

Tests to BS5950 on small scale specimens were carried out at Bath University to evaluate shear resistance. The specimens have two built-in slots designed to induce failure in pure shear when an axial load is applied. From this SCI was able to produce a design equation relating shear resistance to cube strength and fibre dosage. Three dosages were considered, of which the intermediate value of 5.3kg/m³ was found to be the optimum.

Push tests on two sections of composite deck mounted vertically either side of a vertical steel beam were undertaken at Cambridge University to demonstrate the ductility of the welded shear studs and to assess the effect of the geometry of the steel decking. In profiled steel sheeting the geometry of the deck affects the behaviour of the shear connection, and the test allowed an accurate reduction factor, relating the shear resistance of the profiled deck to that of a rectangular slab, to be determined.

This test was carried out in accordance with BS EN 1919 so that it will be applicable to designs to the forthcoming Eurocodes. It showed that both ductility and shear resistance were slightly higher in the fibre reinforced deck than a conventionally reinforced one.

From the test data SCI developed a numerical model which could be extended to other slab conditions and loads.

"Initially we hoped to demonstrate you could reduce the amount of fabric needed," says Dr Hicks, "but the tests showed you could dispense with it altogether. We also proved that you don't need any reinforcing bars to prevent the splitting effect between the deck and the slab."

omitted, as well as loose bars over internal beams, for slab spans and floor loading regimes typically required of this form of construction. The fibres are equivalent to transverse shear reinforcement consisting of T20 bars at 100mm centres. U-bars around shear studs on external beams are the only additional reinforcement needed.

Experience on the Derby project showed that the required quality of finish can be achieved. Techniques such as power-floating can still be used.


Bowmer & Kirkland's Mike Atkinson is enthusiastic about the use of fibres. "Every process has productivity, quality and safety implications," he says. "If you take a whole process out you take out all the implications."

The fact that the fibres are added by the concrete supplier at his plant is a major advantage, says Atkinson: "It's done under their QA process so it's a controlled regime." As much as 10% could be saved from the structural cost, and a huge 25% saving in construction time.

Overall, he says: "Using fibre reinforced floors produced a big programme advantage and a substantial reduction in the time taken to prepare the slab."

Mr Balmer says of the performance on the Derby contract: "We're very pleased. We've learned a lot from this project which we'll be able to build into future ones." He makes the point that it is important to be involved with discussions with the main contractor and flooring contractor about what finish will be required and to make sure the right admixtures are specified. "We're pumping concrete with a high fibre dosage and attention to detail is important," he says. "It's important to pay attention to the business of mix design. We would want to advise on the right admixtures to make sure the concrete is workable and finishable."

He adds that there have been a number of enquiries about the use of the technique from other projects. In summary, he says: "I think it'll make a lot of people's lives easier."



the difference is

The One

When it comes to steel decking, there is only one choice: Richard Lees Steel Decking. No-one has more experience or knowledge. No-one has a bigger commitment to innovation. No-one produces more exciting new products.

And Only

Only Richard Lees Steel Decking has all these products:

Profiles -

- Holorib
- Ribdeck E60
- Ribdeck 80
- Ribdeck AL

Resotec - this innovative new product puts floor vibration in its place. In tests, it reduced vibration by up to 50% compared with standard composite flooring. Whatever steel building you're planning, plan for Resotec.

Safety Nets - having worked at height for over 50 years, this is the first class system we use to protect our own workforce. Now we're making it available for you too.

Strux 90/40 - this exciting new method of concrete reinforcement - produced by Grace Construction - can eliminate the need for mesh and bar reinforcement.

Number One

Who else but the UK number one could give you so much in superior products, service and support. No compromise; no limits - just the certainties of the present and the possibilities of the future.

Richard Lees Steel Decking Ltd

Moor Farm Road West, The Airfield, Ashbourne, Derbyshire DE6 1HD, UK.
Tel: +44 (0) 1335 300 999 Fax: +44 (0) 1335 300 888
Email: rlsd.decks@skanska.co.uk

www.rlsd.com

RICHARD LEES STEEL DECKING



New guide's subdued response factor

Use of the latest design guide on hospital floor vibration has allowed a new Treatment Centre to be constructed in steel to a very tight programme. Jon Masters reports.

FACT FILE

Chichester Treatment Centre
Client: Royal West Sussex NHS Trust
Project Architect: Nightingale Associates
Engineer: Gyoury Self Partnership
Main Contractor: Henry Jones
Steelwork Contractor: F H Dale

Rapid construction of a new Treatment Centre for diagnosis and surgery at Chichester's St Richard's Hospital is on schedule for the first patients to be admitted in April 2005. That the building is being delivered on time owes much to new knowledge of vibration which confirms steel is a viable option for hospital structures.

In designing the innovative structure, consulting engineer Gyoury Self was substantially assisted by the Steel Construction Institute's Dr Stephen Hicks, who provided a pre-publication draft of the new 'Design guide on the vibration of floors in hospitals'. The guide, officially published in February 2004, encouraged the use of steel at Chichester and allowed the centre to effectively demonstrate that steel structures can meet stringent vibration criteria for hospitals both efficiently and affordably.

"The timing was perfect," says Partner Chris Self

of structural engineer Gyoury Self. "We were facing a problem just as Dr Hicks was finishing the new design guide that would ultimately provide the solution. Concrete construction was ruled out early on because the given programme of just 15 months demanded a quicker method of construction. A steel frame was the answer but meeting the existing design criteria meant quite large section sizes."

Vibration is the dominant criterion in hospital design. It is measured by a response factor that compares acceleration on a floor with the 'base value' defined in BS 6472, which defines the threshold of human perception to vibrations. Response factors for hospitals, set to cause minimal disturbance to patients and sensitive equipment, are limited to 1.4 in wards during the night and 1.0 for day- and night-time use in surgical theatres. This compares with a typical response limit for offices of 8.0.



Project Architect Nightingale Associates was given a brief of making the Chichester Treatment Centre a new entrance and focal point of St Richard's Hospital. The response is a dramatic design. The two storey building is a U-shape, 45m wide by 50m deep in plan, wrapped around a 15m wide central atrium. This also leads to the core of the main hospital via a naturally lit corridor that bridges across other existing hospital buildings.

The atrium is an open space to the full height of the building, containing a new main reception area which is topped with a lightweight Texlon cushion roof supported by circular hollow sections. The roof has two skins of self cleaning Texlon, joined to create a pillow effect and inflated by a continuous supply of air to prevent condensation and create a naturally lit space protected from direct sunlight.

Another requirement was provision for future changes of building use. This has been accommodated by use of metal stud work for all internal walls with the exception of wet areas and lift shafts. Additional steel framing has been needed to support lead doors to X-ray rooms and bracing is provided by both diagonal cross-bracing and some portal frames to suit the architectural layout.



- 1 The centre will form a new focal point to St Richard's Hospital
- 2 Slimdek floor's shallow depth left space for services
- 3 New guide allowed steel section depth to be reduced by up to 40%

Gyours Self was initially working to the 1989 vibration design guide SCI Publication 076 for the design of the Chichester Treatment Centre. The firm had selected Corus' Slimdek steel and concrete composite floor system for the two and three storey structure.

"Slimdek enables fast track construction and its relatively thin overall depth, of 335mm at Chichester, gives a lot of flexibility for services, which was essential as a performance specification had been set for the M&E works," Self says.

"It also requires no additional fire engineering for one hour fire resistance and Slimdek's in situ concrete slab provided sufficient mass to meet the desired vibration response. On an elemental basis, though, the guidance current at the time demanded heavy asymmetric steel beams to adequately stiffen the floor."

"We had a scheme that worked but did not present cost effective use of the steel," says Gyours Self Senior Engineer David Simmonds. "That was until Corus put us in touch with Dr Hicks who gave us a draft copy of the new guide. This permitted us to reduce section size by about 40% overall and get rid of some intermediate beams altogether."

The timing dates back to the spring of 2003 when the new design guide was in draft form after five years of work at the SCI dedicated to updating Publication 076. The research included dynamic testing of existing hospital floors with various structural steel arrangements. After determining the walking pace that produced the biggest floor response, controlled walking tests were performed to assess principal response factors.

Comparison with acceptance levels in the NHS performance standard Health Technical Memorandum 2045 followed and the steel composite floors were found to be well within minimum vibration requirements.

Writing the new design guide was the next step, working back from the response test results to

refine analytical modelling of the floors' dynamic properties. The resulting guide was published in February 2004. Crucially, it advises assessment of whole floors as an extension of the traditional practice of checking individual elements.

This was the critical difference made to the Chichester scheme. Simmonds says: "Dr Hicks modelled the whole floor in one hit using some quite sophisticated finite element software. This took the analysis one important stage further and backed up what the guide produced, which was an affordable design that met the vibration criteria."

Confirmation of Gyours Self's new design was the green light for the Chichester Treatment Centre. Work started on site in October 2003 with erection of the steel frame beginning in January 2004. "Main contractor Henry Jones was casting floors by the February, which shows how quickly the steel went up," says Simmonds. "The load-bearing masonry of an adjoining catering building was still only just coming out of the ground."

Construction had to progress rapidly. Client the Royal West Sussex NHS Trust wanted the Treatment Centre to be accepting patients by April 2005 to improve service and waiting times.

The £12M Chichester Treatment Centre is one of around 15 currently being built as part of a national NHS building programme aimed at meeting Government waiting list targets. Treatment Centres are a vital part of the drive for more reliable treatment programmes because they will only provide routine diagnosis and surgery, without interruption from the demands of accident and emergency.

With several months of fit-out and equipment commissioning involved before the Chichester Treatment Centre could be declared open, a main construction programme of just 15 months was set. Henry Jones' contract includes fit out of services and the contractor was able to start this towards the end of 2004, with more than a little help from the result of five years of steel vibration analysis.

VIBRATION TESTS

Results of real tests on real hospital floors have shown how well steel framed composite construction performs against the strict NHS vibration criteria. Limits set down in the Health Technical Memorandum 2045 are easily met by long-span composite beams of the type used so extensively in UK offices.

The longest span tested so far is 15m supporting a 175mm slab, which produced a response factor of 0.49 and a fundamental frequency of 7.6 Hz. This design provided enormous flexibility of the space below and a floor that comfortably met the required response factor of 1.0.

Steel frames are now the standard in the health sector and these are being chosen for their economy and efficiency. Now that it has become well known how easily standard steel floor designs meet vibration criteria, steel is being chosen for the speed and quality of build and the flexibility generated by long spanning solutions.

Logistics centre rises rapidly



FACT FILE

G.Park Bedford

Client -

Gazeley Properties

Main Contractor -

UK GSE Limited

Architect -

Chetwood Associates

Structural Engineer -

Roscoe Capita

Steelwork Contractor -

Atlas Ward Structures Limited

A mammoth distribution shed being erected in Bedford demonstrates the growing market demand for large logistics centres

Close working relationships between the members of a regular team helped Atlas Ward Structures fabricate and erect a massive 1500-tonne distribution shed in just 13 weeks.

The 42,000m² G.Park Bedford is one of a number of centres being developed by Gazeley Properties across five UK sites. The completed building was handed over to the client in November.

The speculatively-built structure consists of four 29m portal frames and overall is 360m long, 116m wide and has a clear height of 15m. Its location in Bedford gives it good strategic links via both the M1 and the A1.

Atlas Ward Structures Engineering Manager Jim Martindale says the project was technically relatively straightforward: "The challenge was in the turn-round time," he says. "From receipt of order to handover we had 13 weeks: seven weeks' fabrication and six weeks' erection."

It was possible to achieve this speed through experience on other contracts, Martindale said. The project was one of a number of recent design and build contracts it has carried out with the same team. This comprises Gazeley, main contractor UK GSE, consulting engineer Capita Symonds, architect Chetwood Associates and quantity surveyor W H Stephens. GSE is responsible for the design and construction of logistics facilities developed by Gazeley throughout Europe, specialising in the construction of bespoke, turnkey buildings.

"The benefit of working with familiar faces is that we know what the client wants. This eliminates variations and helps us to achieve a fast

programme," says Martindale.

Estimating Manager Ian Rackham adds: "As Gazeley use the same two or three architects and engineers on a regular basis, the teamwork approach works a treat.

"The flow of information is always a difficulty on construction projects, so the benefits of keeping the same team together from one project to the next are clear for all to see. For example, using the same details at eaves, valleys or doors can chop out long periods of time waiting for details to come through, which ultimately improves both the lead-in time and the overall programme period."

Rackham says there is still scope to make the process even more efficient, which will benefit the Gazeley team and create repeat business from other key clients.

The market for large distribution sheds of around 20,000m² to 80,000m² is growing. Atlas Ward built around 15 in 2004 and demand appears to be continuing into the first half of this year, Rackham says.

This reflects healthy growth in the industrial sector generally, fuelled by the rise in consumer spending. Atlas Ward's industrial portfolio rose 85% to £29M in 2004.

Gazeley, a subsidiary of WalMart which specialises in developing distribution property, has 12% of the UK market and has developed over 2,000,000m² of space in the UK in the last 15 years. This includes Europe's largest dedicated distribution park, Magna Park in Leicestershire. It has started to introduce the concept across Europe where it plans to develop 30 logistics parks, based on the Magna Park model.



TEKLA Structures



"From the onset of using Tekla Structures, it was apparent that no other detailing package could compete. Moving from wire frame modelling to solid modelling was the biggest advantage."

David Ball – Detailing Group

"We've been 3D detailing in wireframe for about 4 years and switched to Tekla Structures this year. We haven't looked back...the drawings are just so much better, our workshop loves them"

Vic O'Mara – Marton Engineering Services

"We felt our existing software was not developing quickly enough or the way we expected – actually it had almost ground to a halt! We switched over [to Tekla Structures] once we saw the multi-user and multi-material capabilities... we are able to detail much faster now."

James Sutcliffe – Sutcliffe Construction

> We couldn't have said it any better!

Are you still using an older software package for your steel detailing? Is it time you invested in new technology that can boost your productivity and secure your future?

> Here's your opportunity to 'test drive' Tekla Structures for yourself, FREE of charge.

Call now to book your place on our no obligation, no cost evaluation training course* and see how your business can benefit from Tekla Structures.

We have two courses available during February and March 2005. Spaces are limited so call now to avoid disappointment. We can also provide on-site hands-on demonstrations at your offices.

Some say Tekla Structures training is priceless – you can say it was free.

**TEKLA®**

www.tekla.com

Tekla (UK) Limited

Tekla House, Cliffe Park Way, Morley, Leeds, LS27 0RY, U.K.

Tel. +44 113 307 1200 Fax +44 113 307 1201

*Conditions apply. Call for details.

Model and photograph supplied by Sutcliffe Construction Ltd. www.sutcon.co.uk



Bridges breakthrough

Steel overbridges are increasingly appearing on major new highways where once concrete dominated. Nick Barrett analyses the factors behind changing trends in the key part of the bridge market in the UK.

Steel has been the economic solution for medium and long span bridges since the mid 1980s, but for short span bridges on greenfield sites in particular steel has struggled — until now. Steel was typically used on only a limited number of locations, for example where its advantages of speed and ease of installation came into their own. New procurement routes like Design & Build, Private Finance Initiative and Early Contractor Involvement are giving contractors a greater say in the choice of structural material, and with greater freedom to select steel, many are taking that option.

Price is partly the reason. Steel has become more competitive. Main contractors have a detailed knowledge of the relative economics of steel versus concrete and a good understanding of project costs, which are lower for steel. Also, the Highways Agency has started taking speed of construction into account in assessing tenders, which also brings steel to the fore.

Traditional views that steel bridges involved greater whole life costs are being revised. Thanks to a relaxation of Highways Agency standard minimum headroom requirements for weathering steel road overbridges, low maintenance weathering steel is being selected for an increasing number of locations. Another reason for the improving whole life cost profile of steel bridges is that there have been significant advances in coating technology: the latest coating

systems are expected to have a working life in excess of 40 years.

Steelwork contractors say steel is increasingly appreciated for ease of maintenance — and concrete is no longer regarded as quite the maintenance free material it once was. The condition of steelwork can be easily viewed, giving bridge owners the reassurance that all is well. Any problems are readily apparent, and can swiftly be addressed by repainting. The first sign of problems with concrete bridges is often spalling due to the expansive forces created by corroding reinforcement bars.

The privately financed Birmingham Northern Relief Road, now the M6 Toll, was a major success for steel, where concrete might have been expected to capture most of the work in the past. All the 46 overbridges here are in steel — 10 years ago steelwork contractors would have expected to get hardly any business on a new motorway. The M6 Toll is significant primarily because steel composite bridges were chosen even though it was a “greenfield” site, which traditionally favoured concrete bridges.

“There were no overbridges on the M6 Toll in concrete at all, other than an extension to an existing bridge which was built in concrete some years ago,” says steelwork contractor Fairfield Mabey’s Managing Director Dr Peter Lloyd. “We have always thought that bridges with spans of over 25m should be in steel for economy if nothing else,

Steel composite construction is increasingly favoured for ease of construction when crossing live carriageways or difficult terrain as seen in the A1(M)/M62 interchange at Ferrybridge, above, and Pont Dewi Sant and the new Swale crossing, opposite.



Steel was chosen for the recently completed £38.5M Chieveley A34/M4 junction 13 improvement contract, awarded to design and build contractor Costain with designer Mott MacDonald. It is believed to be the first contract where the Highways Agency assigned a monetary value to speed of construction in assessing tenders. It is also one of the first projects to benefit from the Highways Agency's reduction in the minimum headroom for weathering steel girders over roads from 7.5m to the standard 5.3m.

The contract includes five steel overbridges carrying A34 slip roads and a local road which crosses the A34, all of steel composite construction using weathering steel, despite having been shown as concrete in the illustrative design on which tenders were based. David Place, Project Engineer in Mott MacDonald's bridges department, says: "We had to come up with the lowest capital cost, the lowest whole life cost and a solution that would be quickest to build. Without a doubt, for a bridge over a motorway or dual carriageway, for a two, three or four span structure 40m to 100m in overall length, we regard steel composite as the market leader."

A key reason for the growing popularity of steel is that steel decks can be quickly lifted into place during limited carriageway possessions, whereas concrete needs a lot of scaffolding which effectively closes carriageways for extended periods. Even on greenfield sites where lane closures are not a factor, steel appeals because it allows haul roads to be kept open during bridge construction. The main steel for each bridge was erected in under a week.

Place said the Highways Agency's reduction in the minimum headroom requirement for weathering steel beams over roads means weathering steel can compete on more equal terms. The old 7.5m headroom, based on fears about the effect of de-icing salt spray, meant higher earthworks and significant add-on costs.

Dr Lloyd says: "Steel bridges can also be strengthened to meet changing needs easier than concrete bridges. In the event of a bridge-bashing incident steel girders will deflect and can be put back on line using a process of heat straightening. But in a concrete bridge the edge beam may need to be completely replaced if a tendon is broken."

but on the M6 Toll we saw bridges with spans as short as 20m. We are seeing this trend throughout the country and not only on PFI projects."

Dr Lloyd says choice of steel is being increasingly justified by a range of factors, including price, whole life cost, ease of installation and because of recent technical breakthroughs in coating technology and steel fabrication. Price is still quoted by designers and contractors as a deciding factor, despite recent steel price rises. "There is a lot of steel even in a concrete deck," says Dr Lloyd. "A typical steel bridge might contain 326t of steel while a reinforced concrete one still has some 226t. Rebar prices have risen over the past year, with the percentage rise far exceeding that for the steel plates that are normally used for bridge fabrication, and the concrete industry has issued further price warnings recently due to rising energy and raw material costs. Consequently, the competitive situation remains largely unchanged."

It is difficult to compare prices due to the difficulty of comparing like with like. "Until very recently, there have been no reliable figures for the market share of steel versus concrete bridges, and no long term evidence of price trends specifically for bridges has been collated," says Chris Dolling of Corus. "But we can use structural steel versus in situ concrete figures as reasonable proxies. Although these relate to buildings rather than bridges, they come from a neutral source, the Department of Trade and Industry.

"These figures show that concrete construction prices have risen by 20% more in real terms than steel over the past ten years or so, despite the recent steel price rises. Today's structural steelwork prices are the same in real terms as they were in 1995."

A market survey produced for Corus by Construction Markets shows that in 2003, in terms of deck area, steel accounted for 88,900m² out of a total of 165,000m², with 23,000m² precast and 53,300m² in situ concrete. Dolling said: "We do not have comparable figures for earlier years but the figures confirmed to us that steel has made a major breakthrough into the market for road bridges."

Technical breakthroughs have also enhanced the prospects of steel. For example, says Dr Lloyd, being able to curve steelwork in plan without cranked joints is a major development in bridge fabrication of the past five years. "This gives two major advantages, firstly by significantly improving the aesthetic appearance of a structure as all of the main structural members can form smooth curves throughout its the entire length; and secondly, the construction of a typical concrete composite deck is much simpler, allowing a standard size of precast "Omnia" planks and a standard edge cantilever formwork system to be used throughout. There may be some additional costs associated with the steelwork fabrication and erection, but these are far outweighed by the savings in the deck construction."



STEEL ensures economical design

First fruits of a unique, pan-European effort to help designers use the new Eurocodes will be going online later this year. David Fowler reports on progress.

The introduction of the Eurocodes in a year's time will herald a fundamental change in the way buildings are designed. Though there will be a transition period until 2010 before the old codes are withdrawn, public sector clients could insist on the use of the Eurocodes from day one.

The Institution of Structural Engineers identified provision of guidance for designers on using the codes as an urgent priority in a report this year to the Office of the Deputy Prime Minister. It called for government support to help industry develop the relevant documents.

But the steel industry is already addressing the problem. A unique pan-European initiative, STEEL (a Supranational Tool for the Enhancement of the Eurocodes on-line), will provide simple to use web-based information to help construction teams design effectively to the new codes.

The project is being led by the Steel Construction Institute, with steel information centre partners in France (CTICM), Germany (RWTH Aachen), Spain (Labein) and Sweden (SBI). The project is 50% funded by steel producers, led by Corus and Arcelor, and 50% by the European eContent programme. CSC (UK) and e-Training International (Ireland) are also partners. SCI is responsible for information technology management.

Steel designers already have more on their plate than those using other materials. Not only will there be more parts to the steel Eurocode, covering specialist structures such as bridges, masts, silos and pipelines. Designers will also have to refer to more sources of information than in the past.

"To design a low-rise office building to Eurocode 3 could require 34 documents," says Dr Graham Owens, Director of the Steel Construction Institute and Technical Co-ordinator for STEEL.

Traditionally, UK codes of practice such as BS 5950 were intended to be essentially complete design guides. The Eurocodes omit anything considered 'text book material' — such as calculating the critical stress for a frame. The idea is that such information will be included in guidance documents written by the industry and approved by the BSI in the UK, referred to as 'non-contradictory complementary information' or NCCIs.

Other parameters are not specified in the codes, but are to be determined nationally and set out in National Annexes to the codes, which the Office of the Deputy Prime Minister has commissioned the BCSA and the SCI to write. These include deflection limits, factors of safety (see News) and even the effective length of columns, on which the drafting committee could not agree.

The STEEL website aims to fill this information gap, at the same time as taking account of national variations. By making simple design guidance available, it also aims to dispel the myth, current in many European markets, that steel is more complex or specialist than concrete.

"It's cheaper to design in steel than concrete in the UK because so much help is available. That's not true in the rest of Europe," says Dr Owens. "And the leap from most national standards to the Eurocode is bigger for steel than for concrete. The



Avant garde: Terrell International (Partner John Hanlon, left) woke up the French market to steel with buildings such as Le Colisée (below) and La Sequana (right)




Paris-based structural consultant Terrell International, founded by British engineer Peter Terrell, has been instrumental in gaining acceptance for steel-framed buildings in a market where concrete previously dominated. Once developers saw the market's eagerness for offices with large column-free spans steel began to make an impact.

France had no code of practice for composite design until the draft Eurocode ENV 1994 was introduced in the mid-1990s. This enabled Terrell to pioneer composite floors in 1994's Le Colisée. Partner John Hanlon says: "The use of ENV 1994 on composite construction was a key factor in the more widespread acceptance of steel frames in Paris in the 1990s. Careful implementation of the full Eurocodes could create major opportunities for growth in the use of steel in construction elsewhere in Europe."

SCI's "mind maps" summarise barriers to use of steel and where information was lacking

Symbol	Meaning	Code
	Impossible to find information	Barrier to promotion
	Information can be found	Neutral
	Information easily found	Promoter issues



SCI Director Dr Graham Owens: new codes omit "text book material"

threat is that if people don't make the transition there is a risk of losing market share to concrete."

He adds: "I think that in this country we'll do what it takes to make sure the tools are around for engineers to design effectively. In the rest of Europe the steel market is less strong and there is less investment in design aids, so there is more risk."

Conversely, the opportunity exists to make big inroads into overseas markets where steel has a much lower share of the market than in the UK. There is also the opportunity to encourage technology transfer. Composite construction, for example, was virtually unused in France until the draft Eurocode ENV 1994 was published in the mid-1990s, because there was no French code for composite design.

STEEL is concentrating on four areas of design: multi-storey buildings; industrial buildings; residential construction; and cost-effective fire performance. The website will go live with the first of these around the middle of next year, with the others following over the next two years.

There has been extensive consultation with potential users. "The overriding message to us was: we want you to keep the guidance simple, not too academic," says Christine Roszykiewicz, SCI International Co-ordinator and STEEL Project Manager. There will be three levels of information. Level one will include concepts and case studies and will be aimed at clients as well as designers. Level two will be design development information both for architects and engineers, covering topics such as building layout. Level three will be detailed design information for the engineer.

A user-needs analysis workshop involving 100 structural designers from 21 countries held in Brussels last July was used to decide what information STEEL should provide. After briefings on the codes, delegates split into groups for each of the areas of interest — residential, industrial and office buildings. Fire safety engineering was a feature of all three groups. It is such an important topic in continental Europe that it was subsequently decided to treat it as a separate application.

The groups identified stakeholders in each country, including members of the supply chain, and produced flow charts to summarise the design process. It was "a pleasant surprise" to find that these came out pretty similar in each locality, says Dr Owens.

The groups then considered what information clients and contractors needed and what factors

were barriers to or promoters of the choice of steel. Flow charts or "mind maps" identified these factors together with an assessment of how much information was available about each. The intention is that STEEL will concentrate on the areas, whether promoters or barriers, where information is lacking.

Because it would be impossible to provide all the information identified, delegates were then forced to prioritise it. The mechanism was to assign notional monetary values to each parcel of information, with everything on offer adding up to 1500 monetary units. The delegates were given 600 units to 'spend'.

The delegates' choice was simplified information for the design of a complete building, to guide designers through each step in the sequence. It was to be harmonised across Europe and was to include worked examples, NCCIs, flow charts of the design process and guidance on using the Eurocodes for specific applications.

SCI and its partners are now at work to produce this. Information for multi-storey office buildings is most advanced and is on target for the planned website launch this summer. Guidance on industrial buildings, residential blocks and fire engineering will follow over the ensuing year.

The database will be translated into the EU's four main languages — English, French, German and Spanish. A pan-European steering committee will ensure it takes account of local variations.

Each piece of information on the website will be tagged to show whether it is completely harmonised across Europe, or where there are national deviations. Users of the database will have registered the country in which they are working at the outset and when they conduct a search, only items relevant to their locality will come up. Country representatives on the steering committee will be able to say how they want each piece of information flagged. So an item which does not apply in Spain, for example, could either be completely ignored by the search engine or brought to the user's attention with a comment in Spanish attached if that is thought appropriate. In due course the website could be translated into other languages, though that is beyond the scope of the current project.

Funding for the current project runs to June 2006, but Mrs Roszykiewicz says: "We will be disappointed, if the project is as successful as we expect, if there is not interest within the steel industry in adding further content after that."

The Eurocodes are coming... but does the steel know?

Steel's fundamental behaviour is unchanged by the advent of the Eurocodes, and under the surface of the new documents there is much that should be familiar, says SCI Deputy Director David Brown

Plenty of articles are starting to appear about the imminent arrival of the Eurocodes. From the Government down, there is an awakening of interest. In the constructional steelwork sector, projects are in place to support the implementation of the Eurocodes across Europe, and closer to home, detailed guidance for the UK is under way.

But, of course, no-one told the steel. Steel's behaviour is entirely independent of any code — it obeys the laws of structural mechanics, whatever a national standard might say. The Eurocodes cover the very same structural mechanics as our own British Standards, so we would not be surprised to find that capacities (or resistances, in Euro-speak) are quite similar. We would also not be surprised to find that the approaches in, say, BS 5950, are often mirrored in BS EN 1993 (or EC3 for short) — although the methods are cunningly disguised to look different. Remove the disguise, and the methodology often looks comfortably familiar. This article looks at just some of the significant technical areas in the Eurocodes, and tries to show that for BS 5950 designers, it's not a step change to the Eurocodes. BS 449 designers take note...

Load combinations

The load combinations in EC3 look different, with an abundance of unfamiliar symbols, and we will find them to be different, especially as our familiar friend of 'gravity loads only' will have disappeared. The 'gravity load combination' will include some wind load, albeit with a reduced load factor. This is how the Eurocodes approach load combinations — with varying mixes of imposed loads. Thus one case will include full floor loads combined with reduced wind loads, while another will include full wind loads but reduced floor loads.

For further finesse, you could choose to combine higher factors on the dead (or permanent in Euro-speak) loads with lower factors on the imposed loads, and a second combination with lower factors on the permanent loads and higher on the imposed loads. Until the all-important National Annex is published, there is little point in speculating on what the factors will be, but considering different combinations is unlikely to challenge the Eurocode designer.

Brittle Fracture

The Eurocode approach does follow a different approach to BS 5950. We are all familiar with looking at the state of stress, and the stress raisers

present in the steelwork to give a K factor from Table 3 of BS 5950. (At least we should be — but the vast majority of designers leave this important area untouched.) In BS 5950, we can then choose an appropriate sub-grade, depending on the thickest element and the service temperature. The approach in the Eurocode is to calculate a notional 'reference temperature', which is colder than the lowest air temperatures, and depends on the state of stress, strain rate and so on. For colder reference temperatures and thicker elements, a tougher steel sub-grade is required. Again, until the National Annex is published, direct comparisons with BS 5950 cannot be made.

Notional Loads and Sway Stability

One day, designers will thank the authors of BS 5950-1:2000 for introducing issues of sway stability with clarity into the national standard. Without such an introduction, the frame stability clauses in EC3 would be quite new — as it is, they appear as familiar friends. EC3 advises that frame imperfections must be modelled, and offers the diagram shown here as Figure 1.




Figure 1. Modelling of frame imperfections.

Fortunately, the Eurocode also says that instead of modelling the frame with a real out-of-plumb, equivalent horizontal loads can be used. Here a sense of comfort takes over, as the equivalent horizontal loads are 0.5% of the factored vertical loads — our very own Notional Horizontal Forces (ie NHFs) in BS 5950. One interesting difference is that the Eurocode insists that NHFs are included in every load combination — whereas in the UK we only apply them in the 'gravity load only' combination. Many times, delegates on SCI courses have pointed out that the UK practice implies that frame imperfections switch themselves off when the wind blows. Our UK NHFs are so much more intelligent than their continental cousins, we reply.

Having just got used to measuring frame



SCI Deputy Director
David Brown




Figure 2. Diagram of shear areas

stability by λ_{cr} we must change to α_{cr} and a slightly different calculation. But the difference is modest, and becomes insignificant in most buildings – so our structures do not suddenly become unstable. The Eurocode offers various other degrees of finesse in calculating the equivalent horizontal loads, depending on column height (“they can’t lean that much all the way up”) and numbers of columns (“they can’t all lean over like that”), which do look rather enticing to pursue. This can be helpful in reducing the lateral loads to be carried by bracing, for example. The reduced equivalent imperfection loads might also look attractive when calculating α_{cr} . Investigating this for a recent course, however, we discovered that though the reduction looks attractive, the eventual impact in an amplification factor (equivalent to k_{amp} in BS 5950) was a difference only at the third decimal place. C’est la vie!

Member resistances

It is not surprising that the resistance of a steel section is well understood, after all these years. Section classification is a modest change, but cleverly disguised by new symbols and changes to, for example, how outstands are measured. The familiar plastic, elastic and effective moduli are used for bending resistances. Shear and torsion are covered, and become new and exciting when found in combination with bending. Many unfamiliar equations are available. At the simpler end, shear resistance of a rolled section is no longer based on an area of web \times depth, but is instead presented as an area which is less than full depth, but includes the root radii and half the flange (see Figure 2). The difference must be tiny!

Member buckling

Again, since Euler discovered the basic rules of column buckling, we have understood the structural mechanics. Unfortunately, slightly different understandings have been adopted throughout Europe, and agreement on a unified set of checks has been difficult to reach. Whilst the calculated resistance may be very similar to the value according to the BS 5950, the approach in the Eurocode will take some time to become familiar.

Axial Compression

Instead of calculating a p_c value (in BS 5950), the Eurocode approach is to have a reduction factor on the design strength. Thus in S275 steel, a p_c value of 100N/mm² will appear as a reduction factor of $\chi = 100/275$ or 0.36.

Slenderness is also presented differently, as we are used to $\lambda = l/r_y$. In the Eurocode, we will meet $\bar{\lambda}$, which is approximately $\lambda/90$. Instead of a $\lambda = 50$ or $\lambda = 180$ to BS 5950, we will become used to $\bar{\lambda} = 0.5$ or $\bar{\lambda} = 2$. Despite

Which is the ultimate proven purlin profile?...



BESPOKE STRUCTURAL SECTIONS FROM...



sectionbending

inductionbending

pressbraking

platerolling

pipeforming

spiralbending



The **ANGLE RING** Co Ltd

Tel: +44 (0) 121 557 7241

Email: sales@anglerring.com


Fax: +44 (0) 121 522 4555

Web: www.anglerring.com

for ALL your bending needs...

Corrosion Protection

Bodycote
METAL TECHNOLOGY



Sherardizing, a Zinc based heat diffusion process forming a hard Zinc/Iron Alloy surface on metal components has been available in the U.K. for over 80 years.

Even so many Engineers are not aware of the unique properties and advantages that this process offers to improve corrosion protection in access of Galvanised product.

Please take this opportunity to discover how Sherardizing can improve corrosion protection and damage resistance of your components by sending for a **free text book**.

For further information please contact:

Bodycote Metallurgical Coatings Ltd.

Shakespeare Street, Wolverhampton, WV1 3LR

Tel: 01902 452915 Fax: 01902 352917

Email: sales.bmc@bodycote.co.uk

www.sherardizing.com

www.bodycote.co.uk



◀ 27

the different numbers, the buckling curves are almost identical.

Lateral Torsional Buckling

In much the same way as flexural buckling, we will calculate λ_{LT} instead of λ_{LTB} and find a relationship as shown in Figure 3.




Figure 3. Lateral Torsional Buckling Curves

The form of the curves in Figure 3 is familiar, and once we become used to calculating λ_{LT} and finding a reduction factor, χ_{LT} , rather than a bending strength, we will not notice the difference in the final result.

Combined axial and bending

Here be dragons! There is a host of possibilities here, with increasing degrees of deviousness in the calculations. At this stage, it is difficult to predict which approach the National Annex will recommend, and what simplifications may be possible.

This article has looked briefly at a few of the significant technical changes that will appear in the Eurocodes. More detailed articles will follow over the next couple of years, and once the Eurocodes are introduced. In summary, the presentation will be different, and there will be a different approach in some areas, but the calculated resistance will look familiar. If something suddenly becomes half as strong, assume you have made a mistake!

The Institute is running regular courses for those keen to understand the Eurocode approach. Details can be found at www.steel-sci.org/education/ and in the events diary on Page 10

...ours!

Metsec zed,
the ultimate
purlin profile

Everyday, people
build on Metsec
zed purlins
...Here's why!

- Flat flanges make for consistent secure fixings with maximum bearing area... there are no crinkles, wrinkles or ribs to deflect screws or minimise bearing area
- Square flat web makes for easy access fixing, simple connections and erection... with no complicated offsets or cranks to worry about
- Minimum 1.3mm gauge ensures robust site fixings... and minimal site damage

For more information or to discuss your requirements
call us now on

0121 601 6000

METSEC

voestalpine

Broadwell Road, Oldbury, West Midlands, B69 4HE. Fax: 0121 601 6121 www.metsec.com

METSEC
BUILDING PRODUCTS

PurlinDivision

AD 278

Changes to the Building Regulations and Approved Document A3 Disproportionate Collapse — Interim Guidance on the use of BS 5950-1: 2000

This AD provides interim guidance in dealing with the changes to Section A3 of Approved Document A – Structure (2004 Edition) in connection with the England and Wales Building Regulations. The changes came into effect from 1 December 2004. Section A3 has been completely rewritten and should be studied. The main change is that the regulation now applies to all buildings, including those of less than five storeys. Now, all buildings have to be classified according to one of effectively four building classes, 1, 2A, 2B and 3. The forthcoming amendment to BS 5950-1 will revise Section 2.4.5 to be compatible with the changes in Section A3 of Approved Document A

– Structure (2004 Edition). However, proposals for the revision of BS 5950-1 must first be issued for public comment before being accepted and this process may take some time.

In the meantime the SCI recommends that:

- Hot-rolled-steel framed buildings classified as 1 or 2A should be designed to Clause 2.4.5.2 of BS 5950-1: 2000.
- Hot-rolled-steel framed buildings classified as 2B should be designed to Clauses 2.4.5.2 and 2.4.5.3 of BS 5950-1: 2000.
- Hot-rolled-steel framed buildings classified as 3 should be designed to Clauses 2.4.5.2 and

2.4.5.3 of BS 5950-1: 2000 in addition to resisting the design conditions that can reasonably be foreseen as possible during the life of the buildings, to the extent that collapse is not disproportionate to the cause. Approved Document A requires that these design conditions be identified by a systematic risk analysis of normal and abnormal hazards.

Contact: Thomas Cosgrove
Email: t.cosgrove@steel-sci.com
Telephone: 01344 623345

AD 279

Brittle Fracture

This AD gives the limiting thickness t_l (mm) for plates, flats and rolled sections for S275 JR and S355 JR material that are expected to be included in the forthcoming amendment to Table 4 (K=1) of BS 5950-1.

The prohibition of the use of S275 JR and S355 JR material in external conditions has caused much comment since the release of BS 5950-1:2000. Hence the code committee has been working on the issue for some time. Relaxations for t_l values in normal temperature conditions in BS 5950-1:2000 have been proposed as shown below but they will not revert to the thickness in the 1990 standard.

Readers should remember that the forthcoming

Table 1 Limiting thickness t_l in mm for K=1

Standard	Normal Temperature		Lower Temperatures
	Internal	External	
BS EN 10025	- 5°C	-15°C	
S275 JR	36	15	0
S355 JR	25	11	0

amendment must first be issued for public comment and the above values may change. However, the SCI advises that the values in Table 1 should be used for design in the interim.

Contact: Thomas Cosgrove
Email: t.cosgrove@steel-sci.com
Telephone: 01344 623345

**Nationwide delivery service
of all Structural Steel Sections**

RAINHAM

Phone: 01708 522311

AD 280

Structural Integrity of Light Gauge Steel Structures Building Regulations Approved Document A (2004)

The England and Wales Building Regulations and Approved Document A have been revised. The new revision came into force on 1 December 2004. Section A3 has been completely rewritten and should be studied. The main change is that the regulation now applies to all buildings, including those of less than five storeys. Now, all buildings have to be classified according to one of effectively four building classes, 1, 2A, 2B and 3. The forthcoming amendment to BS 5950-1 will revise Section 2.4.5 to be compatible with the changes in Section A3 of Approved Document A – Structure (2004 Edition). However, proposals for the revision of BS 5950-1 must first be issued for public comment before being accepted and this process may take some time.

BS 5950-1:2000 is the structural steelwork Standard referred to by Approved Document A, but this is not directly applicable to the design of the majority of light gauge steel structures. Recommendations for light gauge frames are available in:

1. BS 5950-5:1998 Structural use of steelwork in building – Code of practice for design of cold

formed thin gauge sections, in Clause 2.3.5 Structural Integrity

2. SCI publication P-301 Light Steel Framing in Residential Construction, in Section 2.1.5 Robustness of light steel frames.

P-301 was written to satisfy the England and Wales Building Regulations in force before the 2004 revision. It gives more extensive guidance than BS 5950-5:1998, including design loads for splices in vertical members, removal of elements and the design of key elements. As interim guidance, the SCI recommends that designers use P-301 to satisfy the 2004 regulations for light steel frame buildings, applying Section 2.1.5 as follows:

- Buildings of Classes 1 and 2A: only paragraphs (1) to (4) and (11) need be applied.
- Buildings of Class 2B: paragraphs (1) to (11) should be applied.
- Buildings of Class 3: paragraphs (1) to (11) should be applied as a minimum design requirement. In addition, Class 3 buildings should be designed to have a structural form that reflects the critical conditions that can

reasonably be foreseen as possible during the life of the buildings, to the extent that collapse is not disproportionate to the cause. Approved Document A requires that these critical conditions be identified by a systematic risk analysis of normal and abnormal hazards.

Designers choosing the “removal of columns” option in Section 2.1.5(8) should note that the 2004 Approved Document A necessitates a change from P-301. Clause 5.3 defines the length of external steel stud wall that must be considered to be removed as “the length measured between vertical lateral supports”. For internal steel stud walls, the length considered to be removed remains 2.25 times the storey height.

Where buildings combine both hot rolled and light gauge construction, designers are advised to use a logical combination of the recommendations of this AD and AD278.

Contact: Charles King

Email: c.king@steel-sci.com

Telephone: 01344 623345

S275 & S355 GRADES STEEL

Fax: 01708 559024

Email: sales@rainham-steel.co.uk

Universal Beams
& Columns

•
Parallel Flange Channels


•
Equal & Unequal Angles

•
Hot Finished
& Cold Formed
Structural Hollow
Sections

•
Mild Steel Plate

40 Years Ago in

BUILDING WITH STEEL



The VC10 Hangar at London (Gatwick) Airport


When British United Airways purchased Vickers VC 10 jets the dimensions of these machines, particularly the height of the tail, made it necessary to provide a new hangar to accommodate them for servicing purposes. It is a steel framed building with double sandwich asbestos cladding

and no other material other than steel could have been employed with such success.

The hangar is unique in that it is possibly the largest of its kind in the United Kingdom, and perhaps in Europe. Although it has a floor area of approximately 33,000 sq. ft. only two internal

columns are used and they are positioned to give minimum interference to the various type of craft likely to be parked inside. An interesting feature is the provision of a slot in one side wall through which a wing of a second aircraft can project, allowing the complete fuselage to

be under cover during servicing. By careful planning it has been established that the hangar can in fact house at least three machines simultaneously, e.g. a VC 10 in the centre and a Britannia or a BAC One-Eleven on each side.



Steel framed hangars for the Middle East

During recent years the Air Ministry has placed orders for a number of large steel-framed hangars for destinations abroad. For this type of work steelwork has several important advantages over other methods of construction, apart from those concerned with design. For instance the structural members can be completed in this country, ready for erection, and occupy minimum cargo space when shipping them abroad. On arrival the hangars can be conveniently transported and easily erected on site by local semi skilled labour.

Composite Construction

Recently, a Joint Working Party of the Ministry of Public Building and Works and the British Constructional Steelwork Association has been studying the economic design of multi-storey steel-framed buildings. A complete and factual survey of the investigations into 10-storey office blocks is contained in the paper entitled 'Composite Construction' presented by Mr. L. R. Creasy, O.B.E., B.Sc., M.I.C.E., M.I.Struct.E., Deputy Chief Civil Engineer of the Ministry at a meeting of the Institution of Structural Engineers in London on 10th December 1964.

Both in his paper and at the meeting Mr. Creasy emphasised the advantages to be gained from the use of high yield stress steel and from modern design techniques such as composite construction, ultimate load design and lightweight fire encasement. That these procedures result in designs which make steel highly competitive with other constructional media is evidenced by the fact that the ministry has decided to use structural steelwork for a number of important new Government buildings now under construction.

Increasing Use of Steel in Country's Housing Programme

The use of steelwork for domestic housing is increasing so rapidly that its demand upon the heavy steel industry is likely to be a major factor in the anticipated 50 per cent increase in the

use of steel in the Construction Industry by 1970.

New systems for dwelling houses with steel frames are now available which combine speed of erection with economical cost.

One typical system devotes just one hour for the erection of the steel frame. Six men can finish a pair of semi detached houses of this type and have them ready for occupation in 14 days. An

880-sq. ft. three-bedroom house costs from £1,900 to £1,950; a 950-sq. ft. three-bedroom house, £2,350.

New and Revised Codes and Standards

(from BSI Update October 2004)

BS EN PUBLICATIONS

The following are British Standard implementations of the English language versions of European Standards (ENs).

BS EN 1011:

Welding. Recommendations for welding of metallic materials

BS EN 1011-7:2004

Electron beam welding
No current standard is superseded.

BS EN ISO 15609:

Specification and qualification of welding procedures for

metallic materials. Welding procedure specification.

BS EN ISO 15609-4:2004

Laser beam welding
Supersedes BS EN ISO 9956-11:1997

BS EN ISO 15609-5:2004

Resistance welding
No current standard is superseded.

BS EN ISO 15612:2004

Specification and qualification of welding procedures for metallic materials. Qualification by adoption of a standard welding procedure
Supersedes BS EN 288-7:1995

BS EN ISO 17641:

Destructive tests on welds in metallic materials. Hot cracking tests for weldments. Arc welding processes

BS ISO 17641-1:2004

General
No current standard is superseded.

BS EN ISO 17642:

Destructive tests on welds in metallic materials. Cold cracking tests for weldments. Arc welding processes

BS EN ISO 17642-1:2004

General
No current standard is superseded.

ISO PUBLICATIONS

It is BSI policy to supply the UK version of all adopted standards, which are published as British standards, unless otherwise requested.

ISO 15609:

Specification and qualification of welding procedures for metallic materials. Welding procedure specification

ISO 15609-3:2004

Electron beam welding
Will be implemented as an identical British Standard

SCI Courses January-March 2005

IN-HOUSE TRAINING

All the courses that the SCI offer can be taken as part of company in-house training programmes. In-house courses are a cost-effective way of training employees and can be configured to suit your company's needs.

For further information on in-house training contact **Sandi Gentle (Courses Manager)** on 01344 872776 or email s.gentle@steel-sci.com

For detailed information and programmes for all courses please see www.steel-sci.org/courses

Multi-Storey Steel Frames	13 Jan	London
Key Construction Issues	20 Jan	Dublin
Fire in Boundary Conditions	25 Jan	Dublin
Preparation for Eurocode3	25 Jan	Southampton
Steel in Construction - Evening CPD	27 Jan - 3 Mar	Glasgow
Steel in Construction - Evening CPD	27 Jan - 3 Mar	London
Steel in Construction - Evening CPD	27 Jan - 3 Mar	Manchester
Frame Stability	02 Feb	London
Portal Frame Solutions	10 Feb	Dublin
Excel for Engineers	17 Feb	Edinburgh
Portal Frame Solutions	22 Feb	Manchester
Welding for Engineers	01 Mar	Rotherham
Connection Design Workshop	01 Mar	Manchester
Welding for Engineers	08 Mar	Glasgow
Curved Steel - Angle Ring	10 Mar	Tipton
Preparation for Eurocode3	16 Mar	Swindon
Curved Steel - Practical Applications	22 Mar	Leeds
Floor Vibrations - The problems identified and explained	23 Mar	Birmingham
Preparation for Eurocode3	30 Mar	Edinburgh

RAINHAM STEEL

HOT ROLLED PLATE

NOW AVAILABLE EX-STOCK
From The UK's largest stockholder

S275 JR Plates with 3.1.B Certs

4000 x 2000 • 6000 x 2000
8000 x 2000 • 5000 x 2500
In thicknesses 10 • 12.5 • 15 • 20 • 25

Prime Grade S355 J2 G3 with 3.1.B Certs

4000 x 2000 • 6000 x 2000
8000 x 2000 • 5000 x 2500
In thicknesses 10 • 12.5 • 15 • 20 • 25

Nationwide delivery - Call sales now!

Phone: 01708 522311 Fax: 01708 559024 E-mail: sales@rainham-steel.co.uk



The Steel Construction Institute

The Steel Construction Institute develops and promotes the effective use of steel in construction. It is an independent, membership-based organisation. Membership is drawn from all sectors of the construction industry; this provides beneficial contacts both within the UK and internationally. Its corporate members enjoy access to unique expertise and free practical advice which contributes to their own efficiency and profitability. They also receive an initial free copy of most SCI publications, and discounts on subsequent copies and on courses. Its multi-disciplinary staff of 45 skilled engineers and architects is available to provide technical advice to members on steel construction in the following areas:

- Technical Support for Architects
- Bridge Engineering
- Building Interfaces
- Civil Engineering
- Codes and Standards
- Composite Construction
- Connections
- Construction Practice
- Corrosion Protection
- Fabrication
- Health & Safety — best practice
- Information Technology
- Fire Engineering
- Light Steel and Modular Construction
- Offshore Hazard Engineering
- Offshore Structural Design
- Piling and Foundations
- Specialist Analysis
- Stainless Steel
- Steelwork Design
- Sustainability
- Vibration

Details of SCI Membership and services are available from: Pat Ripley, Membership Manager, The Steel Construction Institute, Silwood Park, Ascot, Berks.

Telephone: +44 (0)1344 623345 Fax: +44 (0)1344 622944

Email: pat.ripley@steel-sci.com Website: www.steel-sci.com

All full members of the BCSA are automatically members of the SCI. Their contact details are listed on the BCSA Members pages

CORPORATE MEMBERS

3E Consulting Engineers Ltd
The AA Group Ltd
A & J Fabtech Ltd
A B Dailey Son & Clarke
A C Bacon Engineering Ltd
A Dawber Limited
Aberdeenshire Council
AceCad Software Ltd
ACL Structures Ltd
Adams Kara Taylor Ltd
ADP Consulting Engineers Ltd
Air Products plc
Aker Kvaerner - E&C Europe
Alan Baxter & Associates
Alan Conisbee & Associates
Alan Dick & Co Ltd
Alan Johnston Partnership
Alcock Lees Partnership
Allerton Engineering Ltd
Allott Brothers & Leigh
Allslade Plc
AMEC Design and Management
AMP Consultants
Andrew Dust Structural Engineers
Andrew Howard & Partners
Andrew Waring Associates
Andrews Kent & Stone Ltd
The Angle Ring Company Ltd
Apex Steel Structures Ltd
APT Marconi
Arbuckle Welding & Fabrications Ltd
Arena Structures
Arramax Structures Ltd
Arup
ASA Steel Structures Ltd
Asme Engineering Ltd
Associated Structural Design
Aston University
Atkins
Atlas Ward Structures Ltd
Atlasco Constructional Engineers Ltd
Aukett Limited
Aylesbury Vale District Council
Ayrshire Metal Products Plc

B & B Structures Ltd
BD Structures Limited
B W Industries Ltd
BAA Plc
BAE SYSTEMS : CS&S International
Baldock Quick Partnership
Balfour Beatty Rail Projects Ltd
Ballykine Structural Engineers Ltd
Barnshaw Section Benders Ltd
Barrett Steel Buildings Ltd
Baxter Glaysher Consulting
BDS Steel Detailers
Bechtel Ltd
Benaim
Beresford Dunne Consultants
Bestech Systems Ltd
Billington Structures Ltd
Birmingham City Council
Bison Structures Ltd

Black & Veatch Consulting - Europe
Blyth & Blyth Consulting
Bodycote Metallurgical Coatings*
Bolton Institute of Higher Education
Bolton Priestley
BOMEL Ltd
Bone Steel Ltd
Border Steelwork Structures Ltd
Bourne Steel Ltd
The Brazier Holt Partnership Ltd
Bridgetown Developments Ltd
The British Constructional Steelwork Association Ltd
British Energy Plc
British Nuclear Fuels Plc
British Stainless Steel Association
Briton Fabricators Ltd
Broadhurst Engineering (UK) Ltd
Broadwell Buildings Ltd
Browne Structures Ltd
Brunner Mond UK Limited
Building Design Partnership
Bullen Consultants Ltd
Bunyan Mayer & Partners Ltd
Bureau Veritas Weeks Consulting
Burks Green Engineers and Architects
Buro Happold
Burroughs Stewart Associates
Bury Metropolitan Borough Council
Butler Building Systems
Butterley Ltd
The BWB Partnership Ltd

C.S.C. Engineers Ltd
CADS (Computer & Design Services Ltd)
Cairnhill Structures Ltd
Caledonian Building Systems
Cameron Taylor Bedford
Campbell Reith Hill Ltd
Capita Gwent Consultancy Ltd
Capita Symonds
Cardiff County Council
Cardiff University
Carl Bro
Carnaby Structures Ltd
Carter Design Group
Cass Hayward LLP
Caution Engineering Ltd
CB&I John Brown Ltd
CEL International Ltd
Charles Haswell & Partners Ltd
Cheshire County Council
Chieftain Contracts Ltd
CIRIA
City of Wakefield MBC
City University
Civil & Structural Computer Services Ltd
Clarke Bond Group Limited
Clarke Nicholls & Marcel
Clarkslegal LLP
Clegg Associates
Cleveland Bridge UK Limited
Collis Engineering Ltd
Compass Engineering Ltd
Complete Design Partnership Ltd

Conder Structures Ltd
Convoy Structural Services Ltd
Cordell Group Ltd
Cornwall County Council
Corus Group plc
Corus Panels & Profiles - Cheltenham
Coventry Construction Ltd
Coventry University
Cowan & Linn
Crown Structural Engineering Ltd
CSC (UK) Ltd
Curtins Consulting Engineers
Curtis Engineering Ltd
Custom Metal Fabrications Ltd
Custom Steel Fabrications Ltd
CWT Partnership
D A Green & Sons Ltd
D H Structures Ltd
D J Barrington (Construction) Ltd
D J Hartigan & Associates Ltd
Dalton Consultants
Deakin Walton Limited
Defence Estates
Devon County Council
Devonport Management Ltd
Dew Construction Ltd
Dewhurst Macfarlane and Partners
DGK Structures
Dibsa Structures Ltd*
Dorman Long Technology Ltd
Dougall Baillie Associates
Doyle Partnership
Dryform Limited*
Dundee City Council

E T Design
Eastwood & Partners
Edmund Nuttall Ltd
Elland Steel Structures Ltd
Elliott Wood Partnership
Emmett Fabrications Ltd
Evadix Ltd
Evans & Langford LLP
Expedition Engineering Limited

F J Samuely & Partners Ltd
F W Consulting
FaberMaunsell
Fabsec Limited
Fairfield-Mabey Ltd
Fisher Engineering Ltd
Flint & Neill Partnership
Fluid Structural Engineers
Fluor Ltd
Foggo Associates Ltd
Frank H Dale Ltd

Galvanizers Association
Gardenwood Ltd
Gary Gabriel Associates
George Mathieson Associates
Gibbs Engineering Ltd
Gifford & Partners Ltd
Glasgow Caledonian University
Glentworth Fabrications Ltd

Goodwin Steel Castings Ltd
Gorge Fabrications Ltd
Graham Wood Structural Ltd
Grays Engineering (Contracts) Ltd
Gregg & Patterson (Engineers) Ltd

H Young Structures Ltd
Had-Fab Ltd
Halcrow Group Ltd
Hallmason Design Ltd
Hambleton Steel Ltd
Hanson Building Products
Harley Haddow Partnership
Harold Newsome Ltd
Harry Marsh (Engineers) Ltd
Harry Peers Steelwork Ltd
Hasler Hawkins Ltd
Hawkes Construction Co
HBG Design Ltd
Henry Smith (Constructional Engineers) Ltd
Hescott Engineering Company Ltd
High-Point Rendel
Highcliffe Court Design Ltd
Hillcrest Structural Ltd
HOP Consulting Ltd
Horwich Steelworks Ltd
HSP Consulting
Hurst Peirce & Malcolm LLP
Hyder Consulting (UK) Ltd

Imperial College London
Integer Software Limited
Inverclyde Council
ISS Limited

J J Campbell & Associates
J Robertson & Co Ltd
Jacobs Babbie
Jacobs Gibb Ltd
James Bros (Hamworthy) Ltd
James Killelea & Co Ltd
James Lupton Consultants
Jenkins & Potter
Jex Engineering Co Ltd
John Reid & Sons (Structural) Ltd
John Wicks & Son Ltd
Johnson Steel Structures Ltd
Jordan Pritchard Gorman
Joy Steel Structures (London) Ltd

Keith Johnson Associates
Kellogg Brown & Root Ltd (KBR)
Kenneth Brown & Partners*
Kier Limited
Kingspan Metl-Con Limited
Kingston University
Kirk McClure Morton
Kirkman & Bradford SKM
Knapp Hicks & Partners Ltd
Knight & Butler Ltd

Laing O'Rourke - Group Technical Services
Leach Structural Steelwork Ltd
Leigh's Paints

Leonard Cooper Ltd
Les Gooding Design Associates
Lindapter International
Liverpool John Moores University
London Borough of Hillingdon
Lowe Engineering (Midland) Ltd

M Hasson & Sons Ltd
Mace Ltd
Madden Steel Erectors
Maldon Marine Ltd
Maltech (UK) Ltd
Manchester City Council
Mario Minchella Architects*
Martec Engineering Group Ltd
Martin Stockley Associates
Marton Engineering Services Ltd
Maslen Brennan Henshaw
Mason Navarro Partnership
Mech Tool Engineering Ltd
Melliss LLP
Metals Industry Skills & Performance
Metek Building Systems
Metronet Rail SSL Ltd
Metsec Plc
Michael Barclay Partnership
Midland Steel Structures Ltd
Midland Structural Services
Mifflin Construction Ltd
Mike Curnow
Mitchell McFarlane & Partners
MJMC Group of Companies
MLM Maddocks Lusher & Matthews
Molabolt Ltd
Morgan Est
Mott MacDonald Group Ltd
Mouchel Parkman Services Ltd
MSL Engineering Ltd
MSW (UK) Ltd

Napier University
Newbridge Engineering Ltd
Newton Fabrications Ltd
NNC Ltd
Norder Design Associates Limited
Nottingham Trent University
NRM Bobrowski
Nusteel Structures Ltd
NW Structural Consultants Ltd

On Site Services (Gravesend) Ltd
Outokumpu Stainless Ltd
Overdale Construction Services Ltd
Owen Williams Consultants
Oxford Brookes University

Pace Structures Ltd
Parsons Brinckerhoff Ltd
Paul Reading & Partners
Pell Frischmann Consultants Ltd
Pencro Structural Engineering Ltd
PEP Civil & Structures Ltd
Peter Brett Associates
Peterborough City Council
Peters Associates (Ripon) Limited
Pick Everard
Pinnacle Consulting Engineers Ltd
Plandescil Ltd
Portakabin Ltd
Portal Ltd
Posford Haskoning Ltd
Powerwall Systems Limited*
Price & Myers Consulting Engineers Llp
Pyper McLarnon Partnership

QMEC Ltd
Qualfab Engineering Ltd

R G Parkins & Partners Ltd
Rainham Steel Co Ltd
RAM International (Europe) Ltd
Ramage Young Partnership
Remnant Engineering Ltd
Renaissance Enlightened Building
Limited
Renfrewshire Council
Research Engineers (Europe) Limited
Richard Jackson plc
Richard Lees Steel Decking Ltd
Richard Wood Engineering Ltd
Rigby & Partners
Rippin Ltd
RMJM Scotland Ltd
Robert Tucker Associates
Roberts Engineering
Robinson Construction
Robinson Consulting Limited
Roger Bullivant Ltd
Rowecord Engineering Ltd
Rowen Structures Ltd
Royal School of Military Engineering

RSL (South West) Ltd

S H Structures Ltd
Scott White & Hookins
Scott Wilson Kirkpatrick & Co Ltd
Scottish Borders Council
Selwyn Construction Engineering Ltd
Severfield-Reeve Structures Ltd
Sheffield City Council
Shell UK Exploration & Production
Shipley Fabrications Ltd
Skanska Technology
SKM Anthony Hunts
Snashall Steel Fabrications
Solway Structural Steel
South Durham Structures Ltd
SSI Group of Companies
Steven Kidd & Associates*
Stewart & Harris
Stirling Maynard & Partners
Structural Design Associates
Structural Design Partnership
Structural Metal Decks Ltd
Structural Sections Ltd
Surrey County Council
Survey Design Associates Ltd

T A Kirkpatrick & Co Ltd
Taylor & Russell Ltd
Teague & Sally Partnership
Techniker Ltd
Tekla (UK) Ltd
Tension Control Bolts Ltd
Terence McCormack Ltd
Terrapin Ltd
Terrell International
Thomas Morgan & Associates
Thomasons LLP
Tillman & Tsoukka
Tony Gee & Partners
TPS Consult Ltd
Traditional Structures Ltd

University of Aberdeen
University of Birmingham
University of Bristol
University of Dundee
University of East London
University of Edinburgh
University of Greenwich
University of Leeds
The University of Manchester
University of Nottingham
University of Paisley
University of Plymouth
University of Portsmouth
University of Salford
University of Sheffield
University of Southampton
University of Surrey
University of the West of England
University of Wales Swansea
University of Warwick
URS Corporation Ltd

W A Fairhurst & Partners
W F Brown Associates Ltd
W S Britland & Co Ltd
Waldrons Limited
Walsh Associates
Walter Watson Ltd
Ward Building Components Ltd
Warley Construction Co Ltd
Waterman Group
Watson Steel Structures Ltd
WCJ Engineers
Wessex Structural Services Ltd
Westbury Park Engineering Ltd
Westok Ltd
Weston Steel Structures Ltd
Whitbybird
White Young Green Consulting Ltd
W I G Engineering Ltd
William Haley Engineering Ltd
William Hare Ltd
William J Marshall & Partners
The Willocks Practice
The Wood Boyle Partnership
Wright Associates
WSP Group

Yolles Partnership Ltd

ORGANISATIONS WITH MEMBER SERVICE AGREEMENTS WITH THE SCI

Construction Industry Directorate
Health & Safety Executive (HSE)

Highways Agency
The Institution of Structural Engineers

INTERNATIONAL CORPORATE MEMBERS

Australia

Australian Steel Institute
BHP Fire and Construction Research
Unit
BlueScope Steel Research

Belgium

Bocad Service International S A
International Iron & Steel Institute (IISI)
Staalinfocentrum - Centre Information
Acier

Brazil

Brazilian Centre of Steel Construction
(CBCA)*
CODEME Engenharia S.A.
Gerdau Acominas S.A.
Universidade Federal da Ouro Preto
USIMINAS

Canada

Canadian Institute of Steel
Construction

Chile

Construcciones Y Montajes S.A
(COYMSA)

Croatia

Institut Gradevinarstva Hrvatske

Finland

Finnish Constructional Steelwork
Association
Rautaruukki Oyj
Seinäjoki Polytechnic
VTT Building and Transport

France

CTICM
Terrell International

Germany

Bauen mit Stahl e.V.
POSCO Research Centre Europe

Greece

Democritus University of Thrace
K.Liaromatis SA
Maraveas & Associates SA
Metallostegastiki SA
Technical Chamber of Greece (TEE)

Hong Kong

Arup Group
Corus Asia Ltd
The Hong Kong Polytechnic University
WSP Asia

Hungary

Kesz Group

India

Bechtel Overseas Corporation
Institute for Steel Development &
Growth

Ireland

Barrett Mahony Consulting Engineers
Barry Kelleher & Associates
C S Pringle Consulting Engineers
Corus Ireland
Coyle Kennedy Ltd
Downes Associates
ESB International Ltd
Frank Fox & Associates
Fusion Building Solutions
Hanley Pepper Consulting Engineers
Joda Engineering Consultants
John Doyle & Associates
Kigallen & Partners Consulting
Engineers Ltd
Michael Punch & Partners
National University of Ireland, Galway
Nestor Kelly
Nordman Profile Ltd
O'Connor Sutton Cronin
Project Management Ltd
RPS-MCOS Ltd
SIAC Butlers Steel Ltd
Stanta Limited
University College Dublin
Walsh Draughting Services Ltd

Italy

FICEP S.p.A.
Politecnico Di Milano
Universita Degli Studi Di Trento

Kenya

David Engineering Ltd
H P Gauff Consulting Engineers

Korea

INI Steel Company
Korea University

Lithuania

Vilnius Technical University

Malaysia

Corus Asia Ltd
Malaysian Structural Steel Association
Universiti Teknologi Malaysia

The Netherlands

Bouwen met Staal
Delft University of Technology

New Zealand

Heavy Engineering Research
Associates

Norway

Tee Consult Holding AS

Philippines

Corus Asia Ltd

Portugal

GEG - Gabinete de Estruturas e
Geotecnia Ltda
Universidade de Aveiro
Universidade de Coimbra

Principality of Liechtenstein

HILTI AG

Qatar

Matar Trading & Contracting Co.
W.L.L.

Republic of Singapore

Corus (South East Asia) Pte Ltd
Jurong Engineering Ltd
LSW Consulting Engineers
Ngee Ann Polytechnic
Singapore Structural Steel Society

Slovenia

University of Ljubljana

South Africa

Southern African Institute of Steel
Construction

Spain

In Hoc Signo Vincas
ITEA
University of Navarra

Sweden

Luleå University of Technology
Outokumpu AB
Swedish Institute of Steel Construction

Turkey

CIMTAS Celik Imalat Montaj Ve
Tesisat A.S.
UMO Architecture Engineering and
Consulting Ltd Co

United Arab Emirates

Corus Middle East
Emirates Building Systems Co LLC
(EBSCO)
GINCO Steel L.L.C.
The PHB Group
Techno Steel Construction Co

USA

American Institute of Steel
Construction Inc
American Iron & Steel Institute (AISI)
Corus America Inc
Epic Metals Corporation
Steel Recycling Institute

**New corporate members since last short
list in November/December 2004 issue*



The British Construction Steelwork Association Ltd

BCSA is the national organisation for the construction industry; its member companies undertake the design, fabrication and erection for all forms of construction in building and civil engineering. Associate Members are those principal companies involved in the purchase, design or supply of components, materials, services etc, related to the industry. Corporate Members are clients, professional offices, educational establishments etc, which support the development of national specifications, health and safety, quality, fabrication and erection techniques, overall industry efficiency and good practice. The principal objectives of the association are to promote the use of structural steelwork; to assist specifiers and clients; to ensure that the capabilities and activities of the industry are widely understood; and to provide members with professional services in technical, commercial and quality assurance matters.

Details of BCSA Membership and services are available from: Gillian Mitchell MBE, Deputy Director General, British Constructional Steelwork Association Ltd, 4 Whitehall Court, Westminster, London SW1A 2ES. Tel 020 7839 8566 Fax 020 7976 1634

ACL STRUCTURES LTD (E F H M 4)
Holland Way Ind. Est., Blandford, Dorset DT11 7TA
Tel 01258 456051 Fax 01258 450566

A & J FABTECH LTD
Walkley Works, Walkley Lane,
Heckmondwike WF16 0PH
Tel 01924 402151 Fax 01924 410227

ASA STEEL STRUCTURES LTD
Brick Kiln Lane, Parkhouse Ind. Est. West,
Newcastle-under-Lyme, Staffs ST5 7EF
Tel 01782 566366 Fax 01782 564785

ALLERTON ENGINEERING LTD (B 5* Q3)
Allerton House, Thurston Road,
Northallerton, N. Yorkshire DL6 2NA
Tel 01609 774471 Fax 01609 780364

ALLOTT BROS & LEIGH
Fullerton Rd, The Ickles,
Rotherham S60 1DJ
Tel 01709 364115 Fax 01709 364696

ALLSLADE PLC
Dundas Lane, Portsmouth, Hants PO3 5SD
Tel 023 9266 7531 Fax 023 9267 9818

THE ANGLE RING CO LTD
Bloomfield Road, Tipton DY4 9EH
Tel 0121-557 7241 Fax 0121-522 4555

APEX STEEL STRUCTURES LTD
Kings Close, Charfleets Industrial Estate,
Canvey Island, Essex SS8 0QZ
Tel 01268 660 828 Fax 01268 660 829

ARBUCKLE WELDING & FABRICATIONS LTD
21 Lenziemill Rd, Lenziemill,
Cumbernauld G67 2RL
Tel 01236 457960 Fax 01236 452250

ARROMAX STRUCTURES LTD (Q4)
Langwith Junction, Mansfield, Notts NG20 9RN
Tel 01623 747466 Fax 01623 748197

ASME ENGINEERING LTD
Asme House, 788 Kenton Lane,
Harrow, Middlesex HA3 6AG
Tel 0208 954 0028 Fax 0208 954 0036

ATLAS WARD STRUCTURES LTD (A 3* Q1)
Sherburn, Malton, N. Yorkshire YO17 8PZ
Tel 01944 710421 Fax 01944 710512

ATLASCO CONSTRUCTIONAL ENGINEERS LTD
Rowhurst Industrial Estate, Apedale, Chesherton,
Newcastle-U-Lyme ST5 6BD
Tel 01782 564711 Fax 01782 564591

B & B STRUCTURES LTD
Unit 3, Bridgewater Business Park,
West Bridgewater St, Leigh, Lancs WN7 4HB
Tel 01942 603055 Fax 01942 608263

B D STRUCTURES LTD (D E F H 5*)
Westthoughton Ind Est, James St,
Westthoughton, Lancs, BL5 3QR
Tel 01942 817770 Fax 01942 810438

A. C. BACON ENGINEERING LTD (E F H 6)
Norwich Rd, Hingham, Norwich NR9 4LS
Tel 01953 850611 Fax 01953 851445

BALLYKINE STRUCTURAL ENGINEERS LTD (E F H J N 4 Q2)
51 Lisburn Rd, Ballynahinch, Co Down BT24 8TT
Tel 028 9756 2560 Fax 028 9756 2751

BARNSHAW SECTION BENDERS LTD
Structural Division, Anchor Lane, Coaseley,
Bilston, West Midlands WV14 9NE
Tel 01902 880848 Fax 01902 880125

BARRETT STEEL BUILDINGS LTD (E F H 1 Q1)
Barrett House, Cutler Heights Lane,
Dudley Hill, Bradford BD4 9HU
Tel 01274 682281 Fax 01274 684281

D. J. BARRINGTON (CONSTRUCTION) LTD
Longmoor, Shirlheath, Kingsland,
Leominster HR6 9RG
Tel 01568 708288 Fax 01568 708815

BILLINGTON STRUCTURES LTD (A 1 Q1)
Barnsley Road, Wombwell S73 8DS
Tel 01226 340666 Fax 01226 755947

BILLINGTON STRUCTURES LTD (A 1 Q1)
456 Badminton Rd, Yate, Bristol BS37 5HY
Tel 01454 318181 Fax 01454 318231

BISON STRUCTURES LTD (D E F H 4 Q1)
London Rd, Tetbury, Gloucs GL8 8HH
Tel 01666 502792 Fax 01666 504246

BONE STEEL LTD
P.O. Box 9300, Wishaw, Lanarkshire ML2 0YA
Tel 01698 375000 Fax 01698 372727

BORDER STEELWORK STRUCTURES LTD (C E F H J N 6)
Winchester House, 58 Warwick Rd,
Carlisle CA1 1DR
Tel 01228 548744 Fax 01228 511073

BOURNE STEEL LTD (A 1 Q2)
St Clements House, St Clements Rd,
Poole, Dorset BH12 4GP
Tel 01202 746666 Fax 01202 732002

W.S. BRITLAND & CO. LTD (Q2)
Tilmanstone Works, Pike Road, Eythorne,
Dover CT15 4NB
Tel 01304 831583 Fax 01304 831983

BRITON FABRICATORS LTD (C F H J K M 6 Q4)
Watnall Road, Hucknall, Notts NG15 6EP
Tel 01115 963 2901 Fax 01115 968 0335

BROADHURST ENGINEERING (UK) LTD
Gargrave St., Moorhey St.,
Moorhey, Oldham OL4 1JU
Tel 01661 628 6888 Fax 01661 628 6999

BROWNE STRUCTURES LTD
Queens Drive, Newhall, Swadlincote,
Derbyshire DE11 0EG
Tel 01283 212720 Fax 01283 215033

BUTTERLEY LTD (B 3* Q4)
Ripley, Derby DE5 3BQ
Tel 01773 573573 Fax 01773 749898

CAIRNHILL STRUCTURES LTD
Sun Works, Waverley Street, Coatbridge,
Lanarkshire ML5 2BE
Tel 01236 449393 Fax 01236 428328

CARNABY STRUCTURES LTD (C E F H 2*)
Lancaster Rd, Carnaby Industrial Estate, Bridlington,
East Yorkshire YO15 3QY
Tel 01262 401325 Fax 01262 401389

CAUNTON ENGINEERING LTD (Q1)
Moorgreen Ind. Park, Moorgreen,
Nottingham NG16 3QU
Tel 01773 531111 Fax 01773 532020

CHIEFTAIN CONTRACTS LTD
Antonine Works, Broomhill Road,
Bonnybridge FK4 2AL
Tel 01324 812911 Fax 01324 814927

CLEVELAND BRIDGE UK LTD (A B 0 Q3)
Cleveland House, Yarm Rd, Darlington,
Co Durham DL1 4DE
Tel 01325 381188 Fax 01325 382320

COMPASS ENGINEERING LTD (C E F H 6)
Whaley Road, Barugh, Barnsley S75 1HT
Tel 01226 298388 Fax 01226 283215

KEY

Categories

- A** All forms of building steelwork
- B*** Bridgework
- C** Heavy industrial plant structures
- D** High rise buildings
- E** Large span portals
- F** Medium/small span portals and medium rise buildings
- G** Footbridge and sign gantries
- H** Large span trusswork
- J** Major tubular steelwork
- K** Towers
- L** Architectural metalwork
- M** Frames for machinery, supports for conveyors, ladders and catwalks
- N** Grandstands and stadia
- S** Small fabrications

Quality Assurance Certification

- Q1** Steel Construction Certification Scheme Ltd
- Q2** BSI
- Q3** Lloyd's
- Q4** Other

Classification Contract Value

- 10** Up to £40,000
- 9** Up to £100,000
- 8** Up to £200,000
- 7** Up to £400,000
- 6** Up to £800,000
- 5** Up to £1,400,000
- 4** Up to £2,000,000
- 3** Up to £3,000,000
- 2** Up to £4,000,000
- 1** Up to £6,000,000
- 0** Above £6,000,000

Notes

- 1** Applicants may be registered in one or more categories to undertake the fabrication and the responsibility for any design and erection of the above.
 - 2** Where an asterisk (*) appears against any company's classification number, this indicates that the assets required for this classification are those of the parent company.
- * For details of bridgework sub-categories contact Gillian Mitchell at the BCSA.

CONDER STRUCTURES LTD (Q2)
Wellington Rd, Burton-on-Trent,
Staffs DE14 2AA
Tel 01283 545377 Fax 01283 530483

LEONARD COOPER LTD (C F H K M 6 Q1)
Balm Road, Hunslet, Leeds LS10 2JR
Tel 0113 270 5441 Fax 0113 276 0659

CORDELL GROUP LTD (Q4)
Unit 2, Perry Avenue, Teesside Industrial Estate,
Thornaby on Tees TS17 9LN
Tel 01642 769526 Fax 01642 769553

COVENTRY CONSTRUCTION LTD (E F H J L M 7 Q1)
Torrington Avenue, Coventry CV4 9AP
Tel 024 7646 4484 Fax 024 7669 4020

BROWN STRUCTURAL ENGINEERING LTD Burma Rd,
Bridworth, Mansfield, Notts NG21 0RT
Tel 01623 490555 Fax 01623 490666

CUSTOM METAL FABRICATIONS LTD
Central Way, Feltham TW14 0XJ
Tel 020 8844 0940 Fax 020 8751 5793

D H STRUCTURES LTD (Q2)
Tollgate Drive, Tollgate Industrial Estate, Beaconside,
Stafford ST16 3HS
Tel 01785 246269 Fax 01785 222077

FRANK H DALE LTD (E F 2 Q4)
Mill Street, Leominster, Herefordshire HR6 8EF
Tel 01568 612212 Fax 01568 619401

DEW CONSTRUCTION LTD (E F H K 6 Q2)
PO Box 35, Oldham OL9 6HH
Tel 0161 624 5631 Fax 0161 627 3556

ELLAND STEEL STRUCTURES LTD (C D E F H K N 2 Q1)
Philmor House, Gibbet St, Halifax HX2 0AR
Tel 01422 380262 Fax 01422 380263

EMMETT FABRICATIONS LTD (E F H 6)
Hirst Wood Works, Hirst Wood Road,
Shipley BD18 4BU
Tel 01274 597484 Fax 01274 588671

EVADX LTD (E F H J L M N 5 Q4)
Unit 9, Tir Llywd Enterprise Park,
St. Asaph Avenue, Kinmel Bay, Rhyl LL18 5JZ
Tel 01745 336413 Fax 01745 339639

FAIRFIELD-MABEY LTD (A B 0* Q4)
Chepstow, Monmouthshire NP16 5YL
Tel 01291 623801 Fax 01291 625453

FISHER ENGINEERING LTD (A 1 Q1)
Ballinamallard, Enniskillen,
Co Fermanagh BT94 2FY
Tel 028 6638 8521 Fax 028 6638 8706

GIBBS ENGINEERING LTD (Q4)
17A Ave Road, Colley Lane Industrial Estate,
Bradgwater, Somerset TA6 5LP
Tel 01278 455253 Fax 01278 453174

GLENTWORTH FABRICATIONS LTD (F H J K L M N 4 Q2)
Molly Millar's Bridge, Molly Millar's Lane,
Wokingham RG41 2WY
Tel 0118 977 2088 Fax 0118 977 2907

GORGE FABRICATIONS LTD
Gorge House, Great Bridge Industrial Estate, Toll End
Road, Tipton, West Midlands DY4 0HR
Tel 0121 522 5770 Fax 0121 557 0415

GRAHAM WOOD STRUCTURAL LTD (A 4)
Lancing Business Park, Chartwell Road,
Lancing BN15 8TY
Tel 01903 755991 Fax 01903 755384

GRAYS ENGINEERING (CONTRACTS) LTD
Globe Industrial Estate, Rectory Road,
Grays, Essex RM17 6ST
Tel 01375 372411 Fax 01375 375079

D A GREEN & SONS LTD (E F H J 3 Q1)
Whapode, Spalding, Lincs PE12 6TL
Tel 01406 370585 Fax 01406 370766

GREGG & PATTERSON (ENGINEERS) LTD (Q2)
Riverside Works, Ballyskeagh Road,
Lambeg, Co Antrim BT27 5TD
Tel 028 9061 8131 Fax 028 9062 2813

HAD-FAB LTD (Q4)
Macmerry Ind. Est., Tranent,
East Lothian EH33 1RD
Tel 01875 612711 Fax 01875 612711

WILLIAM HALEY ENGINEERING LTD (Q1)
Bellcombe Works, East Brent,
nr. Highbridge, Somerset TA9 4DB
Tel 01278 760591 Fax 01278 760587

HAMBLETON STEEL LTD
Gatherley Road, Brompton-on-Swale,
Richmond, North Yorkshire DL10 7JH
Tel 01748 810598 Fax 01748 810601

WILLIAM HARE LTD (A B 0 Q1)
Brandlesholme House,
Brandlesholme Rd, Bury, BL8 1JJ
Tel 0161 609 0000 Fax 0161 609 0409

M. HASSON & SONS LTD (Q1)
17 Glebe Rd, Rasharkin, Co. Antrim BT44 8SS
Tel 028 2957 1281 Fax 028 2957 1575

HAWKES CONSTRUCTION CO
321A Hornchurch Rd, Hornchurch RM12 4TQ
Tel 01708 621010 Fax 01708 621026

HENRY SMITH (CONSTRUCTIONAL ENGINEERS) LTD (C D E F H J 4)
Wharton Steelworks, Winsford CW7 3BW
Tel 01606 592121 Fax 01606 559134

HESCOTT ENGINEERING CO LTD
Lochlands Viaduct, Larbert, Stirlingshire FK5 3NN
Tel 01324 556610 Fax 01324 552970

HILLCREST STRUCTURAL LTD
Hillcrest House, Toynbee Road,
Eastleigh, Hants SO50 9DT
Tel 023 8064 1373 Fax 023 8061 3586

HORWICH STEELWORKS LTD
Unit 10, Horwich Loco Ind. Est.,
Chorley New Rd, Horwich, Bolton BL6 5UE
Tel 01204 695989 Fax 01204 669343

JAMES BROS (HAMWORTHY) LTD (E F H J N 4 Q3)
19 Blandford Rd, Hamworthy, Poole BH15 4AW
Tel 01202 673815 Fax 01202 684033

JOY STEEL STRUCTURES (LONDON) LTD
London Industrial Park, 1 Whittings Way,
East Ham, London E6 6LR
Tel 020 7474 0550 Fax 020 7473 0158

JAMES KILLELEA & CO LTD (C E F H N 1*)
Stoneholme Road, Crawshawbooth,
Rossendale, Lancs BB4 8BA
Tel 01706 229411 Fax 01706 228388

T. A. KIRKPATRICK & CO LTD
Beltenmont, Kirkpatrick-Fleming,
Lockerbie DG11 3NQ
Tel 01461 800275 Fax 01461 800340

LEACH STRUCTURAL STEELWORK LTD
Brookholes Way, Cloughton-on-Brock,
nr Preston PR3 0PZ
Tel 01995 640133 Fax 01995 640719

LOWE ENGINEERING (MIDLAND) LTD
Bramshall Industrial Estate, Stone Road,
Bramshall, Staffs ST14 8SH
Tel 01889 563244 Fax 01889 563554

TERENCE MCCORMACK LTD (Q1)
17 Camlough Rd, Newry BT35 6JS
Tel 028 3026 2261 Fax 028 3026 8177

MADDEN STEEL ERECTORS
Unit 3, 5 Hagmill Road, East Shawhead Industrial
Est., Coatbridge, Lanarkshire ML5 4XD
Tel 01236 424213 Fax 01236 434355

MALDON MARINE LTD
Unit 16, West Station Ind. Est.,
Spital Road, Maldon, Essex CM9 6TW
Tel 01621 859000 Fax 01621 858935

HARRY MARSH (ENGINEERS) LTD
The Parade, Hendon, Sunderland SR2 8LT
Tel 0191 510 9797 Fax 0191 510 9798

MARTEC ENGINEERING GROUP LTD
58 Southcroft Road, Rutherglen,
Glasgow G73 1UG
Tel 0141 647 6789 Fax 0141 646 1056

MIDLAND STEEL STRUCTURES LTD
Golden Acres Lane, Binley, Coventry CV3 2RT
Tel 024 7644 5584 Fax 024 7645 9995

MIFFLIN CONSTRUCTION LTD (D E F H M 4)
Worcester Rd, Leominster, Herefordshire HR6 8AY
Tel 01568 613311 Fax 01568 614935

NEWBRIDGE ENGINEERING LTD
Tees Bay Business Park, Brenda Rd,
Hartlepool TS25 2BU
Tel 01429 866722 Fax 01429 869811

NEWTON FABRICATIONS LTD
9 York Street, Ayr, Ayrshire KA8 8AN
Tel 01292 269135 Fax 01292 610258

NUSTEEL STRUCTURES LTD (B 4* Q1)
Lympe, Hythe, Kent CT21 4LR
Tel 01303 268112 Fax 01303 266098

ON SITE SERVICES (GRAVESEND) LTD (Q4)
Wharf Road, Denton, Graysend, Kent DA12 2RU
Tel 01474 321552 Fax 01474 357778

OVERDALE CONSTRUCTION SERVICES LTD
Millers Avenue, Brynmernyn Industrial Estate,
Bridgend CF32 9TD
Tel 01656 729229 Fax 01656 722101

HARRY PEERS STEELWORK LTD (Q1)
Elton St, Mill Hill, Bolton BL2 2BS
Tel 01204 528393 Fax 01204 362363

PENCRO STRUCTURAL ENGINEERING LTD (Q4)
Orpinsmill Road, Ballyclare, Co. Antrim BT39 0SX
Tel 028 9335 2886 Fax 028 9332 4117

QMEC LTD
Quarry Road, Bolsover, Nr Chesterfield S44 6NT
Tel 01246 822228 Fax 01246 827907

QUALFAB ENGINEERING LTD
53 Glebe Rd, Gillibrands, Skelmersdale WN8 9JP
Tel 01695 557157 Fax 01695 557172

RSL (SOUTH WEST) LTD (E F H M 6)
Millfield Industrial Est., Chard,
Somerset TA20 2BB
Tel 01460 67373 Fax 01460 61669

JOHN REID & SONS (STRUCSTEEL) LTD (A 1)
296-298 Reid Street, Christchurch BH23 2BT
Tel 01202 483333 Fax 01202 499763

REMNANT ENGINEERING LTD
Unit 161, Lydney Industrial Estate, Harbour Road,
Lydney, Gloucestershire GL15 4EJ
Tel 01594 841160 Fax 01594 843208

RIPPIN LTD
Thistle Ind. Est., Church Street,
Cowdenbeath KY4 8LP
Tel 01383 518610 Fax 01383 513099

ROBERTS ENGINEERING
16D Bergen Way, Sutton Fields Ind. Est.,
Hull HU7 0YQ
Tel 01482 838240 Fax 01482 830697

J. ROBERTSON & CO LTD (L M S 9)
Mill Lane, Walton-on-Naze CO14 8PE
Tel 01255 672855 Fax 01255 850487

ROBINSON CONSTRUCTION (C D E F H 1 Q1)
Wincanton Close, Ascot Drive Industrial Estate, Derby
DE24 8NJ
Tel 01332 574711 Fax 01332 861401

ROWECORD ENGINEERING LTD (A B O Q1)
Neptune Works, Uskway, Newport,
South Wales NP20 2SS
Tel 01633 250511 Fax 01633 253219

ROWEN STRUCTURES LTD (A 1)
Fulwood Road (South),
Sutton-in-Ashfield, Notts NG17 2JW
Tel 01623 558558 Fax 01623 440404

S H STRUCTURES LTD
Moor Lane Trading Estate, Sherburn-in-Elmet, North
Yorkshire LS25 6ES
Tel 01977 681931 Fax 01977 681930

SELWYN CONSTRUCTION ENGINEERING LTD
Tarron Road, Tarron Industrial Estate, Moreton, Wirral
CH46 4TU
Tel 0151 678 0236 Fax 0151 678 8959

SEVERFIELD-REEVE STRUCTURES LTD (A 0* Q2)
Dalton Airfield Industrial Estate, Dalton, Thirsk, North
Yorkshire YO7 3JN
Tel 01845 577896 Fax 01845 577411

SHIPLEY FABRICATIONS LTD
Maddocks Park, Ancaster, Grantham,
Lincs NG32 3PL
Tel 01400 231115 Fax 01400 231220

SNASHALL STEEL FABRICATIONS CO LTD
Business Park, Pulham,
nr Dorchester, Dorset DT2 7DX
Tel 01300 345588 Fax 01300 345533

SOLWAY STRUCTURAL STEEL
Killoch, Ochiltree, Cumnock, Ayr KA18 2RL
Tel 01290 700800 Fax 01290 700801

SOUTH DURHAM STRUCTURES LTD
South Church Enterprise Pk, Dovecot Hill, Bishop
Auckland, Co. Durham DL14 6XR
Tel 01388 777350 Fax 01388 775225

TAYLOR & RUSSELL LTD
Stonebridge Mill, Longridge PR3 3AQ
Tel 01772 782295 Fax 01772 785341

THE AA GROUP LTD
Priorswood Place, East Pimbo,
Skelmersdale, Lancs WN8 9QB
Tel 01695 50123 Fax 01695 50133

**TRADITIONAL STRUCTURES LTD
(E F H J K M N 6 Q1)**
Findel Works, Landywood Lane, Cheslyn Hay, Walsall,
West Midlands WS6 7AJ
Tel 01922 414172 Fax 01922 410211

TUBECON
Badminton Road, Yate, Bristol BS17 5HX
Tel 01454 314201 Fax 01454 273029

WARLEY CONSTRUCTION COMPANY LTD
Swinborne Road, Burnt Mills Industrial Estate,
Basilidon, Essex SS13 1LD
Tel 01268 726060 Fax 01268 725285

WALTER WATSON LTD (Q4)
Greenfield Works, Ballylough Rd, Castlewellan,
Co Down BT31 9JQ
Tel 028 4377 8711 Fax 028 4377 2050

WATSON STEEL STRUCTURES LTD (A B 0* Q1) PO
Box 9, Lostock Lane, Bolton BL6 4TB
Tel 01204 699999 Fax 01204 694543

WESTBURY PARK ENGINEERING LTD
Brook Lane, Westbury, Wilts BA13 4ES
Tel 01373 825500 Fax 01373 825511

WESTBURY STRUCTURES LTD (Q1)
Thorp Arch Est., Wetherby,
West Yorkshire LS23 7DB
Tel 01937 840600 Fax 01937 840601

WESTOK LTD (Q2)
Horbury Junction Ind Est, Horbury Junction, Wakefield
WF4 5ER
Tel 01924 264121 Fax 01924 280030

WESTON STEEL STRUCTURES LTD
Burnden Park Works, Summerfield Rd,
Bolton BL3 2NQ
Tel 01204 525335 Fax 01204 362106

JOHN WICKS & SON LTD
Unit 1, Crabbers Cross, Rattery,
South Brent, Devon TQ10 9JZ
Tel 01364 72907 Fax 01364 73054

WIG ENGINEERING LTD
Barnfield, Akeman Street,
Chesterton, Oxon OX26 1TE
Tel 01869 320515 Fax 01869 320513

H. YOUNG STRUCTURES LTD (C E F H J N 8)
Ayton Road, Wymondham, Norfolk NR18 0RD
Tel 01953 601881 Fax 01953 607842

ASSOCIATE MEMBERS

BUILDING COMPONENTS

ALBION SECTIONS LTD (Q4)
Albion Rd, West Bromwich,
West Midlands B70 8BD
Tel 0121 553 1877 Fax 0121 553 5507

**AYRSHIRE METAL PRODUCTS
(DAVENTRY) LTD (Q1)**
Royal Oak Way, Daventry NN11 5NR
Tel 01327 300990 Fax 01327 300885

BARNHAW PLATE BENDING CENTRE LTD
Corporation Rd, Audenshaw,
Manchester M34 5LR
Tel 0161 320 9696 Fax 0161 335 0918

CORUS PANELS & PROFILES (Q1)
Severn Drive, Tewkesbury Business Park, Tewksbury,
Glos GL20 8TX
Tel 01684 856600 Fax 01684 856601

FABSEC LTD
Brooklands Court, Tunstall Road, Leeds LS11 5HL
Tel 0113 385 7830 Fax 0113 272 7587

HI-SPAN LTD
Ayton Rd, Wymondham NR18 0RD
Tel 01953 603081 Fax 01953 607842

KINGSPAN METL-CON LTD (Q4)
Sherburn, Malton, N. Yorkshire YO17 8PQ
Tel 01944 712000 Fax 01944 710555

RICHARD LEES STEEL DECKING LTD
Moor Farm Rd West, The Airfield, Ashbourne,
Derbyshire DE6 1HD
Tel 01335 300999 Fax 01335 300888

MSW STRUCTURAL FLOOR SYSTEMS
Acton Grove, Long Eaton, Nottingham NG10 1FY
Tel 0115 946 2316 Fax 0115 946 2278

METSEC PLC (Q2)
Broadwell Rd, Oldbury, West Mids B69 4HE
Tel 0121 601 6000 Fax 0121 601 6181

STRUCTURAL METAL DECKS LTD
Mallard Hse, Christchurch Rd, Ringwood BH24 3AA
Tel 01425 471088 Fax 01425 471408

STRUCTURAL SECTIONS LTD (Q1)
PO Box 92, Downing St,
Smethwick, Warley B66 2PA
Tel 0121 555 1342 Fax 0121 555 1341

STUDWELDERS LTD
Millennium Hse, Severn Link Distribution Centre,
Newhouse Farm Ind Est, Chepstow, Monmouthshire
NP16 6UN
Tel 01291 626048 Fax 01291 629979

COMPUTER SOFTWARE

ACECAD SOFTWARE LTD
Truro House, Stephenson's Way,
Wyvern Business Park, Derby DE21 6LY
Tel 01332 545800 Fax 01332 545801

COMPUTER SERVICES CONSULTANTS (UK) LTD
Yeadon House, New St, Pudsey, Leeds, LS28 8AQ
Tel 0113 239 3000 Fax 0113 236 0546

PSYCLE INTERACTIVE LTD
The Stable House, Whitewell, Whitchurch, Shropshire
SY13 3AQ
Tel 01948 780120 Fax 08701 640156

RAM INTERNATIONAL (EUROPE) LTD
4 Woodside Place, Glasgow G3 7QF
Tel 0141 353 5168 Fax 0141 353 5112

TEKLA (UK) LTD
Tekla House, Cliffe Park Way,
Morley, Leeds LS27 0RY
Tel 0113 307 1200 Fax 0113 307 1201

DESIGN SERVICES

ARRO-CAD LTD
Bretby Business Park, Ashby Road,
Bretby, Burton-on-Trent DE15 0YZ
Tel 01283 558206 Fax 01283 558207

ODDA DESIGN LTD
The White House, Clifton Marine Parade, Imperial
Business Park, Gravesend, Kent DA11 0DY
Tel 01474 352849 Fax 01474 359116

STEEL PRODUCERS

CORUS CONSTRUCTION CENTRE
Frodingham House, PO Box 1, Brigg Road,
Scunthorpe DN16 1BP
Tel 01724 405060 Fax 01724 404224

CORUS CONSTRUCTION & INDUSTRIAL
Frodingham House, PO Box 1,
Brigg Road, Scunthorpe DN16 1BP
Tel 01724 404040 Fax 01724 404229

CORUS TUBES
PO Box 101, Weldon Rd, Corby,
Northants NN17 5UA
Tel 01536 402121

MANUFACTURING EQUIPMENT

FICEP (UK) LTD
10 The Courtwards, Victoria Park, Victoria Road,
Leeds LS14 2LB
Tel 0113 265 3921 Fax 0113 265 3913

KALTENBACH LTD
6-8 Brunel Road, Bedford MK41 9TJ
Tel 01234 213201 Fax 01234 351226

PEDDINGHAUS CORPORATION UK LTD
Unit 6, Queensway Link,
Stafford Park 17, Telford TF3 3DN
Tel 01952 200377 Fax 01952 292877

VOORTMAN UK LTD
Unit 8, Mercian Park, Felspar Rd,
Ammington Rd, Tamworth B77 4DP
Tel 01827 633000 Fax 01827 65565

PROTECTIVE SYSTEMS

AMERON INTERNATIONAL
Blackwell Road, Huthwaite,
Sutton in Ashfield, Notts NG17 2RL
Tel 01623 511000 Fax 01623 559616

FORWARD PROTECTIVE COATINGS LTD
Vernon St., Shirebrook, Mansfield,
Notts NG20 8SS
Tel 01623 748323 Fax 01623 748730

INTERNATIONAL PAINT LTD
Protective Coatings, Stoneycage Lane, Felling,
Gateshead NE10 0JY
Tel 0191 469 6111 Fax 0191 495 0676

LEIGH'S PAINTS
Tower Works, Kestor Street, Bolton BL2 2AL
Tel 01204 521771 Fax 01204 382115

SITE COAT SERVICES LTD
Unit 11, Old Wharf Road, Grantham,
Lincolnshire NG31 7AA
Tel 01476 577473 Fax 01476 577642

JACK TIGHE LTD
Kirk Sandall Ind. Est., Kirk Sandall,
Doncaster DN3 1QR
Tel 01302 880360 Fax 01302 880370

WEDGE GROUP GALVANIZING
c/o Worktop Galvanizing Claylands Avenue, Worktop,
Notts S81 7BQ
Tel 01909 486384 Fax 01909 482540

SAFETY SYSTEMS

EASI-EDGE
Olერთon Rd, Tuxford, Newark, Notts NG22 0PQ
Tel 01777 870901 Fax 01777 870524

STEEL STOCKHOLDERS

ASD METAL SERVICES - EDINBURGH
24 South Gyle Crescent,
Edinburgh EH12 9EB
Tel 0131 459 3200 Fax 0131 459 3266

ASD METAL SERVICES - BODMIN
Unit 13, Cooksland Ind. Est.,
Bodmin, Cornwall PL31 2PZ
Tel 01208 770666 Fax 01208 77416

ASD METAL SERVICES - LONDON
Thames Wharf, Dock Road, London E16 1AF
Tel 020 7476 9444 Fax 020 7476 0239

ASD METAL SERVICES - CARLISLE
Unit C, Earls Way, Kingsmoor Park Centre, Kingstown,
Cumbria CA6 4SE
Tel 01228 674766 Fax 01228 674197

ASD METAL SERVICES - HULL
Gibson Lane, Melton, North Ferriby,
East Riding of Yorkshire HU14 3HX
Tel 01482 633360 Fax 01482 633370

ASD METAL SERVICES - GRIMSBY
Estate Road No. 5, South Humberside Industrial
Estate, Grimsby DN31 2TX
Tel 01472 353851 Fax 01472 240028

ASD METAL SERVICES - BIDDULPH
PO Box 2, Tunstall Road, Biddulph,
Stoke-on-Trent, Staffs ST8 6JZ
Tel 01782 515152 Fax 01782 522240

ASD METAL SERVICES - DURHAM
Drum Road, Drum Industrial Estate,
Chester-le-Street, Co. Durham DH2 1ST
Tel 0191 492 2322 Fax 0191 410 0126

ASD METAL SERVICES - CARDIFF
East Moors Road, Cardiff CF1 5SP
Tel 029 2046 0622 Fax 029 2049 0105

ASD METAL SERVICES - STALBRIDGE
Station Rd, Stalbridge, Dorset DT10 2RW
Tel 01963 362646 Fax 01963 363260

ASD METAL SERVICES - NORFOLK
Hamlin Way, Kings Lynn, Norfolk PE30 4LQ
Tel 01553 761431 Fax 01553 692394

ASD METAL SERVICES - EXETER
Sidmouth Road, Clyst St Mary, Exeter EX5 1AD
Tel 01395 233366 Fax 01395 233367

ASD METAL SERVICES - DAVENTRY
Royal Oak Ind. Est., Daventry,
Northants NN11 5QQ
Tel 01327 876021 Fax 01327 87612

ASD METAL SERVICES - TIVIDALE
Tipton Road, Tividale, Oldbury,
West Midlands B69 3HU
Tel 0121 520 1231 Fax 0121 520 5664

AUSTIN TRUMANN'S STEEL LTD
Moss Lane, Walkden, Manchester M28 5NH
Tel 0161 790 4821 Fax 0161 799 0411

BROWN MCFARLANE LTD
Ladywell Works, New Century Street, Hanley, Stoke-
on-Trent ST1 5QH
Tel 01782 289909 Fax 01782 289804

CORUS SERVICE CENTRE
Farnham Road Station, South Darenth,
nr Dartford DA4 9LD
Tel 01322 227272 Fax 01322 864893

CORUS SERVICE CENTRE
Badminton Rd Trading Est., Yate,
Bristol BS37 5JU
Tel 01454 315314 Fax 01454 325181

CORUS SERVICE CENTRE
Spittlegate Industrial Estate, Grantham,
Lincolnshire NG31 7UP
Tel 01476 565522 Fax 01476 562459

CORUS SERVICE CENTRE
Blackamore Road, Walker Industrial Estate,
Guide, Blackburn BB1 2LJ
Tel 01254 55161 Fax 01254 670836

CORUS SERVICE CENTRE
South Street, Glasgow G14 0BX
Tel 0141 959 1212 Fax 0141 959 0111

CORUS SERVICE CENTRE
Moira Rd, Lisburn, Co. Antrim BT28 2SN
Tel 01846 660747 Fax 01846 660748

CORUS SERVICE CENTRE
Wakefield Rd, Stourton, Leeds LS10 1AY
Tel 0113 276 0660 Fax 0113 272 4418

CORUS SERVICE CENTRE
The Steelpark, Steelpark Way, Wednesfield,
Wolverhampton WV11 3BR
Tel 01902 484000 Fax 01902 484041

STRUCTURAL FASTENERS

THOMAS WILLIAM LENCH LTD
P O Box 31, Excelsior Works, Carnegie Road, Rowley
Regis, West Mids B65 8BZ
Tel 0121 559 1530 Fax 0121 559 3920


CORPORATE MEMBERS

BALFOUR BEATTY POWER NETWORKS LTD
Tel 01332 661491

GRIFFITHS & ARMOUR
Tel 0151 236 5656

HIGHWAYS AGENCY
Tel 08457 504030

ROGER POPE ASSOCIATES
Tel 01752 263636



Comparative structure cost of modern commercial buildings (Second Edition)

S J Hicks, R M Lawson,
J W Rackham and
P Fordham
ISBN 1 85942 157 1, 94 pp,
A4 paperback, Nov 2004

NEW BOOK

Commercial Buildings

This publication presents the results of a study carried out in 2003/2004 and updates the first edition published in 1993 that proved to be one of our best sellers.

Notable new inclusions in the study are the Slimdek® system, new cellular and fabricated beam designs using fire protective coatings, and a new post-tensioned ribbed slab scheme. The construction programmes for the steel and concrete schemes have been updated to take account of change in costs and modern construction practices.


Two buildings, typical of modern commercial building construction, are fully designed for a range of steel, composite and concrete options. The cost study includes the major variable items of structure, foundations, cladding and services. Account has also been taken of time-related savings in determining the net building costs.

It is shown that the cost variation in the most appropriate steel options is relatively small when considered globally in terms of building cost rather than pure structural cost. The

steel and composite options proved to be more economic than the reinforced concrete options, particularly when the additional time-related savings were taken into account. The cost premium for long span steel construction is negligible for the heavily serviced building (Building B).

It is concluded that most modern structural systems in steel and composite construction have broad economic merit. However, it is necessary to consider the choice of the structural system in relation to the influence on other non-structural, and often more expensive, aspects of the building construction. The conclusions of the study probably apply equally to a wider range of building forms: for example, hospitals, educational and retail buildings.

OFFER PRICES: Non-member £54. Member £27
(Prices include 10% discount)
(FREE P&P in UK- save £5.50. Offer ends 28 February 2005)



Tension control bolts, grade S10T, in friction grip connections

TC Cosgrove
ISBN 1 85942 156 3, 86 pp,
A4 paperback, Nov 2004

NEW BOOK


Tension Control Bolts

Tension Control Bolts Grade S10T are readily available in the UK. However, the manufacture of the bolts and the method of tightening are not explicitly covered by British or European Standards. This publication provides an 'industry standard' for the design of structural steelwork connections using preloaded Tension Control Bolts Grade S10T (TCBs). These fasteners and tightening technology are of Japanese origin and this publication provides advice in the interpretation of the preloaded bolt standards in the UK in regard to TCBs. A design method for preloaded TCBs Grade S10T that satisfies the recommendations of BS 5950-1:2000 and BS 5400-3:2000 is given.

A description of the tightening process, an outline of the manufacturing specifications and procurement requirements are also included. Worked examples are provided, illustrating the design of typical steelwork connections using preloaded TCBs Grade S10T.

Design tables are given for connections using TCBs; the tables give bearing, shear, slip and tensile resistances according to BS 5950-1 and BS 5400-3.

OFFER PRICES: Non-member £27 Member £13.50
(Prices include 10% discount)
(FREE P&P in UK- save £5.50. Offer ends 28 February 2005)



Technical Report: Precast concrete decks for composite highway bridges

E Yandzio and D C Iles
ISBN 1 85942 155 5, 86 pp,
A4 paperback, Nov 2004

TECHNICAL REPORT

Precast Concrete Decks for Composite Highway Bridges

The purpose of this Technical Report is to suggest ways to encourage the use of full-thickness, full-width, precast deck slabs in highway bridges, installed on top of steel girders and made to act compositely in carrying live loads and superimposed dead loads.

The publication introduces the reader to precast deck construction for single span and continuous multi-span bridges. The report considers and compares the different types of precast deck configurations that have already been built or proposed and includes recent research information that supports the use of this form of construction. A recommendation is made as to the most appropriate form of precast deck construction, based on the supporting technical information that is currently available. It is noted, however, that client authorities may need test evidence before accepting this form of construction for any particular project.

A number of key aspects have to be addressed in the design and construction of efficient, safe and economic full-thickness precast concrete decks for steel composite bridges:

- Sizing the precast deck units.
- Seating and alignment of the precast units onto the steel girders.
- Sealing of the concrete steel interface between deck and girder.
- Forming a composite bridge deck.
- Forming an effective joint between precast deck units.
- Formation of the edge beams.

Appendices include case studies and tests on full strength joints for precast concrete deck units.

PRICES: Non-member £25 Member £12.50 (plus P&P)

STRETCH

Your Steelwork, Not Your Cost

Whitehall Rd, Leeds, 18m span office



Douglas Carpark, 16m span



Liverpool College, 16m span



Cyfatha Retail Park, 53m span



Royal Preston Hospital, 17m span



WESTOK CELLULAR BEAMS...

- 20 - 50% lighter than plain beams.
- Each steel price rise increases the competitiveness of Cellular beams.
- Cambers at no extra cost.
- Curves at no extra cost.

The longer the span, the greater the saving.

T: 01924 264121
F: 01924 280030



E: design@westok.co.uk
www.westok.co.uk

Westok Limited, Horbury Junction Industrial Estate, Horbury Junction, Wakefield, West Yorkshire WF45ER

CSC Ad
to come
Monday