

NSC

www.new-steel-construction.com



**Dancing columns at Waterloo
Arsenal FC's new stadium
Bending technology advances**

bend it like...Barnshaws



barnshaws.com



BARNSHAWS
STEEL BENDING

Branches: West Midlands,
Manchester & Hamilton
Curved / Bent Plate: 01902 880250
Curved Sections: 0121 557 8261
Email: sales@barnshaws.com



Cover Image

PALESTRA, SOUTHWARK

Structural Engineer: Buro Happold
Steelwork Contractor: William Hare Ltd

EDITOR

Nick Barrett Tel: 01323 422483
nick@new-steel-construction.com

DEPUTY EDITOR

David Fowler Tel: 01892 538191
david@new-steel-construction.com

CONTRIBUTING EDITOR

Ty Byrd Tel: 01892 524455
ty@barrett-byrd.com

PRODUCTION EDITOR

Andrew Pilcher Tel: 01892 524481
andrew@new-steel-construction.com

ISDN: 01892 557302

ADVERTISING SALES MANAGER

Sally Devine Tel: 01474 833871
sally@new-steel-construction.com

PUBLISHED BY

The British Constructional Steelwork Association Ltd
4 Whitehall Court, Westminster, London SW1A 2ES
Telephone 020 7839 8566 Fax 020 7976 1634
Website www.steelconstruction.org
Email postroom@steelconstruction.org

The Steel Construction Institute

Silwood Park, Ascot, Berkshire SL5 7QN
Telephone 01344 623 345 Fax 01344 622 944
Website www.steel-sci.org
Email reception@steel-sci.org

Corus Construction and Industrial

PO Box 1, Brigg Road, Scunthorpe, North Lincolnshire DN16 1BP
Telephone 01724 404040 Fax 01724 404224
Website www.corusconstruction.com
Email tsm@corusgroup.com

CONTRACT PUBLISHER & ADVERTISING SALES

Barrett, Byrd Associates

Linden House, Linden Close,
Tunbridge Wells, Kent TN4 8HH
Tel: 01892 524455
www.barrett-byrd.com



EDITORIAL ADVISORY BOARD

Dr D Tordoff (Chairman); Mr N Barrett; Mr D Fowler;
Mrs Sally Devine; Mr D G Brown, SCI; Mr J P Cartz, BDP;
Mr M Crosby, FaberMaunsel; Mr R Gordon, Mace Ltd;
Mr W Gover, Consultant; Mr R Harrison, Glentworth Fabrications
Ltd; Mr A Hughes, Tubelines; Mr A Palmer, Buro Happold;
Mr R Steeper, Corus; Mr O Tyler, Wilkinson Eyre,
The role of the Editorial Advisory Board is to advise on the overall style
and content of the magazine.

New Steel Construction welcomes contributions on any suitable topics relating to steel construction. Publication is at the discretion of the Editor. Views expressed in this publication are not necessarily those of the BCSA, SCI, Corus or the Contract Publisher. Although care has been taken to ensure that all information contained herein is accurate with relation to either matters of fact or accepted practice at the time of publication, the BCSA, SCI, Corus and the Editor assume no responsibility for any errors or misinterpretations of such information or any loss or damage arising from or related to its use. No part of this publication may be reproduced in any form without the permission of the publishers.

CHANGES TO THE MAILING LIST

If you wish to notify us of a change:

Non Members of either the SCI or the BCSA please telephone Barrett, Byrd Associates on 01892 538191

Members BCSA Telephone BCSA on 020 7839 8566

Members SCI Telephone SCI on 01344 623 345

SUBSCRIPTIONS

To take out a subscription please telephone 01344 623 345
Annual subscription £92.00 UK, £117.00 elsewhere.

All rights reserved ©2005. ISSN 0968-0098



www.new-steel-construction.com



5 Editor's comment

6 News: International drive to increase constructional use of steel.

10 Letters and Diary

11 Analysis: Market Shares Survey.

COMPANY PROFILE

12 Growth in demand for curved steel is good news for the world's biggest steel bending specialist, Barnshaws Steel Bending.

FEATURES

16 EvadX has erected and fabricated all the structural steelwork on the new Lauries Centre at Birkenhead

18 Arsenal FC's new home looks like being a jewel among stadiums. David Fowler reports from pitchside.

20 Buro Happold faced major challenges on architect Will Alsop's strikingly designed Palestra, a central London office development.

24 The arrival of the Eurocodes calls for a reconsideration of our approach to design. Charles King of the SCI argues that using the Eurocodes, design can in fact be simplified.

28 High grade steel is increasingly being specified for structural use. Richard Barrett of Barrett Steel Buildings explains why.

30 Advisory Desk. The latest advice from the Steel Construction Institute includes guidance on construction for discontinuous columns and continuous beams.

31 Courses

32 40 Years Ago. A backwards glance at the concerns of yesteryear through the pages of Building With Steel.

34 Publications

35 New and revised Codes and Standards

36 BCSA members

38 Register of Qualified Steelwork Contractors and SCI members

39 SCI members



The British
Constructional
Steelwork
Association Ltd



The Steel
Construction
Institute

SPAN

FURTHER

MULTIDECK New Multideck V2 now spans further than ever.

Call now for the new and completely updated Handbook and CD Software on **0870 761 7004** or visit our website **kingspanmetlcon.com**



Kingspan Metl-Con Ltd. Sherburn, Malton, North Yorkshire, YO17 8PQ. England.
Tel: 01944 712000 Fax: 01944 710555 e-mail: sales@kingspanmetlcon.co.uk



International effort will boost use of steel



Nick Barrett - Editor

News of a major International drive by steel manufacturers to enhance the attractiveness of their products to construction should come as welcome news to UK constructional steelwork designers and contractors (see News). A 10% rise in the use of steel in construction is the aim of the £10M, five-year programme being led by the International Iron and Steel Institute and supported by major producers including Corus.

A range of new initiatives is to enhance the competitive edge of the industry, including market research, technology benchmarking, knowledge management, an international architectural competition and demonstration building. This is all great news. It is in the interests of the UK constructional steelwork industry to have similar healthy industries elsewhere. Steel has been remarkably successful for the UK construction industry and if it were as widely used internationally then we would not so often feel that we are climbing learning curves alone; colleague industries would learn from the UK and pass back to us the benefit of their own lessons. International cooperation and technology exchange hold out great prospects for all constructional steelwork industries.

The UK industry of course has a vast reservoir of accumulated knowledge and experience to pass on already. As BCSA President Tom Goldberg pointed out in his speech at the National Dinner, one of the things that have been learned is that the use of steel is promoted mostly by solid technical knowledge and practice in key areas such as design codes, specifications, fire engineering (see below) and composite construction. All of this is coupled in the UK with an increasingly efficient steelwork contracting industry. Nobody ever has perfect knowledge, however, so the IISI-led initiative should enable any gaps to be at least identified and perhaps filled.

Intumescent success

The marked success of off-site applied intumescent fire protection is not quite hidden away among the other good news of the 2004 Market Shares Survey, but it deserves a bit more attention drawn to it. Few, if any, predicted how successful off-site application would become when a small group of fire engineering specialists, engineers and manufacturers first got together under the auspices of the Steel Construction Institute to produce P160, which has had to be updated after eight years to cope with an unexpectedly rapid pace of change and uptake of off-site application.

The off-site intumescent coating application industry is expected to fire-protect over 70,000 tonnes of structural steelwork this year, which represents about one third of the market for intumescent. There are many reasons for the success of off-site application. There are advantages to be gained in terms of cost, speed, improved safety, and quality control. Quality control will quite rightly be uppermost in the mind of anyone thinking about fire protection, and it is worth noting that the quality control procedures contained in the new model specification are regarded as even more stringent than those which apply on site, which themselves lack nothing in rigour.

Beijing tower for Siemens



Work has begun on a new Chinese HQ for electronics giant Siemens. The Siemens Centre Beijing is a 30-storey, 52,260m² steel tower designed to house 3,500 staff, providing space to bring together existing staff from a number of subsidiaries in the capital as well as accommodating growth. The €100M (£69M) building will be one of Siemens's top 10 global investments. It will comprise a 123m tall tower linked to two five-storey base buildings with courtyards.

Project manager is SIBC, originally Siemens Industrial Building Consultants, a joint venture between the electronics firm and Turner & Townsend. T&T, which also managed the Siemens Centre in Singapore, has since taken full control of the venture. Architect is Taiwan's CY Lee, which was also responsible for Taipei 101, the world's tallest tower. Structural engineer is Beijing Paramount Design Institute.

Demolition of Siemens' existing offices on the site, in Beijing's Wangjing District, has just been finished and the building is scheduled for completion in 2007.



Drive to promote use of steel

Increasing the use of steel in construction by 10% is the aim of a five year €14M (£10M) programme launched by the International Iron and Steel Institute and 11 of its members, including Corus.

The leaders of seven of the steel companies formally signed the agreement in London in February and the first meeting of the group has since been held. Those who signed the agreement in London were Arcelor, BlueScope Steel, CELSA, Corus, Mittal Steel, POSCO, and Tata Steel. The Secretary General, Ian Christmas, signed the agreement on behalf

of IISI. The four other companies participating in the programme are Erdemir, IMIDRO, Ispat Industries, and Ruukki.

The new initiative is an opt-in programme for companies active in the construction sector and IISI will continue to try and attract new programme members during 2005. The programme will enhance the competitive edge of steel companies in the construction through a range of new initiatives. These will include market research, technology benchmarking, knowledge management, an international architectural com-

petition and demonstration building.

The programme grew out of the work done by IISI's Steel Solutions and Sustainable Urban Development (Scoping) Project Group, which presented a proposed work plan to IISI's Board of Directors in April 2004. The Project Group demonstrated that there are pockets of construction best practice amongst IISI members. However, no region had fully exploited the contribution steel can make to improved construction.

The first meeting of the participating companies was held from 21–25 February 2005 in Kolkata, India.



Singapore library chooses Corus steel

Corus has supplied structural steel for the prestigious new Singapore National Library, which is due to open in June.

The library, designed by architect TR Hamzah & Young, is claimed to be the most advanced ever built. It is 16 storeys high, boasts an observation pod on the roof, and includes three basement levels and walkway bridges connecting the upper levels.

Corus, as the sole supplier of structural steel, provided a package of structural sections and plates

totalling more than 4,500t.

The material was supplied from Corus's plate mills in Dalzell and Scunthorpe, the beam mill at Teesside and the hollow section mill at Corby. Corus achieved an overall fabrication wastage of 8%, considerably better than the 12% that is typical for a building of such complexity.

Bernard Chung, Technical Manager of Corus International Asia, says: "Corus International's precise organisational structure and

local support network allowed the project to run successfully through to completion. The local network of offices was able to source urgent requirements from stock within the region."

Buro Happold was consultant, including structural design, for client National Library Board. Maunsell Consultants (Singapore) was civil and structural consultant for the design and build project team, which was headed by main contractor Nishimatsu-Lum Chang.

Steel outlook stabilising

Demand for constructional steelwork is rising and the outlook for prices is stabilising, BCSA President Tom Goldberg told the National Dinner in London on 8 March.

"Steel construction is doing well, despite the 60% price rise in our raw material in 2004, and we are in an environment where our prices are now expected to be much more stable," he said. "Price rises for steelwork in 2005 should be of the order of 5%. Demand in the UK is nearly as high as in the last boom of 1988/89: it now totals 1.3M tonnes, and we are gaining market share in a number of key sectors such as residential, hospitals and education."

Mr Goldberg said prices are now sufficient to maintain a healthy level of investment by BCSA members in areas like machinery and in research and development of innovative products and methods. He added that a range of measures were in hand to make the industry even more competitive, and the industry was committed to finding better ways of delivering service to its customers.

BCSA was also striving for operational effectiveness and efficiency in-house and in the past year a review of the organisation and strategic planning had been undertaken. Sister organisations worldwide had been examined, and new strategies and work

programmes instituted as a result.

Guest speaker Mr Philippe Varin, Chief Executive of Corus Group, said construction was the most important market sector for Corus and he aimed to be a value player in steel in construction. Conditions in the steel market were significantly better than they had been for some years. Corus had made a lot of progress recently and a turning point had now been reached. The worldwide demand/supply balance for steel would remain tight as China and other markets grew.

Corus aimed to replicate the success of the UK constructional steelwork industry in capturing dominant market shares in the commercial and industrial buildings markets in other European countries. In the UK residential construction had been identified as a priority for growth. To achieve these and other goals Corus recognised that it had to work alongside its customers.

Mr Varin said consolidation in the steel industry would continue and he expected to see the growth of truly global steel companies. The top five producers in Western Europe account for more than 60% of total steel production; in North America 50% and in Japan, about 80%. But the top five producers in the world account for under 20% of global steel production.



Tom Goldberg, President, BCSA



Philippe Varin, Chief Executive, Corus Group

New Forest, new hospital



Atlas Ward Structures has been awarded a contract to fabricate and erect structural steel for the new PFI Lymington New Forest Hospital in Hampshire.

Main contractor Sussex-based Rydon Construction will work in partnership with associate company and PFI specialist Ryhurst on the £29.8M deal recently signed with New Forest Primary Care Trust.

Atlas Ward Structures will fabricate and erect 500t of structural steelwork and install 8,000m² of metal floor decking.

Peter Blewett, Principal Engineer at structural engineer Upton McGou-

gan, said the hospital was designed with a steel frame "because it is a clean, reliable and quality assured product, which can meet strict NHS standards for acoustic insulation and vibration levels."

The hospital, designed by architect Murphy Philipps, is made up of two buildings on a 3.72ha site. The main hospital building includes a three-storey ward building, a two-storey entrance and a two-storey diagnostic and treatment centre. The second building will provide the hospital's energy, waste and management centre. The project is due to be completed in November 2006.



Taking Cobalt to Newcastle

Cobalt 16 is the latest speculative development on Highbridge Business Parks' Cobalt Park development in Newcastle.

The four-storey development provides 9,400m² of floor space in two wings around the office core. Barrett Steel Buildings designed, fabricated and erected the 450 tonne structural steel frame for main contractor Bowmer & Kirkland.

The steel frame uses asymmetric beams to provide uninterrupted service zones under the precast concrete planks.

The front façade is constructed from full height curtain walling. This needed special attention at the design stage to eliminate all vertical bracing.

The rear elevation is clad in masonry built around full height windows, with 450x450 RHS sections providing floor and window support. Proprietary stainless steel angles supplied and fixed by Barrett support the masonry.

Architect was Ryder HKS and structural engineer was Cundall Johnson and Partners.

Construction News

17 March 2005

The sixth and final section of Heathrow Terminal 5's 17,000-tonne steel roof, fabricated by Watson Steel, was slotted into place by Italian lifting specialist Fagioli earlier this month. The placement is a milestone in BAA's £4.2bn Heathrow project, which has now reached the half-way stage.

Building Canary Wharf (supplement to Building)

18 March 2005

"With structural steelwork, concrete and cladding, we together with our suppliers and contractors have achieved rates of erection not usually seen in the UK." Canary Wharf Contractors Executive Director Dan Frank.

The Structural Engineer

15 March 2005

'Steel construction is doing well... and we are in an environment where our prices are now expected to be much more stable,' announced BCSA President Tom Goldberg at the BCSA's National Dinner. Mr Goldberg said price levels were sufficient to maintain healthy investment in machinery, material handling equipment, computerised systems for design/control/operations, and training and maintenance of an ever-more-competent workforce, and in research and development of innovative products and methods.

Building

4 March 2005

'John Prescott set you a challenge four years ago. Today I set you an even greater one — it is to eliminate all deaths. Why? Because I believe every death in construction is avoidable.' — Construction Minister Nigel Griffiths at the 2005 Health and Safety Summit.

Building

4 March 2005

"The UK industry went through a bit of a hiatus between the loss of traditional craftsmanship and the advent of computer technology. Now I think it is fantastic. Contractors that are using computers are doing incredibly good work. Thomas Vale, which worked with us on the Spiral Café at Birmingham, was great." — David Marks of Marks Barfield, designers of the London Eye.

New guide on intumescent coatings

Design and contractual guidance is being provided by an updated model specification for off site applied intumescent coatings, which will be launched this month by the Steel Construction Institute. The new guide — Structural Fire Design: Off-site Applied Thin Film Intumescent Coatings — is a new edition of SCI P160 which was introduced in 1996 and which is thought to have been overtaken by the rapid success of off-site applied intumescent coatings since then.

The off-site intumescent coating application industry is expected to fire-protect over 70,000 tonnes of structural steelwork this year, a success story which has taken many by surprise. The new guidance has been designed to more

accurately reflect current standards, procedures and expectations of the structural steelwork industry. John Dowling, Chairman of the P160 Development Committee, said: "The first edition provided a new industry standard for the use of off-site applied intumescent coatings, and by presenting a model specification it was hoped that greater uniformity could be achieved in contract specifications.

"We said at the time that we would update the guidance in line with industry experiences and this revision relies heavily on the input of people from across the sector."

The guide is in two parts. The first part, Design Guidance, concerns handling, storing and transporting coated steelwork and has been fully

updated to reflect the experience of the past nine years. The sections on fire protection of beams with web openings, concrete filled hollow sections, connections, composite beams and bracing, reflect the latest thinking. Information has now been included on the protection of partially exposed members.

The second part of the new guide provides Model Specification Clauses for use in the preparation of contract documentation relating to off-site applied thin film coatings. The standard clauses can be modified or omitted as required by the user but most should be capable of use without the need for modification.

The guide will be available to download as a Word document from www.steelbiz.org from 21 April 2005.



Tate's 100 tonne steps

Constructing a 100-tonne steel structure to form the centrepiece of a new exhibition by Sir Anthony Caro at the Tate Modern presented several unusual challenges for steelwork contractor William Hare.

'Millbank Steps', built from 40mm thick weathering steel plate, was made specially for a retrospective

covering 50 years of the sculptor's work.

"One of the main problems was how to get it into the gallery," said Richard Branford, William Hare Project Manager. "We had to size the components to go through doors and around corners, so it was fabricated in L-shaped components."

Welding was not allowed in the gallery, so the 35 pieces had to be bolted together. Because the sculptor wanted clean joints rather than visible bolts, the joints are made with 1500 countersunk bolts in drilled and tapped holes rather than the usual clearance holes. The components were sent to a machining shop to be drilled and tapped to the required accuracy.

The floor is too weak to carry the sculpture directly, so it rests on a transfer structure designed by structural engineer Campbell Reith Hill to direct its weight into load-bearing walls beneath. In addition some props have been used, making it necessary to close off part of the gallery's basement café for the duration of the exhibition.

There were no engineering drawings: William Hare worked from a set of drawings used to produce a plastic scale model provided by the sculptor from which it produced a walk-through X-Steel model for approval.

Due to height restrictions in the gallery and to ensure temporary stability of the sculpture, purpose-made equipment was designed. This included a gantry crane running on rails with movement of the frame being achieved by Tirfor winches, and a temporary support frame that allowed fine adjustments in level and plumb.

The programme for erection was three weeks. "We beat the programme by three or four days," said Mr Branford.

New machines boost T5 productivity



Use of "coupled" steel coping and drilling machines in a single production line significantly speeded up steel fabrication production on BAA's Heathrow T5 project.

Steelwork contractor Severfield-Reeve says new Kaltenbach KC1200 and KDX1215 equipment, installed in Severfield's Dalton facility in Yorkshire, enables the beams to be passed through the copier and drill in a continuous process — producing, in one run, beams with holes drilled and profiles cut.

Traditionally these are separate activities, which increases handling



and machining time. As well as saving time, Severfield's Steve Snow says the new machines greatly increase flexibility as well.

The T5 fabrication also benefited from new software which uses design files to control cutting and drilling of members to almost any contour and combination of holes, with minimal operator input.

The KDX has three axes with five drill spindles and 11.5kW motors per axis, while the KC1200 coping systems have oxyacetylene and plasma cutting heads capable of profiling H, U and L sections.

The T5 structural elements are among the largest ever produced in Severfield's Dalton plant. Beam flanges are up to 125mm thick and weigh in excess of one tonne per metre.

The T5 structure, designed by architect Richard Rogers, contains approximately 60,000t of structural steelwork, of which 45,000t will be produced by Severfield-Reeve. The remaining 15,000t of complex roof support steelwork is being produced by sister company Watson Steel. The airport is on schedule to open in 2008.

Radio and TV presenter John Humphrys has been confirmed to chair the panel discussion on the future construction market at the Steel Construction Conference and Exhibition, to be held at The Brewery, Chiswell Street, London in November.

The Respect for People code of practice, launched at the recent 2005 Construction Health and Safety Summit, has been developed to help the construction industry achieve the targets for injury and ill-health. The targets, set out in the Revitalising Health and Safety programme launched at the 2001 summit, are to be achieved in 2005 and 2010.

Metsec has released an updated version of its LatticeSPEC design software for its range of light-weight steel lattice joists and trusses. The program designs parallel, pitched and tapered trusses but now includes the company's curved beams and curved truss ranges as well. The software is available free on the new Met-SPEC 2005 CD.

Lattice_joists@metsec.com

The British Stainless Steel Association has added two modules to its RIBA approved seminar programme. *The Structural Design of Stainless Steel* is aimed at structural engineers and architects and provides practical guidance on design principles, material properties and grade selection. *Stainless Steel in Swimming Pools* outlines the principles of good design and material selection, with advice on avoiding possible pitfalls.

Lloyd Instruments has demonstrated the ability to automate tensile strength testing of metals at high temperature and at the end of a temperature conditioning cycle, by linking its 100kN LR100K materials testing machine to two furnaces. Any number of heating and cooling cycles can be run automatically. At the end of the cycling process the system performs tensile tests on the sample without intervention from the operator.

Further details: 01489 486399

Big in Bradford



Bradford's biggest single office investment for over a decade, No 1 The Interchange, has been completed. Elland Steel Structures supplied and erected 680 tonnes of steelwork and 8500m² of metal decking for the £12.5M scheme in the city centre, built on the site of an old bus depot. It will provide 5,600m² of prime office space, most of which has been taken by the Inland Revenue.

Tight planning provides key to Stroud Centre

Just in time delivery was a crucial factor in the erection of steelwork for a retail development in Stroud.

Conder Structures had a tough 12-week deadline to erect 800 tonnes of steel on a tight site for the £8.7M Merrywalks Centre. The centre will provide 10,000m² of retail and leisure facilities near the Gloucestershire town's historic commercial centre.

Conder Managing Director Gordon Ridley said: "We've done a number of town centre jobs and one of the diffi-

culties is that it's always a confined site. You can't deliver the steelwork and leave it till it's needed. It required careful planning with delivery to site on a just in time basis."

Mr Ridley says that the ability to handle complex logistics "is a skill you have to develop". He added: "Not only did we have to fit in with Costain, the main contractor but right down the supply chain our suppliers had to work on the same basis. It was vital to the success of the project."



NSC welcomes letters from readers on steel construction related issues. Please keep your letters brief — the editor reserves the right to condense. Address your letters to: The Editor, NSC, BBA Linden House, Linden Close, Tunbridge Wells, Kent TN4 8HH. Fax: 01892 524456. e: info@new-steel-construction.com

Intumescent quality finish

Having had the opportunity to go around and photograph the Wellcome Trust building, I was particularly interested to read your article (NSC March 2005).

I can attest to the very high standard of the detailing and finish, which is only indirectly referred to in your article. It is sometimes said that the use of an intumescent paint is not conducive to a high standard of finish on the columns. I believe that this building disproves this assertion. The column finish was excellent. I am told that the fact that the circular column hollow sections were filled with unreinforced concrete, allowed the intumescent to be of minimal thickness and to go on in one coat, just like any other paint. That such thin coats can still give a one hour fire rating seems to me of great significance to architects, principally because of the superb finish that can be achieved but also because of the cost savings.

Andrew Calland
School of Engineering, Northumbria University, Newcastle upon Tyne

Lessons to learn from overseas

I read with interest Derek Tordoff's comments (NSC March 2005) on the worldwide market development activities in steel construction and the consequent decline in the use of concrete. In France we also have a comprehensive market development programme under way for steel construction which is resulting in increased market share against concrete in many sectors including multi-storey buildings and bridges. There is significant growth potential for steel in construction across the whole of Europe. As part of this programme, together with the European Convention for Constructional Steelwork (ECCS), from 20–21 September we will be holding an International Symposium on Architecture and Steel in Nice. Delegates

from the UK would be most welcome to attend; the presentations will be given in English. Further details can be found from beginning of April at www.scmf.com.fr

Jean Louis Gauliard
Secrétaire Général du Syndicat de la Construction Métallique de France – SCMF

Concrete fire tests needed

Recent events at the Windsor Building in Madrid are a timely reminder that nothing can be taken for granted. The near collapse of the building in a fire which, although of long duration, did not appear to reach the temperatures under which materials are normally tested, indicates that the margins of error and levels of conservatism under which we often assume we operate may not always be valid. The fire has also shown the importance of getting all fire precautions installed correctly, and how a relatively small error such as the reported absence of fire stopping between the floors can have potentially catastrophic consequences. We have been concerned at this state of affairs in the UK, and it formed a part of the report from a Partners in Innovation project in 2003.

Of even greater importance, however, is the fact that the fire also raises questions about the behaviour of the building frame. This is understood to be reinforced concrete, a material which is believed to behave well in fire. However, I am aware that in recent years troubling questions have been raised as to whether this reputation is fully justified, and a number of fires such as that in Madrid, the Channel Tunnel and others which have led to concrete frame collapses have led to calls for a reappraisal of the situation. In particular, I am now finding widespread agreement that phenomena such as excessive spalling and thermal expansion of floors are causing particular

concern and are not sufficiently well understood. For example, any reliance upon "membrane action" is something that requires more understanding.

I would like to add my voice to those who have expressed apprehension and call on the concrete industry to dispel these concerns through a commitment to large scale testing, similar to that carried out by the steel construction sector over the past decade.

David P Sugden
D P Sugden & Associates Ltd

No car park vibration issue

On reading your two articles regarding steel-framed car parks in NSC March 2005, I noticed that the question of vibration was not discussed. Please could you advise me if there are any reference documents regarding this?

Matt Scolin
Bone Steel Ltd

The editor replies: The recently issued "Steel-Framed Car Parks" 3rd edition from Corus Construction & Industrial contains information on dynamic performance in steel-framed car parks. In it advice is given on response factors for car parks and results of a study of nine steel-framed car parks constructed over the last 15 years where no adverse comments about dynamic behaviour had been noted.

This section of the design guide concludes "The study shows that the traditional natural frequency value of 3.0Hz can be maintained for design, and used with confidence". A copy of this design guide is available from Corus literature hotline on 01724 404400 or via the website www.corusconstruction.com.

You may also be happy to hear that a revised and updated edition of the SCI design guide "Design guide on the vibration of floors" (P076) is planned for later this year. This complements the publication in 2004 of "Design Guide on the vibration of floors in hospital" (P331) also by the SCI.

Diary

21 April Launch of SCI P160, Model Specification for Off-site Applied Intumescent Coatings

See page 8. National Liberal Club, Westminster, London.
Contact: Janice Radford, 01724 404863
email janice.radford@corusgroup.com

4-5 May Steel bridges designed to BS5400

Inchyra Grange Hotel, Falkirk
Corus course covering common steel bridge forms, the code basis for loading, design of key elements, fatigue design and connection detailing.
Jane.parkins@corusgroup.com


23 June Structural Steel Design

Awards Luncheon Savoy Hotel, London.
Winners of the 2005 awards, sponsored by Corus, the BCSA and the SCI, will be announced. Contact: Gillian.Mitchell@steelconstruction.org

20-21 September Architecture and Steel International Symposium,

Palace de la Méditerranée, Nice (part of the ECCS 50th anniversary event). Presentations will be given in English. Further details available at www.scmf.com.fr

Concrete market crumbles



The 2004 Market Share Survey confirmed the dominance of steel as the constructional framing material of first choice in the key sectors of the market, as developers and designers continued to turn away from lower-tech alternatives like concrete. Nick Barrett highlights some of the strongest market trends.

One of the most encouraging features of the 2004 Market Share Survey was that in the major growth sector of high rise residential, steel was winning market share. In a market which had grown from 1% of the total accommodation starts in 1999 to 11%, steel has seen its market share increase from 39.4% to 43.5% in a single year.

The number of steel-framed apartments has doubled since 2003, with steel frames used for over 10,000 high rise apartment units in 2004, compared with less than 5,000 units in 2003. These tend to be prestige developments, often waterfront, and the good news is that despite all the worries about the broader housing market, apartment building still looks like being on the increase — and a large proportion of new building will be multi-storey. With the competitive position regarding steel versus concrete frames unchanged by rising steel and cement prices, steel can expect to continue the recent trend of capturing market share as developers latch on to other benefits of steel — not the least important of which for the housebuilders is construction speed and being able to catch windows of market opportunity.

A number of factors have come together to create this rising demand for high rise

accommodation. The house buyers' view of high rise living seems to have undergone a sea change in the past few years. There has been a marked increase in the popularity of city centre living and as people return to towns they are demanding apartments rather than the terraced houses or tenements of the past. An increasing amount of this is being provided in multi-storey structures.

According to a survey by property consultant Savills, there are over 87 high rise blocks of over 20 storeys either under construction or planned across the UK. As well as providing around 19,000 housing units, they will give great views across cities or rivers, and they are being built with car parks, gyms and other features. These signature buildings are a far cry from the public sector high rise failures of the past, and are the most visually arresting part of the urban renaissance of the UK's major cities.

Government policy of encouraging brownfield developments rather than building new homes in the countryside has been a factor in encouraging these inner city, high rise residential developments. Although London will be the focus of the action, hardly a major city does not have a major development or two in the pipeline.

The growing popularity of multi-storey residential blocks is a trend which favours steel



Of those identified by Savills, 49 were in London, but almost 25% were in the North East and North West. Towers are expensive to build; according to data from cost consultants construction costs rise markedly between 20 and 40 floors. As the building's height rises so does the need for foundation strength, and the relatively low self weight of steel helps swing the cost argument further away from concrete.

This is a market which is usually thought to depend to a crucial extent on cost. As Savills' survey pointed out, for the tallest residential buildings of over 50 storeys a developer needs to achieve sales values in excess of £425 per sq ft, which may explain why relatively few tall residential towers have been developed in the past. Savills says that in spite of this, many developers turn a blind eye to the finances as there is an acceptance that a signature building can offer help in promoting a large regeneration scheme. "It may not make the developer his fortune, but the marketing and awareness that it generates for the scheme as a whole, far outweighs any loss in the overall profit margin," Savills argues. Still, we can be sure that price is still in the equation somewhere, which suits steel.

There have been misleading press reports that post-tensioned concrete slabs have doubled their volume in terms of floor area over the past two years and taken share from steel frames. But as the Construction Markets survey shows, the volume of high rise apartments has risen substantially, from 3% of the residential market in 2002 to 11% in 2004. Post-tensioned concrete volumes may well have increased in absolute numbers, but this simply masks the fact that steel frames have also gained, not only in volume but also in market share at the expense of concrete alternatives.

Trends are also running steel's way elsewhere. What was marked in the 'all multi storey non-residential buildings' category was the continued lack of market interest in concrete for frames there. Steel's market share increased to 69.2%, with in-situ concrete down to 16.8%, its lowest level since the survey began in 1980.

The concrete collapse was also marked in multi-storey offices where steel extended its dominance with a share of the market, defined by floor area, of 71.7%, while insitu concrete saw its share of offices fall to 20.9%, from 23.3% in 2003.

In the 'other multi-storey buildings' category, which includes retail, leisure, education and health buildings steel enjoyed a 68.2% market share with insitu concrete being used on just 15%, down from 17.5% in 2003. Load bearing masonry saw its share of these sectors rise to 11.2% from 8.4% in 2003.

Of particular note in steel framed multi-storey non-residential buildings is the continuing rise in the use of intumescent coatings for fire protection. In 1995, around 10% of steelwork in multi-storey buildings used intumescent coatings; in 2004 that figure has risen to 65%. The steel industry's commitment to research and development into steel's fire performance has led to an engineered approach incorporating intumescent coatings becoming the industry standard, with significantly reduced costs and improved safety. Fire performance was once regarded as steel's Achilles Heel, but the improved understanding that has been developed through focused research is now turning it into something of an advantage, particularly when compared with in situ concrete — where designers are increasingly recognising that it is a mistake to consider concrete as inherently fire resistant.



"From the onset it was apparent that no other detailing package could compete with Tekla Structures."
David Ball, Detailing Group



"We switched to Tekla Structures and haven't looked back...the drawings are just so much better - our workshop loves them!"
Vic O'Mara, Marton Engineering Services




"Tekla Structures provides benefits and time saving features that better prepare us for the future!"
James Sutcliffe, Sutcliffe Construction


> Tekla Structures proudly presents:

The Modern CLASSIC


in steel detailing



Easier and more accurate
than 2d detailing



Clear, concise drawings, reports and nc files



> Introducing Version 11. Faster, Better, More Profitable

If you are involved in structural steel projects, as an engineer, fabricator or detailer, you need to take advantage of Tekla Structures 11.

Evolution comes in many forms. Look at what we have achieved.

From the quality of drawings, to the range of cold rolled systems, to the brilliance of our modelling, you will not be disappointed. Couple that with our superb customer service and you are really onto something...

www.tekla.com

Schedule a demonstration now! Call 0113 307 1200 or email sales.uk@tekla.com



TEKLA Structures

...Only ONE can be the Best

Curved steel boosts creative design

Steel bending specialists have invested in research and development for new equipment that is giving designers greater freedom to express their creativity using curved steel. Nick Barrett visits market leader Barnshaws Steel Bending.



Reverse bends in the same section can be created to reduce the welded joints. A straight section in between the curves is usually needed.

Not only is Barnshaws the biggest steel bending company in the world, it can now do the biggest bends thanks to investment in developing new equipment. Architects and engineers can now routinely use curved steel in ways which were not possible 10 years ago, thanks to advances in bending technology.

Investment by companies like Barnshaws means that bends are more economical than ever before — a bend for a rafter might cost only £65. The same investments mean that the highest quality is now routine, with bend tolerances to $\pm 2\text{mm}$. Joints and welds are increasingly disappearing as curves become more common. "Curving is often less expensive than cut and weld," says Managing Director Craig Barnshaw.

"We take on the difficult jobs, for example putting six or seven bends in a single sheet. A lot of fabricators can do the simpler jobs themselves, but none have the capability that we have with our machines. We start where most fabricators have to finish, because we have the tooling. We can bend anything that Corus makes." For the tightest bends Barnshaws insists on using Corus steel for quality reasons. "Not everything that people source

is suitable for bending," says Barnshaw. "Some imported steel for example is presented as High Grade, but what they do to make it high grade sometimes makes it harder to bend."

Barnshaws today employs about 200 at its six UK sites and turns over some £12M for a surprisingly large number of customers — 4,000 live accounts at the moment — ranging from Corus through to fabricators of all sizes to manufacturers of mirror frames and napkin rings. "It is amazing who needs steel to be bent to precise tolerances, but the structural steelwork industry offers us our biggest challenges," says Barnshaw.

The turnover from bending has remained relatively static in recent years but the demand from construction has risen as other customers, such as manufacturers of gear casings, have moved production from the UK to Eastern Europe.

Barnshaws undertakes section and tube and hollow section bending as well as universal beam cambering, tee splitting and straightening, press braking and shearing, and plate rolling. Aluminium extrusions can also be curved and Barnshaws Specialist Profiles Division cuts shapes for architectural supports, stiffeners or features.



Sections and shapes can be designed on AutoCAD and the drawing e-mailed to Barnshaws for manufacture. Multiple radii can be used as shown in the picture.

The growth in tubes and box section curving for buildings and bridges has been marked: "Ten years ago we saw very little of that, but in recent years this has changed," says Barnshaw. "Now we can bend tubes in three dimensions or bend on different axes. We can bend sections to a tighter radius than before as well. Before we may have needed a 10mm thick section but now we can bend 5mm thick sections to the same radius, which cuts material costs."

With price pressures on fabricators, there is an increasing need to reduce the weight of structures. Barnshaws is constantly reducing the radius of sections which can be curved. As a result designers can use lighter sections and reduce the total weight and associated costs like foundations.

Growth is also being seen in the cold rolled market as lighter weight sections are increasingly used in growing markets like off-site. Curved steel usually has high visibility and is seen commonly on new stadiums, a market which continues to expand. Growth is also coming from wherever clients are demanding clear column-free spaces.

Though it is most obvious in high profile structures such as stadiums, the trend to larger spans is apparent in buildings as well. Many designers prefer hollow sections for aesthetic reasons, and as architects become more adventurous in their designs the demand for bending heavier sections increases. This is where Barnshaws' new bending machine comes into its own. It can bend sections with an elastic modulus of up to 84,000cm³, three times the previous maximum section depth.

"Larger parts of buildings are now being curved, not just the feature parts," says Barnshaw. "At one time, not many architects designed using curved steel, but the spread of computer aided design and associated software means that being able to do the calculations for curves is now common."

The pace of change has been rapid recently. Barnshaw says that the Gateshead Millennium Bridge, which has a lot of steel curved by induction bending, might not be done that way now. "Our

new method of cold bending sections offers greater flexibility to fabricators."

The new machine is believed to be the world's biggest bending machine, costing some £750,000 to develop, and is finding ready applications in growing markets. Installed only in November, by March it was already fully booked until summer. The machine underwent testing during last year and has already completed two contracts. It is capable of bending tubes up to 60" or 1524mm diameter x 60mm thick. Typical applications will include stadium roof structures and bridges.

Cold bending has the advantage that the section can be pre-painted, and doesn't have to be heat treated afterwards. "Anyone can bend a section using brute force, but maintaining the section at the same time is much more difficult. We've spent a lot of money on achieving that," says Barnshaws Commercial Manager Greg North.

Previously, the other options for bending large sections were hot bending or induction bending. Hot bending entails heating the section to 1000°C, at which point its strength falls to 5% of its normal yield strength allowing it to be bent easily. But when it cools the yield strength is reduced and heat treatment is needed to get back to the original strength.

The new machine undertook its first job last September when it was used to bend a 457 x 152 x 82kg universal beam to an inside radius of 5534mm, considerably tighter than possible with cold bending previously. It is currently being used on 1000mm diameter, 45mm thick circular hollow sections for Newport Street rail bridge in Bolton, believed to be the world's biggest cold bend tube to date. This is a parabolic arch designed by Cass Hayward and fabricated by Watson Steel. The tightest part of the bend is 8.4m radius. There is no limit on the length of section that can be accommodated.

Barnshaw concludes: "This capacity cannot be achieved anywhere else. We lead the world in this area of bending."

"But it's important for clients to know the limitations of what we can bend and the impact it might have on the geometry of what they're proposing, so they should involve us at an early stage. We're trying to get it into people's minds that much more can be done than ever before, and that they shouldn't design on the basis of what the limitations used to be."

(Guidelines for architects and engineers as to what is technically possible can be found on the Barnshaws website: www.barnshaws.com)



Savings can be made in the fabrication process with the bending and folding of steel plate to eliminate welding. Plate up to 12,000mm long and 100mm thick can be folded. Common applications include flanges for fabricated beams.

The striking kite shaped atrium had to be modelled in 3D to define connection points to the main building



Atrium poses 3D puzzle

Virtual walkthrough software proved to be an essential tool in the detailing and fabrication of steelwork for the striking atrium at Birkenhead's new community based Lauries Centre. Paul Wheeler reports

North Wales based EvadX erected and fabricated all the structural steelwork on the new £3M Lauries Centre, which is taking shape in Birkenhead.

Visualising and detailing the Wirral community centre's atrium provided a few headaches for the design team — or would have done had 3D software not been available.

The Wirral Council funded centre will provide office space for up to eleven community-based organisations, a conference and function hall and a community café. EvadX's £350,000 structural steelwork order includes just under 250t of hot rolled steel and a further 10t of cold rolled secondary steels.

The striking building, structurally designed by consultant Williams Jones & Partners and built by main contractor Lockwood, features an inclined three-dimensional diamond or kite shaped atrium that connects the structure's two and three storey side wings.

The centre is designed to be environmentally efficient and sustainable, in that it includes self-cleaning windows, solar power and boasts high energy efficiency.

The atrium's frame measures 27m from tip to tip and 14.5m across, and at its highest point is 18.5m from the ground. The pitch of the atrium's roof varies from 33° for the main section to 58° for the smaller frame which intersects the main roof of the atrium.

Structurally the atrium works like a cross, says EvadX's Drawing Office Manager Andrew Roberts, and the challenge is all in the shape. It is made up from three trusses, fabricated and assembled at EvadX's Kinmel Bay facility in Rhyl, transported to

site and then bolted together.

As EvadX Managing Director Simon Adams says: "If you were to take out the atrium, the building would be a standard, basic frame. But the atrium was both difficult to detail and make."

The company was unquestionably assisted in this task through the use of the latest version of AceCAD's StruCAD design software, which in version 10 includes a walkthrough graphics facility.

"The atrium is so unusual that it was initially difficult to translate the architect's ideas into workable structural designs," says Roberts. "But through StruWalker, we were able to create a walk through the atrium, showing the connection points and developing the design. Without the software, this would have been very difficult."

Andy Dickinson, Project Engineer with structural engineer Williams Jones & Partners goes further: "Because you've got orthogonal converging angles it was very useful to see it in three dimensions. It meant we could talk through and modify the designs on screen and in one case this identified that the two-dimensional plans did not quite fit in. Without StruCAD it would have been a nightmare to visualise and we would have spent a long time agonising over the detailing."

The proof of the pudding is in the eating, so it was a great relief that once on site the atrium was erected without drama. As Adams points out: "With tolerances of just millimetres, there was nothing to play with."

In fact the design and fabrication of the Lauries Centre atrium proved so unusual that EvadX has submitted its model to StruCAD developer AceCAD's annual international design competition.

ANY SIZE, ANY QUANTITY...



section bending
induction bending
press braking
plate rolling
pipe forming
spiral bending



The **ANGLE RING** Co Ltd

Tel: +44 (0) 121 557 7241
Email: sales@anglering.com

Fax: +44 (0) 121 522 4555
Web: www.anglering.com

for ALL your bending needs...

DISTEK™

Bodycote
METAL TECHNOLOGY

**Distek™ The alternative to
Hot Spun Galvanising
Thickness Range 35 - 130µm**

Bodycote have for many years been associated with the highly successful Sherardizing process, which is based on a heat diffused, zinc alloy coating.

As an addition to this unique coating, Bodycote have recently developed an association with Distek, for the processing of a thicker, more ductile zinc alloy diffusion coating, with an increased thickness range of 35-130 microns.

This new coating will now offer a viable, free fitting alternative, to hot spun galvanised fasteners, whilst achieving a salt spray resistance in excess of 1000 hours.

For your free brochure please contact:

Bodycote Metallurgical Coatings Ltd. Shakespeare Street,
Wolverhampton, WV1 3LR

Tel: 01902 452915 Fax: 01902 352917

Email: sales.bmc@bodycote.com

www.bodycote.com





Modelling scores at Arsenal's new home

Arsenal FC's new home ground is ahead of schedule and looks like being a jewel among stadiums. David Fowler reports on the game plan from pitchside.

Each section of a primary truss weighs 350 tonnes

Self-effacement is not a quality normally associated with a stadium — nor with professional football in general. But for Arsenal's new home ground it was essential. The Emirates stadium is only 0.5km from Highbury, the club's revered home of 92 years, in an area of dense Victorian housing, and gaining planning approval was not a straightforward task.

"It's quite unlike Wembley: it's all about being discreet — for a 60,000-seat stadium," says architect Christopher Lee of HOK Sports Architecture. The Emirates stadium's 46m height would fit three times under the new Wembley arch.

Even a 46m high structure is going to be noticeable. It's likely, though, that Emirates will come to be thought of as a jewel among stadiums, very much in the tradition of Highbury, whose Art Deco east and west stands are listed structures.

Finding a site in the inner city so close to the club's existing home is a minor miracle in itself but it presented a number of construction challenges. The triangular plot is bounded on one side by the East Coast Main Line railway and on the other by the Network Rail line from Moorgate. The Plcaddy and Victoria tube lines run under the railways and a main Thames Water sewer crosses the site from east to west.

The site was most recently used for light industry. Watson Steel Structures is currently welding together the second halves of two primary roof trusses on what will next year be the pitch but last year was a working waste recycling station attracting 200 lorries daily. This waste transfer station continued, fully operational, from the start of construction last February until a new centre, built as part of the project, was ready in August.

Nonetheless, just over a year into the contract and with around 15 months to go, progress is impressive. The north stand superstructure (which is steel for the top tier and reinforced concrete at lower levels) and the north half of the steel roof are well on the way to completion, though at the other end things are less advanced, because of

the lack of access. And two steel bridges to carry pedestrians from the nearby stations across the rail lines to the stadium, the bigger one weighing 380t and measuring 22m wide, were lifted into place last autumn.

Construction of the roof is ahead of schedule. Sir Robert McAlpine Project Director Rolv Kristiansen, a veteran of high-profile projects such as the Millennium Dome, says: "We set ourselves a tough programme for 2004 deliberately, and lifted the roof trusses in December, rather than January as planned."

For the form of the stadium, the architect adopted an elliptical bowl with seats all round as the most efficient way to fit the stadium into the site. The roof, the stadium's most impressive feature and with a plan area of 26,000m², has a "billowing" or saddle-shaped inner edge, which derived from the elliptical plan. The main roof structure consists of two primary trusses spanning north-south between 11m high tripod supports at each end, two secondary trusses spanning between the primaries, and tertiary trusses spanning between the primaries or secondaries and a perimeter truss.

The roof slopes down towards the pitch so that the 15.5m deep truss at the front will be more or less hidden from the outside. The view will be uninterrupted by columns, and a great deal of work has gone into optimising sightlines from all seats. Because of the slope of the roof, rainwater has to be pumped back up the slope from the front.

The primary trusses are being erected in two halves, each 102m long and weighing 350t, with the first halves already in place, spanning between a tripod and a temporary trestle at mid-span. Each 100m secondary truss weighs 100t, while the longest tertiaries are 52m and 37t. The top boom of each primary is formed from 1.2m diameter cold formed circular hollow section.

Buro Happold Project Leader Geoff Werran says: "We worked closely with Watson Steel to make sure temporary stability was OK at every stage."

Elliptical bowl was the most efficient fit for the awkwardly shaped site.





Use of circular hollow sections makes individual members inherently resistant to lateral buckling. All the trusses are three-dimensional with a triangular cross-section, which gives them built-in stability against lateral-torsional buckling.

"When built, the roof members stabilise each other," Werran continues. "The secondaries stabilise the primaries, and even the tertiaries contribute to stability."

Werran adds that "huge investment" in producing a 3D X-Steel fabrication model of the entire structure has paid off: "Producing the model can be quite a painful process — you can't do it in a piecemeal way, you have to have everything detailed for it to work, but it paid off in fit-up."

Watson Steel Structures director Peter Miller says: "We do a 3D X-Steel model for every project now. All the cutting, drilling and burning is done electronically. But on this particular job it would have been very difficult if not impossible to resolve the geometry in any other way."

This is partly because the roof structure is curved in two directions, but also because of progressive deflection as it is built.

"As we build the roof it changes shape. We have to predict the change of shape as we build it so each element will fit." This consequently means that the model has to be set up knowing the sequence of construction. "We spent a long time working with the architect and engineer to get information up-front before starting the manufacturing process."

Mr Miller says this will pay dividends again later because all the necessary brackets for loudspeakers and ancillary components are already detailed and fitted, avoiding possible delays and the additional cost of having to go back and retrofit brackets 40m above ground after the structure has been erected.

Mr Miller adds that collaboration was facilitated by a two-stage tender process by which Sir Robert McAlpine was appointed but did not have to confirm a final price until the design was almost complete. The same applied to subcontractors.

"We were involved in discussions on design, manufacture and programme for two years. By the time we had to submit a final price we'd already solved most of the problems," he says. The contract was then signed as a fixed lump sum.

To illustrate the benefit Mr Miller cites the main trusses. "Working with McAlpine we identified 16 possible erection methods. We weren't sure which was the optimum. We developed a programme and cost details and a list of pros and cons for each, then agreed which would be best for the project as a whole.

"The one chosen was one of the most expensive from the steelwork aspect but saved many months on the overall programme. We wouldn't have offered that on a normal lump sum tender because we may not have won the job."

Highbury is renowned for having the best pitch in the Premiership and much thought has gone into emulating this in the new stadium, with comparative studies being undertaken between the existing and new pitch microclimates. The low overall roof height, allowing plenty of light through, will be the biggest contributor to the pitch quality. The expert view is that the natural microclimate of the new pitch will not quite match that of the old, because the existing stadium has open corners, but that it will be as close as possible.

Meanwhile work continues towards the target of opening in time for the start of the 2006 season. Even after the structure is finished, commissioning the complex IT and ticketing systems and training Arsenal staff in using them will be considerable tasks.

So the collaborative spirit on the project, and the fact that Mr Miller expects the second half of the main trusses will be ready to lift by Easter, with a probable mid-April lift date, can only be good news. He says: "We set out to try and beat the target on the north end and put ourselves in the position that if the civils work was ahead we could take advantage of it. We're hoping to do the same with the south end."

The roof slopes down towards the pitch to maximise light.

FACT FILE

Client:
Arsenal Football Club
Architect:
HOK Sports Architecture
Structural Engineer:
Buro Happold
Main Contractor:
Sir Robert McAlpine Ltd
Steelwork Contractor:
Watson Steel Structures Ltd
Steel Tonnage:
3000t in roof
Project Cost:
£357M
Due for Completion:
July 2006

Tripods 11m high support the main trusses





Palestra's dramatic overhangs reflect the reality of commercial office rents

Dancing columns at Waterloo



A new London office development in Southwark challenges some of the preconceptions of what a building should look like and presented a few challenges to the structural design team, as David Fowler discovered

A framed letter from a worried member of the public hangs in the site office of the new Palestra development near Waterloo in London.

The writer, probably one of the thousands of commuters who pass the Southwark site every day travelling into or out of Charing Cross, wanted to alert the contractor to a serious problem of workmanship which appeared to be afflicting the structure. The ground floor columns, the writer pointed out, were drastically out of plumb, to an extent easily visible to the most casual observer.

However disconcerting this may at first appear, though, the raked columns at the first and seventh storeys of this new speculative office development are intentional. And what architect Will Alsop describes as 'dancing' columns are by no means the building's most dramatic feature.

There is also the external treatment, which divides the 12-storey building into two masses, one box on top of another. The upper box, consisting of the top three stories, cantilevers 1.5m beyond the lower one on three sides — and by a huge 9m, overhanging Blackfriars Road, on the fourth.


Then there is the curtain walling, the bottom edge of which is on a slant so that it rises from ground level at one end of the building to a height of two storeys at the other.

The £68M, 37,098m² gross project, which began on site in January last year, is being developed by Blackfriars Investments and Royal London Asset Management, with Skanska as main contractor. Steelwork contractor is William Hare.

Its unusual features are not simply whims of the architect. The 9m cantilever arises from moving the entire top three storeys over by one grid square for planning reasons, to avoid overshadowing nearby residential properties. The extra 1.5m all round the top storeys recognises the fact that space on upper floors is more desirable and commands a premium rent. The edge of the curtain walling rises to provide public space and an area for a coffee bar at the corner of the building facing the pedestrian route from Southwark tube station to the Tate Modern.

All this provided a number of challenges for the structural design team, Buro Happold. The dancing columns lean over at varying angles and in two directions, inducing horizontal forces at the top and bottom of each. "We paired them so one leaning one way is balanced by one leaning the opposite way somewhere else," says Buro Happold Partner Stephen Brown. The balancing columns are not placed adjacent to each other so that this is not obvious, he adds. But even though this balances

Enlarged holes in the web made service installation easier.



3D CAD was used to model structure and services.

Composite cell beams speed services

One of the factors contributing to Palestra's structural efficiency is the use of cellular beams for the floors, acting compositely with the insitu concrete floor slabs. Rather than the floors resting on the top flange of the beam, as is usual, the flange is cast into the slab. This results in more effective use of the steel, gives greater load carrying capacity in the same structural depth, and removes the need for shear studs.

In a fire, it reduces the ratio of the heated perimeter of the beam to its section area. This means that a single coat of intumescent paint applied off site, rather than two, can

be used. This costs roughly the same as boarding, which is more easily damaged and less attractive aesthetically.

Also, because the depth of the cell beam is greater, the holes in the web through which services pass can be made bigger. In this case, this meant an increase from about 350mm to 430mm in the openings, allowing more room for the ducts and associated fire protection and also the operative's hands, making for a quicker, more efficient service installation. "That's very important — it's real money in a speculative building," says Mr Brown.

the horizontal forces, a twist is still imparted into the floor slab.

"Understanding the twist put into the building was an important part of the design," says Mr Brown. "Both the ground and first floors have to work quite hard to hold the columns."

Between the first to the seventh floors everything remains vertical. Then there is another tier of two-storey dancing columns, compounded by the fact that at the ninth floor the grid changes from a 10m x 7.5m module to 12m x 7.5m because of the 1.5m cantilever all round. "None of the columns meet the columns above at all," says Mr Brown. Moreover, the whole ninth floor is offset by 7.5m to the west. "It causes an interesting twist at the seventh level, plus the overturning effect of the cantilever."

The overturning force induced by the 9m cantilever is considerable: 20 times the average wind load, to be transferred into the stair and lift cores, which use conventional steel K-braced frames.

Buro Happold Associate Andrew Lacey adds: "The 9m cantilever is more or less plugged on to the side of the building. The architect wouldn't allow any visible diagonal bracing, and planning restrictions on the height prevented any structure to suspend it from above roof level."

A solution which would work within the existing floor depths had to be devised, and the result is a fully fixed Vierendeel girder from the ninth to the 12th floors, tied



FACT FILE

Palestra

Project Value:
£68M

Net Office Space:
26,400m²

Client:
Blackfriars Investments
and Royal London
Asset Management
joint venture

Architect:
Alsop Architects

Main contractor:
Skanska

Steelwork contractor:
William Hare Ltd

**Structural and
M&E Engineer:**
Buro Happold

*Lifting in the 9m
cantilevers required a
partial road closure.*

back to the primary core. It is made up of very substantial plate girders with flanges typically made from 70–80mm plate.

"There's as much steel in the ninth floor as in the third to sixth put together," says Mr Lacey. This tends to obscure the fact that the basic steel frame is otherwise very efficient. Even with the cantilever, the weight of steel is a respectable 75kg/m²

Buildability has been a primary concern on the project, given that the site is bounded by roads, the main railway line from Charing Cross and the Jubilee Line underground. "Because of the railway, roads and tube, the building is designed around understanding the contractor's problems," says Mr Brown. Any crane lift of more than 8.5 tonnes is deemed a 'controlled lift' requiring special supervision by Network Rail personnel, so the building is designed to be constructed without exceeding this limit.

The composite steel columns are designed to be structurally efficient, light to lift, and easy to erect (see box). Column splices need just four bolts. The 508mm hot finished circular hollow sections are grouted with concrete after construction, providing two hours fire resistance. The steel section alone is enough to cope with dead loads, however, so erection of the steel frame can continue leaving the grouting to be done later and taking it off the critical path.

Unless high winds intervene to prevent the cantilever steel being lifted into place, steelwork erection was on target for completion on schedule in March, with overall completion scheduled for summer 2006. The finished building will be ideally placed to whet the appetite of fans of modern design on their way to the Tate Modern — provided they aren't too nonplussed by the dancing columns.

The efficient design includes composite cell beams and CHS columns



The column layout of the top three storeys bears no relation to the floors below



Deep cellular beams have large holes for ease of fitting services

Nationwide delivery service of all Structural Steel Sections

RAINHAM

Phone: 01708 522311



*Installing the steelwork
for the cantilever over
Blackfriars Road*

Clean, circular and composite

A great deal of innovative thought has gone into the composite columns and their connections with the floor beams. Composite construction, using circular hollow section columns filled with concrete, is efficient both structurally and from a fire resistance point of view. The concrete acts as a heat sink to conduct heat away from the fire. Because the concrete is confined within the steel tube, it cannot fail by bursting (which is why this approach is used in design to resist earthquakes). The overall column size is kept compact and no external fire protection is needed.


To achieve a two-hour fire rating, Eurocode 4 calls for the concrete to be reinforced. Instead, Buro Happold provided the same area of steel using another CHS (273mm diameter in this case) within the outer one. "This makes life easier for the steelwork contractor, as there's no reinforcement to worry about," says Buro Happold partner Stephen Brown.

Steelwork contractor William Hare supplied the columns to site in three storey lengths, as one unit welded to a common base plate.

At each floor level a 1.5m length of universal column is slotted into the column. A welded plate connecting piece at right angles bolts to dual floor beams running either side of the column. A plate welded to the top of the column provides a bearing for the steel decking for the floor units, and the base plate of the column above is attached by four bolts.

The whole cruciform beam/column connection is then cast into the concrete floor. But because it transfers no moment into the column, the floor beams can be designed as continuous, making them more efficient and allowing them to be spliced away from the columns at the point of minimum bending moment.

The columns are grouted later in lifts of three storeys by filling with self-compacting grout, which requires around 2m³ for each column.



S275 & S355 GRADES

STEEL

Fax: 01708 559024

Email: sales@rainham-steel.co.uk

Universal Beams
& Columns

•
Parallel Flange Channels

•
Equal & Unequal Angles

•
Hot Finished
& Cold Formed
Structural Hollow
Sections

•
Mild Steel Plate

Steel design can be simple using EC3

Many steel designers still hanker for the simpler days of BS 449. But could a simple BS 449-like approach emerge from the apparent complexity of Eurocode 3, asks Charles King

The arrival of Eurocode 3 calls us to reconsider our approach to design. Design can be complex, for those pursuing economy of material, but it can be simplified for those pursuing speed and clarity. Many designers feel depressed when new codes are introduced. There are new formulae and new complications to master, even though there seems to be no benefit to the designer for the majority of his regular workload.

If we study the reasons for the increasing complexity of codes, we can see how it might be possible to simplify design. The increasing complexity generally arises because:

1. earlier design practice over-estimated strength in a few particular circumstances, causing safety issues
2. earlier design practice under-estimated strength in various circumstances affecting economy
3. new forms of structure evolve and codes are expanded to include them.

However, simple design remains a possibility if:

1. a scope of application is defined to avoid the circumstances and the forms of construction in

which strength is over-estimated by simple procedures.

2. the designer is not too greedy in the pursuit of the least weight of steel from the strength calculations.
3. the code requirements are presented in an easy-to-use format, such as the tables of buckling stresses in existing BS codes.

Not pursuing least weight might seem disloyal to the client, but generally it is not. It is well known that least weight of steel usually does not result in the cheapest structure, because lighter members often need more stiffening or strengthening at connections. In addition, many structures are governed by deflection and vibration criteria, so that the strength is not the critical issue for many members.

Observing these points, it is possible to derive design procedures that could be called "Eurocode 3 kept simple". To demonstrate the simplicity of such a procedure, it is compared with BS codes in Table 1 for the design of an unrestrained beam. The comparison includes both BS 449, long regarded as the best code for simplicity, and the simplest BS 59501 procedure. The number of steps is similar in each case.

Table 1: Comparison of Eurocode 3 (EN 1993-1-1) with BS 449 and BS 5950-1:2000 for simplified design

Design an unrestrained UB in S275 steel — the steps commonly used in practice

Eurocode 3 kept simple	BS 449	BS 5950 kept simple
Choose UB size Look up h/t_w , i_z and f_y in tables Calculate slenderness $\frac{l}{i_y}$ Look up $\chi_{LT} f_y / \gamma_{M1}$, the allowable buckling stress in a table such as Table 2 on p26 (values need to be tabulated). Calculate buckling resistance moment $M_{b,Rd} = (\chi_{LT} f_y / \gamma_{M1}) W_{pl}$ Compare applied moment with $M_{b,Rd}$	Choose UB size Look up D/T and r_y in tables Calculate slenderness $\frac{l}{r_y}$ Look up allowable buckling stress p_{bc} in a Table 3a and check thickness in table 2. Calculate applied stress $f_{bc} = \frac{M}{Z}$ Compare f_{bc} with p_{bc}	Choose UB size Look up D/T , r_y and f_y in tables Calculate slenderness $\frac{L_E}{r_y}$ Look up allowable buckling stress p_b from Table 20 assuming $\beta_w = 1$. Calculate buckling resistance moment $M_b = p_b S_x$ Compare applied moment with M_b
Check shear Look up h and t_w in tables Calculate the shear resistance $V_{c,Rd} = (f_y / \gamma_{M0} / \sqrt{3}) h t_w$ (Note that γ_{M0} is expected to be 1.0) Check applied shear $\leq 0.5 V_{c,Rd}$	Check shear Look up D and t in tables Calculate the shear stress $f_q = Q / (Dt)$ Compare f_q with p_q from Table 11	Check shear Look up D and t in tables Calculate the shear resistance $P_v = 0.6 p_y t D$ Check applied shear $\leq 0.6 P_v$

STRETCH

Your Steelwork, Not Your Cost

Whitehall Rd, Leeds, 18m span office



Douglas Carpark, 16m span



Liverpool College, 16m span



Cyfatha Retail Park, 53m span



Royal Preston Hospital, 17m span



WESTOK CELLULAR BEAMS...

- 20 - 50% lighter than plain beams.
- Each steel price rise increases the competitiveness of Cellular beams.
- Cambers at no extra cost.
- Curves at no extra cost.

The longer the span, the greater the saving.

T: 01924 264121
F: 01924 280030



E: design@westok.co.uk
www.westok.co.uk

Westok Limited, Horbury Junction Industrial Estate, Horbury Junction, Wakefield, West Yorkshire WF45ER

Table 2Lateral torsional buckling resistance: Part table of stress $\chi_{LT} f_y / \gamma_{M1}$

UBs, S275 steel, thickness not exceeding 16mm

Slenderness		h/t_f									
I/I_y	$\bar{\lambda}$	5	10	15	20	25	30	35	40	45	50
30	0.35	275	275	275	275	275	275	275	275	275	275
35	0.40	275	275	275	275	275	275	275	275	275	275
40	0.46	275	275	275	275	275	274	274	274	274	274
45	0.52	275	275	272	271	270	269	269	269	268	268
50	0.58	275	273	268	266	265	264	263	263	263	263
210	2.42	238	193	159	135	118	107	98	92	87	83
220	2.53	236	189	154	130	113	102	93	87	82	78
230	2.65	233	185	150	125	109	97	89	83	78	74
240	2.76	223	175	140	117	101	90	82	76	71	68
250	2.88	229	178	141	117	101	89	81	75	70	67

Those who have read EN 1993-1-1 in detail may be surprised by the simplifications in the procedure entitled "Eurocode 3 kept simple". Several procedures in the Eurocode document are omitted because other steps in Table 1 ensure that the calculations comply with the Eurocode even though the procedures do not appear. The explanations are as follows:

1. The classification of the cross-section can be omitted because the use of a UB for bending alone in S275 ensures that the beam is at least Class 2, allowing the use of the plastic modulus, W_{pl} . (This approach has long been used in the application of BS 449 which also has slenderness limits for flanges and webs. They are rarely calculated when using UBs and UCs because designers expect these sections satisfy the limits for S275.)
2. Shear buckling of the web has not been checked because S275 UBs do not have web slenderness sufficient for this type of buckling.
3. The moment gradient has not been considered. The tabulated stresses assume uniform moment even though this may underestimate the buckling resistance of the beam.
4. The cross-section check for bending has been omitted, because it can never be critical in a uniform beam if the buckling check assumes a uniform moment and the coincident shear is not more than 50% of the shear resistance.

5. Reduction of moment resistance by high coincident shear force has been avoided by checking that the shear force is not more than 50% of the shear resistance.

6. The shear area used above is simple whereas the formula in EN 1993-1-1 is complicated. However, for UBs, the simple area above is always slightly conservative and therefore safe.
7. The formulae in Eurocode 3 do not explicitly show I/I_y , but re-arrangement of the formulae in the EN 1993-1-1 allows this tabulation to be performed, because the fundamental approach of the Eurocode is also used by BS 5950 and BS 449.

(The steps 1 to 5 above have also been omitted from the BS 5950 procedure in Table 1 for the same reasons.)

Table 1 only shows the procedure for an unrestrained beam, but simplifications are possible for several other aspects of design, such as columns in simple braced frames. It is hoped that SCI will produce simplified guidance of this type suitable for rapid design both in industry and for universities.

Table 3: EN 1993-1-1 symbols	
i_z	Radius of gyration about minor axis, r_y in BS codes
f_y	Yield stress dependent on the flange thickness
$\bar{\lambda}_{LT}$	Relative slenderness for lateral torsional buckling
χ_{LT}	Strength reduction factor for lateral torsional buckling
W_{pl}	Plastic modulus about the major axis
γ_{M1}	Partial safety factor for buckling resistance
$M_{b,Rd}$	Buckling resistance moment
h	Overall height (or depth) of the section, D in BS codes
t_w	Web thickness
$V_{c,Rd}$	Cross-sectional resistance to shear
γ_{M0}	Partial safety factor for cross-sectional resistance

The Eurocode 3 symbols are new to engineers using BS codes, so the symbols used in Table 1 are explained in Table 3.

Steel Buildings and Bridges



“Steel Buildings” and Steel Bridges books are now available at a special sale price.



STEEL BUILDINGS - The Silver Book The Handbook of Steel Buildings

This book covers everything from steel design; section property tables; industry and multi-storey buildings; cladding and decking; through to fire; transport and erection; software; contracts and case studies.

BRIDGES - The Purple Book Steel Bridges

A practical approach to the design of steel bridges for efficient fabrication and construction.



Please supply:

☐ copies of The Handbook of Steel Buildings @ £20 each inc. P&P in the UK per publication

☐ copies of Steel Bridges @ £20 each inc. P&P in the UK per publication

To: The British Constructional Steelwork Association Ltd
(Publications Dept) 4 Whitehall Court,
Westminster, London SW1A 2ES
Tel: 020 7839 8566 Fax: 020 7976 1634
Email: don.thornicroft@steelconstruction.org

I enclose a cheque for £ made payable to BCSA
(in EU add £3 and outside EU add £6 per publication)

Please debit my VISA/American Express/Access card:

Expiry date:

Name on card

Signature

Address of cardholder

..... Postcode

please deliver to:

Name Tel

Address

.....

.....

Postcode

Please allow 28 days for delivery

High grade steel: the new standard for cost effectiveness

High grade steel is becoming much more popular. Richard Barrett, Chairman of BCSA's Process and Technical Committee, explains why modern designers increasingly prefer high grade over standard grade



*Distribution warehouse
Peterborough*

Twenty years ago the vast majority of structural steelwork was designed in "standard" grade 275 (or grade 43 as it was then known). It was quite unusual on everyday structures to come across "high" grade 355 steel (old grade 50). Today high grade steel is widely used; for example, last year in the author's own business the majority of steel used was 355 grade. What has changed over this period? Why is high grade steel becoming the grade of choice for many designers?

Steel grades

S355 grade steel is not new, and it's not particularly high grade either! It is colloquially referred to as high grade, to differentiate it from standard grade 275. In reality there are many

much higher grades available, but these are not seen on day-to-day structures. So for simplicity I will continue with the "high" grade colloquialism throughout this article, although the purist would refer to S355 grade each time.

The grade refers to the yield strength of the steel – the higher the grade, the higher the yield strength. The various grades are set down in BS EN 10025:2004. Steelmakers can increase the yield strength of their steel through various means — adjusting the chemical composition, using heat treatment and through manufacturing processes such as cold working. The chemical composition of high grade steel will normally differ from standard grade through the addition of either carbon or other elements. Adding carbon increases strength but also reduces the steel's toughness, so it is common to also "alloy" the content by adding trace metals such as manganese, chromium, molybdenum, nickel or copper.

There are various subgrades or so-called "qualities" available with each grade category. In particular, special subgrades will be required for low temperature applications such as external steelwork or exposed cold store steel, where the normal subgrade would not be suitable due to the reduced toughness of steel at lower temperatures.

The steel producer provides a Test Certificate or Inspection Document for the steel which shows the grade, subgrade, and the chemical analysis of the batch, together with results of mechanical tests. These should show that the yield strength is above the minimum required in the product standard for the particular grade.

Fabrication aspects

Whereas with true high grade steel (460 and upwards), welding needs to be carried out with special care, using techniques such as pre-heating this is rarely the case with Grade 355

*Residential development
Solihull*



steel. Fittings material is normally standard grade, being easier to source for items such as flats and angles. There is a danger however, that the use of high grade steel will result in more complex connections, particularly if inappropriately small beams size are selected. The experienced designer will avoid this problem by carefully considering the practicality of the joint when selecting the steel size, to ensure it is possible to form a connection without the need for excessive welding or stiffening.

Commercial factors

One of the major changes over recent years has been the increasing availability of high grade steels. Medium and large sizes of universal beams and columns are now widely available through steel stockholders, as are the Corus Hybox range of hollow sections. As these sizes have become more popular, stocks have increased, creating a virtuous circle of usage and availability. Additionally, the premium charged by steelmakers for high grade over standard grade has been progressively reduced, for some sizes disappearing altogether. High grade now offers a very attractive cost-to-strength ratio when compared with standard grade.

Availability is still an issue for small sections, and is likely to stay that way. This is because there is little or nothing to be gained by using high grade steel for beam sizes below 406mm, and therefore usage is small. Specifying high grade in these small sizes is wholly uneconomical and should be avoided if possible. The same applies with flats, angles and channels.

Design issues

In modern designs, high grade steel is essential to optimise the economy of the steel frame. Many types of buildings will benefit from the use of high grade steel — in single storey structures for large

span portal frames, in multi-storey structures for the columns, and in composite construction for the beams as well. The photographs show examples of the use of high grade steel by the author's company, Barrett Steel Buildings. These building types are the mainstream of the industry and represent the areas where most steel is used — hence the rapidly rising use of high grade steel. Designs for this type of structure incorporating high grade steel will give very economical solutions.

Owing to classification of sections for design purposes, certain sizes are not suitable for plastic action. In standard grade there are just five such sizes (all are UCs). With high grade there are more, seven beams and nine columns. This only affects a few serial sizes, normally the lightest section in the size (such as 356x171x45UB or 406x178x54UB). Consequently these sections are somewhat restricted in suitability for high grade use. Additionally high grade will probably not benefit designs where fatigue loading is present, or when buckling action is the critical case.

It is normal to use standard grade material for connections. Therefore connection design, including weld strength, will be governed by the strength of the connection material rather than the strength of the high grade main members.

Future trends and conclusions

Increasing availability of high grade steel, coupled with diminishing premium costs, means that it offers a very attractive cost-to-strength ratio. Consequently use is increasing rapidly, and this is improving the overall competitiveness of steel framed solutions. In the long term I believe it is likely that Grade 355 will become the standard grade for most beam, column and hollow section sizes, with Grade 275 only being retained for small beams and fittings materials.

AD 285

Floor Systems for Simple Construction using Discontinuous Columns and Continuous Beams

This AD provides advice on the floor-plate systems to be used with discontinuous (storey-high) columns and continuous beams in simple construction. AD 281 provides general advice on this form of construction and AD 283 covers the design of the column. As previously noted, this form of construction need not be restricted to the residential sector alone.

Floor-plate

The column design procedure outlined in AD 283 implicitly relies on rotational restraint both out-of-plane and in-plane to the column ends for the permanent condition, although the column's effective length factor is taken as unity. This allows the use of a simple design model with nominal moments even though the actual behaviour is complex. In BS 5950-1, the term 'rotational restraint' is described as directional restraint. AD 281 and AD 283 assume that the floor-plate is Slimdek but an alternative would




Figure 1 Continuous beam model

be to use precast concrete units in the depth of the floor beam with topping, and with any voids between the precast units and the beams filled with grout. Both solutions are suitable for residential and commercial developments.

The above systems, with the floor-plate within the depth of the beam, have the advantage that the column ends are rotationally restrained out-of-plane by the slab. The use of box ties and structural tees, as shown in AD 281 and AD 283, offers positional restraint during

construction but offers no rotational restraint out-of-plane to the column ends.

Floor beams

The floor beam in this form of construction may be designed as simply supported or continuous but it is assumed that no moment is redistributed from the beam to the column. Therefore, pins (no stiffness) or knife edge supports must be used in the frame or beam analysis. The column is designed in

6 members of our squad that's designed to make you far



ECONOMICAL CUTTING

UP TO 700mm WIDE BARS & SECTIONS




DRILLING & SAWING

STEEL SECTIONS FROM 100mm- 2500mm WIDE



SHEARING, PUNCHING, MARKING & NOTCHING

PROCESS UP TO 250mm WIDE FLATS & ANGLES



FLEXIBLE

CAMBERS BEAMS

FICEP's comprehensive range of machines for the processing of structural steel beams, angles and plates can match the precise production requirements of the smallest or largest fabricator - so now every company can reap the benefits of FICEP's high technology CNC machines. These machines can dramatically increase productivity and profitability, reduce labour costs and improve processing by up to 40%.

FICEP now has a range of almost 100 versatile machines which incorporate precise measuring systems that enhance accuracy to improve quality and fit which in turn reduces errors, lead times and minimise wastage.

All these benefits are supplemented by the highest levels of maintenance and service support which can include remote diagnostic software and comprehensive bespoke service contracts.

Call 0113 265 3921 for more detailed information.



If your goals are to reduce production costs and increase productivity
FICEP UK Ltd., 10 The Courtyards, Victoria Park, Victoria Road, Leeds LS14 2LB.

accordance with the procedure in AD 283, which shows how to determine its nominal moments. Figure 1 shows a continuous beam model with knife edge supports. To provide the necessary in-plane rotational restraint to the columns, the peak moment in the mid-span region of a beam should not exceed 90% of its reduced plastic moment capacity M_p in the presence of axial

force (if any).

Composite section properties may be taken advantage of in sagging regions. In addition, if the beam is continuous, pattern loading must be considered in its analysis and design. Moreover, designers should be aware that the practice of designing beams as simply supported and installing them as two-span continuous

will result in an underestimation of the column loads. Beams need to be analysed as they will be constructed in order to determine the correct column loads.

Contact: Thomas Cosgrove
Email: t.cosgrove@steel-sci.com
Telephone: 01344 623345

SCI Courses April-May 2005

IN-HOUSE TRAINING

All the courses that the SCI offer can be taken as part of company in-house training programmes. In-house courses are a cost-effective way of training employees and can be configured to suit your company's needs.

For further information on in-house training contact **Sandi Gentle (Courses Manager)** on 01344 872776 or email s.gentle@steel-sci.com

For detailed information and programmes for all courses please see www.steel-sci.org/courses

Preparation for Eurocode3	6 April 05	Dublin
Frame Stability (was Second Order Effects)	13 April 05	London
Excel for Engineers	19 April 05	Ascot
Curved Steel - Practical Applications	19 April 05	Leeds
Preparation for Eurocode3	11 May 05	Torquay
Frame Stability	12 May 05	Torquay
Excel for Engineers	24 May 05	Ascot

more competitive in the processing of structural steel



CAMBERING

UP TO 914 UB



DRILLING, PUNCHING, MILLING
& THERMAL CUTTING

PROCESS BARS & PLATES FROM 5MM TO 130MM THICK



SHOT BLASTING +
PAINTING EQUIPMENT

AUTOMATIC ROLLER CONVEYOR
SHOTBLAST SYSTEMS

- we are the leading goalscorers

Sales Tel: 0113 265 3921 Fax: 0113 265 3913. E-mail: info@ficep.co.uk www.ficep.co.uk

40 Years Ago in

BUILDINGWITHSTEEL

Progress Report on the Severn Bridge

A bridge across the Severn has been thought about and talked about for do long that now, when it is approaching actual completion, one can hardly believe in its reality. Yet there it is in its sheer beauty of line and grace straddling the river, gathering up from the river itself the 88 steel deck units which combine to make the complete deck or roadway. Each of these units, which are in high stress steel, weighs 130 tons and the total weight of steelwork thus represented by the completed deck is approximately 12,000 tons.

Nearly everything about the Severn Bridge is unusual and original. Although a similar type of bridge to the Forth Road Bridge opened by the Queen last September (1964), the Severn has the advantage of development work carried out after the Forth Road Bridge design was completed: this work included additional aerodynamic testing which paved the way for an entirely new design to be created for the Severn Crossing.

Whereas the Forth Road Bridge has latticed stiffening girders and separate roadway decking, the Severn bridge is having a single all-welded steel box girder with the road running on the upper surface and the footways and cycle tracks cantilevered out at each side: this box girder is suitably shaped to minimise the effect of wind forces and to ensure aerodynamic stability.


Saving in both weight and cost is achieved by these new methods.

The sequence of fabrication and erection operations is unusual – fabrication of elements, metal spraying and other anti-corrosion processes are being carried out in three separate works in the country then dispatched to a works in Chepstow where they are welded together, launched and finally floated down the river Wye into the Severn and so under the new bridge: each unit is then hoisted from the river to its position on the bridge.


There is here a considerable triumph for welding which contributes greatly to the slender beauty of the bridge.

The Severn Bridge design has created much interest in America where the Verrazano Bridge was opened last November. The British design, with its greater economy in the weight of steel used and consequent saving in cost, has produced lively comment and comparison, much of it favourable to the British design.

The Severn Bridge is part of the grand project which will save 50 miles on the journey from Southern England to South Wales: the project includes the Beachley Viaduct and Wye Bridge with eight miles of approach road and will be finished next year (1966).



1. Cable bands being transported into position.




2. View at mid-span showing cable bands in position.



3. Feeding a suspender into position.



4. Deck section moored in the River Severn.



5. Deck section clear of water and ready for lifting.



6. Washing down a deck section with fresh water.



7. Deck section being lifted with bandrails and ballast tank in position.



8. View along the partially completed deck.

Do you really want more columns in a car park?

Steel-framed car parks have longer spans with less columns providing more room to park and a lighter airier environment. They are quick to build, long lasting and easy to adapt.

Corus has produced new guidance in this area and would welcome the opportunity to visit you and explain what steel-framed car parks have to offer you, your client and the user.



To arrange an in-house presentation about the design and construction of steel-framed car parks please complete your details and fax to (01724) 405383 or telephone us on (01724) 405375

Name

Address

Company

Tel

Email

NSC/01



For a copy of the Steel-framed car parks brochure either contact our literature line on (01724) 404400




or to download a copy of the brochure visit www.corusconstruction.com



For SCI publications, please contact Publication Sales:

Tel: (direct): 01344 872775 Fax : 01344 622944 Email: publications@steel-sci.com

Web: www.shop.steelbiz.org The Steel Construction Institute, Silwood Park, Ascot, SL5 7QN



Steel Designers' Manual – 6th Edition

Editors: B Davison & G W Owens

ISBN 1405134127,
1,368 pp,
246x171 paperback,
April 2005

PAPERBACK REISSUE

Steel Designers' Manual

"It is hard to imagine that there is any steel topic that doesn't receive at least a mention in this book. Even if you can't find the complete answer, each section is riddled with references to places where it might be" — Mike Fewster, (Director, Billington Structures) in New Steel Construction May/June 2003.

This classic manual on structural steelwork design has now been reissued as a paperback edition. It is identical to the hardback edition and retains the restructuring that was introduced in the fifth edition. All chapters have been comprehensively reviewed and revised. Key features of the 6th edition are:

- Text and worked examples revised in accordance with BS 5950 1:2000 and BS 5400 3:2000.
- A completely new chapter on brittle fracture and fatigue, explaining the theory behind the current requirements of BS 5950 and BS 5400.

- New chapter on simple and moment connections, summarising industry best practice in these important areas.
- New chapter on Sustainability and Steel Construction reflecting the rapidly growing importance of the topic.
- New chapter on Eurocodes, summarising the principal differences with current national standards.
- Rewritten chapter on steel piling capturing recent developments

Priced only £45 (hardback was £89.50), the book continues to provide, in one volume, the essential knowledge of conventional steelwork.

PRICE: £45.00

(Free P&P in the UK; offer ends 31 May; ROW please enquire)



Structural Fire Design: Off-site Applied Thin Film Intumescent Coatings (Second Edition)

Editors: L C Newman, J J Dowling, and W I Simms
ISBN 1 85942 162 8,
48 pp,
A4 paperback,
Feb 2004

NEW BOOK

Structural Fire Design: Off-site Applied Thin Film Intumescent Coatings

This publication is presented in two parts. Part 1 covers the background to the use of off site applied intumescent coatings for structural steelwork and acts as a reference text for Part 2, which presents a Model Specification. By presenting a Model Specification it is hoped that greater uniformity will be achieved in contract specifications relating to off site applied intumescent coatings.

This second edition of SCI P160 has been extensively updated. In Part 1, the guidance on handling, storing and transporting coated steelwork has been updated to reflect the experience that has been gained in these areas. The guidance provided on the fire protection of beams with web

openings, concrete filled hollow sections, connections, composite beams and bracing, reflects the latest guidance available. Information has now been included on the protection of partially exposed members.

The Model Specification, Part 2, has been rewritten.

The information presented in this publication is specific to hot rolled structural sections and hot rolled structural hollow sections, designed for use in buildings.

PRICES: Non-member £30

Member £15 (plus P&P)

ANNOUNCEMENT

Essential guide for specifiers and buyers out now

This essential Directory for Specifiers and Buyers in the steel construction industry is now available.

The directory lists details of every BCSA member for 2005; from British steelwork contractors to their suppliers. RQSC (Registered Qualified Steelwork Contractors) listings are also given as are Quality Assurance Certification details.

Images of members' work are shown throughout the directory, which also contains details about steel as a material, the benefits of using it (from fire protection benefits to design possibilities) and essential tables.

To receive your free copy email emma.willoughby@steelconstruction.org or phone 020 7839 8566.



New and Revised Codes and Standards

(from BSI Update February 2005)

BS EN PUBLICATIONS

The following are British Standard implementations of the English language versions of European Standards (ENs). BSI has an obligation to publish all ENs and to withdraw any conflicting British Standards or parts of British Standard. This has led to a series of standards, BS ENs using the EN number.

BS EN 1990:2002 (Package)

Eurocode. Basis of structural design. Package containing BS EN 1990:2002 and the National Annex to BS EN 1990
No current standard is superseded.

BS EN 1997:-

Eurocode 7. Geotechnical design.

BS EN 1997 - 1: 2004

General rules

Supersedes DD ENV 1997-1:1995

BS EN 10163:-

Specification for delivery requirements for surface conditions of hot rolled steel plates, wide flats and sections.

BS EN 10163 - 1:2004

General requirements

Supersedes BS EN 10163-1:1991

BS EN 10163 - 2:2004

Plate and wide flats

Supersedes BS EN 10163-2:1991

BS EN 10163 - 3:2004

Sections

Supersedes BS EN 10163-3:1991

NA to BS EN 1990:2002

UK national annex for Eurocode 0.

Basis of structural design

No current standard is superseded

AMENDMENTS TO BRITISH STANDARDS

BS EN 1011:-

Welding. Recommendations for

welding of metallic materials.

BS EN 1011- 8:2004

Welding of cast irons

CORRIGENDUM 1 AMD 15497

BS EN 1991:-

Eurocode 1. Actions on structures

BS EN 1991-1:-

General actions

BS EN 1991-1-1:2002

Densities, self-weight, imposed

loads for buildings

CORRIGENDUM 1 AMD 15507

BS EN 1991-1- 3:2003

Snow loads

CORRIGENDUM 1 AMD 15509

BS EN 1991-1- 5:2003

Thermal actions

CORRIGENDUM 1 AMD 15510

BS EN 1991- 2:2003

Traffic loads on bridges

CORRIGENDUM 1 AMD 15508

NEW WORK STARTED

BS EN 1993:

Eurocode 3. Design of steel structures

BS EN 1993 - 1:-

General rules

BS EN 1993 - 1- 3

Supplementary rules for cold-formed thin gauge members and sheeting

CEN EUROPEAN STANDARDS

EN 1998:-

Eurocode 8. Design of structures for earthquake resistance

EN 1998 - 1:2004

General rules

BS EN 1993 - 1- 3

General rules, seismic actions and rules for buildings

Specialist Steel Consultancy



Floor
Vibrations



Acoustic
Performance



Thermal
Performance



Product
Development



Fire
Engineering



Advanced
Analysis



Bespoke
Software

Clients choose the SCI for a number of reasons:

- Expert
- Independent
- Confidential

The Steel Construction Institute

Tel: +44 (0)1344 623 345

specialist@steel-sci.com

www.steel-sci.org/consultancy





The British Construction Steelwork Association Ltd

You can find out email and website addresses for all these companies at www.steelconstruction.org

BCSA is the national organisation for the construction industry; its member companies undertake the design, fabrication and erection for all forms of construction in building and civil engineering. Associate Members are those principal companies involved in the purchase, design or supply of components, materials, services etc, related to the industry. Corporate Members are clients, professional offices, educational establishments etc, which support the development of national specifications, health and safety, quality, fabrication and erection techniques, overall industry efficiency and good practice. The principal objectives of the association are to promote the use of structural steelwork; to assist specifiers and clients; to ensure that the capabilities and activities of the industry are widely understood; and to provide members with professional services in technical, commercial and quality assurance matters.

Details of BCSA Membership and services are available from: Gillian Mitchell MBE, Deputy Director General, British Constructional Steelwork Association Ltd, 4 Whitehall Court, Westminster, London SW1A 2ES. Tel 020 7839 8566 Fax 020 7976 1634

ACL STRUCTURES LTD (E F H M 4)

Holland Way Ind. Est., Blandford, Dorset DT11 7TA
Tel 01258 456051 Fax 01258 450566

A & J FABTECH LTD

Walkley Works, Walkley Lane, Heckmondwike WF16 0PH
Tel 01924 402151 Fax 01924 410227

ASA STEEL STRUCTURES LTD

Brick Kiln Lane, Parkhouse Ind. Est. West, Newcastle-under-Lyme, Staffs ST5 7EF
Tel 01782 566366 Fax 01782 564785

ALLERTON ENGINEERING LTD (B 5* Q3)

Allerton House, Thurston Road, Northallerton, N. Yorkshire DL6 2NA
Tel 01609 774471 Fax 01609 780364

ALLOTT BROS & LEIGH

Fullerton Rd, The Ickles, Rotherham S60 1DJ
Tel 01709 364115 Fax 01709 364696

ALLSLADE PLC

Dundas Lane, Portsmouth, Hants PO3 5SD
Tel 023 9266 7531 Fax 023 9267 9818

THE ANGLE RING CO LTD

Bloomfield Road, Tipton DY4 9EH
Tel 0121-557 7241 Fax 0121-522 4555

APEX STEEL STRUCTURES LTD

Kings Close, Charfleets Industrial Estate, Canvey Island, Essex SS8 0QZ
Tel 01268 660 828 Fax 01268 660 829

ARBuckle WELDING & FABRICATIONS LTD

21 Lenziemill Rd, Lenziemill, Cumbernauld G67 2RL
Tel 01236 457960 Fax 01236 452250

ARROMAX STRUCTURES LTD (Q4)

Langwith Junction, Mansfield, Notts NG20 9RN
Tel 01623 747466 Fax 01623 748197

ASME ENGINEERING LTD

Asme House, 788 Kenton Lane, Harrow, Middlesex HA3 6AG
Tel 0208 954 0028 Fax 0208 954 0036

ATLAS WARD STRUCTURES LTD (A 3* Q1)

Sherburn, Malton, N. Yorkshire YO17 8PZ
Tel 01944 710421 Fax 01944 710512

ATLASCO CONSTRUCTIONAL ENGINEERS LTD

Rowhurst Industrial Estate, Apedale, Chesterton, Newcastle-U-Lyme ST5 6BD
Tel 01782 564711 Fax 01782 564591

B & B STRUCTURES LTD

Unit 3, Bridgewater Business Park, West Bridgewater St, Leigh, Lancs WN7 4HB
Tel 01942 603055 Fax 01942 608263

B D STRUCTURES LTD (E F H 5*)

Westhoughton Ind Est, James St, Westhoughton, Lancs, BL5 3QR
Tel 01942 817770 Fax 01942 810438

BHC LTD

Edinburgh Road, Carnwath, Lanarkshire ML11 8LG
Tel 01555 840006 Fax 01555 840036

A. C. BACON ENGINEERING LTD (E F H 6)

Norwich Rd, Hingham, Norwich NR9 4LS
Tel 01953 850611 Fax 01953 851445

BALLYKINE STRUCTURAL ENGINEERS LTD (E F H J 4 Q2)

51 Lisburn Rd, Ballynahinch, Co Down BT24 8TT
Tel 028 9756 2560 Fax 028 9756 2751

BARNSHAW SECTION BENDERS LTD

Structural Division, Anchor Lane, Coseley, Bilston, West Midlands WV14 9NE
Tel 01902 880848 Fax 01902 880125

BARRETT STEEL BUILDINGS LTD (E F H 1 Q1)

Barrett House, Cutler Heights Lane, Dudley Hill, Bradford BD4 9HU
Tel 01274 682281 Fax 01274 684281

D. J. BARRINGTON (CONSTRUCTION) LTD

Longmoor, Shirlheath, Kingsland, Leominster HR6 9RG
Tel 01568 708288 Fax 01568 708815

BILLINGTON STRUCTURES LTD (A 1 Q1)

Barnsley Road, Wombwell S73 8DS
Tel 01226 340666 Fax 01226 755947

BILLINGTON STRUCTURES LTD (A 1 Q1)

456 Badminton Rd, Yate, Bristol BS37 5HY
Tel 01454 318181 Fax 01454 318231

BISON STRUCTURES LTD (D E F H 4 Q1)

London Rd, Tetbury, Gloucs GL8 8HH
Tel 01666 502792 Fax 01666 504246

BONE STEEL LTD

P.O. Box 9300, Wishaw, Lanarkshire ML2 0YA
Tel 01698 375000 Fax 01698 372727

BORDER STEELWORK STRUCTURES LTD (C E F H J N 6)

Winchester House, 58 Warwick Rd, Carlisle CA1 1DR
Tel 01228 548744 Fax 01228 511073

BOURNE STEEL LTD (A 1 Q2)

St Clements House, St Clements Rd, Poole, Dorset BH12 4GP
Tel 01202 746666 Fax 01202 732002

W.S. BRITLAND & CO. LTD (Q2)

Tilmanstone Works, Pike Road, Eythorne, Dover CT15 4NB
Tel 01304 831583 Fax 01304 831983

BRITON FABRICATORS LTD (B C F H J K M 6 Q4)

Watnall Road, Hucknall, Notts NG15 6EP
Tel 0115 963 2901 Fax 0115 968 0335

BROADHURST ENGINEERING (UK) LTD

Gargrave St., Moorhey St., Moorhey, Oldham OL4 1JU
Tel 0161 628 6888 Fax 0161 628 6999

BROWNE STRUCTURES LTD

Queens Drive, Newhall, Swadincote, Derbyshire DE11 0EG
Tel 01283 212720 Fax 01283 215033

BUTTERLEY LTD (B 3* Q4)

Ripley, Derby DE5 3BQ
Tel 01773 573573 Fax 01773 749898

CAIRNHILL STRUCTURES LTD

Sun Works, Waverley Street, Coatbridge, Lanarkshire ML5 2BE
Tel 01236 449393 Fax 01236 428328

CARNABY STRUCTURES LTD (C E F H 2*)

Lancaster Rd, Carnaby Industrial Estate, Bridlington, East Yorkshire YO15 3QY
Tel 01262 401325 Fax 01262 401389

CAUNTON ENGINEERING LTD (Q1)

Moorgreen Ind. Park, Moorgreen, Nottingham NG16 3QU
Tel 01773 531111 Fax 01773 532020

CHIEFTAIN CONTRACTS LTD

Antonine Works, Broomhill Road, Bonnybridge FK4 2AL
Tel 01324 812911 Fax 01324 814927

CLEVELAND BRIDGE UK LTD (A B 0* Q3)

Cleveland House, Yarm Rd, Darlington, Co Durham DL1 4DE
Tel 01325 381188 Fax 01325 382320

COMPASS ENGINEERING LTD (C E F H 6)

Whaley Road, Barugh, Barnsley S75 1HT
Tel 01226 298388 Fax 01226 283215

KEY

Categories

- A** All forms of building steelwork
- B*** Bridgework
- C** Heavy industrial plant structures
- D** High rise buildings
- E** Large span portals
- F** Medium/small span portals and medium rise buildings
- H** Large span trusswork
- J** Major tubular steelwork
- K** Towers
- L** Architectural metalwork
- M** Frames for machinery, supports for conveyors, ladders and catwalks
- N** Grandstands and stadia
- S** Small fabrications

Quality Assurance Certification

- Q1** Steel Construction Certification Scheme Ltd
- Q2** BSI
- Q3** Lloyd's
- Q4** Other

Classification Contract Value

- 10** Up to £40,000
- 9** Up to £100,000
- 8** Up to £200,000
- 7** Up to £400,000
- 6** Up to £800,000
- 5** Up to £1,400,000
- 4** Up to £2,000,000
- 3** Up to £3,000,000
- 2** Up to £4,000,000
- 1** Up to £6,000,000
- 0** Above £6,000,000

Notes

- 1** Applicants may be registered in one or more categories to undertake the fabrication and the responsibility for any design and erection of the above.
 - 2** Where an asterisk (*) appears against any company's classification number, this indicates that the assets required for this classification are those of the parent company.
- * For details of bridgework sub-categories contact Gillian Mitchell at the BCSA.

CONDER STRUCTURES LTD (Q2)

Wellington Rd, Burton-on-Trent, Staffs DE14 2AA
Tel 01283 545377 Fax 01283 530483

LEONARD COOPER LTD (C F H K M 6 Q1)

Balm Road, Hunslet, Leeds LS10 2JR
Tel 0113 270 5441 Fax 0113 276 0659

CORDELL GROUP LTD (Q4)

Unit 2, Perry Avenue, Teesside Industrial Estate, Thornaby on Tees TS17 9LN
Tel 01642 769526 Fax 01642 769553

COVENTRY CONSTRUCTION LTD (Q1)

Torrington Avenue, Coventry CV4 9AP
Tel 024 7646 4484 Fax 024 7669 4020

CROWN STRUCTURAL ENGINEERING LTD

Burma Rd, Blidworth, Mansfield, Notts NG21 0RT
Tel 01623 490555 Fax 01623 490666

CUSTOM METAL FABRICATIONS LTD

Central Way, Feltham TW14 0XJ
Tel 020 8844 0940 Fax 020 8751 5793

D H STRUCTURES LTD (Q2)

Tollgate Drive, Tollgate Industrial Estate, Beaconside, Stafford ST16 3HS
Tel 01785 246269 Fax 01785 222077

FRANK H DALE LTD (E F 2 Q4)

Mill Street, Leominster, Herefordshire HR6 8EF
Tel 01568 612212 Fax 01568 619401

DEW CONSTRUCTION LTD (E F H K 6 Q2)

P.O. Box 35, Oldham OL9 6HH
Tel 0161 624 5631 Fax 0161 627 3556

ELLAND STEEL STRUCTURES LTD (C D E F H K N 2 Q1)

Philmar House, Gibbet St, Halifax HX2 0AR
Tel 01422 380262 Fax 01422 380263

EMMETT FABRICATIONS LTD (E F H 6)

Hirst Wood Works, Hirst Wood Road, Shipley BD18 4BU
Tel 01274 597484 Fax 01274 588671

EVADL LTD (E F H J L M N 5 Q4)

Unit 9, Tir Llydd Enterprise Park, St. Asaph Avenue, Kinmel Bay, Rhyl LL18 5JZ
Tel 01745 336413 Fax 01745 339639

FAIRFIELD-MABEY LTD (A B 0* Q4)

Chepstow, Monmouthshire NP16 5VL
Tel 01291 623801 Fax 01291 625453

FISHER ENGINEERING LTD (A 1 Q1)

Ballinamallard, Enniskillen, Co Fermanagh BT94 2FY
Tel 028 6638 8521 Fax 028 6638 8706

GIBBS ENGINEERING LTD (Q4)

17A Axe Road, Colley Lane Industrial Estate, Bridgwater, Somerset TA6 5LP
Tel 01278 455253 Fax 01278 453174

GLENTWORTH FABRICATIONS LTD (F H J L M N 4 Q2)

Molly Millar's Bridge, Molly Millar's Lane, Wokingham RG41 2WY
Tel 0118 977 2088 Fax 0118 977 2907

GORGE FABRICATIONS LTD

Gorge House, Great Bridge Industrial Estate, Toll End Road, Tipton, West Midlands DY4 0HR
Tel 0121 522 5770 Fax 0121 557 0415

GRAHAM WOOD STRUCTURAL LTD (A 4)

Lancing Business Park, Chartwell Road, Lancing BN15 8TY
Tel 01903 755991 Fax 01903 755384

GRAYS ENGINEERING (CONTRACTS) LTD

Globe Industrial Estate, Rectory Road, Grays, Essex RM17 6ST
Tel 01375 372411 Fax 01375 375079

D A GREEN & SONS LTD (E F H J 3 Q1)

Whapode, Spalding, Lincs PE12 6TL
Tel 01406 370585 Fax 01406 370766

GREGG & PATTERSON (ENGINEERS) LTD (Q2)

Riverside Works, Ballyskeagh Road, Lambeg, Co Antrim BT27 5TD
Tel 028 9061 8131 Fax 028 9062 2813

HAD-FAB LTD (Q4)

Macmerry Ind. Est., Tranent, East Lothian EH33 1RD
Tel 01875 611711 Fax 01875 612711

WILLIAM HALEY ENGINEERING LTD (Q1)

Bellcombe Works, East Brent, Richmond, North Yorkshire DL10 7JH
Tel 01278 760591 Fax 01278 760587

HAMBLETON STEEL LTD

Gatherley Road, Brompton-on-Swale, Richmond, North Yorkshire DL10 7JH
Tel 01478 810598 Fax 01748 810601

WILLIAM HARE LTD (A B 0 Q1)

Brandlesholme House, Brandlesholme Rd, Bury, BL8 1JJ
Tel 0161 609 0000 Fax 0161 609 0409

M. HASSON & SONS LTD (Q1)

17 Gleebe Rd, Rasharkin, Co. Antrim BT44 8SS
Tel 028 2957 1281 Fax 028 2957 1575

HAWKES CONSTRUCTION CO

321A Hornchurch Rd, Hornchurch RM12 4TQ
Tel 01708 621010 Fax 01708 621026

HENRY SMITH (CONSTRUCTIONAL ENGINEERS) LTD (C D E F H J 4)

Wharton Steelworks, Winsford CW7 3BW
Tel 01606 592121 Fax 01606 559134

HESCOTT ENGINEERING CO LTD

Lochlands Viaduct, Larbert, Stirlingshire FK5 3NN
Tel 01324 556610 Fax 01324 552970

HILLCREST STRUCTURAL LTD

Hillcrest House, Toynbee Road, Eastleigh, Hants SO50 9DT
Tel 023 8064 1373 Fax 023 8061 3586

HORWICH STEELWORKS LTD

Unit 10, Horwich Loco Ind. Est., Chorley New Rd, Horwich, Bolton BL6 5UE
Tel 01204 695989 Fax 01204 669343

JAMES BROS (HAMWORTHY) LTD (E F H J N 4 Q3)

19 Blandford Rd, Hamworthy, Poole BH15 4AW
Tel 01202 673815 Fax 01202 684033

JOY STEEL STRUCTURES (LONDON) LTD

London Industrial Park, 1 Whittings Way, East Ham, London E6 6LR
Tel 020 7474 0550 Fax 020 7473 0158

JAMES KILLEEA & CO LTD (C E F H N 1*)

Stoneholm Road, Crawshawbooth, Rossendale, Lancs BB4 8BA
Tel 01706 229411 Fax 01706 228388

T. A. KIRKPATRICK & CO LTD

Beltmont, Kirkpatrick-Fleming, Lockerbie DG11 3NQ
Tel 01461 800275 Fax 01461 800340

LEACH STRUCTURAL STEELWORK LTD

Brookhaves Way, Cloughton-on-Brock, nr Preston PR3 0PZ
Tel 01995 640133 Fax 01995 640719

LOWE ENGINEERING (MIDLAND) LTD

Bramshall Industrial Estate, Stone Road, Bramshall, Staffs ST14 8SH
Tel 01889 563244 Fax 01889 563554

TERENCE MCCORMACK LTD (Q1)

17 Camlough Rd, Newry BT35 6JS
Tel 028 3026 2261 Fax 028 3026 8177

MADDEN STEEL ERECTORS

Unit 3, 5 Hagmill Road, East Shawhead Industrial Est., Coatbridge, Lanarkshire ML5 4XD
Tel 01236 424213 Fax 01236 434355

MALDON MARINE LTD

Unit 16, West Station Ind. Est., Spital Road, Maldon, Essex CM9 6TW
Tel 01621 859000 Fax 01621 858935

HARRY MARSH (ENGINEERS) LTD

The Parade, Hendon, Sunderland SR2 8LT
Tel 0191 510 9797 Fax 0191 510 9798

MARTEC ENGINEERING GROUP LTD

58 Southcroft Road, Rutherglen, Glasgow G73 1UG
Tel 0141 647 6789 Fax 0141 646 1056

MIDLAND STEEL STRUCTURES LTD

Golden Acres Lane, Binley, Coventry CV3 2RT
Tel 024 7644 5584 Fax 024 7645 9995

MIFFLIN CONSTRUCTION LTD (D E F H M 4)

Worcester Rd, Leominster, Herefordshire HR6 8AY
Tel 01568 613311 Fax 01568 614935

NEWBRIDGE ENGINEERING LTD

Tees Bay Business Park, Brenda Rd, Hartlepool TS25 2BU
Tel 01429 866722 Fax 01429 869811

NEWTON FABRICATIONS LTD

9 York Street, Ayr, Ayrshire KA8 8AN
Tel 01292 269135 Fax 01292 610258

NUSTEEL STRUCTURES LTD (B* 4 Q1)

Lympne, Hythe, Kent CT21 4LR
Tel 01303 268112 Fax 01303 266098

ON SITE SERVICES (GRAVESEND) LTD (Q4)

Wharf Road, Denton, Gravesend, Kent DA12 2RU
Tel 01474 321552 Fax 01474 357778

OVERDALE CONSTRUCTION SERVICES LTD

Millers Avenue, Brynmernyn Industrial Estate, Bridgend CF32 9TD
Tel 01656 729229 Fax 01656 722101

HARRY PEERS STEELWORK LTD (Q1)

Elton St, Mill Hill, Bolton BL2 2BS
Tel 01204 528393 Fax 01204 362363

PENCO STRUCTURAL ENGINEERING LTD (Q4)

Orpinsmill Road, Ballyclare, Co. Antrim BT39 0SX
Tel 028 9335 2886 Fax 028 9332 4117

QMEC LTD

Quarry Road, Bolsover, Nr Chesterfield S44 6NT
Tel 01246 822228 Fax 01246 827907

RSL (SOUTH WEST) LTD (E F H M 6)

Millfield Industrial Est., Chard, Somerset TA20 2BB
Tel 01460 67373 Fax 01460 61669

JOHN REID & SONS (STRUCSTEEL) LTD (A 1)

296-298 Reid Street, Christchurch BH23 2BT
Tel 01202 483333 Fax 01202 499763

REMNANT ENGINEERING LTD

Unit 161, Lydney Industrial Estate, Harbour Road, Lydney, Gloucestershire GL15 4EJ
Tel 01594 841160 Fax 01594 843208

RIPPIN LTD

Thistle Ind. Est., Church Street, Cowdenbeath KY4 8LP
Tel 01383 518610 Fax 01383 513099

ROBERTS ENGINEERING

16D Bergen Way, Sutton Fields Ind. Est., Hull HU7 0YQ
Tel 01482 838240 Fax 01482 830697

J. ROBERTSON & CO LTD (L M S 9)

Mill Lane, Walton-on-Naze CO14 8PE
Tel 01255 672855 Fax 01255 850487

ROBINSON CONSTRUCTION (C D E F H 1 Q1)

Wincanton Close, Ascot Drive Industrial Estate, Derby DE24 8NJ
Tel 01332 574711 Fax 01332 861401

ROWECORD ENGINEERING LTD (A B O Q1)

Neptune Works, Uskway, Newport, South Wales NP20 2SS
Tel 01633 250511 Fax 01633 253219

ROWEN STRUCTURES LTD (A 1)

Fulwood Road (South), Sutton-in-Ashfield, Notts NG17 2JW
Tel 01623 558558 Fax 01623 440404

S H STRUCTURERS LTD

Moor Lane Trading Estate, Sherburn-in-Elmet, North Yorkshire LS25 6ES
Tel 01977 681931 Fax 01977 681930

SELWYN CONSTRUCTION ENGINEERING LTD

Tarron Road, Tarron Industrial Estate, Moreton, Wirral CH46 4TU
Tel 0151 678 0236 Fax 0151 678 8959

SEVERFIELD-REEVE STRUCTURES LTD (A O* Q2)

Dalton Airfield Industrial Estate, Dalton, Thirsk, North Yorkshire YO7 3JN
Tel 01845 577896 Fax 01845 577411

SHIPLEY FABRICATIONS LTD

Maddocks Park, Ancaster, Grantham, Lincs NG32 3PL
Tel 01400 231115 Fax 01400 231220

SNASHALL STEEL FABRICATIONS CO LTD

Pulham Business Park, Pulham, nr Dorchester, Dorset DT2 7DX
Tel 01300 345588 Fax 01300 345533

SOLWAY STRUCTURAL STEEL

Killoch, Ochiltree, Cumnock, Ayr KA18 2RL
Tel 01290 700800 Fax 01290 700801

SOUTH DURHAM STRUCTURES LTD

South Church Enterprise Pk, Dovecot Hill, Bishop Auckland, Co. Durham DL14 6XR
Tel 01388 777350 Fax 01388 775225

TAYLOR & RUSSELL LTD

Stonebridge Mill, Longridge PR3 3AQ
Tel 01772 782295 Fax 01772 785341

THE AA GROUP LTD

Priorswood Place, East Pimbo, Skelmersdale, Lancs WN8 9QB
Tel 01695 50123 Fax 01695 50133

TRADITIONAL STRUCTURES LTD

(E F H J K M N 6 Q1)
Findel Works, Landywood Lane, Cheslyn Hay, Walsall, West Midlands WS6 7AJ
Tel 01922 414172 Fax 01922 410211

TUBECON

Badminton Road, Yate, Bristol BS17 5HX
Tel 01454 314201 Fax 01454 273029

WARLEY CONSTRUCTION COMPANY LTD

Swinborne Road, Burnt Mills Industrial Estate, Basildon, Essex SS13 1LD
Tel 01268 726060 Fax 01268 725285

WALTER WATSON LTD (Q4)

Greenfield Works, Ballylough Rd, Castlewella, Co Down BT31 9JQ
Tel 028 4377 8711 Fax 028 4377 2050

WATSON STEEL STRUCTURES LTD (A B O* Q1)PO

Box 9, Lostock Lane, Bolton BL6 4TB
Tel 01204 699999 Fax 01204 694543

WESTBURY PARK ENGINEERING LTD

Brook Lane, Westbury, Wilts BA13 4ES
Tel 01373 825500 Fax 01373 825511

WESTBURY STRUCTURES LTD (Q1)

Thorp Arch Est., Wetherby, West Yorkshire LS23 7DB
Tel 01937 840600 Fax 01937 840601

WESTOK LTD (Q2)

Horbury Junction Ind Est, Horbury Junction, Wakefield WF4 5ER
Tel 01924 264121 Fax 01924 280030

WESTON STEEL STRUCTURES LTD

Burnden Park Works, Summerfield Rd, Bolton BL3 2NQ
Tel 01204 525335 Fax 01204 362106

JOHN WICKS & SON LTD

Unit 1, Crabbers Cross, Rattery, South Brent, Devon TQ10 9JZ
Tel 01364 72907 Fax 01364 73054

WIG ENGINEERING LTD

Barnfield, Akeman Street, Chesterton, Oxon OX26 1TE
Tel 01869 320515 Fax 01869 320513

H. YOUNG STRUCTURES LTD (C E F H J N 6)

Ayton Road, Wymondham, Norfolk NR18 0RD
Tel 01953 601881 Fax 01953 607842

ASSOCIATE MEMBERS**BUILDING COMPONENTS****ALBION SECTIONS LTD (Q4)**

Albion Rd, West Bromwich, West Midlands B70 8BD
Tel 0121 553 1877 Fax 0121 553 5507

AYRSHIRE METAL PRODUCTS (DAVENTRY) LTD (Q1)

Royal Oak Way, Daventry NN11 5NR
Tel 01327 300990 Fax 01327 300885

BARNSHAW PLATE BENDING CENTRE LTD

Corporation Rd, Audenshaw, Manchester M34 5LR
Tel 0161 320 9696 Fax 0161 335 0918

CORUS PANELS & PROFILES (Q1)

Seyvern Drive, Tewkesbury Business Park, Tewksbury, Glos GL20 8TX
Tel 01684 856600 Fax 01684 856601

FABSEC LTD

Brooklands Court, Tunstall Road, Leeds LS11 5HL
Tel 01113 385 7830 Fax 0113 272 7587

HI-SPAN LTD

Ayton Rd, Wymondham NR18 0RD
Tel 01953 603081 Fax 01953 607842

KINGSPAN METL-CON LTD (Q4)

Sherburn, Malton, N. Yorkshire YO17 8PQ
Tel 01944 712000 Fax 01944 710555

RICHARD LEES STEEL DECKING LTD

Moor Farm Rd West, The Airfield, Ashbourne, Derbyshire DE6 1HD
Tel 01335 300999 Fax 01335 300888

MSW STRUCTURAL FLOOR SYSTEMS

Acton Grove, Long Eaton, Nottingham NG10 1FY
Tel 0115 946 2316 Fax 0115 946 2278

METSEC PLC (Q2)

Broadwell Rd, Oldbury, West Mids B69 4HE
Tel 0121 601 6000 Fax 0121 601 6181

STRUCTURAL METAL DECKS LTD

Mallard Hse, Christchurch Rd, Ringwood BH24 3AA
Tel 01425 471088 Fax 01425 471408

STRUCTURAL SECTIONS LTD (Q1)

PO Box 92, Downing St, Smethwick, Warley B66 2PA
Tel 0121 555 1342 Fax 0121 555 1341

STUDWELDERS LTD

Millennium Hse, Severn Link Distribution Centre, Newhouse Farm Ind Est, Chepstow, Monmouthshire NP16 6UN
Tel 01291 626048 Fax 01291 629979

COMPUTER SOFTWARE**ACECAD SOFTWARE LTD**

Truro House, Stephenson's Way, Wyvern Business Park, Derby DE21 6LY
Tel 01332 545800 Fax 01332 545801

COMPUTER SERVICES CONSULTANTS (UK) LTD

Yeadon House, New St, Pudsey, Leeds, LS28 8AQ
Tel 01113 239 3000 Fax 0113 236 0546

PSYCLE INTERACTIVE LTD

The Stable House, Whitewell, Whitchurch, Shropshire SY13 3AQ
Tel 01948 780120 Fax 08701 640156

RAM INTERNATIONAL (EUROPE) LTD

4 Woodside Place, Glasgow G3 7QF
Tel 0141 353 5168 Fax 0141 353 5112

TEKLA (UK) LTD

Tekla House, Cliffe Park Way, Morley, Leeds LS27 0RY
Tel 0113 307 1200 Fax 0113 307 1201

DESIGN SERVICES**ARRO-CAD LTD**

Bretby Business Park, Ashby Road, Bretby, Burton-on-Trent DE15 0YZ
Tel 01283 558206 Fax 01283 558207

ODDA DESIGN LTD

The White House, Clifton Marine Parade, Imperial Business Park, Gravesend, Kent DA11 0DY
Tel 01474 352849 Fax 01474 359116

STEEL PRODUCERS**CORUS CONSTRUCTION & INDUSTRIAL**

Frodingham House, PO Box 1, Brigg Road, Scunthorpe DN16 1BP
Tel 01724 404040 Fax 01724 404229

CORUS TUBES

PO Box 101, Weldon Rd, Corby, Northants NN17 5UA
Tel 01536 402121

MANUFACTURING EQUIPMENT**FICEP (UK) LTD**

10 The Courtyards, Victoria Park, Victoria Road, Leeds LS14 2LB
Tel 0113 265 3921 Fax 0113 265 3913

KALTENBACH LTD

6-8 Brunel Road, Bedford MK41 9TJ
Tel 01234 213201 Fax 01234 351226

PEDDINGHAUS CORPORATION UK LTD

Unit 6, Queensway Link, Stafford Park 17, Telford TF3 3DN
Tel 01952 200377 Fax 01952 292877

VOORTMAN UK LTD

Unit 8, Mercian Park, Felspar Rd, Amington Rd, Tamworth B77 4DF
Tel 01827 633000 Fax 01827 65565

PROTECTIVE SYSTEMS**AMERON INTERNATIONAL**

Blackwell Road, Huthwaite, Sutton in Ashfield, Notts NG17 2RL
Tel 01623 511000 Fax 01623 559616

FORWARD PROTECTIVE COATINGS LTD

Vernon St., Shirebrook, Mansfield, Notts NG20 8SS
Tel 01623 748323 Fax 01623 748730

INTERNATIONAL PAINT LTD

Protective Coatings, Stoneycage Lane, Felling, Gateshead NE10 0JY
Tel 0191 469 6111 Fax 0191 495 0676

LEIGH'S PAINTS

Tower Works, Kestor Street, Bolton BL2 2AL
Tel 01204 521771 Fax 01204 382115

SITE COAT SERVICES LTD

Unit 11, Old Wharf Road, Grantham, Lincolnshire NG31 7AA
Tel 01476 577473 Fax 01476 577642

JACK TIGHE LTD

Kirk Sandall Ind. Est., Kirk Sandall, Doncaster DN3 1QR
Tel 01302 880360 Fax 01302 880370

WEDGE GROUP GALVANIZING

c/o Worktop Galvanizing Claydams Avenue, Worktop, Notts S81 7BQ
Tel 01909 486384 Fax 01909 482540

SAFETY SYSTEMS

EASI-EDGE
Ollerton Rd, Tuxford, Newark, Notts NG22 0PQ
Tel 01777 870901 Fax 01777 870524

STEEL STOCKHOLDERS**ADVANCED STEEL SERVICES LTD**

South Ribble Industrial Estate, Capitol Way, Preston, Lancs PR5 4AJ
Tel 01772 259822 Fax 01772 259561

ASD METAL SERVICES - EDINBURGH

24 South Gyle Crescent, Edinburgh EH12 9EB
Tel 0131 459 3200 Fax 0131 459 3266

ASD METAL SERVICES - BODMIN

Unit 13, Cooksland Ind. Est., Bodmin, Cornwall PL31 2PZ
Tel 01208 77066 Fax 01208 77416

ASD METAL SERVICES - LONDON

Thames Wharf, Dock Road, London E16 1AF
Tel 020 7476 9444 Fax 020 7476 0239

ASD METAL SERVICES - CARLISLE

Unit C, Earls Way, Kingsmoor Park Central, Kingstown, Cumbria CA6 4SE
Tel 01228 674766 Fax 01228 674197

ASD METAL SERVICES - HULL

Gibson Lane, Melton, North Ferriby, East Riding of Yorkshire HU14 3HX
Tel 01482 633360 Fax 01482 633370

ASD METAL SERVICES - GRIMSBY

Estate Road No. 5, South Humberside Industrial Estate, Grimsby DN31 2TX
Tel 01472 353851 Fax 01472 240028

ASD METAL SERVICES - BIDDULPH

PO Box 2, Tunstall Road, Biddulph, Stoke-on-Trent, Staffs ST8 6JZ
Tel 01782 515152 Fax 01782 522240

ASD METAL SERVICES - DURHAM

Drum Road, Drum Industrial Estate, Chester-le-Street, Co. Durham DH2 1ST
Tel 0191 492 2322 Fax 0191 410 0126

ASD METAL SERVICES - CARDIFF

East Moors Road, Cardiff CF1 5SP
Tel 029 2046 0622 Fax 029 2049 0105

ASD METAL SERVICES - STALBRIDGE

Station Rd, Stalbridge, Dorset DT10 2RW
Tel 01963 362646 Fax 01963 363260

ASD METAL SERVICES - NORFOLK

Hamlyn Way, Kings Lynn, Norfolk PE30 4LQ
Tel 01553 761431 Fax 01553 692394

ASD METAL SERVICES - EXETER

Sidmouth Road, Clyst St Mary, Exeter EX5 1AD
Tel 01395 233366 Fax 01395 233367

ASD METAL SERVICES - DAVENTRY

Royal Oak Ind. Est., Daventry, Northants NN11 5QQ
Tel 01327 876021 Fax 01327 87612

ASD METAL SERVICES - TIVIDALE

Tipton Road, Tividale, Oldbury, West Midlands B69 3HU
Tel 0121 520 123

The Register of Qualified Steelwork Contractors

BUILDINGS SCHEME

Applicants may be registered in one or more categories to undertake the fabrication and the responsibility for any design and erection of:

A All forms of steelwork (C-N inclusive)

C Heavy industrial plant structures

D High rise buildings

E Large span portals

F Medium/small span portals and medium rise buildings

H Large span trusswork

J Major tubular steelwork

K Towers

L Architectural metalwork

M Frames for machinery, supports for conveyors, ladders and catwalks

N Grandstands and stadia

S Small fabrications

Company Name	Telephone	A	C	D	E	F	H	J	K	L	M	N	S	QA	Contract Value (1)
ACL Structures Ltd	01258 456051				●	●	●				●				Up to £2,000,000
Adstone Construction Ltd	01905 794561														In process of audit
Atlas Ward Structures Ltd	01944 710421	●	●	●	●	●	●	●	●	●	●			●	Up to £3,000,000*
B D Structures Ltd	01942 817770			●	●	●	●								Up to £1,400,000*
B & K Steelwork Fabrications Ltd	01773 853400		●		●	●	●	●	●		●			●	Up to £4,000,000*
A C Bacon Engineering Ltd	01953 850611				●	●	●								Up to £800,000
Ballykine Structural Engineers Ltd	028 9756 2560				●	●	●	●				●		●	Up to £2,000,000
Barrett Steel Buildings Ltd	01274 682281				●	●	●							●	Up to £6,000,000
Betgate Structures Ltd	01608 677551				●	●	●								Up to £100,000
Billington Structures Ltd	01226 340666	●	●	●	●	●	●	●	●	●	●	●		●	Up to £6,000,000
Bison Structures Ltd	01666 502792			●	●	●	●							●	Up to £2,000,000
Border Steelwork Structures Ltd	01228 548744		●		●	●	●	●				●			Up to £800,000
Bourne Steel Ltd	01202 746666	●	●	●	●	●	●	●	●	●	●	●		●	Up to £6,000,000
Briton Fabricators Ltd	0115 963 2901		●			●	●	●	●	●	●			●	Up to £800,000
CTS Ltd	01484 606416						●	●							Up to £800,000
Carnaby Structures Ltd	01262 401325		●	●	●	●	●								Up to £4,000,000*
Cleveland Bridge UK Ltd	01325 381188	●	●	●	●	●	●	●	●	●	●	●		●	Above £6,000,000*
Compass Engineering Ltd	01226 298388		●		●	●	●		●						Up to £2,000,000
Leonard Cooper Ltd	0113 270 5441		●			●	●		●		●			●	Up to £800,000
Curtis Engineering Ltd	01373 462126					●									Up to £400,000
Frank H Dale Ltd	01568 612212				●	●								●	Up to £4,000,000
Dew Construction Ltd (Fabrication Division)	0161 624 5631					●	●	●		●				●	Up to £800,000
EAGLE Structural Ltd	01507 450081				●	●	●	●		●					Up to £400,000
Elland Steel Structures Ltd	01422 380262		●	●	●	●	●		●			●		●	Up to £4,000,000
Emmett Fabrications Ltd	01274 597484				●	●	●								Up to £800,000
EvadX Ltd	01745 336413				●	●	●	●		●	●	●		●	Up to £1,400,000
Fairfield-Mabey Ltd	01291 623801	●	●	●	●	●	●	●	●	●	●	●		●	Above £6,000,000*
Fisher Engineering Ltd	028 6638 8521	●	●	●	●	●	●	●	●	●	●	●		●	Up to £6,000,000
Glentworth Fabrications Ltd	0118 977 2088				●	●	●	●	●	●	●	●		●	Up to £2,000,000
Graham Wood Structural Ltd	01903 755991	●	●	●	●	●	●	●	●	●	●	●			Up to £2,000,000
D A Green & Sons Ltd	01406 370585				●	●	●	●						●	Up to £3,000,000
William Hare Ltd	0161 609 0000	●	●	●	●	●	●	●	●	●	●	●		●	Above £6,000,000
Harland & Wolff Heavy Industries Ltd	028 9045 8456		●		●	●	●	●	●	●	●			●	Up to £6,000,000
James Bros (Hamworthy) Ltd	01202 673815				●	●	●	●				●		●	Up to £2,000,000
James Killelea & Co Ltd	01706 229411		●		●	●	●					●			Up to £6,000,000*
Meldan Fabrications Ltd	01652 632075		●		●	●	●	●	●		●			●	Up to £2,000,000
Mifflin Construction Ltd	01568 613311			●	●	●	●				●				Up to £2,000,000
Harold Newsome Ltd	0113 257 0156				●	●	●								Up to £1,400,000
Normanby Wefco Ltd	01724 875555		●						●		●			●	Up to £800,000
Oswestry Industrial Buildings Ltd	01691 661596				●	●	●		●		●				Up to £400,000
Quantrill Steel Ltd	01953 881853				●	●	●	●		●	●			●	Up to £40,000
RSL (South West) Ltd	01460 67373				●	●	●				●				Up to £800,000
John Reid & Sons (Strucsteel) Ltd	01202 483333	●	●	●	●	●	●	●	●	●	●	●			Up to £6,000,000
J Robertson & Co Ltd	01255 672855									●	●		●		Up to £100,000
Robinson Construction	01332 574711		●	●	●	●	●							●	Up to £6,000,000
Roll Formed Fabrications Ltd	028 7963 1631				●	●	●	●		●	●	●		●	Up to £800,000
Rowecord Engineering Ltd	01633 250511	●	●	●	●	●	●	●	●	●	●	●		●	Above £6,000,000
Rowen Structures Ltd	01623 558558	●	●	●	●	●	●	●	●	●	●	●			Up to £6,000,000
SIAC Butlers Steel Ltd	00 353 502 23305		●	●	●	●	●	●				●		●	Up to £6,000,000
Severfield-Reeve Structures Ltd	01845 577896	●	●	●	●	●	●	●	●	●	●	●		●	Above £6,000,000*
Henry Smith (Constructional Engineers) Ltd	01606 592121		●	●	●	●	●	●							Up to £2,000,000
Traditional Structures Ltd	01922 414172				●	●	●	●	●		●	●		●	Up to £800,000
Watson Steel Structures Ltd	01204 699999	●	●	●	●	●	●	●	●	●	●	●		●	Above £6,000,000*
Webcox Engineering Ltd	01249 813225				●	●	●				●				Up to £400,000
H Young Structures Ltd	01953 601881		●		●	●	●	●				●			Up to £800,000

Notes (1) Contracts which are primarily steel but which may include associated works. The steelwork contract for which a company is pre-qualified for the Scheme is intended to give guidance on the size of steelwork contract that can be undertaken; where a project lasts longer than a year, the value is the proportion of the steelwork contract to be undertaken within a 12 month period.

(*) Where an asterisk appears against any company's classification number, this indicates that the assets required for this classification level are those of the parent company.



BRIDGEWORKS SCHEME

Based on evidence from the company's resources and portfolio of experience, the Subcategories that can be awarded are as follows:

FG Footbridges and sign gantries
PT Plate girders (>900mm deep), trusswork (>20m long)
BA Stiffened complex platemwork in decks, box girders, arch boxes.

CM Cable stayed bridges, suspension bridges, other major structures (>100m)
MB Moving bridges
RF Bridge refurbishment

X Unclassified
Applicants may be registered in more than one sub-category.

Company Name	Telephone	FG	PT	BA	CM	MB	RF	X	Contract Value (1)
Allerton Engineering Ltd	01609 774471	●	●	●	●	●	●		Up to £1,400,000*
Briton Fabricators Ltd	0115 963 2901	●	●	●			●		Up to £800,000
Butterley Ltd	01773 573573	●	●	●	●	●	●		Up to £3,000,000*
CTS Ltd	01484 606416	●							Up to £800,000
Cleveland Bridge UK Ltd	01325 381188	●	●	●	●	●	●		Above £6,000,000*
Coastground Ltd	01493 650455								in process of audit
Fairfield-Mabey Ltd	01291 623801	●	●	●	●	●	●		Above £6,000,000*
William Hare Ltd	0161 609 0000							●	Above £6,000,000
Harland & Wolff Heavy Industries Ltd	028 9045 8456	●	●	●	●		●	●	Up to £6,000,000
Interserve Project Services Ltd	0121 344 4888						●		Above £6,000,000
Interserve Project Services Ltd	020 8311 5500		●	●		●	●		Up to £400,000*
Mandall Engineering Ltd	0114 243 0001	●	●	●	●	●	●		Up to £800,000*
Meldan Fabrications Ltd	01652 632075	●	●	●	●	●	●		Up to £2,000,000
'N' Class Fabrication Ltd	01733 558989	●	●	●		●	●		Up to £1,400,000
Normanby Wefco Ltd	01724 875555	●	●	●			●		Up to £800,000
Nusteel Structures Ltd	01303 268112	●	●	●	●				Up to £2,000,000*
Rowecord Engineering Ltd	01633 250511	●	●	●	●	●	●		Above £6,000,000
Taylor & Sons Ltd	029 2034 4556	●	●	●	●	●	●		Up to £800,000
Watson Steel Structures Ltd	01204 699999	●	●	●	●	●	●		Above £6,000,000*

Notes (1) Contracts which are primarily steel but which may include associated works. The steelwork contract for which a company is pre-qualified for the Scheme is intended to give guidance on the size of steelwork contract that can be undertaken; where a project lasts longer than a year, the value is the proportion of the steelwork contract to be undertaken within a 12 month period.

(*) Where an asterisk appears against any company's classification number, this indicates that the assets required for this classification level are those of the parent company.

SCI Members



**The Steel
Construction
Institute**

The Steel Construction Institute develops and promotes the effective use of steel in construction. It is an independent, membership-based organisation. Membership is drawn from all sectors of the construction industry; this provides beneficial contacts both within the UK and internationally. Its corporate members enjoy access to unique expertise and free practical advice which contributes to their own efficiency and profitability. They also receive an initial free copy of most SCI publications, and discounts on subsequent copies and on courses. Its multi-disciplinary staff of 45 skilled engineers and architects is available to provide technical advice to members on steel construction in the following areas:

- Technical Support for Architects
- Bridge Engineering
- Building Interfaces
- Civil Engineering
- Codes and Standards
- Composite Construction
- Connections
- Construction Practice
- Corrosion Protection

- Fabrication
- Health & Safety — best practice
- Information Technology
- Fire Engineering
- Light Steel and Modular Construction
- Offshore Hazard

- Engineering
- Offshore Structural Design
- Piling and Foundations
- Specialist Analysis
- Stainless Steel
- Steelwork Design
- Sustainability
- Vibration

Details of SCI Membership and services are available from:

Pat Ripley, Membership Manager, The Steel Construction Institute, Silwood Park, Ascot, Berks.

Telephone: +44 (0)1344 623345 Fax: +44 (0)1344 622944

Email: pat.ripley@steel-sci.com Website: www.steel-sci.com

The Steel Construction Institute would like to welcome the following new Corporate Members:

IRELAND

J B Barry & Partners Limited
 McCabe Delaney
 Pat O'Gorman & Associates

KENYA

Steel Structures Ltd
UK
 BHC Ltd*

*BCSA Members

All full members of the BCSA are automatically members of the SCI. Their contact details are listed on the BCSA Members pages

FabTrol MRP

Estimating & Production Control
Software for Steel Fabricators

There's always a better way
of doing things.

FabTrol® is the perfect example.

FabTrol® MRP is the number one choice for Steel Fabricators throughout the world who are looking to improve efficiency and ultimately the profitability of their business.

It ensures project integration from the drawing office through to production.

One shared objective, one goal.

More efficiency, more profit.

Available as either a modular solution to meet a particular need, or as a totally integrated package to manage material and production throughout the business.

- ▶ Estimating
- ▶ Drawing Management
- ▶ Materials Management
- ▶ Production Management
- ▶ Project Management
- ▶ Revision Control

To see how Fabtrol® can help
your business contact CSC today.



CSC (UK) LTD., Yeadon House, New Street
Pudsey, LEEDS, West Yorkshire LS28 8AQ
tel ▶ +44 (0) 113 239 3000 fax ▶ +44 (0) 113 290 0920
e-mail ▶ sales@cscworld.com website ▶ www.cscworld.com