

NEW STEEL CONSTRUCTION

# NWSC

[www.new-steel-construction.com](http://www.new-steel-construction.com)

**Acute hospital for the Midlands  
Glasgow gets long spans  
Steel bowl for university  
College boosts regeneration**

# The team that can make your company a top performer in 2012




FICEP has over 100 automated steel processing machines in its team lineup that can be used as highly efficient stand-alone performers or integrated into a complete, software controlled production line using state-of-the-art CAM software. The productivity increases and reductions in production costs that are achievable set new performance benchmarks within the structural steel and fabrication industry.

Many of these advanced CNC machines now also incorporate FICEP's unique patented\*, scribing system, a feature which offers further substantial savings in time and labour costs. This proven fully automated system interfaces directly with CAD systems without operator input and is being used successfully in both large and small structural steel fabricators to maximise competitiveness and productivity.

\* Patent pending



**steel projects**  
AUTOMATED  
CAM SOFTWARE



HIGH SPEED DRILLING,  
SAWING & SCRIBING



DRILLING, PUNCHING,  
THERMAL CUTTING,  
MILLING & SCRIBING



ADVANCED CNC PRESS BRAKES



SHOT BLASTING



PERMANENT MAGNETIC  
LIFTING SYSTEM FOR PLATES, BARS & BEAMS



PLASMA &  
GAS CUTTING



PIPE CUTTING





12

These and other  
steelwork articles can  
be downloaded from the  
New Steel Construction  
website at [www.new-steel-construction.com](http://www.new-steel-construction.com)

**Cover Image**  
**New Birmingham Acute and Adult Psychiatric Hospitals**  
Client: Consort Healthcare for the University Hospital NHS Foundation Trust and the Birmingham and Solihull Mental Health NHS Trust  
Architect: BDP  
Steelwork contractor: Severfield-Reeve Structures  
Steel tonnage: 12,500t



- 5 Editor's comment** Nick Barrett welcomes news of encouraging trends from recent government statistics.
- 6 News** A lightweight steel frame is the fastest construction method for residential projects according to a BRE study.
- 12** The **Birmingham New Hospitals** PFI project represents the first new general hospital to be built in the UK's second largest city for more than 70 years.
- 16** Supported on a series of Y-shaped columns, the new **lecture theatre** building for Leeds Metropolitan University is a complex steel framed bowl.
- 18** The latest in NSC's **Case for Steel** series examines the extensive fire performance research which has been undertaken.
- 20** Cellular beams have been used on a shopping centre extension in **Cork**, not for their service openings, but for the light and airy feel they will provide.
- 24** Long internal spans and elevation cantilevers required some complex engineering for a new commercial development in **Glasgow**.
- 26** Andrew Bellerby, Tekla (UK) Managing Director examines the latest developments in **Building Information Modelling**.
- 28** The first **IKEA** store in the Republic of Ireland has relied on steel construction to deliver the project on schedule.
- 30** Situated opposite **Hastings** railway station, a new college building will form a major element of the seaside town's regeneration.
- 32** SCI's Alastair Hughes explains the choice of **lateral torsional buckling curves** according to Eurocode 3 and the UK National Annex.
- 35 40 Years Ago** Our look back through the pages of Building with Steel features an unusual television studio in Chicago.
- 36 Codes and Standards**
- 38 Advisory Desk** The latest advice from SCI - AD 329 - examines dealing with connection design in a 3D frame analysis and - AD 330 - vibration of staircases.
- 40 BCSA members**
- 42 SCI members**

# THE ALTERNATIVE STEEL COMPANY LTD

## THE HOLLOW SECTION SPECIALISTS

Cold Formed  
&  
Hot Finished

S235  
S275  
S355

Sq & Mitre  
Cutting  
In House

Tel: 01942 826677

[www.alternativesteelco.co.uk](http://www.alternativesteelco.co.uk)


Fax: 01942 821999

e-mail: [sales@alternativesteel.com](mailto:sales@alternativesteel.com)

**RÖSLER®**  
*finding a better way ...*

Rösler is a leading manufacturer and supplier of conservation equipment that includes automatic shot blasting, painting and drying systems. Offering modern and innovative solutions Rösler has supplied many major companies throughout the world.

- Shot Blast
- Painting
- Service
- Conservation
- Surface Preparation
- Consultation



### Rösler UK

Unity Grove, School Lane  
Knowsley Business Park  
Prescot, Merseyside, L34 9GT  
Tel: +44 (0) 151 482 0444  
Fax: +44 (0) 151 482 4400  
Email: [rosler@rosleruk.com](mailto:rosler@rosleruk.com)  
Website: [www.rosleruk.com](http://www.rosleruk.com)

After sales service, spare parts and maintenance programmes are also provided through our various distribution points.

**Specialist in solvent to  
water based conversions.**

For more information please contact  
Haydn Kitchen or Paul Rawlinson.



www.new-steel-construction.com

#### EDITOR

**Nick Barrett** Tel: 01323 422483  
nick@new-steel-construction.com

#### DEPUTY EDITOR

**Martin Cooper** Tel: 01892 538191  
martin@new-steel-construction.com

#### CONTRIBUTING EDITOR

**Ty Byrd** Tel: 01892 524455  
ty@barrett-byrd.com

#### PRODUCTION EDITOR

**Andrew Pilcher** Tel: 01892 524481  
andrew@new-steel-construction.com

#### PRODUCTION ASSISTANT

**Alastair Lloyd** Tel: 01892 524536  
alastair@barrett-byrd.com

#### NEWS REPORTERS

**Mike Walter, Victoria Millins**  
**ADVERTISING SALES MANAGER**  
**Sally Devine** Tel: 01474 833871  
sally@new-steel-construction.com

#### PUBLISHED BY

**The British Constructional Steelwork Association Ltd**  
4 Whitehall Court, Westminster, London SW1A 2ES  
Telephone 020 7839 8566 Fax 020 7976 1634  
Website www.steelconstruction.org  
Email postroom@steelconstruction.org

#### The Steel Construction Institute

Silwood Park, Ascot, Berkshire SL5 7QN  
Telephone 01344 636525 Fax 01724 404224  
Website www.steel-sci.org  
Email reception@steel-sci.org

#### Corus Construction and Industrial

PO Box 1, Brigg Road, Scunthorpe, North Lincolnshire DN16 1BP  
Telephone 01724 404040 Fax 01724 404224  
Website www.corusconstruction.com  
Email construction@corusgroup.com

#### CONTRACT PUBLISHER & ADVERTISING SALES

**Barrett, Byrd Associates**  
Linden House, Linden Close,  
Tunbridge Wells, Kent TN4 8HH  
Tel: 01892 524455  
www.barrett-byrd.com



#### EDITORIAL ADVISORY BOARD

Dr D Tordoff (*Chairman*); Mr N Barrett; Mr D G Brown, SCI;  
Mr M Crosby, Capita Symonds; Mr R Gordon, Mace Ltd;  
Mr W Gover, Consultant; Mr R Harrison, Glentworth Fabrications  
Ltd; Mr A Palmer, Buro Happold; Mr R Steeper, Corus;  
Mr O Tyler, Wilkinson Eyre; Mrs K Lloyd, Corus;  
Mr M Thompson, Mott MacDonald  
The role of the Editorial Advisory Board is to advise on the overall style  
and content of the magazine.

New Steel Construction welcomes contributions on any suitable topics relating to steel construction. Publication is at the discretion of the Editor. Views expressed in this publication are not necessarily those of the BCSA, SCI, Corus or the Contract Publisher. Although care has been taken to ensure that all information contained herein is accurate with relation to either matters of fact or accepted practice at the time of publication, the BCSA, SCI, Corus and the Editor assume no responsibility for any errors or misinterpretations of such information or any loss or damage arising from or related to its use. No part of this publication may be reproduced in any form without the permission of the publishers.

#### CHANGES TO THE MAILING LIST

If you wish to notify us of a change:

**Non Members** Non Members of either the SCI or the BCSA  
please telephone Corus on 01709 825452

**Members BCSA** Telephone BCSA on 020 7839 8566

**Members SCI** Telephone SCI on 01344 636525

All rights reserved ©2009. ISSN 0968-0098

## Recession forges quality solutions

Are the first green shoots of recovery visible in the new construction orders figures released by the government before Christmas? The three month rolling figures to the end of October were certainly a major improvement on the trend revealed previously.

Private commercial orders were substantially down, 17% lower than the previous twelve months, but they were 10% up over three months compared to the previous three month period. Private industrial orders were down 26% in the 12 months to October, but were 44% higher than the previous three months. Encouraging as these trends might be it is of course far too early to say any recovery is in sight, let alone under way. Construction however just might have the bottom of this recession in view.

As we highlighted in our December issue, there is a massive boost coming to government funded construction programmes such as education and transport. The procurement process has been revealed to have serious shortcomings which mean this work is not coming through as quickly as our industry would like, but it is coming. A long term benefit of this might be an overhaul of the way projects are procured, which would benefit construction as well as the people who rely on the facilities like schools, hospitals and roads that the industry builds.

Demand for goods and services is substantially down across UK industry, but a feeling is growing that maybe we have been a bit guilty of 'glass half empty' syndrome. There is still work around and unprecedented steps have been taken to deliver major boosts to world economies. Other major work sources like the London Olympics and Crossrail are gathering pace. The fall in the value of sterling is boosting the competitive situation of the UK's manufacturing exporters. The scale of the government intervention means that there must be a chance that for once construction won't be the last out of a recession.

Since the last significant recession that sent construction reeling in the early 1990's the market and competitive dominance of steel has been on an upward trend. As clients came out of recession they looked with new eyes at what value they were getting for their money, and thanks to the investment in productivity and other improvements by the steel construction sector that had continued through those harsher times, there were better than ever steel solutions available.

Even now we see steelwork contractor members of the BCSA making major investments in new machinery that will deliver productivity and quality advances for years to come. Other research and development programmes by Corus and the Steel Construction Institute and industry partners are continuing.

Difficult times may still lie ahead, but the steel construction sector can be confident that it will be delivering better value and quality than ever when better times return.



Nick Barrett - Editor





# Steel frames are the fastest way to build homes

A lightweight steel frame offers the fastest way to build sustainable, affordable and high quality homes. This is according to a BRE study, known as the SmartLife Housing Demonstration Project, conducted to find the best ways to deliver a greater volume of homes in less time.

BRE's Director of Innovation and Housing, Oliver Novakovic, said the organisation had carried out the

study because of the lack of data showing how cost effective and quick modern building methods of construction were.

He said the study's findings showed housebuilders had to become more efficient.

"We now have a robust body of knowledge that will inform and enlighten our approach to future house building – once the current credit crisis abates," he said.

Dr Bassam Burgan, Chair of the Steel Homes Group, said: "For a long time we have been saying that light gauge steel offers a quicker, cheaper alternative to other forms of construction, and it is great to see that recognised in a well respected study."

The construction of 106 homes on three Cambridgeshire sites formed the basis for the study. The same house types were built using

four methods: brick and block, lightweight steel frame, panelised timber frame and concrete formwork.

The highest achieving system used in terms of speed and cost was light gauge steel frame. On a site with unproblematic access and storage, a steel frame house took an average of 800 man hours per house to build, followed by the next best performer, brick and block.

## Steel passes examination for Newcastle school

Covering an area the size of four football pitches (19,000m<sup>2</sup>), the recently opened steel framed Kenton Secondary School in Newcastle-Upon-Tyne has been described as a blueprint for future educational construction projects due to its innovative design.

The school is made up of five main teaching blocks connected via a curved crescent, or street, which ends at a large sports hall complex.

Mike Goldsmith, Project Engineer for Parsons Brinckerhoff, said the most challenging aspect of the job was the shape, in particular the curved geometry of the street and the sports hall's rear wall.

"The curves of the street aren't uniform, between each teaching block they change," he explains. "Another challenge was where to split the structure for movement joints as generally the whole building doesn't lend itself to this."

Steelwork contractor Hambleton Steel was on site for 21 weeks and erected approximately 1,100t of structural steel for the job.

Michael Dixon, Hambleton's Project Manager,



said the job was very complex as there were no square grids. "All steelwork is at a radius, nothing is straight even the teaching block's footprints fan out."

Kenton School, with lottery funded, part public sports facilities, has been handed over to Newcastle City Council's private sector partner Aura.

Aura Chief Executive Kirsty Thirlwell said:

"This is the sixth and largest new school we have delivered for Newcastle and it is a great example of the benefit properly directed investment can bring to education."

Partners in Aura are Newcastle City Council, Parsons Brinckerhoff, Sir Robert McAlpine, Robertson Capital Projects and Building Schools for the Future Investments. .

## Curving iconic museum docks in Glasgow

An innovative and eye catching landmark structure is taking shape at the confluence of the rivers Clyde and Kelvin in Glasgow.

The £74M Riverside Transport Museum is the vision of Iraqi born architect Zaha Hadid, and is being constructed by main contractor BAM.

When complete, the twisting, curving roof of the 11,200m<sup>2</sup> building will stream away from huge, glazed gable end elevations to become the city's newest museum.

Watson Steel Structures are currently undertaking the steelwork erection which is expected to be completed later this Spring. The museum will open in 2010.



## BCSA provides sourcing option for specifiers

Sustainability requirements are becoming increasingly common in construction specifications, and many companies in the BCSA's membership have signed the Steel Construction Sustainability Charter and been audited to become Sustainability Charter Members. This allows clients with sustainable ambitions to select steelwork companies that share their ideals.

The BCSA scheme is founded on best practice and continuous improvement so that companies can proceed from entry level membership through Silver to Gold status. Recognising that clients are seeking assurance about responsible sourcing, the BCSA has extended the scheme's requirements with respect to supply chain engagement.

It is already a requirement that

Gold Members of the scheme must have environmental management systems that are certified in accordance with BS EN ISO 14001. From January 2009 all Gold Members of the scheme must ensure that at least 80% of their supplies of steel are manufactured by companies that also meet the BS EN ISO 14001 certification standard. This requirement is met for all steel products

manufactured in the UK by Corus as all its facilities have been certified as meeting the standard.

Specifiers selecting SCM Gold Members will benefit from BCSA's responsible sourcing initiative in the knowledge that these companies are ensuring that their supply chain partners are paying proper management attention to environmental issues.



### Stadium work relies on tube expertise

A number of high profile stadium projects are currently under way across the UK and Ireland, with many of them using tubular steel sections for the grandstand roofs.

PP ProTube has recently cut and prepped tubes for two new rugby stadiums, the Leicester Tigers new ground and Munster's Thomond Park Stadium in Cork (pictured).

"Our CNC machines can offer both flame and plasma tube cutting facilities

from 48mm up to 1,016mm diameter with a maximum wall thickness of 50mm," said Paul Owen, PP ProTube Account Manager.

From its facility in St Helens, Merseyside, the company can also cut lengths of up to 17m which can be handled with a maximum piece weight of 15t.

PP ProTube has also recently profiled tubes for Watson Steel Structures' prestigious Glasgow Transport Museum project.



### Green warehouse lands on blue planet

Atlas Ward Structures has completed erection of nearly 2,000t of structural steelwork for a pioneering warehouse in Newcastle-under-Lyme, Staffordshire for Gazeley, the global provider of sustainable logistic space, and main contractor McLaren Construction.

The project known as G.Park Blue Planet Chatterley Valley is described as a truly 'carbon positive' development and consists of a single 34,000m<sup>2</sup> distribution centre with ancillary office space.

The warehouse forms the initial phase of the wider Chatterley Valley park project which will eventually create thousands of new jobs on the 12.5 hectare former colliery site.

The site's carbon positive credentials will be enhanced by a bio-mass micro power station, which will produce sufficient power and heat for the on site buildings and a surplus that will provide enough energy to power up to 650 local homes.

Other sustainable features of the development

will include thermally efficient buildings with air tightness and thermal insulation, systems for energy reduction and the latest solar cell technology which will eliminate night time light pollution.

Tom Haughey, CEO Severfield-Rowen Group, said: "We are pleased to be involved with such a high profile sustainable project as we believe sustainability is key to each of our subsidiaries.

"We have recently achieved Gold standard under the Steel Construction Sustainability Charter."



**The Structural Engineer**

4 November 2008

**Value engineering**

Part forming the roof over the auditorium is the project's largest single steel element; a 160t 48m long roof truss. With plate girders forming its top and bottom chords, the 6.5m deep truss was lifted into position in 24 individual pieces. It required temporary towers to support it until the entire truss was bolted into position with its connecting steel members and secondary trusses.

**Contract Journal**

22 October 2008

**Speculating with steel**

One of the key elements of a speculative build development is a quick construction programme and the entire project has been completed in under two years. Choosing steel instead of other framing materials has helped speed up the programme as all of the 1,800t of structural steelwork was fabricated, supplied and erected in just 26 weeks.

**Build It**

December 2008

**On the crest of a wave**

The steel was supplied by fabrication company Evadx in Rhyl after John consulted with experts at Corus. "I phoned Corus to ask their advice on the steel frame and they couldn't have been more helpful. They recommended a mild structural steel that was painted in Bradite epoxy coating for maximum resistance to corrosion and weathering.

**New Civil Engineer**

27 November 2008

**Lights camera action**

(Referring to Media City in Salford) "We looked at all framing possibilities for each individual building and steel was the best option for the studio, not just because of the spans, but also acoustically," says Bovis Lend Lease Project Director John Hyne.

## Reusing steel is the sustainable choice

The BCSA has recently received a number of enquires regarding the design and construction of projects to be done, in part, with reused steel sections.

"Structural sections can be reused or infinitely multicycled into new steel, unlike other construction materials which usually end up in landfill," said BCSA Director General Derek Tordoff. "When designing with reused steel sections designers

need to take into account that the dimensions and mechanical properties vary depending on the date of manufacture."

The BCSA recommends designers refer to the 'Historical Structural Steelwork Handbook' at [www.SteelConstruction.org](http://www.SteelConstruction.org) for more in depth information on the subject.

An example of reused steel being utilised in a new build project is the BCSA's new Yorkshire office near

Garforth. This structure was designed and built using reused sections taken from a nearby demolished warehouse.

Developer John Wilson used 82t of reused steel for the new office building. All the sections were disassembled and then refabricated in to a new frame.

"This is something we do on a regular basis," said Oliver Wilson Corrigan of John Wilson.

### Efficiency up at Cleveland Bridge



A new high speed FICEP 1203 CNC DJB Drilling and Bandsaw machine has been installed at Cleveland Bridge's fabrication facility.

Steve Wright, Works Manager for Cleveland Bridge, said: "It is essential during a substantial downturn of the construction industry that we should look to invest in our production capabilities to offer our clients the best possible prices without in any way compromising

quality. This FICEP machine provides the efficiencies we required and its unique scribing system offers additional benefits to ourselves and our clients."

This is Cleveland Bridge's first investment in new production machinery for some time and it will operate the 1203 unit alongside another FICEP machine, a TIPO B 25 which was purchased more than seven years ago.

### Architectural HQ opts for steel framing

Architect BDP's new Manchester head office has been completed with the aid of Metsec's site fixed framing system (SFS).

The striking six storey building, part of the city's £250M Piccadilly Basin regeneration scheme, is viewed as a flagship HQ and will house 275 BDP staff.

Metsec worked with contractor CPL to design and build an outward leaning external wall, a key feature of the canal side building.

A quantity of 150mm wide studs were supplied by Metsec. These

were attached at an angle to the main concrete slab frame with a series of slotted cleats, to form the external sloping facade. To form the inner skin a number of 100mm studs were supplied.

Sustainability was a key requirement for the building, which is the first naturally ventilated office building in Manchester to achieve a BREEAM 'Excellent' rating.





## New viaduct for A34 crossing



Steelwork erection for the first section of the new Wolvercote Viaduct on the A34 at Oxford has recently been completed.

The existing concrete viaduct, built in the 1960s has suffered extensive deterioration and is being replaced with a new steel composite structure. The viaduct carries traffic over the A40 Oxford to Cheltenham road, the Oxford to Birmingham railway and the Oxford Canal.

The new viaduct will sit in the same position as the

existing structure and causing minimal traffic disruption on the busy A34 means the project team have come up with a novel approach.

A new temporary southbound bridge has now been erected by Costain and steelwork contractor Fairfield Mabey adjacent to the existing bridge. Once this structure is completed, southbound traffic will use it, while northbound traffic is switched to the old southbound bridge. This will allow the northbound bridge to be demolished and completely rebuilt. Once finished northbound traffic will be diverted on to the new structure, allowing the southbound bridge to be demolished.

New concrete piers for the southbound bridge will be constructed and then the entire 250m long temporary bridge deck will be jacked up and slide across on to the new southbound piers. "It's a complex procedure," said Darren Dobson, Costain Project Manager. "But it allows the A34 to have four lanes open during the majority of the works."

The new viaduct is scheduled for completion mid-2010.

## Cladding the factory of the future



The Advanced Manufacturing Research Centre (AMRC) dubbed 'the Factory of the Future' has recently been completed by Bowmer & Kirkland for the University of Sheffield.

The facility houses the latest manufacturing equipment and state-of-the-art production capabilities to enable businesses to trial new developments on a full scale commercial production capacity.

The steel framed building, erected by Conder Structures incorporates roofing and cladding products manufactured by

Architectural Profiles (APL).

The APL Energi System used on the AMRC is based on a StrongBak structural wall framing system which is said to be one of the fastest methods of total building enclosure and air seal.

The Energi System was able to achieve a 0.2 w/m<sup>2</sup>/Oc insulation performance against a Buildings Regulations requirement of 0.35 and air seal of 2.71m<sup>3</sup>/hr/m<sup>2</sup>. Both of these are considered by BREEAM to be in the 'Excellent' rating category.

## Witney retail development gets a car park



Conder Structures, working on behalf of Simons Developments, has completed erecting 850t of steelwork for a retail development's car park in Witney, Oxfordshire.

The steel framed car park will

provide 650 vehicle spaces for the new £50M, 14 unit Marriotts Close retail and leisure centre (NSC September 2008).

The car park's dimensions of 73.7m x 70.3m were dictated by the

need to fit in a required number of spaces into a restricted site.

As part of its extended contract, Conder supplied and installed precast 150mm hollow core concrete units for all eight split levels with a design loading of 2.5kN/m<sup>2</sup>. The design delivers a minimum floor to floor height of 3.075m, with a 2.1m clear height.

In a service yard beneath level three, Conder created a 674m<sup>2</sup> area clear of internal columns. This was achieved by installing two 21.13m long lattice vierendeel trusses, each weighing 23t.

The ends of the diagonal members were slotted to fit over gusset plates and on the centre line of the booms. The trusses had a critical depth measurement of 3.15m, designed to fit exactly within the storey levels.

**Billington Structures** has won the prize for business growth at the Barnsley Business Awards 2008. The award, sponsored by the Barnsley Chronicle recognised Billington's achievement of significant and sustained growth over the past three years.

BCSA has formed the **Fabrication and Welding Users group** and its first meeting was held at the BCSA's Yorkshire office on 25 November. The aim of the group is to provide BCSA members with a forum to discuss and address the complete range of practical and technical issues affecting day to day operations. The first meeting discussed the forthcoming introduction of CE Marking and the associated standards BS EN 1090-1 and BS EN 1090-2, the new welding standards and developments in material processing machinery and software.

The new **European Standard for the fabrication and erection of structural steelwork**, BS EN 1090-2, was expected to be published by the BSI as NSC went to press at the end of December. BS EN 1090-2 will eventually replace British Standards such as BS 5950-2, BS 5400-6 and parts of BS 8110.

The doubts associated with application of **BS 6399-2** to large-span single storey buildings together with the recent issues association with the forthcoming wind Eurocode, EC1: Part 1.4 have prompted the BCSA to commission the Building Research Establishment (BRE) to monitor the wind load on a typical hangar. The purpose of the work is to collect data with a view to assessing the validity of the wind load models in BS 6399-2 and EC1: Part 1.4 and whether or not the recommendation 'to ignore local wind pressures in the design of the steel frame' should be reinstated in BS 5950-1. Measurements are to be made during a four month period this winter.

## Steel success story at London seat of learning


The London School of Economics' (LSE) new £34M Academic Building opened for the Autumn term after an extensive remodelling which required 450t of structural steelwork and the installation of two Corefast modular cores.

The building totals 12,600m<sup>2</sup> across 11 floors and is arranged in a U-shaped configuration around a glazed atrium.

The building's original facades were retained while the internal structure was demolished and replaced with new floors suspended from a steel transfer truss at roof floor level. This provided an extensive column free 400 seat lecture theatre at basement level.

The 15t steel transfer truss is 17.5m long and is supported on two CHS columns which extend right through the new build section of the building. These columns are 559mm diameter at the lower levels, decreasing to 508mm diameter further up the structure.

The building was designed by Grimshaw Architects and built by Osborne, the engineer was Alan Baxter & Associates and the steelwork contractor was Bourne Steel.



## Hospital car park increases capacity and security



A £8.6M steel framed three level car park has been completed for the Basildon & Thurrock University Hospital NHS Foundation Trust, increasing both capacity and visitor security.

Built on the site of the hospital's former 800 space surface car park, the new car park features fluorescent lighting and 50 CCTV cameras to provide security which has been accredited under the Park Mark Safe Parking Scheme.

Tommy Chambers, Divisional Director for main contractor Osborne, said: "Most hospital campuses are fixed and finding more space to expand is difficult. By building a multi storey car park, the Trust has improved parking on site significantly,

managed its historical problem of illegal parking and dramatically enhanced safety and security."

The 154m x 64m steel frame was erected by SIAC Tetbury Steel and required 850t of galvanised steelwork. The steel was erected around a 7.2m x 16m grid, which equated to 22 bays long x four bays wide.

Mark Fox, SIAC Tetbury Steel's Associate Construction Director, said: "The project was erected with mobile cranes in nine phases, as this allowed continuity for both steel erection and installation of the precast concrete planks.

"Due to the success of this project we have now been awarded three more car parks with Osborne."

## Diary

For all Corus events visit [www.corusevents.com](http://www.corusevents.com) email [events@corusgroup.com](mailto:events@corusgroup.com) tel: 01724 405060  
For all BCSA events contact Gillian Mitchell tel 020 7747 8121 email: [gillian.mitchell@steelconstruction.org](mailto:gillian.mitchell@steelconstruction.org)

29 January 2009  
**EC4 Composite Design Course**  
Birmingham



12 February 2009  
**ISE Connection Design Course**  
London



The SCI provide a range of in-house training courses to both Members and Non-Members of the SCI. Courses can be customised to suit a company's CPD objectives.

4 February 2009  
**EC3 2 Day course**  
Dublin



24-25 February 2009  
**EC3 2 Day course**  
London



SCI's In-House training is a cost effective approach to ensure your staff receive the most relevant and up-to-date training materials.

11 February 2009  
**EC4 Composite Design Course**  
Dublin



26 February 2009  
**Preparation for Eurocodes**  
London




For a list of all in-house courses or to discuss your requirements please  
Contact: Jane Burrell  
email [education@steel-sci.com](mailto:education@steel-sci.com)  
tel: + 44 (0) 1344 636500



# Three new releases on one disc...

# ... and our previous hits, re-mastered.



Introducing the **Westok Design Suite** -  
a collection of three new items of SCI software,  
all contained on one CD:



Cellular Beams - Engineers Design Guide - 48-page



Ultra Shallow Floor Beams Design Guide - 20-page



Binder



Ultra Shallow Floor Beams Design Guide - 20-page

**UPDATED**

**Westok**  
CELLBEAM v7.0  
**AutoMate**

**CELLBEAM AutoMate v7.0**  
The latest version of SCI's  
well-established  
cellular beam design software.

**NEW**

**Westok-USFB**  
**AutoMate v1.0**

**USFB AutoMate v1.0**  
The first ever software to design  
Ultra Shallow Floor Beams.  
Also written by SCI.

**NEW**

**Westok**  
**CellVibe**  
v1.0

**CellVibe v1.0**  
Written by SCI in accordance with P354, *The Design  
Guide on the Vibration of Floors*, this software quickly  
calculates a floor's critical response factor.

To receive a **FREE** copy of the **Westok Design Suite** please complete the details below and fax back to Westok.  
Alternatively, email your request to [info@westok.co.uk](mailto:info@westok.co.uk) or phone **01924 264121**.

## FAX YOUR REQUEST TO WESTOK ON 01924 280030

- Please send me a **FREE** copy  
of the **Westok Design Suite**.


☐

- Please contact me to arrange one of the following  
CPD Seminars:

☐

- Cellular Beams & USFBs - Design & Applications

☐

- Vibration & Floor Response Analysis + CellVibe Software Use

☐

- Westok Design Suite Software Training Session

Please tick as appropriate

Name: \_\_\_\_\_

Position: \_\_\_\_\_

Company: \_\_\_\_\_

Address: \_\_\_\_\_

Postcode: \_\_\_\_\_

Email: \_\_\_\_\_



**ASD Westok Limited**  
Charles Roberts Office Park  
Charles Street, Horbury Junction  
Wakefield, West Yorkshire  
WF4 5ER

Tel: 01924 264121  
Fax: 01924 280030  
Email: [design@westok.co.uk](mailto:design@westok.co.uk)

**[www.westok.co.uk](http://www.westok.co.uk)**



# New hospitals are super in steel

*Speed, efficiency and cost effectiveness are just some of the reasons why a massive Birmingham hospital project is relying entirely on steel as its framing material. Martin Cooper reports from the UK's new super hospital.*

The Birmingham New Hospitals (BNH) PFI project is the first new general hospital to be built in the UK's second largest city for more than 70 years and the largest community healthcare development outside of London.

Once complete in 2012, this new 'super hospital' being constructed on a 50 acre site adjacent to the existing Queen Elizabeth Hospital in Edgbaston, will offer 1,213 beds, 30 operating theatres, 15 laboratories, 300 teaching rooms as well as 3,700 car spaces spread over three new multi-storey car parks and a series of other ground level car parks.

Plans for the new hospital and the existing estate also include streamlining local medical services by absorbing all healthcare activities currently being undertaken at Selly Oak Hospital, which will be closed down. Waiting times will also be significantly lowered as the new hospital will be able to treat 21% more patients in its operational area.

The project is undoubtedly big, and the size and complexity of the job has led the project team to use a number of innovative design solutions to provide the most economic and functional structure.

The main structure, known as the Acute Hospital, actually started out as a fully reinforced concrete

frame, but as the design developed this changed to a mixture of steel and concrete and then finally a full steel frame.

"Using steel has been a real success on this project," explains BNH Balfour Beatty Project Director Roger Frost. "The speed it can be erected on a project of this size is important and it's efficient and less labour intensive."

This last point is important to BNH, as during 2008 the number of workers on site peaked at around 1,300, a total Mr Frost estimates would have been much higher if prefabricated methods were not used.

"On a project as large as this one, managing the workforce is vital," he adds. "We are extremely safety conscious, but the larger the workforce the greater the possibility of accidents."

Keeping the project moving at a steady pace has also led BNH to use as many off-site prefabricated products as possible, such as fully fitted bathroom pods and fully equipped bed head walls. "Steel comes to site ready to be erected, it's also a pre-fabricated product," adds Mr Frost.

Advance works began on site in late 2004, with the main construction programme kicking off in



*Above: The project's main features are the three truncated pods containing the hospital's wards.*



*Left: BNH estimates that using steel has saved the client time and money while the need for fewer workers has meant a safer site.*

*Right: Structural steel model of Sector 1 (the first pod to be completed).*

## Analysis proves vibration performance

Vibration from a number of sources, such as air handling units, was considered in the structural design process. The result of the preliminary design was a robust steel frame utilising a 225mm composite concrete/profiled metal deck floor slab spanning between composite primary and secondary beams. "By using 225mm thick slabs we were able to provide floor beams with a high natural frequency and a slab with inherent mass to damp induced vibration," says Mr Garland.

"It was essential to maintain standard grid arrangements with continuous lines of secondary beams to promote the mobilisation of large areas of floor plate and increase the modal mass for vibration damping."

To validate the preliminary vibration design Severfield-Reeve commissioned SCI to undertake finite element analyses of the floor plates. From these analyses it was found that nine reasonably closely spaced modes of vibration existed which were likely to be the basis for resonant vibration. By adopting accurate loadings and damping factors it was confirmed that the design would meet the vibration requirements of

HTM2045 Acoustics Design Considerations 1996.

Following the erection of the steel frame and the installation of the floor slabs, additional elements of sensitive medical equipment were introduced into the building. This equipment comprised MRI and CT scanners and in May 2008 WYG Engineering undertook a review of the now complete Sector 3 structure to assess the feasibility of providing adequately robust spaces to house MRI and CT scanners on areas of existing suspended floor slab. This exercise required an assessment of the structural capacity of the affected areas of the existing building and a vibration analysis, undertaken firstly by hand and then by in-situ testing, to confirm that the structure met with the stringent performance requirements specified by the equipment manufacturers. Vibration measurements were then undertaken on 1 September 2008 to evaluate the response of the floors in accordance with BS6472: 2008 which confirmed that the structure successfully met the vibration acceptance criterion specified for the scanners.

### FACT FILE

**New Birmingham Acute and Adult Psychiatric Hospitals**

**Client:** Consort Healthcare for the University Hospital Birmingham NHS

**Foundation Trust and the Birmingham and Solihull Mental Health NHS Trust**

**Lead architect:** BDP

**Main contractor:**

Balfour Beatty Construction and Haden Young (BNH JV)

**Structural engineer:**

WYG Engineering

**Steelwork contractor:**

Severfield-Reeve Structures

**Steel tonnage:** 12,500t

January 2006. The early part of the programme saw the first of three steel framed multi storey car parks built. This freed up space for the rest of the project to get under way, as much of the site was formerly taken up by a ground level hospital car park.

Three new steel framed mental health units were also erected early in the programme. This allowed the existing mental health hospital to decamp into the new facility, which in turn meant

**BNH used as many off-site prefabricated products as possible, such as fully fitted bathroom pods and fully equipped bed head walls.**

the old mental health unit could be demolished to free up even more space for the new Acute hospital building.

The design for the new Acute hospital consists of three truncated pods, connected by walkways and set upon a three storey rectangular podium block. Four reinforced concrete slip form cores, in addition

to localised systems of vertical steel bracing, provide each of the pods with their lateral stability.

"The main steel frame was tied into the shear cores using cast in steel embedment plates which were installed during the slip form works," says Andy Garland, Associate at White Young Green (WYG) Engineering. "This ensured that the steel

frame would be positively tied to the reinforcement within the core walls and negated the need for drilling of post fixed connections." Fin plates were subsequently welded to the embedment plates ready to receive the floor beams.

The pods are approximately 50m high and contain the hospital's wards on floor levels three to seven, with plant space at level eight. These truncated pod structures have a hollow centre which acts as a large lightwell and allows natural light to penetrate the interior wards. The ward structures also feature sloping roofs which mean they contain six levels on the northern elevation and one less floor on the southern elevation.

On the ground floor of the podiums the accommodation consists of several departments, the major ones being imaging, and outpatients. On the first floor the departments include A&E and education, while the next floor up is the interstitial plant room level known as 2a. The top floor of the podium section, the third floor, contains the main theatre department.

The location of the plant rooms changed during the design process with a view of finding the most functional and cost effective solution. Each change had major ramifications on the civil and structural design, impacting on both the structural grid and the steel frame.

The inclusion of an interstitial plant space was



*Above: As steelwork was being completed on the last pod, the cladding process was following close behind.*

finally adopted at level 2a (third level of podium) which forms the horizontal interface between the podium block and the six storey oval shaped pod above. Transfer structures were installed to transmit the tower column loads into the podium columns beneath, which are subsequently supported directly onto piled foundations.

"The decision to go for an interstitial floor linked in to an overall M+E services strategy connected with theatre locations and riser requirements," explains Mr Garland.

To form this dedicated plant floor Severfield-Reeve Structures designed, fabricated and erected a series of 1,200mm deep plate girder transfer beams

which were incorporated into the construction. In this respect, transfer structures occur partly over the upper most rectangular floor plate of the podium, and partly over the lower most radial floor plate of the pods.


Steelwork contractor Severfield-Reeve has also liaised closely with the cladding contractor to ensure the correct connections were supplied and erected. "All cladding is being landed and affixed from inside the building," explains Mr Frost. "This highly efficient method, again because we are using steel, means there is no need for scaffolding."

Efficiency as well as speed of construction have played integral roles so far on this project.

**The INNOVATIVE STEEL  
POWER  
of PEDDINGHAUS**

info@peddinghaus.co.uk FAX. 01952.292.8





*Above: Model of one of the ward pods, its cores and the podium.*

*Above right: All cladding has been fitted from inside the building, negating the need for any scaffolding.*

*Right: The three pods are linked by slipformed concrete cores.*



As Mr Frost sums up: "By using steel and as much off-site construction as possible we create a more efficient, environmentally friendly and cost effective programme."

Others agree, as the project recently won an award at the Chartered Institution of Wastes Management (CIWM) Awards for Environmental Excellence. The project's award submission outlined the vision to create sustainable, energy efficient, environmentally friendly buildings. The judges were impressed by the clear waste reduction, re-use and recycling measures, with arrangements made with suppliers to ensure products are being delivered without unnecessary waste.

# FABRICATING TECHNOLOGIES

377 TEL. 01952.200.377

**Peddinghaus**



# Bowled over by steel

*A fully glazed bowl shaped lecture theatre is the centrepiece of a new faculty building for Leeds Metropolitan University. Martin Cooper reports.*

Leeds is a city on the move. Like many of the UK's former manufacturing giants, it is reinventing itself with a host of developments, including commercial, residential and hotels, currently under construction.

One of the most striking developments is known as the Rose Bowl, a new home for the Business and Law Faculty of Leeds Metropolitan University.

Situated opposite Leeds Civic Hall, in the heart of the city's Civic Quarter, the main U-shaped building wraps around a distinctive glazed bowl structure which protrudes from the front. Supported on a series of Y-shaped columns, the Rose Bowl will house the faculty's lecture theatres and provides the establishment with a signature frontage.

Describing the job, architectural practice Sheppard Robson says its design has responded to the University's aspirations and the development integrates it with a wider context of its location, and orientates the campus towards Leeds city centre, improving the University's status.

Very much at the heart of the project, the Rose Bowl lecture theatre 'pod' will contain one 250-seat theatre, two 140-seat and four 60-seat theatres. As well as having a highly unusual bowl-like shape, which also tapers out as it gets higher, the structure is clad in distinctive triangulated bolt-fixed reflective glass panels.

A series of bridges cross a semi public atrium, day lit by a high level structural glazed rooflight, linking the 'pod' to the outer U-shaped four storey main floorplates, which house offices and ancillary teaching spaces.

As well as a complex steel design, the project has also featured a long preparatory programme. The site, formerly occupied by a car park, was sloping, so much so that when the basement was dug out, one end was excavated to a depth of 11m while the other only needed to be dug to a depth of 8m.


This large muckshifting operation, which began in early 2007, resulted in a flat basement slab which eventually took more than 6 months to cast. The cast in-situ concrete basement also includes a piled retaining wall.



1. Feature Y-shaped columns were tied to adjacent members.
2. Columns are connected to a steel diagrid.
3. Scaffolding enabled the pod to be glazed.
4. Fully glazed, the complete Rose Bowl pod.





**FACT FILE****Rose Bowl, Leeds****Main client:**

Leeds Metropolitan University

**Architect:**

Sheppard Robson

**Structural engineer:**

Arup

**Main contractor:**

BAM Construction

**Steelwork contractor:**

Fisher Engineering

**Steel tonnage:** 1,350t**Project value:** £36M

*Above: The project's city centre location meant there was little room for steel deliveries.*

*Left: The front elevation features the distinctive bowl shaped lecture theatre.*



*Below: Back elevation: The U-shaped office block wraps around the Rose Bowl pod.*



From ground level up the structure is steel framed, and steelwork contractor Fisher Engineering initially started by erecting the outer U-shaped faculty. This part of the project primarily contains offices and classrooms, is four stories high with a plant room on the roof.

"We started by erecting the faculty building up to third floor and then the Rose Bowl to the

**The design certainly lent itself to steel, especially the 'pod' theatre structure.**

same level," explains Barry Craig, Fisher Engineering Project Manager. "We were then able to use the third floor slab to run our cherrypickers on for the steelwork erection of the upper levels."

Logistically, the steel erection programme was very challenging as the site is extremely tight, surrounded by busy roads on three sides and the Civic Hall on the eastern elevation.

Consequently, there was little or no room for setting down of steel deliveries. Steel was delivered to site in a 'just in time' sequence. The above ground superstructure was always going to be steel for its speed of construction," comments Simon Sutcliffe, BAM Construction Project Manager. "The design certainly lent itself to steel, especially the 'pod' theatre structure, as well as the need for long spans in the office block."

Clear spans of 15m are a constant feature of the office block on every floor. "The nature of the occupants means there will be lots of services," comments Mr Sutcliffe. "So cellular beams are used throughout to maximise the 3.9m floor to ceiling heights."

The office block has an approximate length of 60m along its back elevation, and 45m length along the two protruding finger wings. The construction process for this part of the programme was mostly traditional 'stick and beam' using the two on site tower cranes and bringing in a mobile crane when needed.

To begin erecting the Rose Bowl four internal main columns were erected first. "The bowl is essentially an elongated circle in plan, 24m wide x 30m," explains Mr Sutcliffe.

"These four columns were tied in and formed a central braced core, with temporary props in place, the steel was then erected off these large members," adds Mr Craig.

The ring of Y-columns needed a 100t mobile crane, as each of these columns, which were brought to site as complete pieces, weighed around 5.5t.

"We started with the Y-column at the 12 O'Clock position," explains Mr Craig. "Holding this in position with a crane, we then erected an adjacent column with another crane and tied them together with a beam."

Once the first two columns were up Fisher was then able to complete the entire ring of columns, by tying them into adjacent members.

This series of Y-shaped feature columns are connected to a horizontal truss, or steel diagrid, which goes around the circular structure. A series of these diagrids form the bowl shape which is fully glazed.

The node points on each diagrid has a total of six beams connecting to each other. "Accuracy was key for this part of the steel fabrication, because if one node was out the entire 'pod' wouldn't have fitted together," sums up Mr Craig.



# Fire performance makes a case for steel

*The latest in our Case for Steel series highlights that thanks to a long term, comprehensive research, more is known about how steel performs in fires than any other construction material.*

*Above: Slimdek flooring can achieve 60 minutes fire resistance without additional applied protection.*

Thanks to extensive, long term research more is known about how steel framed buildings will behave in fires than about the fire performance of any other construction material. Structural designers have begun asking questions about the performance of other materials in fire, which are relatively under-researched – for example, concrete has never been large scale fire tested and major doubts have recently been raised about the understanding of the extent and speed of concrete spalling.

The steel sector's commitment to establishing the facts about steel in fires means there are no such worries facing the design community over steel frames. The steel sector has invested considerable resources into understanding how structural steel components respond in fires, so that designers can engineer in the confidence that steel is a safe option.

Steel structures dominate the multi storey buildings market, reflecting the fact that a fire protected steel solution is cheaper than any alternatives, and comes with the confidence of knowing just how a steel structure will stand up to the stresses imposed by fire. Thanks to full scale testing at the BRE's Cardington facility which addressed the behaviour of complete structures in fire, straightforward design approaches have been developed that reduce the extent of fire protection needed. This and much other research, whose results have been freely shared with the design community, provide reassurance that the available steel solutions are technically sound.

**The steel sector has invested considerable resources into understanding how structural steel components respond in fires.**

**Reliable and economic solutions**  
Steel has been proven to provide a reliable and economic solution, whether protected by any of the wide range of proven protection materials,

or left unprotected thanks to advances in structural analysis techniques (see box on structural fire engineering).

The full-scale testing mentioned above has addressed the behaviour of complete structures, and led to advanced design approaches using sophisticated analysis techniques which reduce the extent of fire protection. Simple methods are also available for the analysis of composite metal deck construction which can lead to the elimination of fire protection on most secondary beams.

Development of a competitive and efficient structural fire protection industry within the UK has encouraged further commitment to research and development within the steel sector, so specifiers can take advantage of greater choice at lower cost than anywhere else in the world.

#### **Offsite breakthrough**

The development of offsite application of







*Above: Tests on intumescent coatings have generated product specific performance data, which has been used on projects such as the Royal Shakespeare Company's theatre at Stratford upon Avon.*

*Below: The Dublin O<sub>2</sub> project extensively used offsite application of intumescent coating.*



intumescent coatings has been a breakthrough for the steel construction sector. Offsite application has a number of advantages including reducing construction times; improvements in site safety; speedier access to site for follow-on trades; improved quality control and reduced weather sensitivity. Most long span and cellular construction uses offsite application, as does over half the steel framed commercial construction in the south-east of England.

Not all steel requires fire protection and construction methods have been developed requiring no fire protection. The most successful of these has been Slimdek and Slimflor, pre-engineered shallow construction flooring systems, which can be designed to achieve 60 minutes fire resistance without additional applied protection. If normal downstand composite beams are adopted, simple design guidance is available that can eliminate fire protection from 30% of the secondary beams.

A new British Standard, BS 9999, will be an alternative to the Approved Document B, and will be a source of information and guidance on fire precautions in buildings. Structural fire precautions in this standard will vary from

### **Protected steel solutions are easily inspected and tested.**

those in the Approved Document, sometimes higher and sometimes lower. However, it will see a significant increase in the number of buildings requiring only 30 minutes fire resistance. In many cases it is possible to design structural steelwork to achieve 30 minutes fire resistance without additional fire protection, by increasing the weight of steel sections or substituting a higher grade of steel.

A good example of how the steel sector's commitment to research benefits designers and developers is the work carried out on long span beams with openings, which has led to an in depth understanding of behaviour at elevated temperatures. Subsequent developments and thorough testing on a number of intumescent coatings has generated reliable product-specific performance data.

Protected steel solutions are easily inspected and tested, compared to the difficulties associated with inspection and testing of concrete construction on site.

## Wealth of test data supports structural analysis

Structural Fire Engineering (SFE) is the name given to a new generation of finite element frame analysis based techniques that allow more efficient fire engineering of structures. SFE has been developed using the results of the extensive testing carried out on how steel behaves in fires over many years.

It means that fire protection to most secondary steelwork can be dispensed with while maintaining a building's ability to perform in line with stringent codes. This analysis can also pinpoint where in a structure additional protection might be added to enhance fire performance.

Architects have seized on the potential of SFE to enhance their freedom to fully express their design ideas, eliminating the need for painted protection for example in areas that they would rather use exposed steelwork for aesthetic reasons. The UK has taken a world lead in development of these techniques and several landmark buildings taking advantage of what SFE has to offer have already been built, saving resources, and time and money for developers.

Designers say SFE is a more rational way of ensuring fire-safe designs than the old prescriptive way of ensuring safety for the time demanded by Building Regulations. It considers the actual loads that fire imposes on structural members, taking account of any shielding applied and considering secondary structural actions.

Alternative load paths are analysed, allowing confident predictions of how the building will behave in a real fire. The traditional approach is based on standard fire tests that do not necessarily reflect accurately what happens in fires; some of the tests relied on for concrete for example are up to 70 years old. Since steel has been extensively and recently tested, there is a wealth of accurate and contemporary data available to inform this sort of structural analysis.





# Steel shows worth in congested Cork

**FACT FILE**

**Douglas Village Shopping Centre, Cork**

**Main client:**  
Shipton Group

**Architect:**  
Wilson Architecture

**Main contractor:**  
Bowen Construction

**Structural engineer:**  
Arup Consulting Engineers

**Steelwork contractor:**  
Walter Watson

**Steel tonnage:** 5,000t

*A large steel framed shopping centre extension is being constructed on the outskirts of Cork. Martin Cooper reports on how 5,000t of steel has been delivered and erected on a site surrounded by shoppers and their vehicles.*

Building a new shopping centre can be a time consuming operation and one which demands a whole host of criteria to be planned well in advance. Constructing a new shopping centre adjacent to an existing mall, one which is surrounded by car parks and busy roads can only exacerbate the workload.

This is precisely the challenge that steelwork contractor Walter Watson has had to overcome while erecting 5,000t of steelwork at the second oldest shopping centre in Ireland, Douglas Village Shopping Centre in Cork.

A new ground level mall, containing a Tesco anchor store with a mezzanine floor, topped with three levels of car parking is being constructed as part of the overall redevelopment of the existing shopping centre, which has remained open throughout the building work.

"We are actually putting the steelwork up on the existing centre's ground level car park," explains Trevor Irvine, General Manager Structural Division of Walter Watson. "The old car park has to remain open throughout, but as our steelwork advances it is getting more confined."

Working around shoppers and their cars is a tricky proposition and steel deliveries have had to be timed so they are delivered and off-loaded

outside normal working hours, and then erected that day, as lay down areas are almost non-existent.

The project developer has had to guarantee a minimum number of car parking spaces during the construction work and to facilitate this the new multi-storey car park was partially opened in November, this then allowed steel erection to advance further into the old car park.

Prior to steelwork going up, the old car park was piled with concrete bases and bolts installed for the future steelwork. These foundations were then asphalted over to recreate parking areas.







Above: Braced cores provide the stability for the extension.

**Unusually, cellular beams were specified for the light and airy atmosphere they will create in the car park.**

Left: The project is surrounded by roads and an existing car park.



Above: Cellular beams will allow more light into the large car park, especially at night.

"The asphalt is dug up to expose the foundations immediately prior to steel erection," explains Mr Irvine.

Working in a live environment and having to keep enough parking spaces available for shoppers are just two of the challenges associated with the job, says James Duggan, Associate Director and Project Manager for Arup. "As well as piling into difficult limestone ground conditions we also had to divert two rivers, with new culverts, which ran right across the site."

The shopping centre's extension is L-shaped and abuts and joins up to the existing mall along two elevations. Steel erection began at the car park entrance - which is half way along the longest elevation - and then advanced in two opposite directions.

This work also included installing the car park ramps from ground floor level to the car park's first floor level. The ramps are steel formed and are a spiral scissor configuration.

They are constructed with box sections which were installed with stubs and crash barriers already attached and once in place they were then infilled with cross member beams.

There are two helical ramps, one for each direction," explains Mr Duggan. "They are a complicated shape and could not have been designed without the aid of a 3D computer design package."

The steelwork for the ground floor level of the extension (retail) is based around a uniform 16m x 7.5m grid pattern, except for the Tesco anchor store which required its own varying grid pattern. The entire floor has a 6m floor to ceiling height and this has allowed Tesco, which takes up approximately half of the ground floor footprint, to have an additional mezzanine level installed. A series of large plate girder transfer structures above the Tesco store and ramp allowed the transition to occur between the varying grids.

Walter Watson began steel erection in August 2008 and completed its work during December. The company had two 50t capacity mobile cranes on site as well six cherrypickers.

"Initially we were erecting 100t of steel a day, which is four truck loads," says Mr Irvine.

"However, as the steel frame began to cover large areas of the existing car park our programme slowed down slightly as we could only erect steel at the rate that the old car park was given over to us."

Above the retail level the three floors of car parking are also based around a 16m x 7.5m grid pattern, with a 5.6m cantilever above the existing mall. A central row of columns in the car park, consisting of 356 x 287 members, take the back span loading from the 22m long Westok beams.

"Erecting a cantilever over a functioning shopping centre required careful planning and erection," says Mr Duggan.

Throughout the project more than 2,000t of Westok beams, painted white, have been used for all floors. Unusually, cellular beams were specified for the majority of the project, not for their service holes, but for the light and airy atmosphere they will create in the car park.

The car park has a relatively low head height and the beams will visually open up the space. This was considered very important so that users are not intimidated particularly at night.

"Services will run through the beams at the retail level, but the thinking behind this design for the carpark was that holes in the Westok beams will allow natural light to penetrate through them and they allow for greater dispersion of artificial light at night. Plus, the long spans obviously mean fewer columns casting shadows," explains Mr Irvine.

Stability for the entire extension is derived from six steel braced cores containing lifts and stairs and moment frame connections on the cantilever. Heavy tubular bracing has been used as a feature element along one elevation, while Walter Watson has also erected all secondary steelwork along the two main elevations which will have rainscreen cladding attached to it.

Also included in the project is a new local public library which is attached to the lower end of the L-shape. This is a steel framed two storey structure which shares columns with the rest of the extension.

Keeping the shopping centre's visitors happy with enough parking spaces aside, the construction team are on schedule and the redevelopment is due to open in mid-2009.

Briar Hill Primary School, Northampton  
Jessons CofE Primary School, Dudley  
Holycross High School, Wishaw  
Mossley Primary School, Co Antrim  
Queen Margaret University College, Musselbrough  
Sacred Heart High School (sports hall)  
Bridge Academy, Hackney, London  
Cannon Sharpes CofE Primary School, Wigan  
Hobmoor School, Birmingham  
Newstevenston Primary School, Motherwell  
Sundridge Primary School, Kingstanding  
Anglia Polytechnic University, Chelmsford  
Bulwell Academy, Nottingham  
CETL Entrance, Univeristy of Northumbria  
Magee College, Derry  
Edlington School, Doncaster  
Leaney Primary School, Ballymoney  
Chapelhall Primary School, Airdrie  
Yewlands School, Sheffield  
Hinde House, Primary School, Sheffield  
Tresham Institute, Kettering

### **Failsworth School, Manchester**

Unity Academy  
Open University, Milton Keynes  
Whitgift School, Croydon  
Clowne Secondary School, Clowne  
Greenbank High School, Southport  
Project Scan, Manchester University  
Shiremoor Middle School  
Willesden Leisure Centre, London  
Northburn School  
Hackney School, London  
University of Warwick, Warwick  
Camphill Primary School, Ballymena  
Thrybergh School, Rotherham  
Old Hall Secondary School, Rotherham  
Richard Pates School, Cheltenham  
Soundwell Technical College, Bristol  
Guildford High School for Girls, Guildford  
Tong High School, Bradford  
Hunsbury Park Primary School Extension, Northampton  
Bellinge Primary School, Northampton







**Top Marks** - over 70% of all new UK educational buildings use a structural steel frame



Steel scores top marks for value, flexibility, sustainability and speed. It provides a modern, pleasant and productive environment in which to work and live. Steel is tough, resilient and adaptable, so it is ideal for schools, colleges, universities and their accommodation buildings. Steel is top of the class.

To find a steelwork contractor to help build your new school, college or university, visit:

[www.steelconstruction.org](http://www.steelconstruction.org)

# Cantilevered for success

*A new commercial development in Glasgow has been highly engineered to provide both long internal spans and significant elevation cantilevers, reports Martin Cooper.*

The credit crunch may be biting hard in some construction sectors - most notably the residential and commercial markets - but in Glasgow there are still a number of high profile jobs on the go, judging by the number of tower cranes visible across the city's skyline.

One of the most visible projects is a new 10-storey office development rising up on the plot of 29 Wellington Street in the city centre. This steel framed building is replacing a concrete framed structure which was built in the late 1960s, although the new build now includes a one level basement car park.

BAM Construction in its role as management contractor has been on site since mid-2007 and began by demolishing the original building. Once this was completed a series of 12m deep cantilevering permanent exposed sheet piles were installed around the site's perimeter, in lieu of contiguous or secant bored piles as suggested by BAM Design.

"This saved weeks of construction time when compared with the alternatives," explains John Keys, BAM Construction's Project Manager. "This greatly facilitated the basement excavation and therefore steelwork erection could commence earlier."

The original architectural concept was based on a standard 9m x 8m central column grid. However, BAM Design suggested losing a line of columns and this resulted in a far more desirable 9m x 16m grid pattern.

This large grid pattern is based around four large 356 x 406 x 634 columns, positioned around 3.5m from one elevation, which also form part of a four-bay full building height moment frame. These columns are 8.9t each and extend from ground floor all the way to roof level. They were installed in three sections: 2 x 13m long columns and then one 7m long member for the eighth floor to tenth floor phase. The column splices were designed by steelwork contractor BHC, based on BAM Design's connection concept featuring countersunk bolt heads, maximising net lettable area.

Structurally one of the main features of the building are its feature cantilevers, one at 3.4m and the other reaching a maximum length of 4.4m. To control the end displacement, the 16m back span beams were designed as continuous non-composite with regards to strength, while deriving benefit from composite action with regards to deflection.

## FACT FILE

29 Wellington Street,  
Glasgow

### Main client:

BAM Properties

### Architect:

3D Reid

### Main contractor:

BAM Construction

### Structural engineer:

BAM Design

### Steelwork contractor:

BHC

### Steel tonnage:

1,100t

Steelwork starts at ground level and is based around a large 9m x 16m grid.





*Above: The tight and confined city centre site.*

*Below: Feature tubular bracing.*

*Bottom: Impression of the completed building.*



"These cantilevers support a unitised glazing system, which stipulates highly onerous deflection criteria of less than 10mm both horizontally and laterally," explains Mohammad Ziauddin, BAM Design Project Engineer. "Furthermore, the building is designed for multiple occupancy, which means that the cantilevers are subject to movement up or down relative to the floor above and below."

Westok beams ranging from 480mm deep to 580mm deep have been used for the long internal spans and cantilevers. This not only provided the benefits of weight efficiency gains and complimentary pre-cambering, but also an integrated distribution of lateral services within the structural zone, giving added flexibility for future multi-tenancy.

***"There was no waiting around for the concrete cores to be completed before steelwork erection could begin."***

Lateral stability of the steel framed structure is achieved by the use of both steel cross bracing in stair/lift cores as well as moment frames. One elevation has cross bracing comprising 219mm diameter tubular sections in full view as an architectural feature. The lateral forces are transferred to the vertical bracing systems via the concrete floor slabs by a diaphragm action. The horizontal displacement of the building has major significance to the design of the glazing system, due to the potential for racking under wind loading.

"Many projects of this type would have gone with concrete shear walls, but we decided on steel cross braced walls which are easier to erect and much quicker, as they go up with the main steel frame," adds Mr Ziauddin. "There was no waiting around for the concrete cores to be completed

before steelwork erection could begin."

The entire superstructure was modelled by BAM Design in CSC's Fastrak Building Designer with lateral loads such as NHF and wind being applied automatically. The Westok beams were also modelled in Fastrak Building Designer but designed using SCI's specialist Cellbeam software. All floor plates are based on the typical second floor level which features the largest floor area. Other floors are simple variations on this level, featuring cut-outs and recesses.

For the steel erection BHC's initial phase was the basement to the second floor. Once this was completed and the floors decked, the second floor slab was cast and this allowed other trades to carry on working below while BHC put its cherrypickers on the slab to erect the floors up to level five.

This methodology was then repeated for another two phases with BHC erecting steelwork from fifth floor to eighth floor, and then finally working off of the eighth floor slab to erect floors nine and ten.

Working in this way the entire construction team was able to erect and fit out the floors in a quick manner. Another consideration, and one which surfaces on many inner projects was the lack of available space for on-site materials storage.

"We had to bring steel to site in 15t loads and lift them immediately to the floor we were erecting off," explains Jim MacDonald, BHC Project Manager. "In this way we didn't overload the on-site tower crane's capacity and we were able to erect each load as it came in."

"It was all down to planning the logistics of the job well ahead as a team," sums up Mr MacDonald.

Keeping ahead of the game and thus completing the project on time are all key reasons why the design team says they chose their methodology.

29 Wellington Street is due for completion by the third quarter of 2009.



*Wembley Stadium steelwork model, courtesy of Oakwood Engineering, showing 4D information retrospectively added to the model for visualisation of critical project dates.*

## Modelling for project success

*Developments in Building Information Modelling have moved on in leaps and bounds in recent times. Andrew Bellerby, Managing Director of Tekla (UK), explains how structural models provide added value to construction projects.*

The structural steel segment has always been ahead of the main building and construction industry players by adopting 3D modelling technology. Even though we are approaching twenty-years of 3D product modelling, many companies still only use the model data for the production of 2D fabrication drawings; for feeding their MIS systems and for producing NC data. However, many companies are realising that the potential usage of the structural model data is actually far greater.

Companies are now starting to wake-up to the power of the rich data within the structural model and where else it can be used within their internal processes. They also are discovering how structural models allow them to provide additional added value to the projects they are working on. While Building Information Modelling (BIM) as a practise and a process is becoming more commonplace, the structural model, provided by the steelwork contractor, becomes the normal "as-built" project model, as it contains the exact quantities and precise information required for successful completion of the project and so it has become one of the most vital parts on every project.

### **Who can use the data within the structural model and how?**

We have already seen CNC machine manufacturers such as Ficep, with their partner Steel Projects, making use of the Tekla Open API provided with the Tekla Structures software. The application programming interface was utilised to develop a link to extract information from the model to drive their scribing tools and start to move the steelwork industry towards a potentially paper-free workshop.

Another example would be Richard Lees Steel Decking, who have developed a solution for placing the structural decking into the structural model. This allows them to take all the connection materials into account, which they would not previously have easy access to. Other key benefits include being able to "fly" under the deck and identify areas where additional supports are required. The decking sheets can now be downloaded to a laser cutting machine directly from the model, moving the cutting of the deck offsite.

More recently, a bi-directional link between Tekla Structures and Leighs Paints' FIRETEX software has been developed to improve the somewhat time



consuming task of fire protection paint calculations. The link will enable information to be passed between the software packages allowing the user to transfer geometry and information regarding the steel structure with speed and accuracy at the click of a button. The FIRETEX software then calculates the required coating thickness based on the information from the model and the required fire ratings, these thicknesses can then be inserted directly back into the model, saving valuable time, providing more accurate paint volumes, and reducing the possibility of errors within the current workflow.

### RFID Technology in Construction

The use of bar-coding in manufacturing in the construction industry has never really taken off in a big way, limited often on the shop floor by paint, grime and damage to the bar code stickers themselves. Radio Frequency Identification (RFID) certainly has the potential to take this type of technology to the next level, providing status information of parts, not only in fabrication workshops, but also on the construction site, as well as providing other advantageous information.

RFID technology can give "real time" status information at all stages of the manufacturing and erection processes. Vela Systems ([www.velasystems.com](http://www.velasystems.com)) have been working with Tekla to synchronise the status information provided through their RFID software with the Tekla Structures building information model. At each stage of the fabrication, despatch, shipping and erection processes the tags can be read either by scanning manually or by automatic readers positioned at strategic locations.

This information can then be uploaded to a web server at regular intervals. The uploaded data on the web server is synchronised with the Tekla model to provide a visual representation of the 4D (time) project status. This ensures critical aspects of supply chain management and co-ordination becoming centralised in the model. Powerful filtering and visualisation tools in the Tekla software allow the running of simulations and analysing "what if" scenarios to minimise risk and take advantage of the data previously not so readily available. The potential time-savings on projects are huge.

### Data Storage by CE Marking

As RFID technology evolves it offers many more options for data storage that could be tagged to the constructed parts for ongoing facilities management. CE marking for the steelwork industry is legislation that we all need to deal with, and the RFID technology certainly opens up new options for storage of associated information.

While many companies will adopt a method of adding the CE marks to drawings and other documents, there is no reason why design or procurement information for example could not reside in the building information model and also on the individual parts by means of an RFID sticker, which of course would still be able to be read even if the stickers are painted over.




Modelling

### Tekla with Trimble on Site

Site planning, design co-ordination, and crane positioning are already utilising the 3D interface and the 4D schedule that is associated with the model parts. Development between Tekla and Trimble ([www.trimble.com](http://www.trimble.com)) now takes the Tekla model information into the Trimble Robotic Total Station to simplify the surveying and layout tasks. Tools have been developed so that a survey path and control points are defined in the model. This co-ordination and other information can be exported to the Robotic Total Station, along with a DXF file of the arrangement drawing, visually showing the same information.

The site layout can then be carried out by one person as the information from the Total station is transmitted by radio, the control points are shot, the site features measured, and all project set out points created. This gives an accurate as-built vs. as-designed survey with the information brought back into the model for reporting and tracking. Any re-work is minimised and potential error prone manual calculations are eliminated.

*Above: Complicated steelwork designs, such as Wembley Stadium, have been made easier thanks to 3D modelling packages.*



*Above: Trimble Total Station displaying the drawing and survey control points.*

### Conclusions

Any streamlining of existing practises and processes will help minimise costs, which is essential for every company and for every project in the currently economic climate. Making better use of the rich data in the structural model is certainly one way of ensuring that this will happen. The building information model can empower and improve many of the processes currently executed, minimising replication of data input and providing accurate information to help manage projects more effectively and therefore help reduce risk and costs.

*Below: The use of 3D models, on projects such as More London plot 7, was critical for the completion of offsite cutting of metal decking.*





# Flat pack modular construction



*An IKEA furniture store and car park in Dublin contains long spans with heavy floor planks requiring the structure to be erected in box-like modules to allow the lifting process to succeed.*

*Above: Various store functions required two different steel grid patterns.*

Swedish furniture giant IKEA is entering the Irish market with the construction of its first store in the Republic at Ballymun, County Dublin.

The steel framed store, which is due to open later this year, will have more than 1,500 car parking spaces and carry almost 10,000 products showcased in over 50 fully furnished room layouts. In house features will also include a number of ancillary facilities such as a 500 seat restaurant, a bistro, a cafe and a Swedish food hall.

Atlas Ward Structures fabricated and erected 2,700t of structural steelwork for the building which has an overall floorspace of more than 53,000m<sup>2</sup>.

Its scope of works also included the provision and installation of floor planks, staircases, precast walls, floor decking and intumescent fire protection.

Overall, the structure comprises a ground floor undercroft car park with two floors above forming the main store. At ground level (car park) the steelwork is based around a 16m x 8m grid pattern.

At first floor level, the building divides into a warehouse and storage area, which is two levels high and covers approximately 40% of the footprint, while the remainder of the building features a two level retail zone with a market hall on the first floor and a showroom zone on the second floor.

***"Because of the different store functions the grid patterns alter at first floor level."***

**Hot Finished  
& Cold Formed  
Structural  
Hollow  
Sections**

**GRADE S355J2H**

**Hot**

**RAINHAM STEEL**



**FACT FILE****IKEA Dublin****Main client:**

IKEA Ireland

**Main contractor:**

RG Group

**Architect:** OMS (Dublin)**Structural engineer:**Blyth & Blyth Consulting  
Engineers**Steelwork contractor:**

Atlas Ward Structures

**Steel tonnage:** 2,700t

*Above: A modular construction method was used because of the structure's large footprint.*

"Because of the different store functions the grid patterns alter at first floor level," explains David Fiddes, Project Engineer for Blyth & Blyth. "For the warehouse it was important to have a large two-storey high open plan area and so the grid is a larger 16m x 24m pattern."

The adjacent first floor market hall in contrast stays on a 16m x 8m grid. However, on the second floor, this changes, for the showroom area, to the larger 16m x 24m grid.

"So at roof level there are a series of trusses, some spanning 24m and others spanning 16m," adds Mr Fiddes.

Because of the long spans and the high loadings which will be imposed on the frame, especially on the warehouse zone's floor, large 914 x 419 x 388 beam sections were specified. These beams each

weighed approximately 6t and carry planks which are 8m long and 400mm deep for the warehouse and 200mm deep elsewhere. In order to achieve an efficient and cost effective design all the beams were designed to act compositely with the precast floor units.

"Because we were responsible for installing the planks along with the steelwork, we had to erect the structure in complete boxes, with each section from floor to roof, including the purlins finished before we moved onto the next zone," explains Bill Armstrong, Atlas Ward's Project Manager. "This was the only way we could have got the heavy planks and beams into place with mobile cranes. The building is just too big to lift sections into place from the perimeter to the middle without using extremely large cranes."



**Head Office:** 01708 522311 **Fax:** 01708 559024 **Bolton Office:** 01204 847089 **Fax:** 01204 848248  
**e-mail:** [sales@rainhamsteel.co.uk](mailto:sales@rainhamsteel.co.uk) **www:** [www.rainhamsteel.co.uk](http://www.rainhamsteel.co.uk)



# Seaside college connection

*Above: Steelwork starts at podium level, above a large underground car park.*

*Strong coastal winds and an innovative flooring system all contributed to the need for bespoke steelwork connections at a college project in Hastings.*

*Below: Bracing is located in steel cores.*

The educational sector has been buoyant of late, with new schools, university buildings and colleges all being built across the UK. One of the largest on-going projects in the south of England is the work being undertaken at Hastings, which will provide two new state-of-the-art college buildings for the Sussex Coast College.

The major part of this project is situated adjacent to the town's railway station and known as Station Plaza. Here main contractor Laing O'Rourke is constructing a six-storey steel framed college building which will provide 20,000m<sup>2</sup> of new learning space.

Overall, the Station Plaza scheme also incorporates four other buildings - three residential blocks containing 103 apartments and a primary care centre - all of which sit on one large concrete podium containing a 324 space underground car park.

Formerly the site was occupied by the railway station's old car park and prior to steelwork erection beginning in March 2008 a large earthmoving operation was required to excavate the underground car park and podium.

The steel framed college building occupies approximately just over half of the podium's footprint and steel is mostly based around a 7m x 8m grid pattern. The structure's entrance area is predominantly a curved facade, constructed with deep curved steel box sections, while the other three elevations are straight. The entire building wraps around an inner atrium which is glazed at roof level.

"We've had to sequence the steelwork with the concrete," explains Paul Westbrook, Erections Manager for steelwork contractor Graham Wood Structural. "We have four elevations and each one was a phase. We erected one phase up to third level

and then moved onto the next, while the concreting team worked on the previous phase."

Graham Wood Structural completed four phases and then returned to phase one to erect steelwork from third floor up to roof level. This allowed the sequence to start over again with the concreting team again following on behind.

The reasoning behind this sequencing was the installation of the project's 8m long concrete planks. "They are too long to be lifted through six floors of steelwork," says Mr Westbrook.

The concrete planks in question are Tarmac's TermoDeck and they had an important bearing on the steelwork design. TermoDeck planks are a fan assisted heating, cooling and ventilating system. They use the high thermal mass of structural, hollowcore slabs to warm or cool fresh air before it is distributed into room spaces of the building.

Controlled by the building's management system, a supply of air passes through holes in the slab very slowly, giving plenty of time for passive heat exchange between the air and the slabs. To accommodate these innovative and high efficiency planks, shallow but heavy beams were required.

"We had to keep the floor void slim while the concrete planks sat at the same level as the steel beams, instead of on top of them as would normally be the case," says Steve Forder, Project Engineer for Gifford. "Structurally we had to form a flat soffit so the planks could be dropped into place."

The building's services will actually run along the top of the planks within the structural void. To allow this the design specified shallow, but heavier sections than normal. Gifford provided all the relevant loadings for these beams to Graham Wood and this then allowed them to design bespoke connections.

"As well as the connections we also designed



the beams to have a plate welded to the bottom flange which the planks then sit on," explains Chris Barnfather, Graham Wood's Chief Engineer. "The majority of floor beams also had pre-drilled holes for the plank's rebars."

Hastings is a coastal town and constructing close to the sea brings with it a whole set of unique challenges, not least the wind. The new college building is not only a stone's throw from the seafront, but also in a valley which exposes the structure to winds from two directions.

"Wind loadings played a critical role in the steel design of the building," says Mr Forder. "Because of the site's exposed location there are potentially some big uplifts on the trusses which span the atrium."

***"Wind loadings played a critical role in the steel design of the building"***

There are four trusses spanning the structure's central atrium; because the building and atrium are slightly tapered, the longest truss is 21m while

the shortest at the opposite end is 16m long.

Each roof truss weighs 2.5t and is 2m deep. "They were all brought to site in one piece and lifted into position by tower crane," explains Mr Westbrook.

To negate any uplift the long span trusses have some deep tie connections. The building was also designed with high torsional loads, particularly around the perimeter, and this also required deep tie connections.

Stability for the structure is provided by braced bays, which are located within stairwell and lift shafts. The design team were faced with the



problem of limited locations for putting the bracing, and as the majority of the elevations have windows at regular spacings, the ideal place was within the steel cores.

Summing up the project, Sue Middlehurst, Principal of Hastings College, adds: "With academic and vocational facilities for 2,500 students, our new college buildings will help transform further education in the area. This iconic and inspirational building will also help to mark us out as a leading provider of post-16 education."

The college is expected to open by the end of 2009.

*Above: The college will transform the area around Hastings Railway Station.*

*Below: Shallow heavy beams were required to facilitate the installation of the long TermoDeck planks.*

**FACT FILE**

**Sussex Coast**

**College, Hastings**

**Main client:** John Laing

**Architect:** SMC Charter Architects

**Main contractor:**

Laing O'Rourke

**Structural engineer:**

Gifford

**Steelwork contractor:**

Graham Wood

Structural

**Steel tonnage:** 1,730t

**Project value:** £75M





# Choice of lateral-torsional buckling curves – according to Eurocode 3 and the UK National Annex

*Alastair Hughes of the SCI explains some of the subtleties of the interaction between the UK National Annex and the Eurocode itself.*

## Introduction

Lateral-torsional buckling (LTB) is the instability phenomenon which is liable to limit the bending resistance of a beam whose compression flange is unrestrained, intermittently restrained or flexibly restrained. What distinguishes it from regular strut buckling is that the tension flange, which naturally tends to remain straight, exerts some control over the wayward compression flange to which it is attached. If the compression flange is to buckle laterally, and the tension flange is not, the beam is forced to twist – hence the description ‘lateral-torsional’. All conventional sections and even some exceptionally slim and slender RHS are prone to LTB.

Eurocode 3, like BS5950, provides the designer with buckling curves from which a ‘buckling resistance moment’ can be derived. In Eurocode terms this is  $M_{b,Rd}$  – b for buckling, R for resistance, d for design. Needless to say it is a major axis moment  $M_y$ .  $M_{b,Rd}$  is the product of what the section’s bending resistance would otherwise be, eg.  $W_{pl,y} f_y$  for a class 1 or 2 section, and  $\chi_{LT}$ , a reduction factor for LTB, which is the ordinate of the buckling curve. As with struts, the buckling curves plot (or, in BS 5950, tabulate) strength reduction against slenderness, but an important difference from BS 5950 is that the slenderness in Eurocode buckling curves is ‘non-dimensional’. This is tautology, since all slendernesses are non-dimensional, but it is the term that Eurocode 3 has chosen. Eurocode 4 chose ‘relative slenderness’ and other authors have variously chosen ‘reduced’ or ‘generalized’ slenderness. What it actually means, in the LTB context, is given by the expression:

$$\text{Non-dimensional slenderness (NDS)} \quad \bar{\lambda}_{LT} = \sqrt{\frac{W_y f_y}{M_{cr}}}$$

where  $W_y f_y$  is, again, what the bending resistance would otherwise be, depending on the class of the section, and  $M_{cr}$  is what the buckling resistance would theoretically be if strength were limitless (but  $E$ -value same as steel). The Code itself is silent on the calculation of  $M_{cr}$ , regarding it as a matter for textbooks or NCCI (non-conflicting complementary information). Plenty of the latter is available and the subject has been covered in previous issues of NSC.

The advantage of the non-dimensional presentation is that separate curves are not needed

for S275 and S355, nor for the stepwise reductions in yield strength at element thicknesses of (in UK) 16 and 40mm.

This article is concerned with the choice of curve for LTB once the NDS has been established.

## What buckling curves allow for

Just as with struts, beams failing by LTB deform until the weak-direction moment acting on the flange, magnified by eccentricity, exceeds available resistance. There is interaction between stiffness and strength, because as soon as the extreme fibre yields the bending stiffness of the flange is eroded. This will depend on the residual stresses which result from cooling of the section after rolling or welding. Geometrical imperfections such as initial out-of-straightness also have an effect, and theoreticians have traditionally found it convenient to formulate buckling curves as if nothing else mattered, using a single ‘equivalent’ geometrical imperfection. Eurocode 3 ‘imperfection factors’ of Table 6.3, each associated with a curve of the set (labelled **a** to **d** in order of severity) represent a continuation of this tradition. For practical purposes, however, the means by which the curves were generated is almost irrelevant; they might as well be regarded as empirical because the assignment of different curves to different sections is made by reference to test results. It is found that deeper-proportioned sections need to be treated more severely than shallow ones and the effects of residual stresses are more severe in welded sections than in rolled ones.

These differences are most pronounced over the middle part of the slenderness spectrum, the one occupied by most practical beams. At very high slenderness, where there is little influence of material strength, the curves tend to converge with each other (and with elastic theory). At very low slenderness, LTB tests indicate that a ‘plateau’ of  $\chi_{LT} = 1$  extends as far as NDS = 0.4 or thereabouts. One of the differences between LTB and regular strut buckling is that for the latter the corresponding plateau only extends half as far.

## A choice of two sets of buckling curves for LTB

Eurocode 3 offers the designer a choice, for I-sections at least, between two sets of curves. These are presented in clauses 6.3.2.2 and 6.3.2.3



respectively. Sharp-eyed readers will observe that the 6.3.2.2 set is identical to the strut curves of 6.3.1, save for the plateau extension granted in 6.3.2.2(4) which, incidentally, results in a cliff edge discontinuity at  $NDS = 0.4$ .

The alternative, and generally more productive, set of curves is on offer in 6.3.2.3 for rolled I-sections and equivalent welded I-sections. I-sections obviously includes H-sections, and the word 'equivalent' is interpreted to mean 'of similar dimensions', i.e. up to about 1 metre in height. But that interpretation hardly matters to UK designers, since the UK National Annex takes advantage of an opportunity to exercise national choice. It does so by resetting the parameters in the buckling curve formulation with the effect that for welded sections the curves of 6.3.2.3 now match those of 6.3.2.2 exactly, and they are denied the plateau extension (in either case). For a welded section, the only remaining advantage to 6.3.2.3 is the availability of a favourable modification factor in 6.3.2.3(2), discussed later.

More positively, the UK NA extends the scope of 6.3.2.3 beyond I-sections to include angles (for moments in the 'major principal plane'), all other hot-rolled sections and cold-formed hollow sections. So while choice is (virtually) taken away for welded sections, it is extended to other sections that are rolled.

Figure 1 compares all the buckling curves from clauses 6.3.2.2 and 6.3.2.3. These are the curves available to rolled sections in the UK.

Two traps for the unwary:

- The only thing the two curves named 'c' have in common is the 'imperfection factor' used to derive them. Curve **c** of 6.3.2.3 lies well above its 6.3.2.2 namesake (and even exceeds curve **a** of 6.3.2.2 over parts of the slenderness range). It is a similar story for curves **b** and **d**. Curve **a** is not used in 6.3.2.3.
- This apparent advantage of choosing 6.3.2.3 is reduced, though mostly not eliminated, by the differences between Tables 6.4 and 6.5 which assign curves to sections. For example, for a UKC section the choice is between curve **a** of 6.3.2.2 and curve **b** of 6.3.2.3, as shown in Figure 2, and it will remain advantageous to opt for the latter. Similarly for most UKB sections curve **c** of 6.3.2.3 will be preferable to curve **b** of 6.3.2.2, as shown in Figure 3, but beware that the UK NA, with its replacement for Table 6.5, has penalized what we might describe as 'slimline' sections with  $h/b > 3.1$  (which includes several of the recent additions to the UKB range) by assigning them to curve **d** of 6.3.2.3. Depending on slenderness, it may be advantageous to choose curve **b** of 6.3.2.2 for these, as shown in Figure 4 (over page).

Another consequence of the UK NA's intervention to replace Table 6.5 is that distinctions are made between monosymmetric and doubly symmetric sections.

Monosymmetric rolled sections, such as Corus ASB, are allowed to use 6.3.2.3, but they too are relegated to curve **d**. However Table 6.4,




Figure 1. All seven LTB curves from EC3




Figure 2 Choice of curve for UKC ( $h/b \leq 2$ )




Figure 3 Choice of curve for most (but not all) UKB ( $2 < h/b \leq 3.1$ )

unaltered by the NA, assigns a rolled I-section with  $h/b \leq 2$  to curve **a** of 6.3.2.2 which is likely to be advantageous, as shown in Figure 5 (over page). A welded lookalike, excluded from 6.3.2.3, would be assigned to curve **c** of 6.3.2.2.

#### Welded sections

As already noted, welded beams are relatively harshly treated by the UK NA, so it may become commercially important to consider whether sections such as SFB and Cellbeams could




Figure 4 Choice for 'slimline' ( $h/b > 3.1$ ) UKB 1016x305, 610x178, 533x165




Figure 5 Choice of curve for ASB




Figure 6 Curves for welded sections (UK)

receive honorary 'rolled' status for LTB purposes. Although these are fabricated by welding, it may be argued that the welds are distant enough from the compression flange not to impact the LTB resistance. For these and other out-of-the-ordinary sections, there may be potential for curve assignments to be upgraded if tests are undertaken to overcome the present paucity of data.

The curves for welded sections are shown in Figure 6. There is no choice; the higher curve **c** is

for  $h/b \leq 2$  and the lower curve **d** is for typical beam proportions. The UK NA's upper limit (of 3.1) to  $h/b$  for the use of curve **d** of 6.3.2.3 does not apply to 6.3.2.2, so its effect is a subtle one: purely to deny a slimline welded beam the use of the modification factor.

## A word about the modification factor of 6.3.2.3(2)

This modification factor is to allow for the favourable effect of nonuniform moment, and is influenced by NDS. It can only increase  $\chi_{LT}$ , so it could safely be ignored. Its favourable effect may not be all that great – a few % at most for a simply supported beam with UDL – but in other situations it can be more significant. Designers should not be perturbed by the fact that nonuniformity of moment may already have been taken into account in the assessment of  $M_{cr}$  – this second correction is perfectly in order (as will be a third, if an evaluation of the  $k$ -factors of expressions 6.61/62 is to follow). It may also be helpful to be reassured that what the UK NA has to say about the modification factor (in NA 2.18) is not in any way conflicting with what is in the Code, merely offering a more general formulation.

The effect of this modification factor could tip the balance in favour of 6.3.2.3 over 6.3.2.2 in a marginal case, because (whether by accident or design) it is not available to the latter.

## Conclusion

While 6.3.2.3's buckling curves (which are specifically for LTB) will normally be more productive than those of 6.3.2.2 (which are, essentially, the strut curves and regarded as a safe lower bound) there are circumstances in which either the Code or the UK NA rules them out. There are also sections whose curve assignments by the Code and/or the NA have the effect that the reverse will, or (depending on slenderness) may, be true. If comparison is necessary to decide which is advantageous, it is not enough simply to look at the buckling curves, because of 6.3.2.3's  $\chi_{LT}$ -enhancing modification factor.

## Footnote

The Code's formulae for the lateral buckling curves are to be found in expressions 6.56 (for 6.3.2.2) and 6.57 (for 6.3.2.3), using imperfection factors from Table 6.3 in both cases. The UK NA endorses these recommended values, and the curve assignments of Table 6.4 for use with 6.3.2.2. However it exercises national choice in two ways where 6.3.2.3 is concerned. For welded sections only, it resets the parameters of expression 6.57 so as to make the curves identical to those of 6.3.2.2 (and the strut curves). One of these parameters is the plateau length. Because 6.3.2.2(4) obtains this from 6.3.2.3, the effect is to deny welded beams the plateau extension irrespective of clause allegiance. The second major intervention of the UK NA is its Table 6.5 substitute whose effects, on both rolled and welded sections, are described above.



40 Years Ago in

## BUILDING WITH STEEL

### Unusual television studio



The building illustrated is clad with 85 tons of sheet lead – chosen for its sound insulating qualities – colour a soft grey. The cantilever doubly curved roof is a steel space truss: three arches in high tensile steel span the building between two concrete piers. The arches have tapered wide flange cross sections which have a maximum depth of 27 in. at the apexes. The steel space truss resists the roof deadload of a 4 in. thick lightweight concrete slab: this is cast on steel mesh and finishes flush with the top surface. Under live load the concrete roof and supporting space trusses act compositely.

Steel tubes – maximum diameter 8 in. – for extra heavy cross sections form the longitudinal, diagonal and edge members of the cantilever spans. Gusset plates at the connections of the tube resist shear stresses between truss and concrete deck, so ensuring composite action.

The building is in Marina City, Chicago, and was designed by Bernard Goldberg Associates, architect-engineers of that city. The unusual roof was designed by Hannskari Bandel, Severud Associates, New York.



Estimating - Sales - Tenders  
- Contracts - CAD Integration  
- Revisions - Documents  
Stock Control - Suppliers  
Materials - Purchasing - Budgets  
- Nesting - Production  
Planning - Model Tracking  
Timesheets - Bar Coding - Reports  
Shipping - Quantity Surveying  
- .NET Technology

## Building bridges between departments, suppliers and clients

StruM.I.S .NET Software leads the way in the steel industry for  
its integrated best practice workflow.

- |                       |                         |
|-----------------------|-------------------------|
| Less repetition ■     | 100% traceability ■     |
| Eliminate errors ■    | Improved efficiency ■   |
| Lead time reduction ■ | Greater profitability ■ |

## StruM.I.S.NET

The Ultimate Management Information System  
For steelwork Fabricators

t: 01332 545 800

e: [sales@acecadsoftware.com](mailto:sales@acecadsoftware.com)

w: [www.acecadsoftware.com](http://www.acecadsoftware.com)

**AceCad**  
SOFTWARE



### New and Revised Codes & Standards

(from BSI Updates October and November 2008)

#### BRITISH STANDARDS

##### NA to BS EN 1994:-

UK National Annex to Eurocode 4.  
Design of composite steel and concrete structures

##### NA to BS EN 1994-1-1:2004

General rules and rules for buildings  
*No current standard is superseded*

##### NA to BS EN 1994-1-2:2005

General rules. Structural fire design  
*No current standard is superseded*

##### NA to BS EN 1998:-

UK National Annex to Eurocode 8.  
Design of structures for earthquake resistance

##### NA to BS EN 1998-1:2004

General rules, seismic actions and rules for buildings  
*No current standard is*

*superseded*

##### NA to BS EN 1998-4:2006

Silos, tanks and pipelines  
*No current standard is superseded*

##### NA to BS EN 1998-5:2004

Foundations, retaining structures and geotechnical aspects  
*No current standard is superseded*

##### NA to BS EN 1998-6:2005

Towers, masts and chimneys  
*No current standard is superseded*

#### BRITISH STANDARDS REVIEWED AND CONFIRMED

##### BS 5080:-

Structural fixings in concrete and masonry

##### BS 5080-1:1993

Method of test for tensile loading

##### BS 5080-2:1986

Method for determination of resistance to loading in shear

##### BS 5950:-

Structural use of steelwork in building

##### BS 5950-8:2003

Code of practice for fire resistant design

##### BS 8100:-

Lattice towers and masts

##### BS 8100-2:1986

Guide to the background and use of Part 1 'Code of practice for loading'

##### BS 8100-3:1999

Code of practice for strength assessment of members of lattice towers and masts

##### BS 8100-4:1995

Code of practice for loading of guyed masts

#### DRAFT BRITISH

#### STANDARDS FOR PUBLIC COMMENT

##### 08/30167121 DC

**BS EN ISO 14174** Welding consumables. Fluxes for submerged arc welding and electroslag welding. Classification

##### 08/30167126 DC

**BS EN ISO 14171** Welding consumables. Solid wire electrodes, tubular cored electrodes and electrode/flux combinations for submerged arc welding of non alloy and fine grain steels. Classification

##### 08/30177295 DC

**BS ISO 14341** Welding consumables. Wire electrodes and deposits for gas shielded metal arc welding of non alloy and fine grain steels. Classification

## SPECIALIST CONSULTANCY FROM THE SCI



FLOOR VIBRATIONS



ACOUSTIC PERFORMANCE



THERMAL PERFORMANCE



PRODUCT DEVELOPMENT



ADVANCED ANALYSIS



FIRE ENGINEERING



BESPOKE SOFTWARE

T: +44 (0)1344 636525


E: [specialist@steel-sci.com](mailto:specialist@steel-sci.com)

<http://consultancy.steel-sci.org>



# Seven good reasons to specify USFB.

How low can you get?



Any depth you require,  
however shallow

Some things are easier to tie  
than others.



Regular web openings for  
the placing of tie bars

Don't accept it has to be flat.



Pre-cambers at no cost

Rapid turnaround.



Made from ex-stock steel -  
delivery within days if required

Our range of sizes goes on,  
and on, and on..



Vast range of sections to cater  
for any loading conditions

Size inequality can work so well.



Any degree of asymmetry

Enjoy the wide open spaces.



Elongated openings  
for services

## USFB™ - the shallowest form of construction + the speed, cost & flexibility of Steel.

I am interested in the following services from Westok:

(please tick all that apply)

☐ FREE Design Service ☐ Project Design Meeting with a Westok Advisory Engineer ☐ USFB Design Guide (please state no. of copies required) ☐ Technical Seminars: 'Cellular Beams & USFBs - Applications & Design'

Name

Company

Address

Postcode

Tel  Fax

Email

**FAX BACK TO WESTOK ON: 01924 280030**

ASD Westok. Part of the ASD metal services group.



ASD Westok Limited  
Charles Roberts Office Park  
Charles Street  
Horbury Junction, Wakefield  
West Yorkshire WF4 5FH  
Tel: 01924 264121 Fax: 01924 280030  
Email: design@westok.co.uk

**www.westok.co.uk**

## AD 329

### Dealing with connection design in a 3D frame analysis

For a structure modelled in a 3D frame analysis, the ends of every beam element have six degrees of freedom and hence there are six possible forces or moments that can be transferred through each connection. The default assumption of a normal 3D general frame analysis package (as opposed to a design model package used for whole building design) is that all degrees of freedom are constrained; then each connection transfers two shear forces (forces orthogonal to the member axis), two bending moments, a torsional moment (about the member axis), and an axial force. However, in many practical cases of building frames, the magnitudes of some of these forces and moments are very modest and can be neglected. Where this is the case, some of the constraints can be omitted and the following offers advice on modelling the connections in a 3D general frame analysis.

- i) Ensure that the end restraints to beam elements reflect the behaviour of the connections. For example, a normal moment connection between a beam and a column flange has significant moment capacity and stiffness for bending in the plane of the beam and column but is weak out of plane. The model should reflect that

behaviour and hence the ends of the beam element should be restrained about its major axis direction and pinned about its minor axis direction.

- ii) If the presence of 'pinned connections' about the beam minor axis at the ends of beam elements causes instabilities in the global analysis model, provide end restraints and then consider whether the out of plane moments are small enough to be ignored. 'Small' is a question of judgment, based on the magnitude of the forces and the scale of the connection.
- iii) Provide torsional restraints at both ends of a beam member, to avoid instability in the analysis model. Unless there are torsional loads on a beam, the resulting torsional moments will normally be sufficiently small that they can be ignored.
- iv) In all cases, the design assumptions must be compatible with the physical details – and the practical connection details should be carefully considered before making assumptions in the design model.

If the frame analysis gives significant out of plane bending and torsional moments in a 3D analysis model the reasons should be carefully examined – it may be that an unstable part of the structure is being supported by twisting of a member and torsion on a connection, when the more appropriate approach would be to re-configure the structure.

Note that published connection design models only deal with major axis bending, shear and axial force. Configurations that give rise to significant minor axis effects or torsional effects will require more detailed design of the connections.

Further guidance is given in SCI publication P148 (*Modelling of steel structures for computer analysis*, 1995) and chapter 3 (Connection design programmes) of BCSA publication No 41/05 (*Steel details*).

Original text provided by  
Alan Rathbone of CSC (UK) Ltd

Contact: Abdul Malik  
Tel: 01344 636525  
Email: [advisory@steel-sci.com](mailto:advisory@steel-sci.com)


# 2009 STEEL CONSTRUCTION DIARY

The 2009 Steel Construction desk diary is available from BCSA price £10.00 per copy inclusive of postage and packing.

The diary represents excellent value, containing the main part of the National Structural Steelwork Specification (5th edition) and key extracts from the Handbook of Structural Steelwork.

Cheques should be made payable to BCSA or payment can be made by credit card.

Contact: Publications on 020 7839 8566





## AD 330

### Vibration of steel staircases

The Advisory Desk has received a number of queries asking for guidance on vibration of steel staircases. In fact, guidance is already given in several parts of SCI publication *Design of floors for vibration: A new approach (P354)*. This AD collects that guidance and adds references to other sources of information that may be relevant when analysing the vibration behaviour of steel staircases. This AD also identifies some other design considerations that may be relevant.

#### General approach

Steel staircases are, by their nature, highly susceptible to vibration as they combine low levels of damping (typically  $\zeta \approx 0.5\%$ ), low mass and high levels of human-induced excitation. The general approach outlined in Chapter 6 of SCI P354 can be used to determine the dynamic behaviour of the staircase, but clearly the applied forces will be different for people travelling up and down staircases than for walking across floors, and acceptable levels of vibration also differ.

#### Applied Loads

In P354, the response is determined from the modal properties of the staircase (frequencies, modal masses and mode shapes) and the frequency and amplitude of the applied vertical load. The peak amplitude of the load in each mode is generally given in terms of Fourier coefficients,  $\alpha_n$ , which represent the proportion of a person's weight that is acting at each harmonic of the activity frequency. These Fourier coefficients are given in *Human induced loading of flexible staircases* (Bishop, Willford & Pumphrey, 1995 and Kerr & Bishop, 2001), and depend on the speed of ascent or descent. ISO 10137: 2007 (*Bases for design of structures – Serviceability of buildings and walkways against vibrations*) reproduces the worst case of these in Table A.4, and these are also given in Table 3.2 of P354:

Activity	Harmonic number, $n$	Common range of forcing frequency, $nf$ (Hz)	Fourier coefficient for vertical direction, $\alpha_{nv}$
Ascending or descending stairs	1	1.2 to 4.5	1.1
	2	2.4 to 9.0	0.22

In P354 floors are categorised as either low-frequency or high-frequency, the latter case responding to impulsive excitations rather than responding resonantly. No specific analysis is given by Bishop et al for the impulsive loads that will be experienced by staircases with natural frequencies that exceed the upper limits of the Fourier terms given in ISO 10137. Further Fourier coefficients (up to the 6th harmonic) are presented in the paper; these could be used to determine a more comprehensive response.

#### Acceptability criteria

Bishop et al. also give guidance on the acceptability criteria for staircases, and their research indicates that for multi-person excitation, a maximum multiplying factor of 64 applies. Typically this is achieved by designing staircases for a limiting multiplying factor of 32 for light use (such as offices) or 24 for heavy use (such as public buildings and stadia) under single person excitation using the Fourier terms given above. The limits for staircases are higher than for floors because the frequency of exposure to staircase vibration is generally significantly lower than for a floor, and the audio and visual stimuli that accompany the movement reduce the associated level of annoyance. For narrow staircases with no landings, it is unlikely that there will be stationary people on the stairs to receive the vibration, and as vibration is, in the main, a serviceability issue, in these cases the level or response is less critical.

#### Other design considerations

An additional design consideration for staircases is to ensure that the interaction between a staircase and the floors it links is such that excessive vibration does not carry onto the floor plate and therefore affect nearby rooms. This can generally be achieved by attaching the staircase in the vicinity of columns, and by avoiding features such as cantilever beams which are highly susceptible to vibration issues.

Contact: Andy Smith

Tel: 01344 636530

Email: a.smith@steel-sci.com

www.rlsd.com



## Trust is everything

- 60+ years' experience supplying structural flooring products
- A reputation for industry 'firsts'
- Proven on some of the world's most prestigious projects

Capability. Innovation. Knowledge. It's strengths like these that make Richard Lees Steel Decking such a powerful choice. And enable us to create such a positive, dependable difference to your structural flooring projects. For more products, more experience and more reassurance, talk to Richard Lees Steel Decking. It's everything you need.



#### Richard Lees Steel Decking Ltd

Moor Farm Road West, The Airfield, Ashbourne, Derbyshire DE6 1HD, UK.

Tel: +44 (0) 1335 300 999 | Fax: +44 (0) 1335 300 888

Email: rlsd.decks@skanska.co.uk



# The British Construction Steelwork Association Ltd

You can find email and website addresses for all these companies at [www.steelconstruction.org](http://www.steelconstruction.org)

BCSA is the national organisation for the steel construction industry. Details of BCSA membership and services can be obtained from **Gillian Mitchell MBE**, Deputy Directory General, BCSA, 4 Whitehall Court, London SW1A 2ES  
Tel: 020 7839 8566 Email: [gillian.mitchell@steelconstruction.org](mailto:gillian.mitchell@steelconstruction.org)

## KEY

### Categories

- A** All forms of building steelwork
- B\*** Bridge work
- C** Heavy industrial plant structures
- D** High rise buildings
- E** Large span portals
- F** Medium/small span portals and medium rise buildings
- H** Large span trusswork
- J** Major tubular steelwork
- K** Towers
- L** Architectural metalwork
- M** Frames for machinery, supports for conveyors, ladders and catwalks
- N** Grandstands and stadia
- S** Small fabrications

### Quality Assurance Certification

- Q1** Steel Construction Certification Scheme Ltd
- Q2** BSI
- Q3** Lloyd's
- Q4** Other

### Classification Contract Value

- 10** Up to £40,000
- 9** Up to £100,000
- 8** Up to £200,000
- 7** Up to £400,000
- 6** Up to £800,000
- 5** Up to £1,400,000
- 4** Up to £2,000,000
- 3** Up to £3,000,000
- 2** Up to £4,000,000
- 1** Up to £6,000,000
- 0** Above £6,000,000

### Notes

- 1** Applicants may be registered in one or more categories to undertake the fabrication and the responsibility for any design and erection of the above.
  - 2** Where an asterisk (\*) appears against any company's classification number, this indicates that the assets required for this classification are those of the parent company.
- \* For details of bridgework subcategories contact Gillian Mitchell at the BCSA.

### ACLS STRUCTURES LTD (F H M 3)

Holland Way Ind. Est., Blandford, Dorset DT11 7TA  
Tel 01258 45051 Fax 01258 45056

### ASA STEEL STRUCTURES LTD (F H L M S 6\*)

Brick Kiln Lane, Parkhouse Ind. Est. West, Newcastle-under-Lyme, Staffs ST5 7EF  
Tel 01782 56636 Fax 01782 56475

### ASME ENGINEERING LTD (F L M S 10 Q4)

Asme House, 788 Kenton Lane, Harrow, Middlesex HA3 6AG  
Tel 0208 954 0028 Fax 0208 954 0036

### AWF STEEL LTD (F L S 9)

21 Lenziemill Rd, Lenziemill, Cumbernauld G67 2RL  
Tel 01236 457960 Fax 01236 452250

### ADEY STEEL LTD (F H J L M 3)

Falcon Industrial Park, Meadow Lane, Loughborough, Leics LE11 1HL  
Tel 01509 566677 Fax 01509 828639

### ADSTONE CONSTRUCTION LTD (E F 2)

Adstone House, Wassage Way, Hampton Lovett Industrial Estate, Droitwich WR9 9NX  
Tel 01905 794561 Fax 01905 794040

### ADVANCED FABRICATIONS POYLE LTD (F J H J K L M 7 Q4)

772-775 Buckingham Avenue, Slough, Berkshire SL1 4NL  
Tel 01753 531116 Fax 01753 531120

### ALLERTON ENGINEERING LTD (B S\* Q3)

Allerton House, Thurston Road, Northallerton, N. Yorkshire DL6 2NA  
Tel 01609 774471 Fax 01609 780364

### ALLSLADE PLC (F H L 2)

Limberline Works, Limberline Road, Hilsae, Portsmouth PO3 5JF  
Tel 023 9266 7531 Fax 023 9267 9818

### ANDREW MANNION STRUCTURAL ENGINEERS LTD (D E F H J M N 1 Q4)

Clara Road, Moate, Co Westmeath, Republic of Ireland  
Tel 00 353 90 648 1184 Fax 00 353 90 648 1735

### THE ANGLE RING CO LTD

Blomfield Road, Tipton DY4 9EH  
Tel 0121-557 7241 Fax 0121-522 4555

### APEX STEEL STRUCTURES LTD (F H L M 6)

Kings Close, Charlfeats Industrial Estate, Canvey Island, Essex SS8 0DZ  
Tel 01268 660 828 Fax 01268 660 829

### ARROMAX STRUCTURES LTD (C D E F H J K L M 6)

Llangwyl Junction, Mansfield, Notts NG20 9RN  
Tel 01623 747466 Fax 01623 748197

### ATLAS WARD STRUCTURES LTD (A O Q1)

Sherburn, Malton, N. Yorkshire YO17 8PZ  
Tel 01944 710421 Fax 01944 710512

### ATLASCO CONSTRUCTIONAL ENGINEERS LTD (E F H 4)

Rothwell Industrial Estate, Apedale, Chesterton, Newcastle-U-Lyme ST5 6BD  
Tel 01782 564711 Fax 01782 564591

### B D STRUCTURES LTD (F H M 5)

Westthorpe Ind Est, James St, Westthorpe, Lincs, BL5 3JR  
Tel 01942 817770 Fax 01942 810438

### BHC LTD (C D E F H 0)

Edinburgh Road, Carnwath, Lanarkshire ML11 8LG  
Tel 01555 840006 Fax 01555 840036

### BSB STRUCTURAL LTD (E F 6)

Whitcross Industrial Park, Whitecross, Nr Lintilhough, West Lothian EH49 6LH  
Tel 01506 840937 Fax 01506 840932

### A. C. BACON ENGINEERING LTD (E F H 5)

Norwich Rd, Hingham, Norwich NR9 4LS  
Tel 01953 850611 Fax 01953 851445

### BALLYKINE STRUCTURAL ENGINEERS LTD (E F H J N 4 Q2)

51 Lisburn Rd, Ballynahinch, Co Down BT24 8TT  
Tel 028 9756 2560 Fax 028 9756 2751

### BARRETT STEEL BUILDINGS LTD (E F H 1 Q1)

Barrett Court, Cutler Heights Lane, Dudley Hill, Bradford BD4 9HZ  
Tel 01274 266800 Fax 01274 266860

### BARRETT'S OF ASPLEY LTD (F L M 3)

North Common Farm, Woburn Road, Lidington, Bedfordshire MK43 0NN  
Tel 01525 280136 Fax 01525 280137

### BILLINGTON STRUCTURES LTD (A O Q1)

Barnsley Road, Wombwell S73 8DS  
Tel 01226 340666 Fax 01226 755947

### BONE STEEL LTD (D E F H L N 1\*)

P.O. Box 9300, Wishaw, Lanarkshire ML2 0YA  
Tel 01698 375000 Fax 01698 372727

### F J BOOTH & PARTNERS LTD (E F H M S 2 Q2)

Dockside Road, Middlesbrough, Cleveland TS3 8AT  
Tel 01642 241581 Fax 01642 223398

### BORDER STEELWORK STRUCTURES LTD (C E F H 4)

Winchester House, 58 Warwick Rd, Carlisle CA1 1DR  
Tel 01228 548744 Fax 01228 511073

### BOURNE CONSTRUCTION ENGINEERING LTD (A O Q2)

St Clements House, St Clements Rd, Poole, Dorset BH12 4GP  
Tel 01202 746666 Fax 01202 732002

### W.S. BRITLAND & CO. LTD (Q2)

Timanstone Works, Pike Road, Eynhorpe, Dover CT15 4NB  
Tel 01304 831583 Fax 01304 831983

### BRITON FABRICATORS LTD (B 4 Q4)

Warrall Road, Hucknall, Notts NG15 6EP  
Tel 0115 963 2901 Fax 0115 968 0335

### BROWNE STRUCTURES LTD (F J S 7)

Queens Drive, Newhall, Swadincote, Derbyshire DE11 0EG  
Tel 01283 212720 Fax 01283 215033

### BUTTERLEY LTD (Q4)

Ripley, Derby DE5 3BQ  
Tel 01773 573573 Fax 01773 749898

### CMF LTD (F H J L M S 1)

Central Way, Feltham TW14 0XJ  
Tel 020 8844 0940 Fax 020 8751 5793

### CAIRNHILL STRUCTURES LTD (C F H J L M S 4 Q4)

Sun Works, Waverley Street, Coatbridge, Lanarkshire ML5 2BE  
Tel 01236 449393 Fax 01236 428328

### CAUTION ENGINEERING LTD (C E F H J M N 1 Q1)

Moorgreen Ind. Park, Moorgreen, Nottingham NG16 3QU  
Tel 01773 531111 Fax 01773 532020

### CHEFTAIN CONTRACTS LTD (E F S 7)

Antonie Works, Broomhill Road, Bonnybridge FK4 2AL  
Tel 01324 812911 Fax 01324 814927

### CLEVELAND BRIDGE UK LTD (A B 0\* Q3)

Cleveland House, Yarm Rd, Darlington, Co Durham DL1 4DE  
Tel 01325 381188 Fax 01325 382320

### COMPASS ENGINEERING LTD (C E F H 4)

Whaley Road, Barugh, Barnsley S75 1HT  
Tel 01226 298388 Fax 01226 283215

### CONDER STRUCTURES LTD (D E F H M N S 1 Q2)

Wellington Rd, Burton-on-Trent, Staffs DE14 2AA  
Tel 01283 545377 Fax 01283 530483

### LEONARD COOPER LTD (C F H K M 6 Q1)

Balm Road, Hunslet, Leeds LS10 2JR  
Tel 0113 270 5441 Fax 0113 276 0659

### CORDELL GROUP LTD (Q4)

Sotherby Road, Skippers Lane Industrial Estate, South Bank, Middlesbrough TS6 6LP  
Tel 01642 452406 Fax 01642 464118

### COVENTRY CONSTRUCTION LTD (E F H L M S 5)

Torrington Avenue, Coventry CV4 9AP  
Tel 024 7646 4484 Fax 024 7669 4020

### CRONIN BUCKLEY FABRICATION & CONSTRUCTION LTD (E F H M 1)

Killumney, Ovens, Co Cork, Republic of Ireland  
Tel: 00 353 214 870 017 Fax: 00 353 214 872 890

### CROWN STRUCTURAL ENGINEERING LTD (E F H K M S 01)

Burma Rd, Blidworth, Mansfield, Notts NG21 0RT  
Tel 01623 490555 Fax 01623 490666

### D H STRUCTURES LTD (F M 8)

Tollgate Drive, Tollgate Industrial Estate, Beaconsfield, Stafford ST16 3HS  
Tel 01785 246269 Fax 01785 222077

### FRANK H DALE LTD (D E F 1 Q4)

Mill Street, Leominster, Herefordshire HR6 8EF  
Tel 01568 612212 Fax 01568 619401

### DISCAIN PROJECT SERVICES LTD (F L M S 5 Q1)

Harburn Close, Crow Lane Industrial Estate, Northampton NN3 9UE  
Tel 01604 787276 Fax 01604 407290

### DUGGAN STEEL LTD (D E F H M 1)

The Square, Millstreet, Co Cork, Republic of Ireland  
Tel 00 353 29 70072 Fax 00 353 29 70073

### ELLAND STEEL STRUCTURES LTD (A 1 Q1)

Philmar House, Gibbet St, Halifax HX2 0AR  
Tel 01422 380262 Fax 01422 380263

### ELSONE STRUCTURES LTD (F L M 6\*)

Welby Road, Asfordby Hill, Melton Mowbray, Leicestershire LE14 3RD  
Tel 01664 813234 Fax 01664 813341

### EMMETT FABRICATIONS LTD (E F H 6)

Hirst Wood Works, Hirst Wood Road, Shipley BD18 4BU  
Tel 01274 597484 Fax 01274 588671

### EVADUX LTD (A 3 Q4)

Unit 9, Tir Llywd Enterprise Park, St. Asaph Avenue, Kinnel Bay, Rhyl LL18 5JZ  
Tel 01745 336413 Fax 01745 336639

### FAIRFIELD-MABEY LTD (A B 0 Q4)

Chepstow, Monmouthshire NP16 5YL  
Tel 01291 623801 Fax 01291 625453

### FISHER ENGINEERING LTD (A 1 Q1)

Ballinamallard, Enniskillen, Co Fermanagh BT94 2FY  
Tel 028 6638 8521 Fax 028 6638 8706

### FOX BROS ENGINEERING LTD (E F H J M 3)

Ballycanew, Gorey, Co Wexford, Republic of Ireland  
Tel 00 353 53 942 1677 Fax 00 353 53 942 1733

### GME STRUCTURES LTD (E F H J L M S 6)

Unit E11-E14, Wem Industrial Estate, Souton Road, Wem, Shropshire SY4 5SD  
Tel 01939 233023 Fax 01939 234059

### GIBBS ENGINEERING LTD (F H J L M 6 Q4)

17A Axe Road, Colley Lane Industrial Estate, Bridgwater, Somerset TA6 5LP  
Tel 01278 455253 Fax 01278 453174

### GLENWORTH FABRICATIONS LTD (F J K L M N S 6)

Molly Millar's Bridge, Molly Millar's Lane, Wokingham RG41 2VW  
Tel 0118 977 2088 Fax 0118 977 2907

### GORGE FABRICATIONS LTD (F H J L 5)

Gorge House, Great Bridge Industrial Estate, Toll Road, Tipton, West Midlands DY4 0HR  
Tel 0121 522 5770 Fax 0121 557 0415

### GRAHAM WOOD STRUCTURAL LTD (A 1)

Lancing Business Park, Chartwell Road, Lancing BN15 8TY  
Tel 01903 755991 Fax 01903 755384

### GRAYS ENGINEERING (CONTRACTS) LTD (F J L M 8)

Globe Industrial Estate, Rectory Road, Grays, Essex RM17 6ST  
Tel 01375 372411 Fax 01375 375079

### D A GREEN & SONS LTD (A 1 Q1)

Whaplode, Spalding, Lincs PE12 6TL  
Tel 01406 370585 Fax 01406 370766

### GREGG & PATTERSON (ENGINEERS) LTD (E F H J N 2 Q4)

Riverside Works, Ballyskeagh Road, Lambeg, Co Antrim BT27 5TD  
Tel 028 9061 8131 Fax 028 9062 2813

### HAD-FAB LTD (K M S 5 Q4)

Macmerry Ind. Est., Tranent, East Lothian EH33 1RD  
Tel 01875 611711 Fax 01875 612711

### WILLIAM HALEY ENGINEERING LTD (E F K M 4 Q1)

Bellcombe Works, East Brent, nr. Highbridge, Somerset TA9 4DB  
Tel 01748 810598 Fax 01748 810601

### HAMBLETON STEEL LTD (D E F H J N 1 Q1)

Gatherley Road, Brompton-on-Swale, Richmond, North Yorkshire DL10 7JH  
Tel 01748 810598 Fax 01748 810601

### WILLIAM HARE LTD (A O Q1)

Brandslesholme House, Brandslesholme Rd, Bury, BL8 1JJ  
Tel 0161 609 0000 Fax 0161 609 0409

### M. HASSON & SONS LTD (E F H J K L M S 3 Q1)

17 Glebe Rd, Rasharkin, Co. Antrim BT44 8SS  
Tel 028 2957 1281 Fax 028 2957 1575

### HENRY SMITH (CONSTRUCTIONAL ENGINEERS) LTD (C D E F H J 2)

Wharton Steelworks, Winsford CW7 3BW  
Tel 01606 592121 Fax 01606 559134

### HESCOTT ENGINEERING CO LTD (E F H L S 3)

Lochlands Viaduct, Larbert, Stirlingshire FK5 3NN  
Tel 01324 556610 Fax 01324 552970

### HILLS OF SHOEBUYNNESS LTD (L M S 6)

17-19 Towerfield Road, Shoebuynness, Essex SS3 9QL  
Tel 01702 296321 Fax 01702 297072

### JAMES BROS (HAMWORTHY) LTD (E F H M 5 Q4)

Stanley House, 3 Fleets Lane, Poole, Dorset BH15 3AJ  
Tel 01202 673815 Fax 01202 684033

### JAMES KILLELEA & CO LTD (C D E F H N 1\*)

Stonholm Road, Crawshawbooth, Rossendale, Lancs BB4 8BA  
Tel 01706 229411 Fax 01706 228388

### LEACH STRUCTURAL STEELWORK LTD (C E F H J M 5)

Brockholes Way, Cloughton-on-Brock, nr Preston PR3 0PZ  
Tel 01995 640133 Fax 01995 640719

### LEONARD ENGINEERING (BALLYBAY) LTD (E F H M 3)

St Patrick's Street, Ballybay, Co Monaghan, Republic of Ireland  
Tel 00 353 42 974 1099 Fax 00 353 42 974 1001

### LOWE ENGINEERING (MIDLAND) LTD (L S 6 Q4)

Bramshall Industrial Estate, Stone Road, Bramshall, Staffs ST14 8SH  
Tel 01889 563244 Fax 01889 563554

### M&S ENGINEERING LTD (F K L M S 5)

East Road, Lovthertown, Eastgriggs DG12 6TD  
Tel 01461 40111 Fax 01461 40542

### TERENCE MCCORMACK LTD (E F H J 6 Q1)

17 Camlough Rd, Newry BT36 6JS  
Tel 028 3026 2261 Fax 028 3026 8177

### MALDON MARINE LTD (F J K L 5)

Unit 16, West Station Ind. Est., Spital Road, Maldon, Essex CM9 6TW  
Tel 01621 859000 Fax 01621 859835

</



**ROWEN STRUCTURES LTD (A 0\*)**

17 Maisies Way, The Village, South Normanton, Derbyshire DE55 2DS  
Tel: 01773 860086 Fax: 01773 814077

**S H STRUCTURES LTD (H J K L 3)**

Moor Lane Trading Estate, Sherburn-in-Elmet, North Yorkshire LS25 6ES  
Tel: 01977 681931 Fax: 01977 681930

**SELWYN CONSTRUCTION ENGINEERING LTD (L M S 9 Q4)**

Tarron Road, Tarron Industrial Estate, Moreton, Wirral CH46 4TU  
Tel: 0151 678 0236 Fax: 0151 678 8959

**SEVERFIELD-REEVE STRUCTURES LTD (A 0 02)**

Dalton Airfield Industrial Estate, Dalton, Thirsk, North Yorkshire YO7 3JN  
Tel: 01845 577896 Fax: 01845 577411

**SHIPLEY FABRICATIONS LTD (E F H K L M S 8)**

Maddocks Park, Ancaster, Grantham, Lincs NG32 3RT  
Tel: 01400 231115 Fax: 01400 231220

**SIAC BUTLERS STEEL LTD (D E F H J M N 0 Q4)**

Lea Road, Portarlington, Co Laois, Republic of Ireland  
Tel: 00 353 57 8623305 Fax: 00 353 57 8623207

**SIAC TETBURY STEEL LTD (D E F H 3 Q1)**

London Rd, Tetbury, Gloucs GL8 8HH  
Tel: 01666 502792 Fax: 01666 504246

**SNASHALL STEEL FABRICATIONS CO LTD (E F H S 4)**

Fulham Business Park, Fulham, nr Dorchester, Dorset DT2 7DX  
Tel: 01300 345588 Fax: 01300 345533

**SOUTH DURHAM STRUCTURES LTD**

South Church Enterprise Pk, Dovecot Hill, Bishop Auckland, Co. Durham DL14 6XR  
Tel: 01388 777950 Fax: 01388 775225

**W & H STEEL & ROOFING SYSTEMS LTD (E F H J 2)**

Kilkenny Road, Castlecomer, Co Kilkenny, Republic of Ireland  
Tel: 00 353 56 444 1855 Fax: 00 353 56 444 1860

**THE AA GROUP LTD (C D E F H M 5)**

Priorswood Place, East Pimbo, Skelmersdale, Lancs WN8 9QB  
Tel: 01695 50133 Fax: 01695 50133

**THE STEEL PEOPLE LTD (F L S 9)**

Unit 3E, Priory Park, Mills Road, Aylesford, Kent ME20 7PP  
Tel: 01622 715900 Fax: 01622 715905

**TRADITIONAL STRUCTURES LTD (D E F H J K M N 3\* Q1)**

Findel Works, Landywood Lane, Cheslyn Hay, Walsall, West Midlands WS6 7AJ  
Tel: 01922 414172 Fax: 01922 410211

**PADDY WALL & SONS (E F H J 1 Q4)**

Waterford Road Business Park, Waterford Road, New Ross, Co Wexford, Republic of Ireland  
Tel: 00 353 51 420 515 Fax: 00 353 51 420 516

**WALTER WATSON LTD (E F H J N 1 Q4)**

Greenfield Works, Ballylough Rd, Castlewelling, Co Down BT31 9JQ  
Tel: 028 4377 8111 Fax: 028 4377 2050

**WATSON STEEL STRUCTURES LTD (A B 0 Q1)**

Lockstock Lane, Bolton BL6 4BL  
Tel: 01204 699899 Fax: 01204 694543

**WESTBURY PARK ENGINEERING LTD (F J K L M Q4)**

Brook Lane, Westbury, Wilts BA13 4ES  
Tel: 01373 825500 Fax: 01373 825511

**WESTOK LTD**

Horbury Junction Ind Est, Horbury Junction, Wakefield WF4 5ER  
Tel: 01924 264121 Fax: 01924 280030

**WIG ENGINEERING LTD (F L 7)**

Barnfield, Akeman Street, Chesterton, Oxon OX26 1TE  
Tel: 01869 320615 Fax: 01869 320513

**H. YOUNG STRUCTURES LTD (E F H J M 4)**

Ayton Road, Wymondham, Norfolk NR18 0RD  
Tel: 01953 601881 Fax: 01953 607842

**ASSOCIATE MEMBERS****STRUCTURAL COMPONENTS****ALBION SECTIONS LTD (Q4)**

Albion Rd, West Bromwich, West Midlands B70 8BD  
Tel: 0121 553 1877 Fax: 0121 553 5507

**AYRSHIRE METAL PRODUCTS (DAVENTRY) LTD (Q2)**

Royal Oak Way, Daventry NN11 5NR  
Tel: 01327 300990 Fax: 01327 300885

**BARNSHAW PLATE BENDING CENTRE LTD (Q2)**

Corporation Rd, Audenshaw, Manchester M34 5LR  
Tel: 0161 320 9696 Fax: 0161 335 0918

**BARNSHAW SECTION BENDERS LTD (Q2)**

Structural Division, Anchor Lane, Coseley, Bilston, West Midlands WV14 9NE  
Tel: 01902 880848 Fax: 01902 880125

**CELLBEAM LTD**

Unit 518, Thorp Arch Estate, Wetherby, West Yorkshire LS23 7DB  
Tel: 01937 840614 Fax: 01937 840608

**COMPOSITE METAL FLOORING LTD**

Unit 3, Mamhill Technology Park, Old Abergavenny Road, Mamhill NP4 0JJ  
Tel: 01495 761080

**COMPOSITE PROFILES UK LTD**

15 Moor Road, Broadstone, Dorset BH18 8AZ  
Tel: 01202 659237 Fax: 01202 659288

**CORUS PANELS & PROFILES (Q1)**

Severn Drive, Tewkesbury Business Park, Tewksbury, Glos GL20 8TX  
Tel: 01684 856600 Fax: 01684 856601

**DAVER STEELS LTD**

395 Petre Street, Sheffield S4 8LN  
Tel: 0114 261 1999 Fax: 0114 261 1888

**FLI STRUCTURES**

Waterwells Drive, Waterwells Business Park, Gloucester GL2 2AA  
Tel: 01452 722200 Fax: 01452 722244

**FABSEC LTD**

1st Floor, Unit 3, Calder Close, Calder Business Park, Wakefield WF4 3BA  
Tel: 0845 094 2530 Fax: 0845 094 2533

**HI-SPAN LTD**

Ayton Rd, Wymondham NR18 0RD  
Tel: 01953 603081 Fax: 01953 607842

**KINGSPAN STRUCTURAL PRODUCTS (Q4)**

Sherburn, Malton, N. Yorkshire YO17 8PQ  
Tel: 01944 712000 Fax: 01944 710555

**RICHARD LEES STEEL DECKING LTD**

Moor Farm Rd West, The Airfield, Ashbourne, Derbyshire DE6 1HD  
Tel: 01335 300999 Fax: 01335 300888

**MSW STRUCTURAL FLOOR SYSTEMS**

Acton Grove, Long Eaton, Nottingham NG10 1FY  
Tel: 0115 946 2316 Fax: 0115 946 2278

**MSW (UK) LTD**

16 Jacobean House, 1 Glebe Street, East Kilbride G74 7LY  
Tel: 01355 232266 Fax: 01355 266766

**METSEC PLC (Q2)**

Broadwell Rd, Oldbury, West Mids B69 4HE  
Tel: 0121 601 6000 Fax: 0121 601 6181

**NORTHERN STEEL DECKING LTD**

Aston House, Campbell Way, Dinnington, Sheffield S25 3QD  
Tel: 01909 550054 Fax: 01909 569443

**NORTHERN STEEL DECKING SCOTLAND LTD**

23 Mary Street, Johnston, Renfrewshire, PA5 8BT  
Tel: 01505 328830 Fax: 01505 331201

**PP PROTECTOR LTD**

Bay 6, Bold Industrial Park, Neills Road, Bold, St Helens WA9 4TU  
Tel: 01744 818992 Fax: 01744 820179

**SCHOCK LTD**

Barford Road, Bloxham, Banbury, Oxon OX15 4FF  
Tel: 0845 241 3390 Fax: 0845 241 3391

**STRUCTURAL METAL DECKS LTD**

The Outlook, Ling Road, Towser Park, Poole, Dorset BH12 4PY  
Tel: 01202 718896 Fax: 01202 714980

**STRUCTURAL SECTIONS LTD (Q1)**

123 West Bromwich Street, Oldbury, West Midlands B69 3AZ  
Tel: 0121 555 1342 Fax: 0121 555 1341

**STUDWELDERS LTD**

Millennium Hse, Severn Link Distribution Centre, Newhouse Farm Ind Est, Chepstow, Monmouthshire NP16 6UN  
Tel: 01291 626048 Fax: 01291 629979

**COMPUTER SOFTWARE****ACCAD SOFTWARE LTD**

Truro House, Stephensons Way, Wyvern Business Park, Derby DE21 6LY  
Tel: 01332 545800 Fax: 01332 545801

**BENTLEY SYSTEMS (UK) LTD**

4 Woodside Place, Glasgow G3 7QF  
Tel: 0141 353 5168 Fax: 0141 353 5112

**COMPUTER SERVICES CONSULTANTS (UK) LTD**

Yeadon House, New St, Pudsey, Leeds, LS28 8AQ  
Tel: 0113 239 3000 Fax: 0113 236 0546

**STEEL PROJECTS UK LTD**

6 Highfield Drive, Gildersome, Leeds LS27 7DW  
Tel: 0113 253 2171 Fax: 0113 252 8781

**TEKLA (UK) LTD**

Tekla House, Cliffe Park Way, Morley, Leeds LS27 0RY  
Tel: 0113 307 1200 Fax: 0113 307 1201

**DESIGN SERVICES****ARRO-CAD LTD**

Bretby Business Park, Ashby Road, Bretby, Burton-on-Trent DE15 0YZ  
Tel: 01323 558206 Fax: 01283 558207

**DEVELOPMENT DESIGN DETAILING SERVICES LTD**

171 Bradshawgate, Bolton, Lancs BL2 1BH  
Tel: 01204 396606 Fax: 01204 396634

**STEEL PRODUCERS****CORUS**

Frodingham House, PO Box 1, Brigg Road, Scunthorpe DN16 1BP  
Tel: 01724 404040 Fax: 01724 404229

**CORUS TUBES**

PO Box 101, Weldon Rd, Corby, Northants NN17 5UA  
Tel: 01536 402121

**MANUFACTURING EQUIPMENT****FCPE (UK) LTD**

10 The Courtyards, Victoria Park, Victoria Road, Leeds LS14 2LB  
Tel: 0113 265 3921 Fax: 0113 265 3913

**KALTENBACH LTD**

6-8 Brunel Road, Bedford MK41 9TJ  
Tel: 01234 213201 Fax: 01234 351226

**PEDDINGHAUS CORPORATION UK LTD**

Unit 6, Queensway Link, Stafford Park 17, Telford TF3 3DN  
Tel: 01952 200377 Fax: 01952 292877

**PEDDINGHAUS CORPORATION UK LTD**

Lockstown, Valley Mount, Co Wicklow, Republic of Ireland  
Tel: 00 353 87 2577 884 Fax: 00 353 45 867 028

**RÖSLER UK**

Unity Grove, Knowsley Business Park, Prescot, Merseyside L34 9GT  
Tel: 0151 482 0444 Fax: 0151 482 4444

**VOORTMAN UK LTD**

Unit 5, Mercian Park, Felspar Rd, Amington Rd, Tamworth B77 4DP  
Tel: 01827 63300 Fax: 01827 65565

**PROTECTIVE SYSTEMS****FORWARD PROTECTIVE COATINGS LTD**

Vernon St, Shirebrook, Mansfield, Notts NG20 8SS  
Tel: 01623 748323 Fax: 01623 748730

**INDUSTRIAL SHOTBLAST & SPRAYING**

Unit 7, Tetbury Industrial Estate, Cirencester Road, Tetbury, Gloucestershire GL8 8EZ  
Tel: 0845 130 6715 Fax: 0845 130 6716

**INTERNATIONAL PAINT LTD**

Protective Coatings, Stonegate Lane, Felling, Gateshead NE10 0JY  
Tel: 0191 469 6111 Fax: 0191 495 0676

**LEIGHS PAINTS**

Tower Works, Kestor Street, Bolton BL2 2AL  
Tel: 01204 521771 Fax: 01204 382115

**PPG PROTECTIVE & MARINE COATINGS**

Micro House, Station Approach, Wood Street North, Alfreton, Derbyshire DE55 7JR  
Tel: 01773 837300 Fax: 01773 837302

**SITE COAT SERVICES LTD**

Unit 11, Old Wharf Road, Grantham, Lincolnshire NG31 7AA  
Tel: 01476 577473 Fax: 01476 577642

**JACK TIGHE LTD**

Kirk Sandall Ind. Est., Kirk Sandall, Doncaster DN3 1QR  
Tel: 01302 880360 Fax: 01302 880370

**WEDGE GROUP GALVANIZING**

c/o Worktop Galvanizing Claydams Avenue, Worktop, Notts S81 7BQ  
Tel: 01909 486384 Fax: 01909 482540

**WELLS PROTECTIVE COATINGS LTD**

Unit 21, Wright Business Park, Carr Hill, Doncaster DN4 8DE  
Tel: 01302 733611 Fax: 01302 733639

**SAFETY SYSTEMS****CELLSHIELD**

Unit 516, Thorp Arch Estate, Wetherby, West Yorkshire LS23 7DB  
Tel: 01937 840600 Fax: 01937 840601

**COMBISAFE INTERNATIONAL LTD**

Unit 1, Zone A, Cheaney Drive, Grange Park, Northampton NN4 5FB  
Tel: 01604 660600 Fax: 01604 662960

**ESL-EDGE LTD**

Ollerton Rd, Tuxford, Newark, Notts NG22 0PQ  
Tel: 01777 870901 Fax: 01777 872047

**TRAILERPAL LTD**

Carmel Drive, Harlescott Industrial Estate, Shrewsbury, Shropshire SY1 3TB  
Tel: 01743 446666 Fax: 01743 442448

**STEEL STOCKHOLDERS****ADVANCED STEEL SERVICES LTD**

South Ribbles Industrial Estate, Capitol Way, Preston, Lancs PR5 4AJ  
Tel: 01772 259822 Fax: 01772 259561

**ALTERNATIVE STEEL CO LTD**

Dobson Park Way, Ince, Wigan WN2 2DY  
Tel: 01942 610601 Fax: 01942 821999

**ASD METAL SERVICES - EDINBURGH**

24 South Gyle Crescent, Edinburgh EH12 9EB  
Tel: 0131 458 3200 Fax: 0131 458 3266

**ASD METAL SERVICES - BODMIN**

Unit 13, Cooksland Ind. Est., Bodmin, Cornwall PL31 2PZ  
Tel: 01208 77066 Fax: 01208 77416

**ASD METAL SERVICES - LONDON**

Thames Wharf, Dock Road, London E16 1AF  
Tel: 020 7476 9444 Fax: 020 7476 0239

**ASD METAL SERVICES - CARLISLE**

Unit C, Earls Way, Kingsmoor Park Central, Kingstown, Cumbria CA6 4SE  
Tel: 01228 674766 Fax: 01228 674197

**ASD METAL SERVICES - HULL**

Gibson Lane, Melton, North Ferriby, E. Yorkshire HU14 3HX  
Tel: 01482 633360 Fax: 01482 633370

**ASD METAL SERVICES - GRIMSBY**

Estate Road No. 5, South Humber Industrial Estate, Grimsby DN31 2TX  
Tel: 01472 353851 Fax: 01472 240028

**ASD METAL SERVICES - BIDDULPH**

PO Box 2, Tunstall Road, Biddulph, Stoke-on-Trent, Staffs ST8 6JZ  
Tel: 01782 515152 Fax: 01782 522240

**ASD METAL SERVICES - DURHAM**

Drum Road, Drum Industrial Estate, Chester-le-Street, Co. Durham DH2 1ST  
Tel: 0191 492 2322 Fax: 0191 410 0126

**ASD METAL SERVICES - CARDIFF**

East Moors Road, Cardiff CF1 5SP  
Tel: 01292 2046 0622 Fax: 029 2049 0105

**ASD METAL SERVICES - STALBRIDGE**

Station Rd, Stalbridge, Dorset DT10 2RW  
Tel: 01963 362646 Fax: 01963 362620

**ASD METAL SERVICES - NORFOLK**

Hamlin Way, Kings Lynn, Norfolk PE30 4LQ  
Tel: 01553 761431 Fax: 01553 692394

**ASD METAL SERVICES - EXETER**

Sidmouth Road, Clyst St Mary, Exeter EX5 1AD  
Tel: 01395 233366 Fax: 01395 233367

**ASD METAL SERVICES - DAVENTRY**

Royal Oak Ind. Est., Daventry, Northants NN11 5QQ  
Tel: 01327 876021 Fax: 01327 87612

**ASD METAL SERVICES - TIVIDALE**

Tipton Road, Tividale, Oldbury, West Midlands B69 3HU  
Tel: 0121 520 1231 Fax: 0121 520 5684

**AUSTIN TRUMANN'S STEEL LTD**

Brightgate House, Cobra Court, Trafford Park, Manchester M32 0TB  
Tel: 0161 866 0266 Fax: 0161 866 0291

**BARRETT STEEL SERVICES LTD**

Barrett House, Cutler Heights Lane, Dudley Hill, Bradford BD4 9HU  
Tel: 01274 682281 Fax: 01274 651205



The Steel Construction Institute develops and promotes the effective use of steel in construction. It is an independent, membership-based organisation. Membership is drawn from all sectors of the construction industry; this provides beneficial contacts both within the UK and internationally. Its corporate members enjoy access to unique expertise and free practical advice which contributes to their own efficiency and profitability. They also receive an initial free copy of most SCI publications, and discounts on subsequent copies and on courses. Its multi-disciplinary staff of 45 skilled engineers and architects is available to provide technical advice to members on steel construction in the following areas:

- Technical Support for Architects
- Bridge Engineering
- Building Interfaces
- Civil Engineering
- Codes and Standards
- Composite Construction
- Connections
- Construction Practice
- Corrosion Protection
- Fabrication
- Health & Safety — best practice
- Information Technology
- Fire Engineering
- Light Steel and Modular Construction
- Offshore Hazard Engineering
- Offshore Structural Design
- Piling and Foundations
- Specialist Analysis
- Stainless Steel
- Steelwork Design
- Sustainability
- Vibration

Details of SCI Membership and services are available from: Sandi Gentle, Membership Manager, The Steel Construction Institute, Silwood Park, Ascot, Berks.  
**Telephone:** +44 (0) 1344 636509 **Fax:** +44 (0) 1344 636570  
**Email:** [s.gentle@steel-sci.com](mailto:s.gentle@steel-sci.com) **Website:** [www.steel-sci.com](http://www.steel-sci.com)

All full members of the BCSA are automatically members of the SCI. Their contact details are listed on the BCSA Members pages

## CORPORATE MEMBERS

3E Consulting Engineers Ltd  
 3E Consulting Engineers Ltd  
 A C Bacon Engineering Ltd  
 A Dawber Limited  
 A Steadman & Son Ltd  
 Aberdeenshire Council  
 Abraham Consulting Engineers  
 Absolute Consulting Engineers  
 ACE (Leicester)  
 AceCad Software Ltd  
 ACL Structures Ltd  
 Active Design  
 Adams Kara Taylor Ltd  
 Adey Steel Ltd  
 ADP Consulting Engineers Ltd  
 Adstone Construction Ltd  
 Advanced Fabrications  
 Poyle Ltd  
 Air Products Plc  
 Aker Process Ltd  
 AKSWard  
 Alan Baxter & Associates  
 Alan Conisbee & Associates  
 Alan Dorman Consulting  
 Engineer  
 Alan Johnston Partnership  
 Albion Sections Ltd  
 Alcock Lees Partnership  
 Allerton Engineering Ltd  
 Allslade Plc  
 AMEC NNC Limited  
 AMP Consultants  
 Andrew Dust Structural  
 Engineers  
 Andrew Howard & Partners  
 Apex Steel Structures Ltd  
 Architectural Profiles Ltd  
 Arromax Structures Ltd  
 Arrow Structural Framing  
 Sales Ltd  
 Arup  
 Arup Associates  
 ASA Steel Structures Ltd  
 ASD Westok Ltd  
 Asme Engineering Ltd  
 Associated Structural Design  
 Atkins  
 Atkins MSL Engineering Ltd  
 Atlas Ward Structures Ltd  
 Atlasco Constructional  
 Engineers Ltd  
 AWF Steel Ltd  
 Ayrshire Metal Products Plc  
 B D Structures Ltd  
 B W Industries Ltd  
 BAA Capital Projects

Balfour Beatty Rail Projects Ltd  
 Ballykine Structural  
 Engineers Ltd  
 BAM Construct UK Ltd  
 BAM Nuttall Ltd  
 Barrett Steel Buildings Ltd  
 Barretts of Aspley Ltd  
 Baxter Glaysheer Consulting  
 BDO Offsite  
 BDS Steel Detailers  
 Bechtel Ltd  
 Benaim  
 Bentley Systems  
 Beresford Dunne  
 Consultants Ltd  
 Bestech Systems Ltd  
 BHC Ltd  
 Billington Structures Ltd  
 Birmingham City Council  
 Black & Veatch Ltd  
 Blyth & Blyth Consulting  
 Bodycote Metallurgical  
 Coatings  
 Bolton Priestley  
 Bone Steel Ltd  
 Border Steelwork  
 Structures Ltd  
 Bourne Construction  
 Engineering Ltd  
 Bridgetown Developments Ltd  
 British Constructional  
 Steelwork Association Ltd  
 British Energy Plc  
 British Nuclear Group  
 British Stainless Steel  
 Association  
 Briton Fabricators Ltd  
 Browne Structures Ltd  
 Brunner Mond UK Ltd  
 BSB Structural Ltd  
 Building & Structural  
 Consultants  
 Building Design Partnership  
 Bunyan Meyer & Partners Ltd  
 Buro Happold  
 Burroughs Stewart Associates  
 Butterley Ltd  
 BWB Consulting Ltd  
 C.S.C. Engineers Ltd  
 CADS (Computer & Design  
 Services Ltd)  
 Cairnhill Structures Ltd  
 Caledonian Building Systems  
 Cameron Taylor  
 CampbellReith  
 Capita Bobrowski  
 Capita Gwent Consultancy Ltd  
 Capita Symonds

Cardiff County Council  
 Cardiff University  
 Carnaby Steel Structures  
 Carter Design Group  
 Cass Hayward LLP  
 Caution Engineering Ltd  
 CB&I UK Limited  
 CEL International Ltd  
 Cheshire County Council  
 Chieftain Contracts Ltd  
 CIRIA  
 City University  
 Civil & Structural Computer  
 Services Ltd  
 Clarke Bond Group Limited  
 Clarke Nicholls & Marcel  
 Clarkslegal LLP  
 Clegg Associates  
 Cleveland Bridge UK Ltd  
 CMF Limited  
 Compass Engineering Ltd  
 Complete Design  
 Partnership Ltd  
 Composite Design Ireland LLP  
 Conder Structures Ltd  
 Construction Design Solutions  
 Conwy County Borough  
 Council  
 Cordell Group Ltd  
 Cornwall County Council  
 Corus  
 Corus Rail  
 Coventry Construction Ltd  
 Coventry University  
 Crown Structural  
 Engineering Ltd  
 CSC (UK) Ltd  
 Cundall  
 Curtins Consulting  
 CWT Partnership  
 D H Structures Ltd  
 Dalton Consultants  
 Deakin Walton Limited  
 Defence Estates  
 Devon County Council  
 Devonport Management Ltd  
 Dewhurst Macfarlane and  
 Partners  
 Discairn Project Services Ltd  
 Dorman Long Technology Ltd  
 Doyle Partnership  
 Dundee City Council  
 Elland Steel Structures Ltd  
 Elliott Wood Partnership LLP  
 Elsmore Structures Ltd  
 Emile Sanan  
 Emmett Fabrications Ltd

Engineered Off-Site  
 Systems Ltd  
 Engineering & More Ltd  
 Engineering Solutions  
 Partnership  
 Eurobond Laminates Ltd  
 Evadix Ltd  
 Evans & Langford LLP  
 Expedition Engineering Limited  
 F J Booth & Partners Ltd  
 F J Samuely & Partners Ltd  
 Faber Maunsell  
 Fabsec Ltd  
 Fairfield-Mabey Ltd  
 Fisher Engineering Ltd  
 Flint & Neill Partnership  
 Fluid Structural Engineers  
 Fluor Ltd  
 Foggo Associates Ltd  
 Forbes King  
 Fothergill  
 Fox Bros Engineering Ltd  
 Framing Solutions plc  
 Frank H Dale Ltd  
 G K Mitchell Associates Ltd  
 Galvanizers Association  
 Gardenwood Ltd  
 Gary Gabriel Associates  
 George Mathieson Associates  
 Gibbs Engineering Ltd  
 Gibson Design Consultancy Ltd  
 Gifford  
 Gifford Ltd  
 Glasgow Caledonian University  
 Glentworth Fabrications Ltd  
 GME Structures Ltd  
 Goodwin Steel Castings Ltd  
 Gordon S Muir Civil &  
 Structural Eng. Design  
 Gorge Fabrications Ltd  
 Graham A Reeve Associates Ltd  
 Graham Wood Structural Ltd  
 Grays Engineering  
 (Contracts) Ltd  
 Gregg & Patterson  
 (Engineers) Ltd  
 Grontmij  
 H Young Structures Ltd  
 Had-Fab Limited  
 Halcrow Group Ltd  
 Halcrow Yolles  
 Hallmason Design Ltd  
 Hambleton Steel Ltd  
 Hanson Building Products Ltd  
 Harold Newsome Ltd  
 Harry Marsh (Engineers) Ltd

Harry Peers Steelwork Limited  
 Henrob Limited  
 Henry Smith (CE) Ltd  
 Henry Venables Products Ltd  
 Hescott Engineering  
 Company Ltd  
 Highcliffe Court Design Limited  
 High-Point Rendel  
 Highways Agency  
 Hill Cannon (UK) LLP  
 Hills of Shoburyness Ltd  
 Hi-Span Ltd  
 Hockley & Dawson Consulting  
 Engineers Ltd  
 Holywell Structural Design  
 HOP Consulting Ltd  
 HSP Consulting  
 Hurst Peirce & Malcolm LLP  
 Impaq Ltd  
 Imperial College London  
 Institution of Structural  
 Engineers (IStructE)  
 Integer Software Limited  
 Integrated Environmental  
 Solutions Ltd  
 Inverclyde Council  
 J Robertson & Co Ltd  
 Jacobs Babbie  
 Jacobs Engineering UK  
 Jacobs Engineering UK Ltd  
 Jacobs UK Ltd  
 James Bros (Hamworthy) Ltd  
 James Killelea & Co Ltd  
 James Lupton Consultants  
 Jenkins & Potter Ltd  
 John Reid & Sons  
 (Strucsteel) Ltd  
 JPG (Holdings) Ltd  
 K K Consultancy Ltd  
 KB2  
 Keith Kendal Consultants  
 Kellogg Brown & Root Ltd  
 Kier Engineering Services  
 Kingspan Limited  
 Kingspan Offsite  
 Kingspan Offsite - Profiles  
 & Sections  
 Kingspan Off-Site Ltd  
 Kingston University  
 Knapp Hicks & Partners Ltd  
 LA Elwell Ltd  
 Leach Structural Steelwork Ltd  
 Leighs Paints  
 Lindapter International  
 Liverpool John Moores



University  
London Borough of Hillingdon  
Lowe Engineering  
(Midland) Ltd

M & S Engineering Ltd  
M Hasson & Sons Ltd  
Mace Ltd  
Magna Buildings Ltd  
Maslen Brennan Henshaw  
Mason Navarro Pledge Ltd  
Mech Tool Engineering Ltd  
Melliss LLP  
Metals Industry Skills &  
Performance (MetSkill)  
Metek UK Ltd  
Metsec Plc  
Michael Barclay Partnership  
Midland Steel Structures Ltd  
Midland Structural Services Ltd  
Mifflin Construction Ltd  
Mike Curnow  
Mitchell McFarlane & Partners  
MJM Consulting Engineers Ltd  
MLM Maddocks Lusher &  
Matthews  
Morgan Est  
Mott MacDonald  
Mouchel Limited  
MPN (UK) Ltd  
MSP Consultants  
MSW (UK) Ltd

Napier University  
Newbridge Engineering Ltd  
Newton Fabrications Ltd  
Nolan Associates  
Norder Design Associates  
Limited  
Nottingham Trent University  
NPS North East Ltd  
Nusteel Structures Ltd  
Nuttall John Martin  
NW Structural Consultants  
Limited

On Site Services  
(Gravesend) Ltd  
Overdale Construction  
Services Ltd  
Owen Williams Consultants  
Oxford Brookes University

Parsons Brinckerhoff Ltd  
Patrick Ryan Associates Ltd.  
Pencro Structural  
Engineering Ltd  
PEP Civil & Structures Ltd  
Peter Brett Associates  
Peter Marshall (Fire  
Escapes) Ltd  
Peter Taylor & Partners Ltd  
Pick Everard  
Plandescil Ltd  
PMS Fabrications Ltd  
Portakabin Ltd  
Powerwall Systems Limited  
Price & Myers Consulting  
Engineers LLP  
Ramboll Whitbybird  
PRP:  
Pyper McLarnon Partnership

Queen's University Belfast

R G Parkins & Partners Ltd  
R S Mann  
RAM International (Europe) Ltd  
Ramage Young Limited  
Ramboll Whitbybird  
Remnant Engineering Ltd  
Renfrewshire Council  
Richard Lees Steel Decking Ltd  
Richard Wood Engineering Ltd  
Rigby & Partners  
Rippin Ltd  
Rivergate Consultants Ltd  
RMJM Scotland Ltd  
Robert Bird & Partners  
Robert Tucker Associates

Roberts Engineering  
Robinson Construction  
Roger Bullivant Ltd  
Rowecord Engineering Ltd  
Rowen Structures Ltd  
Royal Haskoning  
Royal School of Military  
Engineering  
RPS Burks Green  
RPS Consulting Engineers  
RSL (South West) Ltd  
Ruukki UK Ltd

S H Structures Ltd  
Schoeck Ltd  
Scott White & Hookins  
Scott Wilson Ltd  
Sellafeld Ltd  
Selwyn Construction  
Engineering Ltd  
Severfield-Rowen PLC  
Shell UK Exploration &  
Production  
Shipley Fabrications Ltd  
Sinclair Knight Merz  
Sir Robert McAlpine  
Skanska Technology  
Skidmore, Owings & Merrill Inc  
Snashall Steel Fabrications  
South Durham Structures Ltd  
South Lincs Consulting Ltd  
Steel Design Solutions Limited  
Stephen Johnson Consulting  
Engineers Ltd  
Stewart & Harris  
Stirling Maynard & Partners  
Structural Design Associates  
Structural Design Partnership  
Structural Metal Decks Ltd  
Structural Sections Ltd  
Structural Solutions  
Surrey County Council

T W P  
Taylor Lane Timber Frame Ltd  
Teague & Sally Limited  
Techniker Ltd  
Tekla (UK) Ltd  
Tension Control Bolts Ltd  
Terence McCormack Ltd  
Terrapin Ltd  
The AA Group Ltd  
The Angle Ring Company Ltd  
The Brazier Holt Partnership Ltd  
The Steel People Ltd  
Thomas Grieve Ltd  
Thomas Morgan & Associates  
Thomasons LLP  
Tony Gee and Partners LLP  
TPS Consult Ltd  
Traditional Structures Ltd  
TRP Consulting Ltd

University of Aberdeen  
University of Bath  
University of Birmingham  
University of Bolton  
University of Dundee  
University of East London  
University of Edinburgh  
University of Greenwich  
University of Leeds  
University of Liverpool  
University of Manchester  
University of Nottingham  
University of Plymouth  
University of Portsmouth  
University of Salford  
University of Sheffield  
University of Southampton  
University of Surrey  
University of the West of  
England  
University of the West of  
Scotland  
University of Wales Swansea  
University of Warwick  
URS Corporation Limited  
V-Consult Limited

Vertex Systems

W A Fairhurst & Partners  
W F Brown Associates Ltd  
W. S. Britland & Co Ltd  
Wakefield MDC Building  
Control  
Walter Watson Ltd  
Waterman Environmental  
Waterman Group  
Waterman International  
Watson Steel Structures Ltd  
WCJ Engineers  
Wessex Structural Services Ltd  
Westbury Park Engineering Ltd  
White Young Green Consulting  
Ltd  
WIG Engineering Ltd  
William Haley Engineering Ltd  
William Hare Ltd  
William J Marshall & Partners  
Wright Associates  
WSP Group

## ORGANISATIONS WITH MEMBER SERVICE AGREEMENTS WITH THE SCI

Highways Agency  
The Institution of Structural  
Engineers

## INTERNATIONAL CORPORATE MEMBERS

**Australia**  
Australian Steel Institute  
BlueScope Steel Research  
Cocciardi Pty Ltd  
Corus Australia  
Greentram Software Pty Ltd

**Belgium**  
Bocad Service International S A  
Staalinfocentrum - Centre  
Information Acier  
World Steel Association

**Brazil**  
CBCA - Brazilian Center of Steel  
Construction  
CODEME Engenharia S.A.  
Federal University of Minas  
Gerais  
Gerdau Açominas S/A  
Universidade de São Paulo  
Universidade Federal de  
Ouro Preto  
USIMINAS

**Canada**  
Canadian Institute of Steel  
Construction

**Croatia**  
Institut Gradevinarstva  
Hrvatske d.d.

**Finland**  
Hamk University of Applied  
Sciences  
Rautaruukki Oyj  
Ruukki Construction  
Seinäjoki Polytechnic  
VTT Technical Research Centre  
of Finland

**France**  
CTICM  
TERRELL

**Germany**  
Bauen mit Stahl e.V.  
  
**Greece**  
Computer Control Systems SA  
Democritus University

of Thrace  
Elias Chavantzis  
K Liarmatis S.A.  
Maraveas & Associates SA  
NSH  
Technical Chamber of  
Greece (TEE)

**Hong Kong**  
The Hong Kong Polytechnic  
University

**Hungary**  
Lindab Building Systems

**Ireland**  
Andrew Mannion  
Engineering Ltd  
Barrett Mahony Consulting  
Engineers Ltd  
Bechtel Overseas Corporation  
C. S. Pringle Ltd  
CBA Consulting Engineers  
Coyle Kennedy Ltd  
Cronin Buckley  
DBFL Consulting Engineers Ltd  
Denis O'Sullivan & Associates  
Downes Associates  
Duggan Profiles & Steel  
Service Centre Ltd  
Duggan Steel  
ESB International Ltd  
Frank Fox & Associates  
Fusion Building Systems  
Glenbeigh Off Site (GOS)  
Hayes Higgins Partnership  
Institute for Steel Development  
& Growth (INSDAG)  
J B Barry & Partners Limited  
Joda Engineering Consultants  
Kilgallen & Partners Consulting  
Eng Ltd  
Leonard Engineering  
(Ballybay) Ltd  
McCabe Delaney  
Metcon  
Michael Punch & Partners  
Milltown Engineering Ltd  
National University of Ireland,  
Galway  
Newell Roofing Products  
O'Connor Sutton Cronin  
Oliver Russell & Associates Ltd  
Pinnacle Consulting  
Engineers Ltd  
Project Management Ltd  
Project Management Ltd  
R G Parkins & Partners Ltd  
Royal Haskoning  
RPS Consulting Engineers Ltd  
Scott Wilson Ltd  
SIAC Butlers Steel Ltd  
Steel & Roofing Systems Ltd  
T J O'Connor & Associates  
The McKenna Pearce Practice  
TOBIN Consulting Engineers  
Walsh Associates  
Walsh Draughting Services Ltd

**Italy**  
Politecnico Di Milano  
Universita Degli Studi Di Trento

**Jersey**  
D J Hartigan & Associates Ltd

**Kenya**  
David Engineering Ltd  
Mabati Rolling Mills Ltd

**Liechtenstein**  
HILTI AG

**Lithuania**  
Vilnius Gediminas Technical  
University

**Luxembourg**  
Lindab-Astron Group

**Malaysia**  
Inotek Prima Sdn Bhd  
Universiti Kebangsaan  
Malaysia (UKM)  
Universiti Teknologi Malaysia  
TBA Periti

**New Zealand**  
HERA  
NNN Ltd

**Norway**  
Tee Consult Holding AS

**Poland**  
Project Management Ltd

**Portugal**  
Universidade de Aveiro  
Universidade de Coimbra -  
Polo II

**Qatar**  
Metalex Trading &  
Contracting Co. W.L.L

**Republic of Singapore**  
Jurong Engineering Ltd  
LSW Consulting Engineers  
Ngee Ann Polytechnic  
Singapore Structural  
Steel Society

**Russia**  
Steel Construction LLC

**South Africa**  
J W Swallow & Associates  
Southern African Institute of  
Steel Construction  
Tricom Structures

**South Korea**  
Hyundai Steel Company  
POSCO

**Spain**  
In Hoc Signo Vincas S.L.  
ITEA - Instituto Tecnico de  
la Estructura en Acero  
University of Navarra


**Sweden**  
Lulea University of Technology  
Swedish Institute of Steel  
Construction

**The Netherlands**  
Bouwen met Staal  
Delft University of Technology

**Turkey**  
Almetsan  
CIMTAS Celik Imalat Montaj  
Ve Tesisat A.S.  
UMO Architecture Engineering  
& Consulting Ltd Co

**United Arab Emirates**  
Emirates Building Systems LLC  
Future Vision Steel  
Construction Contg.LLC  
GINCO Steel L.L.C.  
Techno Steel Construction Co  
WSP Middle East Ltd

**USA**  
American Iron & Steel Institute  
Epic Metals Corporation  
Steel Recycling Institute



MetFloor® 55



MetFloor® 60



MetFloor® 80

**Simply one of the best performing  
composite metal floordeck ranges in the UK**